



Tolerances (Excerpts from API Specifications)

Pipe Specification	API 5L	API 5LU
1.500 in. and smaller 2-3/8 in. through 18 in.	+ 0.016 in. - 0.031 in. + 0.75% - 0.75%	
20 in. through 36 in. Non-expanded Cold-expanded	+ 1.00% - 0.25% + 0.75% - 1.00%	Less than 20 in. 20 in. and larger
Larger than 36 in. Non-expanded Cold-expanded*2	+ 1.00% - 1.00% + 1/4 in. - 1/8 in.	
10-3/4 in. and smaller	+ 1/15 in. (measured with ring gage)	10-3/4 in. and smaller
12-3/4 in. through 20 in.	+ 3/32 in. (measured with ring gage)	12-3/4 in. through 20 in.
Larger than 20 in. (22 in. and larger)	+ 3/32 in. (measured with diameter tape)	Larger than 20 in.
Welded Pipe	Grade A, B + 20.0% + 18.0% + 15.0% + 17.5%	Welded Pipe. 18 in. OD and smaller 20 in. OD and larger
2-8/75 in. OD and smaller	X42 through X70 + 15.0% + 15.0% + 15.0% + 19.5%	
3-1/2 in. OD	- 12.5% - 12.5% - 12.5% - 10.0%	
4 in. through 18 in. OD	- 12.5% - 12.5% - 12.5% - 10.0%	
20 in. OD and larger	- 12.5% - 12.5% - 12.5% - 10.0%	
Seamless Pipe	Grade A, B + 20.0% + 18.0% + 15.0% + 15.0%	Seamless Pipe. 18 in. OD and smaller 20 in. OD and larger
2-8/75 in. OD and smaller	X42 through X70 + 15.0% + 15.0% + 15.0% + 17.5%	
3-1/2 in. OD	- 12.5% - 12.5% - 12.5% - 10.0%	
4 in. through 18 in. OD	- 12.5% - 12.5% - 12.5% - 10.0%	
20 in. OD and larger	- 12.5% - 12.5% - 12.5% - 10.0%	
Standard weight	+ 10.0% - 3.5%	Regular weight
Regular weight	+ 10.0% - 5.0%	Special light weight
Double extra strong weight		
Special plain end weight		
Single length		
Cartload lots		
Straightness	For pipe 4-1/2 in. OD and larger Max 0.2%	Max 0.2%
Out of Roundness (for pipe larger than 20 in. OD)	Max. OD - specified OD $\leq 1\%$ x specified OD Specified OD - min. OD $\leq 1\%$ x specified OD	Max. OD - specified OD $\leq 1\%$ x specified OD Specified OD - min. OD $\leq 1\%$ x specified OD
Pipe End Preparation	For pipe 2-3/8 in. OD and larger Bevel angle 30°, + 5° - 0° Root face 1/16 in. + 1/32 in. Squareness for 10-3/4 in. OD and larger max. 1/16 in.	Bevel angle 30°, + 5° - 0° Root face 1/15 in. + 1/32 in. Squareness 10-3/4 in. OD and larger max 1/16 in.

Note *1 Pipe and tolerances are applicable 4 in. from either end.

*2 Not applicable to pipe hydrostatically tested to pressures in excess of standard test pressures.

Tolerances (Excerpts from API Specifications)

Tensile and Chemical Requirements (Excerpts from API Specifications, 1983 edition)

Application	Grade	Tensile Requirements						
		Yield Strength			Tensile Strength			Elongation
		psi min	MPa min	kg/mm ² min	psi min	MPa min	kg/mm ² min	% min
Line Pipe	API 5L Grade A	30,000	207	21.1	48,000	331	33.7	$e = \frac{625,000}{U} \frac{A}{0.9}$
	API 5L Grade B	35,000	241	24.6	60,000	413	42.2	
	API 5L Grade X42	42,000	289	29.5	60,000	413	42.2	
	API 5L Grade X46	46,000	317	32.3	63,000	434	44.3	
	API 5L Grade X52	52,000	358	36.6	(1) 66,000 *1 (2) 72,000	(1) 455 (2) 496	46.4 50.6	
	API 5L Grade X56 *6	56,000	386	39.2	(1) 71,000 *1 (2) 75,000	(1) 489 (2) 517	49.9 52.7	
	API 5L Grade X60 *3 *6	60,000	413	42.2	(1) 75,000 *1 (2) 78,000	(1) 517 (2) 537	52.7 54.8	
	API 5L Grade X65 *8 *11	65,000	448	45.7	(1) 77,000 *1 (2) 80,000	(1) 530 (2) 551	54.1 56.2	
	API 5L Grade X70 *6 *11	70,000	482	49.2	82,000	565	57.6	
	API 5LU Grade X80	80,000	551	56.2	*4 95,000/125,000	655/862	66.8/87.8	
	API 5LU Grade X100	100,000	689	70.3	*4 110,000/135,000	758/931	77.3/94.9	

- *1 (1) Wall thickness > 0.375 in., OD ≥ 20 in.
Any wall thickness, OD < 20 in.
(2) Wall thickness ≤ 0.375 in., OD ≥ 20 in.

- *2 The minimum elongation in 2 inches (50.8 mm) shall be determined by the following formula:

$$e = \frac{625,000}{U} \frac{A}{0.9}$$

where:

e = minimum elongation in 2 inches (50.8 mm) in per cent rounded to the nearest 1/2 per cent

A = cross sectional area of the tensile test specimen in square inches, based on specified outside diameter or nominal specimen width and specified wall thickness rounded to the nearest 0.01 sq. in., or 0.75 sq. in., whichever is smaller.

U = specified tensile strength, psi.

- *3 The minimum tensile strength for grade X60 electric-resistance welded pipe in all sizes and wall thicknesses shall be 75,000 psi (52.7 kg/mm²).

- *4 Tensile strength means min. value/max. value

- *5 Figures in parentheses are values for seamless pipe. Upper line value means non-expanded. Lowerline value means cold-expanded. In grades X42 through X65, for each reduction of 0.01 per cent below the maximum carbon content, an increase of 0.05 per cent manganese above the specified maximum is permissible, up to a maximum of 1.45 per cent for X52 and lower and up to a maximum of 1.60 per cent for grades higher than X52.

- *6 Other chemical analyses may be furnished by agreement between purchaser and manufacturer.

- *7 Either columbium, vanadium, titanium, or a combination thereof, shall be used at the discretion of the manufacturer.

Tolerances (Excerpts from API Specifications)

Chemical Requirements for Ladle Analyses, %							
C ^{*5}	Si	Mn ^{*5}	P	S	Cb	V	Ti
max	max	max	max	max	min	min	min
0.21 (0.22)		0.90	0.04	0.05			
0.26 (0.27)		1.15	0.04	0.05			
^{*13} 0.28 (0.29)		1.25	0.04	0.05			
0.30 (0.31) ^{*13} 0.28 (0.29)		1.35 1.25	0.04	0.05			
0.30 (0.31) ^{*13} 0.28 (0.29)		1.35 1.25	0.04	0.05			
0.26		1.35	0.04	0.05	0.005 ^{*7}	0.02 ^{*7}	0.03 ^{*7}
0.26		1.35	0.04	0.05	0.005 ^{*7}	0.02 ^{*7}	0.03 ^{*7}
0.26		1.40	0.04	0.05	0.005 ^{*9}	0.02 ^{*9}	
0.23 ^{*10}		1.60 ^{*10}	0.04	0.05			
0.26 ^{*12}	0.35	1.40 ^{*12}	0.04	0.05			
0.26 ^{*12}	0.35	1.40 ^{*12}	0.04	0.05			

*8 For grades X65 in sizes 16 in. and larger with wall thickness 0.500 in. and less, the chemical composition shall be as shown or as agreed upon between the purchaser and manufacturer. For other sizes and wall thicknesses the chemical composition shall be as agreed upon between the purchaser and manufacturer. (Applicable to welded pipe only.)

*9 Either columbium or vanadium or a combination of both shall be used at the discretion of the manufacturer.

*10 For each reduction of 0.01 per cent below the specified maximum carbon content, an increase of 0.05 per cent manganese above the specified maximum is permissible.

*11 For seamless pipe of grades X65 and X70, the chemical composition shall be agreed upon between the purchaser and manufacturer.

*12 For each reduction of 0.01% below the specified maximum carbon content, an increase of 0.05% manganese above the specified maximum is permissible, up to a maximum of 1.50%.

*13 For cold expanded seamless pipe in size 20 in. and larger, the maximum carbon content shall be 0.28 percent.

Tolerances (Excerpts from API Specifications)

Mechanical Values					Chemical Analysis							
Material	Tensile Strength N/mm ²	Yield Strength (Min)	Elongation % min	C %	Si %	Mn %	P % max	S % max	Mo %	Cr %	Ni %	Div %
A53-Grade A	min 330	205	variable	max 0.25	-	max 0.95	0.050	0.80				
A53-Grade B	min 415	240	variable	max 0.30	-	max 1.20	0.050	0.60				
A106-Grade A	min 330	205	35	max 0.25	min 0.10	0.27-0.93	0.048	0.058				
A106-Grade B	min 415	240	30	max 0.30	min 0.10	0.29-1.06	0.048	0.058				
A179	Hardness Rb max 72			0.06-0.18	-	0.27-0.63	0.048	0.058				
A333-Grade 1	min 379	207	35	max 0.30	-	0.40-1.06	0.050	0.60				
A333-Grade 6	min 414	241	30	max 0.30	min 0.10	0.29-1.06	0.048	0.058				
A333-Grade 3	min 448	241	30	max 0.19	0.18-0.37	0.31-0.64	0.050	0.050			3 18-3.82	
A335-Grade P1	min 379	207	30	0.10-0.20	0.10-0.50	0.30-0.80	0.045	0.045	0.44-0.65			
A335-Grade P5	min 414	207	30	max 0.15	max 0.50	0.30-0.60	0.030	0.030	0.44-0.55	4.00-6.00		
A335-Grade P11	min 414	207	30	max 0.15	0.50-1.00	0.30-0.60	0.030	0.030	0.44-0.65	1.00-1.50		
A335-Grade P12	min 414	207	30	max 0.15	max 0.50	0.30-0.60	0.045	0.045	0.44-0.65	0.80-1.25		
A335-Grade P22	min 414	207	30	max 0.15	max 0.50	0.30-0.60	0.030	0.030	0.87-1.13	1.90-2.60		
API-5L-Grade A	min 331	207	variable	max 0.22	-	max 0.90	0.040	0.050				
API-5L-Grade B	min 413	241	variable	max 0.27	-	max 1.15	0.040	0.050				
API-5L-Grade X42	min 413	289	variable	max 0.29	-	max 1.25	0.040	0.050				
API-5L-Grade X46	min 434	317	variable	max 0.29	-	max 1.35	0.040	0.050				
API-5L-Grade X52	min 455	358	variable	max 0.31	-	max 1.35	0.040	0.050				
API-5L-Grade X56	min 489	386	variable	max 0.26	-	max 1.35	0.040	0.050				
API-5L-Grade X60	min 517	413	variable	max 0.26	-	max 1.35	0.040	0.050				
BS3059/1-320	320-480	195	25	max 0.16	-	min 0.30	0.050	0.050				
BS3059/2-360	360-500	215	24	max 0.17	max 0.35	0.40-0.80	0.045	0.045				
BS3601-ERW320	320-440	195	25	max 0.16	-	0.30-0.70	0.050	0.050				
BS3601-ERW360	360-480	215	24	max 0.17	max 0.35	0.40-0.80	0.045	0.045				
BS3602-ERW/SAW410	410-530	235	22	max 0.21	max 0.35	0.40-1.20	0.050	0.050				
BS3601-S360	360-480	215	24	max 0.17	max 0.35	0.40-0.80	0.050	0.050				
BS3601-S410	410-530	235	22	max 0.21	max 0.35	0.40-1.20	0.050	0.050				
BS3602/1-360	360-500	215	24	max 0.17	max 0.35	0.40-0.80	0.045	0.045				
BS3602/1-410	410-550	245	22	max 0.21	max 0.35	0.40-1.20	0.045	0.045				
BS3602/1-490Nb	490-630	340	20	max 0.23	max 0.35	0.80-1.50	0.045	0.045			Nb 0.01-0.10	
BS3602/2-410	410-550	245	24	max 0.20	max 0.35	0.50-1.30	0.040	0.040				
BS3603-410	410-530	235	22	max 0.20	max 0.35	0.60-1.20	0.045	0.045				
BS3603-503	440-590	245	16	max 0.15	0.15-0.35	0.30-0.80	0.025	0.020			3 25-3.75	
BS3604-620	440-590	290	22	0.10-0.18	0.10-0.35	0.40-0.70	0.050	0.050	0.45-0.65	0.70-1.10		
BS3604-622	440-640	275	20	0.08-0.15	max 0.50	0.40-0.70	0.040	0.040	0.90-1.20	2.00-2.50		
BS3604-625	450-600	170	20	max 0.15	max 0.50	0.30-0.60	0.040	0.040	0.45-0.65	4.00-6.00		
BS4360-50D	490-640	355	20	max 0.20	max 0.40	max 1.40	0.040	0.040			Nb 0.003-0.10 V 0.0003-0.1	

Tolerances (Excerpts from API Specifications)

Technical Standards			Comparable Qualities					
Material	Specification Standard	Dimensional Standard	ASTM	API	BS	DIN	Euro Standard EU 25-72	DIV
A53	A53	ANSI-B36 10		API-5L-Gr.A	3601-320/360	St. 37.0	FE 310	
A53	A53	ANSI-B36 10		API-5L-Gr B	3601-410	St. 44.0	Fe 360B/430B	BS4360-43B/C
A106/A530	A106/A530	ANSI-B 36 10		API-5L-Gr A	3602-S360	St. 35.8		
A106/A530	A106/A530	ANSI-B 36 10		API-5L-Gr B	3602-S410	St. 45.8		
A179/A450	A179/A450	ANSI-B 36 10			3059-320/360	St. 35.8		
A333/A530	A333/A530	ANSI-B 36 10			360 1HFS27LT50	TT St.35N		
A333/A530	A333/A530	ANSI-B 36 10			3603HFS503LT100	TT St 35V		
A333/A530	A333/A530					10 Ni 14		
A335/A530	A335/A530	ANSI-B 36 10				15 Mo 3/16 Mo 5		
A335/A530	A335/A530	ANSI-B 36 10			3604-625	12 Cr Mo 19.5		
A335/A530	A335/A530	ANSI-B 36 10			3604-620-440-460	13 Cr Mo 44		
A335/A530	A335/A530	ANSI-B 36 10			3604-620-440-460	13 Cr Mo 44		
A335/A530	A335/A530	ANSI-B 36 10			3604-620-440	10 Cr Mo 910		
API-5L	API-5L	API-5L	A53 Gr.A		3601-320/360	St. 37.0	Fe 310	St.E 210.7
API-5L	API-5L	API-5L	A53 Gr.B		3601-410-4360-43B/C	St. 44.0	Fe 360B/430B	St.E 240.7
API-5L	API-5L	API-5L			4360-43 B/C	St. E 290.7	Fe 430B	
API-5L	API-5L	API-5L				St. E 320.7		
API-5L	API-5L	API-5L			4360-50 B/C/D	St. E 360.7	Fe510B/C/D	St. E 355
API-5L	API-5L	API-5L				St. E 385.7		
API-5L	API-5L	API-5L				St. E 415.7		
BS3059 part1	BS3059 part1	BS3059 part1	A179			St.35.8/St.37.8		
BS3059 part2	BS3059 part2	BS3059 part2	A179			St.35.8/St.37.8		
BS3601	BS3601	BS1600/BS3600	A53 Gr A	5L-Gr.A		St. 33	Fe 310	
BS3601	BS3601	BS1600/BS3600	A53 Gr B	5L-Gr.B		St.37.0/St.37.2	Fe 360B	A672-B60
BS3601	BS3601	BS1600/BS3600	A53 Gr B	5L-Gr B	4360-43B/C	St.44.0/St.44.3	Fe430B/C	A672-B65/C65
BS3601	BS3601	BS1600/BS3600	A106 Gr B	5L-Gr B		St.37.0/St.37.2	Fe 360B	
BS3601	BS3601	BS1600/BS3600	A106 Gr B	5L-Gr.B		St.44.0/St.44.3		
BS3602 part1	BS3602 part1	BS1600/BS3600	A106 Gr B	5L-Gr B		St.35.8/St.37.8		
BS3602 part1	BS3602 part1	BS1600/BS3600	A106 Gr B	5L-Gr B		St.45.8		
BS3602 part1	BS3602 part1	BS1600/BS3600		5L-Gr X52	4360-50 B/C/D	St.52/St.52.3	Fe510 B/C/D	
BS3602 part2	BS3602 part2	BS1600/BS3600	A672 B65/C65	5L-Gr B	4360-43 B/C	St. E240.7	Fe 430 B/C	
BS3603	BS3603	BS1600/BS3600	A333 Gr.6			TT St. 35V		
BS3603	BS3603	BS1600/BS3600	A333 Gr.3			10 Ni 14		
BS3604	BS3604	BS1600/BS3600	A335 P12			13 Cr Mo 44		
BS3604	BS3604	BS1600/BS3600	A335 P22			10 Cr Mo 910		
BS3604	BS3604	BS1600/BS3600	A335 P5			12 Cr Mo 195		
BS4360	BS4360	BS1600	A671 CC70	5L-X52		St. 52-3	Fe 510D	St. E 555

API Pipes

Size						Weight			Hydrostatic Test Pressure														
Outside Diameter			Wall Thickness			lb/ft	kg/m	kg/ft	API 5L				API 5LX										
									A		B		X42	X46	X52	X56	X60	X65	X70				
Nominal Size	in	mm	Sch No	in	mm				Std	Alt	Std	Alt											
1/4	0.405	10.3	40(Std)	0.068	1.73	0.24	0.36	-	700	-	700	-	-	-	-	-	-						
			80(XS)	0.096	2.41	0.31	0.45	-	850	-	850	-	-	-	-	-	-						
1/4	0.540	13.7	40(Std)	0.088	2.24	0.42	0.63	-	700	-	700	-	-	-	-	-	-						
			80(XS)	0.119	3.02	0.54	0.80	-	850	-	850	-	-	-	-	-	-						
3/8	0.675	17.1	40(Std)	0.091	2.31	0.57	0.85	-	700	-	700	-	-	-	-	-	-						
			80(XS)	0.126	3.20	0.74	1.10	-	850	-	850	-	-	-	-	-	-						
1/2	0.840	21.3	40(Std)	0.109	2.77	0.85	1.27	-	700	-	700	-	-	-	-	-	-						
			80(XS)	0.147	3.73	1.09	1.62	-	850	-	850	-	-	-	-	-	-						
			(XXS)	0.294	7.47	1.71	2.55	-	1000	-	1000	-	-	-	-	-	-						
3/4	1.050	26.7	40(Std)	0.113	2.87	1.13	1.68	-	700	-	700	-	-	-	-	-	-						
			80(XS)	0.154	3.91	1.47	2.19	-	850	-	850	-	-	-	-	-	-						
			(XXS)	0.308	7.82	2.44	3.63	-	1000	-	1000	-	-	-	-	-	-						
1	1.315	33.4	40(Std)	0.133	3.38	1.68	2.50	0.76	700	-	700	-	-	-	-	-	-						
			80(XS)	0.179	4.55	2.17	3.23	0.99	850	-	850	-	-	-	-	-	-						
			160	0.250	6.35	2.84	4.23	1.29	-	-	-	-	-	-	-	-	-						
			(XXS)	0.358	9.09	3.66	5.45	1.66	1000	-	1000	-	-	-	-	-	-						
1 1/4	1.660	42.2	40(Std)	0.140	3.56	2.27	3.38	1.03	1200	-	1300	-	-	-	-	-	-						
			80(XS)	0.191	4.85	3.00	4.47	1.36	1800	-	1900	-	-	-	-	-	-						
			160	0.250	6.35	3.76	5.60	1.71	-	-	-	-	-	-	-	-	-						
			(XXS)	0.382	9.70	5.21	7.76	2.37	2200	-	2300	-	-	-	-	-	-						
1 1/2	1.900	48.3	40(Std)	0.145	3.68	2.72	4.05	1.23	1200	-	1300	-	-	-	-	-	-						
			80(XS)	0.200	5.08	3.63	5.41	1.65	1800	-	1900	-	-	-	-	-	-						
			160	0.281	7.14	4.86	7.24	2.21	-	-	-	-	-	-	-	-	-						
			(XXS)	0.400	10.16	6.41	9.55	2.91	2200	-	2300	-	-	-	-	-	-						
2	2 1/4	60.3	40(Std) 80(XS) 160 (XXS)	0.083	2.11	2.03	3.02	0.92	1260	-	1470	-	1760	1930	2180	2350	2520	2730	2940				
				0.109	2.77	2.64	3.93	1.20	-	-	-	2310	2530	2860	3000	3000	3000	3000					
				0.125	3.18	3.00	4.47	1.36	-	-	-	2650	2910	3000	3000	3000	3000	3000					
				0.141	3.58	3.36	5.00	1.53	-	-	-	2990	3000	3000	3000	3000	3000	3000					
				0.154	3.91	3.65	5.44	1.66	2330	-	2500	-	3300	3000	3000	3000	3000	3000	3000				
				0.172	4.37	4.05	6.03	1.84	2500	-	2500	-	3000	3000	3000	3000	3000	3000	3000				
				0.188	4.78	4.39	6.54	1.99	2500	-	2500	-	3000	3000	3000	3000	3000	3000	3000				
				80(XS)	0.218	5.54	5.02	7.48	2.28	2500	-	2500	-	3000	3000	3000	3000	3000	3000	3000			
				0.250	6.35	5.67	8.45	2.57	2500	-	2500	-	3000	3000	3000	3000	3000	3000	3000				
				0.281	7.14	6.28	9.35	2.85	2500	-	2500	-	3000	3000	3000	3000	3000	3000	3000				
				160	0.344	8.74	7.46	11.11	3.39	-	-	-	3000	3000	3000	3000	3000	3000	3000				
				(XXS)	0.436	11.07	9.03	13.45	4.10	2500	-	2500	-	3000	3000	3000	3000	3000	3000	3000			
				2 1/2	2 1/2	73.0	40(Std) 80(XS) 160 (XXS)	0.083	2.11	2.47	3.68	1.12	1040	-	1040	-	1460	1590	1800	1940	2080	2250	2430
								0.109	2.77	3.22	4.80	1.46	-	-	-	1910	2090	2370	2550	2730	2960	3000	
								0.125	3.18	3.67	5.47	1.67	-	-	-	2190	2400	2710	2920	3000	3000	3000	3000
								0.141	3.58	4.12	6.14	1.87	-	-	-	2470	2710	3000	3000	3000	3000	3000	3000
0.156	3.96	4.53	6.75					2.06	1950	-	2280	-	2730	3000	3000	3000	3000	3000	3000				
0.172	4.37	4.97	7.40					2.26	2150	-	2500	-	3000	3000	3000	3000	3000	3000	3000				
0.188	4.78	5.40	8.04					2.45	2350	-	2500	-	3000	3000	3000	3000	3000	3000	3000				
40(Std)	0.203	5.16	5.79					8.62	2.63	2500	-	2500	-	3000	3000	3000	3000	3000	3000				
0.216	5.49	6.13	9.13					2.78	2500	-	2500	-	3000	3000	3000	3000	3000	3000	3000				
0.250	6.35	7.01	10.44					3.18	2500	-	2500	-	3000	3000	3000	3000	3000	3000	3000				
80(XS)	0.276	7.01	7.66					11.41	3.48	2500	-	2500	-	3000	3000	3000	3000	3000	3000	3000			
160	0.375	9.52	10.01					14.31	4.54	-	-	-	3000	3000	3000	3000	3000	3000	3000				
(XXS)	0.552	14.02	13.69					20.39	6.22	2500	-	2500	-	3000	3000	3000	3000	3000	3000	3000			
3	3 1/2	88.9	40(Std) 80(XS) 160 (XXS)					0.083	2.11	3.03	4.51	1.38	850	-	1000	-	1200	1310	1480	1590	1710	1850	1990
								0.109	2.77	3.95	5.88	1.79	-	-	-	1570	1720	1940	2090	2240	2430	2620	
								0.125	3.18	4.51	6.72	2.05	1290	-	1500	-	1800	1970	2230	2400	2570	2790	3000
				0.141	3.58	5.06	7.54	2.30	-	-	-	2030	2220	2510	2710	2900	3000	3000					
				0.156	3.96	5.57	8.30	2.53	1600	-	1870	-	2250	2460	2780	3000	3000	3000	3000				
				0.172	4.37	6.11	9.10	2.77	1770	-	2060	-	2480	2710	3000	3000	3000	3000	3000				
				0.188	4.78	6.65	9.91	3.02	1930	-	2260	-	2710	2970	3000	3000	3000	3000	3000				
				40(Std)	0.216	5.49	7.58	11.29	3.44	2220	-	2500	-	3000	3000	3000	3000	3000	3000	3000			
				0.250	6.35	8.68	12.93	3.94	2500	-	2500	-	3000	3000	3000	3000	3000	3000	3000				
				80(XS)	0.281	7.14	9.66	14.39	4.39	2500	-	2500	-	3000	3000	3000	3000	3000	3000	3000			
				160	0.300	7.62	10.25	15.27	4.65	2500	-	2500	-	3000	3000	3000	3000	3000	3000	3000			
				(XXS)	0.438	11.13	14.32	21.33	6.50	-	-	-	3000	3000	3000	3000	3000	3000	3000	3000			
				0.600	15.24	18.58	27.67	8.44	2500	-	2500	-	3000	3000	3000	3000	3000	3000	3000	3000			
				3 1/2	4	101.6	40(Std) 80(XS)	0.083	2.11	3.47	5.17	1.58	750	-	870	-	1050	1150	1290	1390	1490	1620	1740
								0.109	2.77	4.53	6.75	2.06	980	-	1140	-	1370	1500	1700	1830	1960	2130	2290
								0.125	3.18	5.17	7.70	2.35	1120	-	1310	-	1580	1720	1950	2100	2250	2440	2630
0.141	3.58	5.81	8.65					2.64	1270	-	1480	-	1700	1950	2200	2370	2540	2750	2960				
0.156	3.96	6.40	9.53					2.91	1400	-	1640	-	1970	2150	2430	2620	2810	3000	3000				
0.172	4.37	7.03	10.47					3.19	1550	-	1810	-	2170	2370	2680	2890	3000	3000	3000				
0.188	4.78	7.65	11.39					3.47	1690	-	1970	-	2370	2590	2930	3000	3000	3000	3000				
40(Std)	0.226	5.74	9.11					13.57	4.14	2030	-	2370	-	2850	3000	3000	3000	3000	3000	3000			
0.250	6.35	10.01	14.91					4.54	2250	-	2620	-	3000	3000	3000	3000	3000	3000	3000	3000			
80(XS)	0.281	7.14	11.16					16.62	5.07	2530	-	2800	-	3000	3000	3000	3000	3000	3000	3000			
0.318	8.08	12.50	18.62					5.68	2800	-	2800	-	3000	3000	3000	3000	3000	3000	3000	3000			

API Pipes

Size						Weight			Hydrostatic Test Pressure																				
Outside Diameter			Wall Thickness			lb/ft	kg/m	kg/ft	API 5L				API 5LX																
									A		B		X42	X46	X52	X56	X60	X65	X70										
Nominal Size	in	mm	Sch No	in	mm	Std	Alt	Std	Alt																				
1/4	0.405	10.3	40(Std) 80(XS)	0.068 0.096	1.73 2.41	0.24 0.31	0.36 0.45	- -	700 850	- -	700 850	- -	- -	- -	- -	- -	- -												
1/4	0.540	13.7	40(Std) 80(XS)	0.088 0.119	2.24 3.02	0.42 0.54	0.63 0.80	- -	700 850	- -	700 850	- -	- -	- -	- -	- -	- -												
3/8	0.675	17.1	40(Std) 80(XS)	0.091 0.126	2.31 3.20	0.57 0.74	0.85 1.10	- -	700 850	- -	700 850	- -	- -	- -	- -	- -	- -												
1/2	0.840	21.3	40(Std) 80(XS) (XXS)	0.109 0.147 0.294	2.77 3.73 7.47	0.85 1.09 1.71	1.27 1.62 2.55	- -	700 850 1000	- -	700 850 1000	- -	- -	- -	- -	- -	- -												
3/4	1.050	26.7	40(Std) 80(XS) (XXS)	0.113 0.154 0.308	2.87 3.91 7.82	1.13 1.47 2.44	1.68 2.19 3.63	- -	700 850 1000	- -	700 850 1000	- -	- -	- -	- -	- -	- -												
1	1.315	33.4	40(Std) 80(XS) 160 (XXS)	0.133 0.179 0.250 0.358	3.38 4.55 6.35 9.09	1.68 2.17 2.84 3.66	2.50 3.23 4.23 5.45	0.76 0.99 1.29 1.66	700 850 1000	- -	700 850	- -	- -	- -	- -	- -	- -												
1 1/4	1.660	42.2	40(Std) 80(XS) 160 (XXS)	0.140 0.191 0.250 0.382	3.56 4.85 6.35 9.70	2.27 3.00 3.76 5.21	3.38 4.47 5.60 7.76	1.03 1.36 1.71 2.37	1200 1800 2200	- -	1300 1900 2300	- -	- -	- -	- -	- -	- -												
1 1/2	1.900	48.3	40(Std) 80(XS) 160 (XXS)	0.145 0.200 0.281 0.400	3.68 5.08 7.14 10.16	2.72 3.63 4.86 6.41	4.05 5.41 7.24 9.55	1.23 1.65 2.21 2.91	1200 1800 2200	- -	1300 1900 2300	- -	- -	- -	- -	- -	- -												
2	2.375	60.3	40(Std) 80(XS) 160 (XXS)	0.083 0.109 0.125 0.141 0.154 0.172 0.188 0.218 0.250 0.281 0.344 0.436	2.11 2.77 3.18 3.58 3.91 4.37 4.78 5.54 6.35 7.14 8.74 11.07	2.03 2.64 3.00 3.36 3.65 4.05 4.39 5.02 5.67 6.41 7.46 9.03	3.02 3.93 4.47 5.00 5.44 6.03 6.54 7.48 8.45 9.35 11.11 13.45	0.92 1.20 1.36 1.53 1.66 1.84 1.99 2.28 2.57 2.85 3.39 4.10	1260 1470	- -	1760 1930 2180 2350 2520 2730 2940	- -	1930 2180 2350 2520 2730 2940	- -	2180 2350 2520 2730 2940	- -	2350 2520 2730 2940	- -	2520 2730 2940	- -	2730 2940	- -	2940						
2 1/2	2.875	73.0	40(Std) 80(XS) 160 (XXS)	0.083 0.109 0.125 0.141 0.156 0.172 0.188 0.203 0.216 0.250 0.276 0.375 0.552	2.11 2.77 3.18 3.58 3.96 4.37 4.78 5.16 5.49 6.35 7.01 9.52 14.02	2.47 3.22 3.67 4.12 4.53 4.97 5.40 5.79 6.13 7.01 7.66 10.01 13.69	3.68 4.80 5.47 6.14 6.75 7.40 8.04 8.62 9.13 10.44 11.41 14.91 20.39	1.12 1.46 1.67 1.87 2.06 2.26 2.45 2.63 2.78 3.18 3.48 4.54 6.22	1040 1040	- -	1460 1590 1800 1940 2080 2250 2430	- -	1590 1800 1940 2080 2250 2430	- -	1800 1940 2080 2250 2430	- -	1940 2080 2250 2430	- -	2080 2250 2430	- -	2250 2430	- -	2430						
3	3.500	88.9	40(Std) 80(XS) 160 (XXS)	0.083 0.109 0.125 0.141 0.156 0.172 0.188 0.216 0.250 0.281 0.438 0.600	2.11 2.77 3.18 3.58 3.96 4.37 4.78 5.49 6.35 7.14 11.13 15.24	3.03 3.95 4.51 5.06 5.57 6.11 6.65 7.58 8.68 9.66 14.32 18.58	4.51 5.88 6.72 7.54 8.30 9.10 9.91 11.29 12.93 14.39 21.33 27.67	1.38 1.79 2.05 2.30 2.53 2.77 3.02 3.44 3.94 4.39 6.50 8.44	850 1000 1290 1600 1870 2060 2260 2500 2500 2500	- -	1000 1500 1870 2060 2260 2500 2500	- -	1500 1870 2060 2260 2500 2500	- -	1870 2060 2260 2500 2500	- -	2060 2260 2500 2500	- -	2260 2500 2500	- -	2500	- -	2500						
3 1/2	4	101.6	40(Std) 80(XS)	0.083 0.109 0.125 0.141 0.156 0.172 0.188 0.226 0.250 0.281 0.318	2.11 2.77 3.18 3.58 3.96 4.37 4.78 5.74 6.35 7.14 8.08	3.47 4.53 5.17 5.81 6.40 7.03 7.65 9.11 10.01 11.16 12.50	5.17 6.75 7.70 8.65 9.53 10.47 11.39 13.57 14.91 16.62 18.62	1.58 2.06 2.35 2.64 2.91 3.19 3.47 4.14 4.54 5.07 5.68	750 980 1120 1270 1400 1550 1690 2030 2250 2530 2800	- -	870 1140 1310 1480 1640 1810 1970 2370 2620 2800	- -	1140 1310 1480 1640 1810 1970 2370 2620 2800	- -	1310 1480 1640 1810 1970 2370 2620 2800	- -	1480 1640 1810 1970 2370 2620 2800	- -	1640 1810 1970 2370 2620 2800	- -	1810 1970 2370 2620 2800	- -	1970 2370 2620 2800	- -	2370 2620 2800	- -	2620 2800	- -	2800

API Pipes (Continued)

Size						Weight			Hydrostatic Test Pressure							
Outside Diameter			Wall Thickness			lb/ft	kg/m	kg/ft	API 5L				API 5LX			
Nominal Size	in	mm	Sch No	in	mm				A		B		X42	X46	X52	X56
4	4 1/2	114.3	40(Std)	0.083	2.11	3.92	5.84	1.78	660	770	930	1020	1150	1240		
				0.109	2.77	5.11	7.61	2.32	870	1020						
				0.125	3.18	5.84	8.70	2.65	1000	1170	1400	1530	1730	1870		
				0.141	3.58	6.56	9.77	2.98	1130	1320	1580	1730	1960	2110		
				0.156	3.96	7.24	10.78	3.29	1250	1460	1750	1930	2160	2330		
				0.172	4.37	7.95	11.84	3.61	1380	1610	1930	2110	2390	2570		
				0.188	4.78	8.66	12.90	3.93	1500	1750	2110	2310	2610	2810		
				0.203	5.16	9.32	13.88	4.23	1620	1890	2270	2490	2810	3000		
				0.219	5.56	10.01	14.91	4.54	1750	2040	2450	2690	3000	3000		
				0.237	6.02	10.79	16.07	4.90	1900	2210	2650	2910	3000	3000		
			60	0.250	6.35	11.35	16.91	5.15	2000	2330	2800	3000	3000	3000		
				0.281	7.14	12.66	18.66	5.75	2250	2620	3000	3000	3000	3000		
				0.312	7.92	13.96	20.79	6.34	2500	2800	3000	3000	3000	3000		
				0.337	8.56	14.98	22.31	6.80	2700	2800	3000	3000	3000	3000		
				0.438	11.13	19.00	28.30	8.53	2800	2800	3000	3000	3000	3000		
				0.531	13.49	22.51	33.53	10.22	2800	2800	3000	3000	3000	3000		
				0.674	17.12	27.54	41.02	12.50	2800	2800	3000	3000	3000	3000		
			80(XS)	0.083	2.11	4.86	7.24	2.21	540	630						
				0.125	3.18	7.26	10.81	3.30	810	940						
				0.156	3.96	9.01	13.42	4.09	1010	1180						
				0.188	4.78	10.79	16.07	4.90	1220	1420						
				0.219	5.56	12.50	18.62	5.68	1420	1650						
				0.258	6.55	14.62	21.76	6.63	1670	1950						
				0.281	7.14	15.85	23.61	7.20	1820	2120						
				0.312	7.92	17.50	26.05	7.94	2020	2360						
				0.344	8.74	19.17	28.55	8.70	2230	2600						
				0.375	9.52	20.78	30.94	9.43	2430	2800						
5	5 1/2	141.3	40(Std)	0.083	2.11	5.80	8.54	2.63	450	560	660	790	860	980	1050	
				0.109	2.77	7.59	11.37	3.45	590	740	860	1040	1140	1280	1380	
				0.125	3.18	8.68	12.93	3.94	680	850	990	1190	1300	1470	1580	
				0.141	3.58	9.78	14.54	4.43	770	960	1120	1340	1470	1660	1790	
				0.156	3.96	10.78	16.36	4.89	850	1060	1240	1480	1620	1840	1980	
				0.173	4.37	11.85	17.65	5.38	930	1170	1360	1640	1790	2030	2180	
				0.188	4.78	12.92	19.24	5.87	1020	1280	1490	1790	1960	2210	2380	
				0.203	5.16	13.92	20.73	6.32	1100	1380	1590	1930	2110	2390	2579	
				0.219	5.56	14.98	22.31	6.80	1190	1490	1740	2080	2280	2580	2780	
				0.250	6.35	17.02	25.35	7.73	1360	1700	1980	2380	2600	2940	3000	
			60	0.280	7.11	18.97	28.26	8.61	1520	1900	2220	2660	2920	3000	3000	
				0.312	7.92	21.04	31.34	9.55	1700	2120	2470	2970	3000	3000	3000	
				0.344	8.74	23.08	34.38	10.48	1870	2340	2730	3000	3000	3000	3000	
				0.375	9.52	25.03	37.28	11.36	2040	2550	2980	3000	3000	3000	3000	
				0.432	10.97	28.57	42.56	12.97	2350	2850	2740	2800	3000	3000	3000	
				0.500	12.70	32.77	48.12	14.55	2720	2800	2800	3000	3000	3000	3000	
				0.562	14.27	36.89	54.20	16.52	2800	2800	2800	2800	3000	3000	3000	
				0.625	15.88	40.05	59.65	18.18	2800	2800	2800	2800	3000	3000	3000	
				0.719	18.26	45.85	67.53	21.59	2800	2800	2800	2800	3000	3000	3000	
				0.864	21.95	55.10	79.16	24.77	2800	2800	2800	2800				
6	6 3/4	168.3	40(Std)	0.125	3.18	11.35	16.91	5.15	520	650	610	760	910	1000	1130	1220
				0.156	3.96	14.11	21.02	6.41	650	810	760	950	1140	1250	1410	1520
				0.188	4.78	16.94	25.03	7.69	780	980	920	1140	1370	1500	1700	1830
				0.203	5.16	18.26	27.20	8.29					1480	1620	1840	2000
				0.219	5.56	19.66	29.28	8.93	910	1140	1070	1330	1600	1750	1980	2130
				0.250	6.35	22.36	33.51	10.15	1040	1300	1220	1520	1830	2000	2260	2430
				0.277	7.04	24.70	36.79	11.21	1160	1450	1350	1690	2020	2220	2510	2700
				0.312	7.92	27.70	41.26	12.58	1300	1630	1520	1900	2280	2500	2820	3000
				0.322	8.19	28.55	42.53	12.95	1340	1680	1570	1960	2350	2580	2910	3000
				0.344	8.74	30.42	45.31	13.81	1440	1790	1680	2090	2510	2750	3000	3000
			60	0.375	9.52	33.04	49.21	15.00	1570	1960	1830	2280	2740	3000	3000	3000
				0.406	10.31	35.64	53.09	16.16								
				0.438	11.13	38.30	57.05	17.39	1830	2290	2130	2670	3000	3000	3000	3000
				0.500	12.70	43.39	64.63	19.70	2090	2610	2430	2800	3000	3000	3000	3000
				0.562	14.27	48.40	72.39	21.97	2350	2800	2740	2800	3000	3000	3000	3000
				0.594	15.09	50.95	75.89	23.13								
				0.625	15.88	53.40	79.54	24.24	2610	2800	2800	2800	3000	3000	3000	3000
				0.719	18.26	60.71	90.43	27.56	2800	2800	2800	2800	3000	3000	3000	3000
				0.812	20.62	67.76	100.93	30.76								
				0.875	22.22	72.42	107.87	32.88	2800	2800	2800	2800				
				0.906	23.01	74.69	111.25	33.91								

API Pipes (Continued)

Size						Weight			Hydrostatic Test Pressure							
Outside Diameter			Wall Thickness			lb/ft	kg/m	kg/ft	API 5L				API 5LX			
Nominal Size	in	mm	Sch No	in	mm				A		B		X42	X46	X52	X56
									Std.	Alt.	Std.	Alt.				
16	16	406.4	40(XS)	0.438	11.13	72.80	108.44	33.02	990	1230	1150	1440	1950	2140	2420	2610
				0.469	11.91	77.79	115.87	35.29					2090	2290	2590	2790
				0.500	12.70	82.77	123.29	37.54	1120	1410	1310	1640	2230	2440	2760	2980
				0.562	14.27	92.66	138.02	42.03	1260	1580	1480	1840	2510	2750	3000	3000
				0.625	15.88	102.63	152.87	46.55	1410	1760	1640	2050	2790	3000	3000	3000
				0.656	16.66	107.50	160.12	48.80								
			60	0.688	17.48	112.51	167.58	51.03	1550	1940	1810	2260	3000	3000	3000	3000
				0.750	19.05	122.15	181.94	55.41	1690	2110	1970	2460	3000	3000	3000	3000
				0.812	20.62	131.71	196.18	59.74	1830	2280	2130	2660	3000	3000	3000	3000
				0.844	21.44	136.61	203.48	62.02								
				0.875	22.22	141.34	210.53	64.11	1970	2460	2300	2800	3000	3000	3000	3000
				0.938	23.83	150.89	224.75	68.44	2110	2640	2460	2800	3000	3000	3000	3000
			80	1.000	25.40	160.20	238.62	72.67	2250	2800	2620	2800	3000	3000	3000	3000
				1.062	26.97	169.43	252.37	76.85	2390	2800	2790	2800	3000	3000	3000	3000
				1.125	28.58	178.72	266.20	81.07	2530	2800	2800	2800	3000	3000	3000	3000
18	18	457.2	10	0.188	4.78	35.76	53.26	16.22	380	470	440	550	750	820	920	990
				0.219	5.56	41.59	61.95	18.87	440	550	510	640	870	950	1080	1160
				0.250	6.35	47.39	70.59	21.50	500	620	580	730	990	1090	1230	1320
				0.281	7.14	53.18	79.21	24.12	560	700	660	820	1110	1220	1380	1490
				0.312	7.92	58.94	87.79	26.74	620	780	730	910	1240	1360	1530	1650
				0.344	8.74	64.87	96.62	29.43	690	860	800	1000	1360	1490	1690	1820
			20	0.375	9.52	70.59	105.14	32.02	750	940	880	1090	1490	1630	1840	1980
				0.406	10.31	76.29	113.63	34.61					1610	1760	1990	2150
				0.438	11.13	82.15	122.36	37.26	880	1100	1020	1280	1740	1900	2150	2320
				0.469	11.91	87.81	130.79	39.83					1860	2040	2300	2480
				0.500	12.70	93.45	139.19	42.39	1000	1250	1170	1460	1980	2170	2460	2640
				0.562	14.27	104.67	155.91	47.48	1120	1400	1310	1640	2230	2440	2760	2970
			40	0.625	15.88	115.98	172.75	52.61	1250	1560	1460	1820	2480	2720	3000	3000
				0.688	17.48	127.21	189.48	57.70	1380	1720	1610	2010	2730	2990	3000	3000
				0.750	19.05	138.17	205.80	62.67	1500	1880	1750	2190	2980	3000	3000	3000
				0.812	20.62	149.06	222.02	67.61	1620	2030	1890	2370	3000	3000	3000	3000
				0.875	22.22	160.03	238.36	72.59	1750	2190	2040	2550	3000	3000	3000	3000
				0.938	23.83	170.92	254.59	77.53	1880	2340	2190	2740	3000	3000	3000	3000
			60	1.000	25.40	181.56	270.43	82.36	2000	2500	2330	2800	3000	3000	3000	3000
				1.062	26.97	192.11	286.15	87.14	2120	2660	2480	2800	3000	3000	3000	3000
				1.125	28.58	202.75	302.00	91.97	2250	2800	2620	2800	3000	3000	3000	3000
				1.187	30.15	213.14	317.47	96.68	2370	2800	2770	2800				
				1.188	30.18	213.31	317.73	96.76					3000	3000	3000	3000
				1.250	31.75	223.61	333.07	101.43	2500	2800	2800	2800	3000	3000	3000	3000
20	20	508.0	10	0.219	5.56	46.27	68.92	20.99	390	490	460	570	830	910	1020	1100
				0.250	6.35	52.73	78.54	23.92	450	560	520	660	940	1040	1170	1260
				0.281	7.14	59.18	88.15	26.84	510	630	590	740	1060	1160	1320	1420
				0.312	7.92	65.60	97.71	29.76	560	700	660	820	1180	1290	1460	1570
				0.344	8.74	72.21	107.56	32.75	620	770	720	900	1300	1420	1610	1730
				0.375	9.52	78.60	117.07	35.65	680	840	790	980	1420	1550	1760	1890
			20	0.406	10.31	84.96	126.55	38.54					1530	1680	1900	2050
				0.438	11.13	91.51	136.30	41.51	790	990	920	1150	1660	1810	2050	2210
				0.469	11.91	97.83	145.72	44.38					1770	1940	2190	2360
				0.500	12.70	104.13	151.40	47.23	900	1120	1050	1310	1890	2070	2340	2520
				0.562	14.27	116.67	173.78	52.92	1010	1260	1180	1480	2120	2330	2630	2750
				0.625	15.88	129.33	192.64	58.66	1120	1410	1310	1640	2360	2590	2750	2750
			40	0.688	17.48	141.90	211.36	64.37	1240	1550	1440	1810	2600	2750	2750	2750
				0.750	19.05	154.19	229.67	69.94	1350	1690	1580	1970	2750	2750	2750	2750
				0.812	20.62	166.40	247.85	75.48	1460	1830	1710	2130	2750	2750	2750	2750
				0.875	22.22	179.72	266.20	81.07	1580	1970	1840	2300	2750	2750	2750	2750
				0.938	23.83	190.96	284.43	86.62	1690	2110	1970	2460	2750	2750	2750	2750
				1.000	25.40	202.92	302.25	92.04	1800	2250	2100	2620	2750	2750	2750	2750
			60	1.062	26.97	214.80	319.94	97.43	1910	2390	2230	2750	2750	2750	2750	2750
				1.125	28.58	226.78	337.79	102.87	2020	2530	2360	2750	2750	2750	2750	2750
				1.187	30.15	238.50	355.25	108.18	2140	2670	2490	2750				
				1.188	30.15	238.68							2750	2750	2750	2750
				1.250	31.76	250.31	372.84	113.54	2250	2760	2620	2750	2750	2750	2750	2750
				1.312	33.32	261.86	390.04	118.78	2360	2750	2750	2750	2750	2750	2750	2750
22	22	558.8	20	1.375	34.92	273.51	407.39	124.06	2480	2750	2750	2750	2750	2750	2750	
				0.219	5.56	50.94	75.88	23.11	360	450	420	520	750	820	930	1000
				0.250	6.35	58.07	86.50	26.34	410	510	480	600	860	940	1060	1150
				0.281	7.14	65.18	97.09	29.57	460	570	540	670	970	1060	1200	1290
				0.312	7.92	72.27	107.65	32.78	510	640	600	740	1070	1170	1330	1430
				0.344	8.74	79.56	118.50	36.09	560	700	660	820	1180	1290	1460	1580
22	22	558.8	20	0.375	9.52	6.61	129.01	39.29	610	770	720	890	1290	1410	1600	1720

API Pipes (Continued)

Size						Weight			Hydrostatic Test Pressure							
Outside Diameter			Wall Thickness			lb/ft	kg/m	kg/ft	API 5L				API 5LX			
Nominal Size	in	mm	Sch No	in	mm				A		B		X42	X46	X52	X56
									Std	Alt	Std	Alt				
22	22	558.8	30	0.406	10.31	93.63	139.46	42.47					1400	1530	1730	1860
				0.438	11.13	100.86	150.23	45.75	720	900	840	1050	1510	1650	1860	2010
				0.469	11.91	107.85	160.64	48.92					1610	1770	2000	2150
				0.500	12.70	114.81	171.01	52.08	820	1020	950	1190	1720	1880	2130	2290
				0.562	14.27	128.67	191.65	58.36	920	1150	1070	1340	1930	2120	2390	2500
				0.625	15.88	142.68	212.52	64.72	1020	1280	1190	1490	2150	2350	2500	2500
			60	0.688	17.48	156.60	233.26	71.03	1130	1410	1310	1640	2360	2500	2500	2500
				0.750	19.05	170.21	253.53	77.21	1230	1530	1430	1790	2500	2500	2500	2500
				0.812	20.62	183.75	273.70	83.35	1330	1660	1550	1940	2500	2500	2500	2500
				0.875	22.22	197.41	294.02	89.55	1430	1790	1670	2090	2500	2500	2500	2500
				0.938	23.83	211.00	314.28	95.71	1530	1920	1790	2240	2500	2500	2500	2500
				1.000	25.40	224.28	334.07	101.73	1640	2050	1910	2390	2500	2500	2500	2500
			80	1.062	26.97	237.48	353.73	107.72	1740	2170	2030	2500	2500	2500	2500	2500
				1.125	28.58	250.81	373.58	113.77	1840	2300	2150	2500	2500	2500	2500	2500
				1.188	30.15	263.85	393.00	119.68	1940	2430	2270	2500	2500	2500	2500	2500
				1.250	31.75	277.01	412.61	125.65	2050	2500	2390	2500	2500	2500	2500	2500
				1.312	33.32	289.88	431.78	129.22	2150	2500	2500	2500	2500	2500	2500	2500
				1.375	34.92	302.88	451.14	137.39	2250	2500	2500	2500	2500	2500	2500	2500
			100	1.437	36.50	315.58	470.06	143.15	2350	2500	2500	2500	2500	2500	2500	2500
				1.438	36.53								2500	2500	2500	2500
				1.500	38.10	328.41	489.17	148.97	2450	2500	2500	2500	2500	2500	2500	2500
24	24	609.6	10	0.250	6.35	63.41	94.45	28.76	380	470	440	550	790	860	980	1050
				0.281	7.14	71.18	106.02	32.29	420	530	490	610	890	970	1100	1180
				0.312	7.92	78.93	117.57	35.80	470	580	550	680	980	1080	1220	1310
			20	0.344	8.74	86.91	129.45	39.42	520	640	600	750	1080	1190	1340	1440
				0.375	9.52	94.62	140.94	42.92	560	700	660	820	1180	1290	1460	1580
				0.406	10.31	102.31	152.39	46.41					1280	1400	1580	1710
			30	0.438	11.13	110.22	164.17	50.00	660	820	770	960	1380	1510	1710	1840
				0.469	11.91	117.86	175.55	53.46					1480	1620	1830	1970
				0.500	12.70	125.49	186.92	56.92	750	940	880	1090	1580	1720	1950	2100
			40	0.562	14.27	140.68	209.54	63.81	840	1050	980	1230	1770	1940	2190	2300
				0.625	15.88	156.03	232.41	70.78	940	1170	1090	1370	1970	2160	2300	2300
				0.688	17.48	171.29	255.14	77.70	1030	1290	1200	1500	2170	2300	2300	2300
			60	0.750	19.05	186.23	277.39	84.47	1120	1410	1310	1640	2300	2300	2300	2300
				0.812	20.62	201.09	299.52	91.21	1220	1520	1420	1780	2300	2300	2300	2300
				0.875	22.22	216.10	321.88	98.02	1310	1640	1530	1910	2300	2300	2300	2300
			80	0.938	23.83	231.03	344.12	104.80	1410	1760	1640	2050	2300	2300	2300	2300
				1.000	25.40	245.64	365.88	111.42	1500	1880	1750	2190	2300	2300	2300	2300
				1.062	26.97	260.12	387.52	118.01	1590	1990	1860	2300	2300	2300	2300	2300
			100	1.125	28.58	274.84	409.37	124.65	1690	2110	1970	2300	2300	2300	2300	2300
				1.187	30.15	289.20	430.76	131.18	1780	2230	2080	2300	2300	2300	2300	2300
				1.188	30.18	289.44							2300	2300	2300	2300
			120	1.250	31.75	303.71	452.38	137.76	1880	2300	2190	2300	2300	2300	2300	2300
				1.312	33.32	317.91	473.53	144.20	1970	2300	2300	2300	2300	2300	2300	2300
				1.375	34.92	332.25	494.89	150.71	2060	2300	2300	2300	2300	2300	2300	2300
			140	1.437	36.50	346.28	515.78	157.07	2160	2300	2300	2300	2300	2300	2300	2300
				1.438	36.53	346.50							2300	2300	2300	2300
				1.500	38.10	360.45	536.89	163.50	2250	2300	2300	2300	2300	2300	2300	2300
			160	1.562	39.67	374.31	557.53	169.79	2300	2300	2300	2300	2300	2300	2300	2300
26	26	660.4	10	0.250	6.35	68.75	102.40	31.19	350	430	400	500	730	800	900	970
				0.281	7.14	77.18	114.96	35.01	390	490	450	570	820	890	1010	1090
				0.312	7.92	85.60	127.59	38.83	430	540	500	630	910	990	1120	1210
			20	0.344	8.74	94.26	140.40	42.76	480	600	560	690	1000	1100	1240	1330
				0.375	9.52	102.63	152.87	46.55	520	650	610	760	1090	1190	1350	1450
				0.406	10.31	110.98	165.30	50.34					1180	1290	1460	1570
			30	0.438	11.13	119.57	178.10	54.24	610	760	710	880	1270	1390	1580	1700
				0.469	11.91	127.88	190.48	58.01					1360	1490	1690	1820
				0.500	12.70	136.17	202.83	61.77	690	870	810	1010	1450	1590	1800	1940
			40	0.562	14.27	152.68	227.42	69.26	780	970	910	1130	1630	1790	2000	2000
				0.625	15.88	169.38	252.29	76.83	870	1080	1010	1260	1820	1990	2000	2000
				0.688	17.48	185.99	277.03	84.37	950	1190	1110	1390	2000	2000	2000	2000
			60	0.750	19.05	202.25	301.25	91.74	1040	1300	1210	1510	2000	2000	2000	2000
				0.812	20.62	218.43	325.35	99.08	1120	1410	1310	1640	2000	2000	2000	2000
				0.875	22.22	234.79	349.72	106.50	1210	1510	1410	1770	2000	2000	2000	2000
			80	0.938	23.83	251.07	373.97	113.89	1300	1620	1520	1890	2000	2000	2000	2000
				1.000	25.40	267.00	397.70	121.11	1380	1730	1620	2000	2000	2000	2000	2000
28	28	711.2	10	0.250	6.35	74.09	110.36	33.61	320	400	370	470	680	740	840	900
				0.281	7.14	83.19	123.91	37.73	360	450	420	530	760	830	940	1010
				0.312	7.92	92.26	137.42	41.85	400	500	470	580	840	920	1040	1120

API Pipes (Continued)

Size						Weight			Hydrostatic Test Pressure							
Outside Diameter			Wall Thickness			lb/ft	kg/m	kg/ft	API 5L				API 5LX			
Nominal Size	in	mm	Sch No	in	mm				A		B		X42	X46	X52	X56
									Std	Alt	Std	Alt				
28	28	711.2	20	0.344	8.74	101.61	151.35	46.09					930	1020	1150	1240
				0.375	9.52	110.64	164.80	50.19	480	600	560	700	1010	1110	1250	1350
				0.406	10.31	119.65	178.22	54.27					1100	1200	1360	1450
				0.438	11.13	128.93	192.04	58.48	560	700	660	820	1180	1300	1460	1580
				0.469	11.91	137.90	205.40	62.55					1270	1390	1570	1690
				0.500	12.70	146.85	218.73	66.61	640	800	750	940	1350	1480	1670	1800
				0.562	14.27	164.69	245.31	74.70	720	900	840	1050	1520	1660	1880	2020
				0.625	15.88	182.73	272.18	82.89	800	1000	940	1170	1690	1850	2090	2250
				0.688	17.48	200.68	298.91	91.03	880	1100	1030	1290	1860	2030	2300	2480
				0.750	19.05	218.27	325.11	99.01	960	1210	1120	1410	2020	2220	2510	2700
			30	0.812	20.62	235.78	351.19	106.95	1040	1300	1220	1520	2190	2400	2710	2920
				0.875	22.22	253.58	377.56	114.98	1120	1410	1310	1640	2360	2590	2920	3000
				0.938	23.83	271.10	403.80	122.97	1210	1510	1410	1760	2530	2770	3000	3000
				1.000	25.40	288.36	429.51	130.80	1290	1610	1500	1880	2700	2960	3000	3000
			10	0.250	6.35	79.43	118.31	36.03	300	370	350	440	630	690	780	840
				0.281	7.14	89.19	132.85	40.46	340	420	390	490	710	780	880	940
				0.312	7.92	98.93	147.36	44.87	370	470	440	550	790	860	970	1050
				0.344	8.74	108.95	162.28	49.42					870	950	1070	1160
				0.375	9.52	118.65	176.73	53.82	450	560	520	660	940	1040	1170	1260
				0.406	10.31	128.32	191.13	58.21					1020	1120	1270	1360
				0.438	11.13	138.29	205.98	62.73	530	660	610	770	1100	1210	1370	1470
				0.469	11.91	147.92	220.33	67.10					1180	1290	1460	1580
				0.500	12.70	157.53	234.64	71.46	600	750	700	880	1260	1380	1560	1680
				0.562	14.27	176.69	263.18	80.15	670	840	790	980	1420	1550	1750	1890
30	30	762.0	30	0.625	15.88	196.08	292.06	88.94	750	940	880	1090	1580	1720	1950	2100
				0.688	17.48	215.38	320.81	97.70	830	1030	960	1200	1730	1900	2150	2310
				0.750	19.05	234.29	348.97	106.27	900	1120	1060	1310	1890	2070	2340	2520
				0.812	20.62	253.12	377.02	114.82	970	1220	1140	1420	2050	2240	2530	2730
				0.875	22.22	272.17	405.40	123.46	1050	1310	1220	1530	2200	2420	2730	2940
				0.938	23.83	291.14	433.65	132.06	1130	1410	1310	1640	2360	2590	2930	3000
				1.000	25.40	309.72	461.53	140.49	1200	1500	1400	1750	2520	2760	3000	3000
				1.062	26.97	328.22	488.88	148.88	1270	1590	1490	1860	2680	2930	3000	3000
				1.125	28.58	346.93	516.75	157.37	1350	1690	1580	1970	2840	3000	3000	3000
				1.188	30.18	365.56	544.60	165.82	1430	1780	1660	2080	2990	3000	3000	3000
				1.250	31.75	383.81	571.68	174.10	1500	1880	1750	2190	3000	3000	3000	3000
			10	0.250	6.35	84.77	126.26	38.45	280	350	330	410	580	650	730	790
				0.281	7.14	95.19	141.79	43.18	320	400	370	460	660	730	820	890
				0.312	7.92	105.59	157.28	47.90	350	440	410	510	740	810	910	980
				0.344	8.74	116.30	173.23	52.75					810	890	1010	1080
				0.375	9.52	126.66	188.66	57.45	420	530	490	620	890	970	1100	1180
				0.406	10.31	136.99	204.05	62.14					960	1050	1190	1280
				0.438	11.13	147.64	219.91	66.97	490	620	570	720	1030	1130	1280	1380
				0.469	11.91	157.94	235.25	71.64					1110	1210	1370	1480
				0.500	12.70	168.21	250.55	76.30	560	700	660	820	1180	1290	1460	1580
				0.562	14.27	188.70	281.07	85.58	630	790	740	920	1330	1450	1640	1770
30	30	812.8	40	0.625	15.88	209.43	311.95	95.00	700	880	820	1030	1480	1620	1830	1970
				0.688	17.48	230.08	342.70	104.36	770	970	900	1130	1630	1780	2010	2170
				0.750	19.05	250.31	372.64	113.54	840	1050	980	1230	1770	1940	2190	2360
				0.812	20.62	270.47	402.87	122.69	910	1140	1070	1330	1920	2100	2380	2560
				0.875	22.22	290.86	433.24	131.93	980	1230	1150	1440	2070	2260	2560	2760
				0.938	23.83	311.17	463.49	141.15	1060	1320	1230	1540	2220	2430	2740	2950
				1.000	25.40	329.58	493.14	150.18	1120	1410	1310	1640	2360	2590	2920	3000
				1.062	26.97	350.90	522.74	159.17	1190	1490	1390	1740	2510	2750	3000	3000
				1.125	28.58	370.96	552.54	168.27	1270	1580	1480	1850	2660	2910	3000	3000
				1.188	30.18	390.94	582.31	177.33	1340	1670	1560	1950	2810	3000	3000	3000
34	34	863.6	10	0.250	6.35	90.11	134.22	40.87	260	330	310	390	560	610	690	740
				0.281	7.14	101.19	150.72	45.90	300	370	350	430	620	680	770	830
				0.312	7.92	112.25	167.20	50.92	330	410	390	480	690	760	860	920
				0.344	8.74	123.65	184.18	56.09					760	840	950	1020
				0.375	9.52	134.67	200.59	61.09	400	500	460	580	830	910	1030	1110
				0.406	10.31	145.67	216.98	66.08					900	990	1120	1200
				0.438	11.13	157.00	233.85	71.22	460	580	540	680	970	1070	1210	1300
				0.469	11.91	167.95	250.16	76.18					1040	1140	1290	1390
				0.500	12.70	178.89	266.46	81.14	530	660	620	770	1110	1220	1380	1480
				0.562	14.27	200.70	298.94	91.04	600	740	690	870	1250	1370	1550	1670
				20	0.625	15.88	222.78	331.83	101.05	660	830	770	970	1390	1520	1720
			0.688		17.48	244.77	364.58	111.03	730	910	850	1060	1530	1680	1890	2040
			0.750		19.05	266.32	396.70	120.81	790	990	930	1160	1670	1830	2060	2220
			0.812		20.62	287.81	428.69	130.55	860	1070	1000	1250	1810	1980	2240	2410

API Pipes (Continued)

Size						Weight			Hydrostatic Test Pressure								
Outside Diameter			Wall Thickness			lb/ft	kg/m	kg/ft	API 5L				API 5LX				
Nominal Size	in	mm	Sch No	in	mm				A		B		X42	X46	X52	X56	
									Std	Alt	Std	Alt					
34	34	863.6			0.875	22.22	309.55	461.07	140.41	930	1160	1080	1350	1950	2130	2410	2590
					0.938	23.83	331.21	493.34	150.24	990	1240	1160	1450	2090	2280	2580	2780
					1.000	25.40	352.44	524.96	162.13	1060	1320	1240	1540	2220	2440	2750	2960
					1.062	26.97	373.59	556.46	169.46	1120	1410	1310	1650	2360	2590	2920	3000
					1.125	28.58	394.99	588.34	179.17	1190	1490	1390	1740	2500	2740	3000	3000
					1.188	30.18	416.31	620.09	188.84	1260	1570	1470	1830	2640	2890	3000	3000
					1.250	31.75	437.21	651.22	198.32	1320	1650	1540	1930	2780	3000	3000	3000
36	36	914.4	10	0.250	6.35	95.45	142.17	43.30	250	310	290	360	520	580	650	700	
				0.281	7.14	107.20	159.67	48.63	280	350	330	410	590	650	730	790	
				0.312	7.92	118.92	177.13	53.94	310	390	360	450	660	720	810	870	
				0.344	8.74	131.00	195.12	59.42					720	790	890	960	
				0.375	9.52	142.68	212.52	64.72	380	470	440	550	790	860	980	1050	
			20	0.406	10.31	154.34	229.89	70.01					850	930	1060	1140	
				0.438	11.13	166.35	247.78	75.46	440	550	510	640	920	1010	1140	1230	
				0.469	11.91	177.97	265.09	80.73					980	1080	1220	1310	
				0.500	12.70	189.57	282.36	85.99	500	620	580	730	1050	1150	1300	1400	
				0.562	14.27	212.70	316.82	96.48	560	700	660	820	1180	1290	1460	1570	
			30	0.625	15.88	236.12	351.72	107.11	620	780	730	910	1310	1440	1620	1750	
				0.688	17.48	259.42	386.48	117.70	690	860	800	1000	1440	1580	1790	1930	
				0.750	19.05	282.35	420.56	128.07	750	940	880	1090	1580	1720	1950	2100	
				0.812	20.62	305.16	454.54	138.42	810	1020	950	1180	1710	1870	2110	2270	
				0.875	22.22	328.24	488.91	148.89	880	1090	1020	1280	1840	2010	2280	2450	
			40	0.938	23.83	351.25	523.19	159.33	940	1170	1090	1370	1970	2160	2440	2630	
				1.000	25.40	373.80	556.78	169.56	1000	1250	1170	1460	2100	2300	2600	2800	
				1.062	26.97	396.27	590.24	179.75	1060	1330	1240	1550	2230	2440	2760	2970	
				1.125	28.58	419.02	624.13	190.07	1130	1410	1310	1640	2360	2590	2930	3000	
				1.188	30.18	441.69	657.90	200.35	1190	1480	1390	1730	2490	2730	3000	3000	
1.250	31.75	463.91	690.99	210.43	1250	1560	1460	1820	2630	2870	3000	3000					
38	38	965.2		0.312	7.92	125.58	187.05	56.96	300	370	340	430	620	680	770	830	
				0.344	8.74	138.35	206.07	62.76	330	410	380	480	680	750	850	910	
				0.375	9.52	150.69	224.45	68.35	360	440	410	520	750	820	920	990	
				0.406	10.31	163.01	242.80	73.94	380	480	450	560	810	880	1000	1080	
				0.438	11.13	175.71	261.72	79.70	410	520	480	610	870	950	1080	1160	
				0.469	11.91	187.99	280.01	85.27	440	560	520	650	930	1020	1160	1240	
				0.500	12.70	200.25	298.27	90.83	470	590	550	690	990	1090	1230	1330	
				0.562	14.27	224.71	334.71	101.93	530	670	620	780	1120	1220	1380	1490	
				0.625	15.88	249.48	371.60	113.16	590	740	690	860	1240	1360	1540	1660	
				0.688	17.48	274.16	408.36	124.36	650	810	760	950	1370	1500	1690	1830	
				0.750	19.05	298.37	444.42	135.34	710	890	830	1040	1490	1630	1850	1990	
				0.812	20.62	322.50	480.36	146.29	770	960	900	1120	1620	1770	2000	2150	
				0.875	22.22	346.93	516.75	157.37	830	1040	970	1210	1740	1910	2160	2320	
				0.938	23.83	371.28	553.02	168.41	890	1110	1040	1300	1870	2040	2310	2490	
				1.000	25.40	395.16	588.59	179.24	950	1180	1110	1380	1990	2180	2460	2650	
				1.062	26.97	418.96	624.04	190.04	1010	1260	1170	1470	2110	2310	2620	2820	
				1.125	28.58	443.05	659.92	200.97	1070	1330	1240	1550	2240	2450	2770	2980	
				1.188	30.18	467.06	695.69	211.86	1130	1410	1310	1640	2360	2590	2930	3000	
				1.250	31.75	490.61	730.76	222.54	1180	1480	1380	1730	2490	2720	3000	3000	
				40	40	1016.0		0.312	7.92	132.25	196.99	59.99	280	350	330	410	590
0.344	8.74	145.69	217.01					66.08	310	390	360	450	650	710	800	870	
0.375	9.52	158.70	236.38					71.99	340	420	390	490	710	780	880	940	
0.406	10.31	171.68	255.72					77.87	370	460	430	530	770	840	950	1020	
0.438	11.13	185.06	275.65					83.94	390	490	460	570	830	910	1020	1100	
	0.469	11.91	198.01				294.94	89.82	420	530	490	620	890	970	1100	1180	
	0.500	12.70	210.93				314.18	95.68	450	560	520	660	940	1040	1170	1260	
	0.562	14.27	236.71				352.58	107.37	510	630	590	740	1060	1160	1320	1420	
	0.625	15.88	262.83				391.49	119.22	560	700	660	820	1180	1290	1460	1580	
	0.688	17.48	288.86				430.25	131.03	620	770	720	900	1300	1420	1610	1730	
	0.750	19.05	314.39				468.28	142.61	680	840	790	980	1420	1550	1760	1890	
	0.812	20.62	339.84				506.19	154.15	730	910	850	1070	1530	1680	1900	2050	
	0.875	22.22	365.62				544.59	165.85	790	980	920	1150	1650	1810	2050	2200	
	0.938	23.83	391.32				582.87	177.50	840	1060	980	1230	1770	1940	2190	2360	
	1.000	25.40	416.52				620.41	188.93	900	1120	1050	1310	1890	2070	2340	2520	
	1.062	26.97	441.64				657.82	200.33	960	1190	1120	1390	2010	2200	2490	2680	
	1.125	28.58	467.08				695.72	211.87	1010	1270	1180	1480	2130	2330	2630	2830	
	1.188	30.18	492.44				733.49	223.37	1070	1340	1250	1560	2250	2460	2780	2990	
	1.250	31.75	517.31				770.53	234.65	1130	1410	1310	1640	2360	2590	2930	3000	
42	42	1066.8		0.344	8.74	153.04	227.95	69.42	290	370	340	430	620	680	770	830	
				0.375	9.52	166.71	248.31	75.62	320	400	380	470	680	740	840	900	
				0.406	10.31	180.35	268.63	81.81	350	430	410	510	730	800	900	970	
				0.438	11.13	194.42	289.59	88.19	380	470	440	550	790	860	980	1060	

API Pipes (Continued)

Size						Weight			Hydrostatic Test Pressure							
Outside Diameter			Wall Thickness			lb/ft	kg/m	kg/ft	API 5L				API 5LX			
									A		B		X42	X46	X52	X56
in	in	mm	Sch No	in	mm				Std	Alt	Std	Alt				
52	52	1320.8		0.375	9.52	206.76	307.97	93.79								
				0.406	10.31	223.72	333.23	101.48								
				0.438	11.13	241.20	359.27	109.41	300	380	350	440	640	700	790	850
				0.469	11.91	258.11	384.45	117.08	320	410	380	470	680	750	840	910
				0.500	12.70	275.01	409.63	124.74	350	430	400	500	730	800	900	970
				0.562	14.27	308.74	459.87	140.04	390	490	450	570	820	890	1010	1090
				0.625	15.88	342.93	510.79	155.55	430	540	500	630	910	1000	1130	1210
				0.688	17.48	377.03	561.69	171.02	480	600	560	690	1000	1100	1240	1330
				0.750	19.05	410.51	611.45	186.21	520	650	610	760	1090	1190	1350	1450
				0.812	20.62	443.91	661.20	201.36	560	700	660	820	1180	1290	1460	1570
				0.875	22.22	477.76	711.62	216.71	610	760	710	880	1270	1390	1580	1700
				0.938	23.83	511.53	761.92	232.03	650	810	760	950	1360	1490	1690	1820
				1.000	25.40	544.68	811.30	247.07	690	870	810	1010	1450	1590	1800	1940
				1.062	26.97	577.75	860.56	262.07	740	920	860	1070	1540	1690	1910	2060
				1.125	28.58	611.26	910.47	277.27	780	970	910	1140	1640	1790	2030	2180
				1.188	30.18	644.69	960.27	292.43	820	1030	960	1200	1730	1890	2140	2300
				1.250	31.75	677.51	1009.15	307.32	870	1080	1010	1260	1820	1990	2250	2420
56	56	1422.4		0.375	9.52	222.78	340.77	101.05								
				0.406	10.31	241.06	359.06	109.34								
				0.438	11.13	259.91	387.14	117.90	280	350	330	410	590	650	730	790
				0.469	11.91	278.15	414.30	126.17	300	380	350	440	630	690	780	840
				0.500	12.70	296.37	441.44	134.43	320	400	380	470	680	740	840	900
				0.562	14.27	332.75	495.63	150.94	360	450	420	530	760	830	940	1010
				0.625	15.88	369.63	550.56	167.66	400	500	470	590	840	920	1040	1120
				0.688	17.48	406.42	60.536	184.35	440	550	520	650	930	1020	1150	1240
				0.750	19.05	442.55	659.18	200.74	480	600	560	700	1010	1110	1250	1350
				0.812	20.62	478.60	712.87	217.09	520	650	610	760	1100	1200	1360	1460
				0.875	22.22	515.14	767.30	233.67	560	700	660	820	1180	1290	1460	1570
				0.938	23.83	551.60	821.61	250.21	600	750	700	880	1270	1390	1570	1690
				1.000	25.40	587.40	874.93	266.44	640	800	750	940	1350	1480	1670	1800
				1.062	26.97	623.12	928.14	282.65	680	850	800	1000	1430	1570	1780	1910
				1.125	28.58	659.32	982.06	299.07	720	900	840	1050	1520	1660	1880	2020
				1.188	30.18	695.45	1035.87	315.46	760	950	890	1110	1600	1760	1990	2140
				1.250	31.75	730.91	1088.69	331.54	800	1000	940	1170	1690	1850	2090	2250
60	60	1524.0		0.375	9.52	238.80	355.69	108.32								
				0.406	10.31	258.40	384.89	117.21								
				0.438	11.13	278.62	415.00	126.38								
				0.469	11.91	298.19	444.15	135.26								
				0.500	12.70	317.73	473.26	144.12	300	380	350	440	639	690	780	840
				0.562	14.27	356.76	531.39	161.83	340	420	390	490	710	780	880	940
				0.625	15.88	396.33	590.33	179.78	380	470	440	550	790	860	980	1050
				0.688	17.48	435.71	649.14	197.88	420	520	480	600	870	950	1070	1160
				0.750	19.05	474.59	706.90	215.27	450	560	530	660	950	1030	1170	1260
				0.812	20.62	513.29	764.55	232.83	490	610	570	710	1020	1120	1270	1360
				0.875	22.22	552.52	822.98	250.62	530	660	610	770	1100	1210	1370	1470
				0.938	23.83	591.67	881.29	268.38	560	700	660	820	1180	1290	1460	1580
				1.000	25.40	630.12	936.56	285.82	600	750	700	880	1260	1380	1560	1680
				1.062	26.97	668.48	995.70	303.22	640	800	740	930	1340	1470	1660	1780
				1.125	28.58	707.38	1053.64	320.87	680	840	790	980	1420	1550	1760	1890
				1.188	30.18	746.20	1111.40	338.48	710	890	830	1040	1500	1650	1850	2000
				1.250	31.75	784.31	1168.23	355.76	750	940	880	1090	1580	1720	1950	2100
64	64	1625.6		0.375	9.52	254.82	379.55	115.59								
				0.406	10.31	275.75	410.73	125.08								
				0.438	11.13	297.33	442.87	134.87								
				0.469	11.91	318.22	473.99	144.34								
				0.500	12.70	339.09	505.07	153.81	280	350	330	410	590	650	730	790
				0.562	14.27	380.76	567.14	172.71	320	400	370	460	660	730	820	890
				0.625	15.88	423.03	630.10	191.89	350	440	410	510	740	810	910	980
				0.688	17.48	464.21	692.93	211.02	390	480	450	560	810	890	1010	1080
				0.750	19.05	506.63	754.63	229.81	420	530	490	610	890	970	1100	1180
				0.812	20.62	547.98	816.22	248.56	460	570	530	670	960	1050	1190	1280
				0.875	22.22	589.90	878.66	267.58	490	620	570	720	1030	1130	1280	1380
				0.938	23.87	631.74	940.98	285.56	530	660	620	770	1110	1210	1370	1480
				1.000	25.40	672.84	1002.20	303.20	560	700	660	820	1180	1290	1460	1570
				1.062	26.97	713.85	1063.28	323.80	600	750	700	870	1250	1370	1550	1670
				1.125	28.58	755.44	1125.22	342.67	630	790	740	920	1330	1460	1650	1770
				1.188	30.18	796.65	1187.06	361.50	670	840	780	970	1400	1540	1740	1870
				1.250	31.75	837.71	1247.77	379.99	700	880	820	1030	1480	1620	1830	1970