



mGas

M GAS STEEL SDN BHD

API Pipes

API Pipes

Specification		API 5L		API 5LU	
Outside Diameter	1,900 in. and smaller	+ 0.016 in. + 0.75%	- 0.031 in. - 0.75%	Less than 20 in. 20 in. and larger	+ 0.75% + 1.00% - 0.75% - 1.00%
	20 in. through 36 in. Non-expanded Cold-expanded	+ 1.00% + 0.75%	- 1.00% - 0.25%		
Pipe Body	Larger than 36 in. Non-expanded Cold-expanded*2	+ 1.00% + 1/4 in.	- 1.00% - 1/8 in.	10-3/4 in. and smaller	+ 1/16 in. (measured with ring gage) + 3/32 in. (measured with ring gage) + 3/32 in. (measured with diameter tape)
	10-3/4 in. and smaller	+ 1/15 in. (measured with ring gage)	- 1/64 in. (measured with ring gage)		
Pipe Ends*1	12-3/4 in. through 20 in.	+ 3/32 in. (measured with ring gage)	- 1/32 in. (measured with ring gage)	12-3/4 in. through 20 in. Larger than 20 in.	+ 1/16 in. (measured with ring gage) + 3/32 in. (measured with ring gage) + 3/32 in. (measured with diameter tape)
	Larger than 20 in. (22 in. and larger)	+ 3/32 in. (measured with diameter tape)	- 1/32 in. (measured with diameter tape)		
Wall Thickness	Welded Pipe: 2,875 in. OD and smaller	Grade A, B + 20.0% + 18.0% + 15.0% + 17.5%	- 12.5% - 12.5% - 12.5% - 10.0%	Welded Pipe: 18 in. OD and smaller 20 in. OD and larger	+ 15.0% + 19.5% - 12.5% - 8.0%
	3-1/2 in. OD and smaller	Grade A, B + 20.0% + 18.0% + 15.0% + 17.5%	- 12.5% - 12.5% - 12.5% - 10.0%		
Weight	Seamless Pipe: 2,875 in. OD and smaller	Grade A, B + 20.0% + 18.0% + 15.0% + 17.5%	- 12.5% - 12.5% - 12.5% - 10.0%	Seamless Pipe: 18 in. OD and smaller 20 in. OD and larger	+ 15.0% + 17.5% - 12.5% - 10.0%
	3-1/2 in. OD and smaller	Grade A, B + 20.0% + 18.0% + 15.0% + 17.5%	- 12.5% - 12.5% - 12.5% - 10.0%		
Straightness	Standard weight	+ 10.0%	- 3.5%	Regular weight	+ 10.0% - 3.5%
	Regular weight	+ 10.0%	- 5.0%		
Out of Roundness (for pipe larger than 20 in.)	Extra strong weight	+ 10.0%	- 5.0%	Special light weight	+ 10.0% - 5.0%
	Double extra strong weight	+ 10.0%	- 5.0%		
Pipe End Preparation	Special plain end weave	+ 10.0%	- 5.0%	Max. OD - specified OD Specified OD - min. OD	Max. 75% 0.2%
	For pipe 4-1/2 in. OD and larger	+ 10.0%	- 5.0%		
Tolerances	For pipe 2/38 in. OD and larger	+ 1% x specified OD - 1% x specified OD	- 1% x specified OD - 1% x specified OD	Bevel angle 30° ± 5° Root face 1/16 in. ± 0° Squareness for 10-3/4 in. through 20 in. OD and larger max. 1/16 in.	% x specified OD % x specified OD 32 in. OD and larger max. 1/16 in.
	For pipe 2/38 in. OD and larger	+ 1% x specified OD - 1% x specified OD	- 1% x specified OD - 1% x specified OD		

Tolerances (Excerpts from API Specifications)

Tensile and Chemical Requirements (Excerpts from API Specifications, 1983 edition)

Application	Grade	Tensile Requirements						
		Yield Strength			Tensile Strength			Elongation
		psi min	MPa min	kg/mm ² min	psi min	MPa min	kg/mm ² min	% min
Line Pipe	API 5L Grade A	30,000	207	21.1	48,000	331	33.7	$e = \frac{625,000}{U} \frac{A^{0.2}}{0.9}$
	API 5L Grade B	35,000	241	24.6	60,000	413	42.2	
	API 5L Grade X42	42,000	289	29.5	60,000	413	42.2	
	API 5L Grade X46	46,000	317	32.3	63,000	434	44.3	
	API 5L Grade X52	52,000	358	36.6	(1) 66,000 * ¹ (2) 72,000	(1) 455 (2) 496	46.4 50.6	
	API 5L Grade X56 * ⁶	56,000	386	39.2	(1) 71,000 * ¹ (2) 75,000	(1) 489 (2) 517	49.9 52.7	
	API 5L Grade X60 * ³ * ⁶	60,000	413	42.2	(1) 75,000 * ¹ (2) 78,000	(1) 517 (2) 537	52.7 54.8	
	API 5L Grade X65 * ⁸ * ¹¹	65,000	448	45.7	(1) 77,000 * ¹ (2) 80,000	(1) 530 (2) 551	54.1 56.2	
	API 5L Grade X70 * ⁶ * ¹¹	70,000	482	49.2	82,000	565	57.6	
	API 5LU Grade X80	80,000	551	56.2	* ⁴ 95,000/125,000	655/862	66.8/87.8	
	API 5LU Grade X100	100,000	689	70.3	* ⁴ 110,000/135,000	758/931	77.3/94.9	

- *1 (1) Wall thickness > 0.375 in., OD ≥ 20 in.
Any wall thickness, OD < 20 in.
(2) Wall thickness ≤ 0.375 in., OD ≥ 20 in.

- *2 The minimum elongation in 2 inches (50.8 mm) shall be determined by the following formula:

$$e = \frac{625,000}{U} \frac{A^{0.2}}{0.9}$$

where:

e = minimum elongation in 2 inches (50.8 mm) in per cent rounded to the nearest 1/2 per cent.

A = cross sectional area of the tensile test specimen in square inches, based on specified outside diameter or nominal specimen width and specified wall thickness rounded to the nearest 0.01 sq. in., or 0.75 sq. in., whichever is smaller.

U = specified tensile strength, psi.

- *3 The minimum tensile strength for grade X60 electric-resistance welded pipe in all sizes and wall thicknesses shall be 75,000 psi (52.7 kg/mm²).

- *4 Tensile strength means min. value/max. value

- *5 Figures in parentheses are values for seamless pipe. Upper line value means non-expanded, Lowerline value means cold-expanded. In grades X42 through X65, for each reduction of 0.01 per cent below the maximum carbon content, an increase of 0.05 per cent manganese above the specified maximum is permissible, up to a maximum of 1.45 per cent for X52 and lower and up to a maximum of 1.60 per cent for grades higher than X52.

- *6 Other chemical analyses may be furnished by agreement between purchaser and manufacturer.

- *7 Either columbium, vanadium, titanium, or a combination thereof, shall be used at the discretion of the manufacturer.

Tolerances (Excerpts from API Specifications)

Chemical Requirements for Ladle Analyses, %							
C ^{*5}	Si	Mn ^{*5}	P	S	Cb	V	Ti
max	max	max	max	max	min	min	min
0.21 (0.22)		0.90	0.04	0.05			
0.26 (0.27)		1.15	0.04	0.05			
^{*13} 0.28 (0.29)		1.25	0.04	0.05			
0.30 (0.31) ^{*13} 0.28 (0.29)		1.35 1.25	0.04	0.05			
0.30 (0.31) ^{*13} 0.28 (0.29)		1.35 1.25	0.04	0.05			
0.26		1.35	0.04	0.05	0.005 ^{*7}	0.02 ^{*7}	0.03 ^{*7}
0.26		1.35	0.04	0.05	0.005 ^{*7}	0.02 ^{*7}	0.03 ^{*7}
0.26		1.40	0.04	0.05	0.005 ^{*9}	0.02 ^{*9}	
0.23 ^{*10}		1.60 ^{*10}	0.04	0.05			
0.26 ^{*12}	0.35	1.40 ^{*12}	0.04	0.05			
0.26 ^{*12}	0.35	1.40 ^{*12}	0.04	0.05			

*8 For grades X65 in sizes 16in. and larger with wall thickness 0.500 in. and less, the chemical composition shall be as shown or as agreed upon between the purchaser and manufacturer. For other sizes and wall thicknesses the chemical composition shall be as agreed upon between the purchaser and manufacturer. (Applicable to welded pipe only.)

*9 Either columbium or vanadium or a combination of both shall be used at the discretion of the manufacturer.

*10 For each reduction of 0.01 per cent below the specified maximum carbon content, an increase of 0.05 per cent manganese above the specified maximum is permissible.

*11 For seamless pipe of grades X65 and X70, the chemical composition shall be agreed upon between the purchaser and manufacturer.

*12 For each reduction of 0.01% below the specified maximum carbon content, an increase of 0.05% manganese above the specified maximum is permissible, up to a maximum of 1.50%.

*13 For carbon steels, the maximum carbon content shall be 0.28 percent.

Tolerances (Excerpts from API Specifications)

Mechanical Values					Chemical Analysis							
	Tensile	Yield	Elongation	Reduction of Area	As Supplied	Mn	P	S	Mo	Cr	Ni	Div
Material	Strength N/mm2	Strength (Min)	% min.	%	%	%	% max.	% max.	%	%	%	%
A53-Grade A	min. 330	205	variable	max. 0.25	-	max. 0.95	0.050	0.80				
A53-Grade B	min. 415	240	variable	max. 0.30	-	max. 1.20	0.050	0.60				
A106-Grade A	min. 330	205	35	max. 0.25	min. 0.10	0.27-0.93	0.048	0.058				
A106-Grade B	min. 415	240	30	max. 0.30	min. 0.10	0.29-1.06	0.048	0.058				
A179	Hardness Rb. max. 72			0.06-0.18	-	0.27-0.63	0.048	0.058				
A333-Grade 1	min. 379	207	35	max. 0.30	-	0.40-1.06	0.050	0.60				
A333-Grade 6	min. 414	241	30	max. 0.30	min. 0.10	0.29-1.06	0.048	0.058				
A333-Grade 3	min. 448	241	30	max. 0.19	0.18-0.37	0.31-0.64	0.050	0.050			3.18-3.82	
A335-Grade P1	min. 379	207	30	0.10-0.20	0.10-0.50	0.30-0.80	0.045	0.045	0.44-0.65			
A335-Grade P5	min. 414	207	30	max. 0.30	0.10-0.50	0.30-0.80	0.045	0.045	0.44-0.65			

mGas

M GAS STEEL SDN BHD

Tolerances (Excerpts from API Specifications)

Technical Standards			Comparable Qualities					
Material	Specification Standard	Dimensional Standard	ASTM	API	BS	DIN	Euro Standard EU 25-72	DIV
A53	A53	ANSI-B36.10		API-5L-Gr.A	3601-320/360	St. 37.0	FE 310	
A53	A53	ANSI-B36.10		API-5L-Gr.B	3601-410	St. 44.0	Fe 360B/430B	BS4360-43B/C
A106/A530	A106/A530	ANSI-B 36.10		API-5L-Gr.A	3602-S360	St. 35.8		
A106/A530	A106/A530	ANSI-B 36.10		API-5L-Gr.B	3602-S410	St. 45.8		

A179/A450	A179/A450	ANSI-B 36.10			3059-320/360	St. 35.8		
A333/A530	A333/A530	ANSI-B 36.10			360 1HFS27LT50	TT St.35N		
A333/A530	A333/A530	ANSI-B 36.10			3603HFS503LT100	TT St.35V		
A333/A530	A333/A530					10 Ni 14		
A335/A530	A335/A530	ANSI-B 36.10				15 Mo 3/16 Mo 5		
A335/A530	A335/A530	ANSI-B 36.10			3604-625	12 Cr Mo 19.5		
A335/A530	A335/A530	ANSI-B 36.10			3604-620-440-460	13 Cr Mo 44		
A335/A530	A335/A530	ANSI-B 36.10			3604-620-440-460	13 Cr Mo 44		
A335/A530	A335/A530	ANSI-B 36.10			3604-620-440	10 Cr Mo 910		
API-5L	API-5L	API-5L	A53 Gr.A		3601-320/360	St. 37.0	Fe 310	St E 210.7
API-5L	API-5L	API-5L	A53 Gr.B		3601-410-4360-43B/C	St. 44.0	Fe 360B/430B	St E 240.7
API-5L	API-5L	API-5L			4360-43 B/C	St. E 290.7	Fe 430B	
API-5L	API-5L	API-5L				St. E 320.7		
API-5L	API-5L	API-5L			4360-50 B/C/D	St. E 360.7	Fe510B/C/D	St. E 355
API-5L	API-5L	API-5L				St. E 385.7		
API-5L	API-5L	API-5L				St. E 415.7		
BS3059 part1	BS3059 part1	BS3059 part1	A179			St.35.8/St.37.8		
BS3059 part2	BS3059 part2	BS3059 part2	A179			St.35.8/St.37.8		
BS3601	BS3601	BS1600/BS3600	A53 Gr.A	5L-Gr.A		St. 33	Fe 310	
BS3601	BS3601	BS1600/BS3600	A53 Gr.B	5L-Gr.B		St.37.0/St.37.2	Fe 360B	A672-B60
BS3601	BS3601	BS1600/BS3600	A53 Gr.B	5L-Gr.B	4360-43B/C	St.44.0/St.44.3	Fe430B/C	A672-B65/C65
BS3601	BS3601	BS1600/BS3600	A106 Gr.B	5L-Gr.B		St.37.0/St.37.2	Fe 360B	
BS3601	BS3601	BS1600/BS3600	A106 Gr.B	5L-Gr.B		St.44.0/St.44.3		
BS3602 part1	BS3602 part1	BS1600/BS3600	A106 Gr.B	5L-Gr.B		St.35.8/St.37.8		
BS3602 part1	BS3602 part1	BS1600/BS3600	A106 Gr.B	5L-Gr.B		St.45.8		
BS3602 part1	BS3602 part1	BS1600/BS3600		5L-Gr.X52	4360-50 B/C/D	St.52/St.52.3	Fe510 B/C/D	
BS3602 part2	BS3602 part2	BS1600/BS3600	A672 B65/C65	5L-Gr.B	4360-43 B/C	St. E240.7	Fe 430 B/C	
BS3603	BS3603	BS1600/BS3600	A333 Gr.6			TT St. 35V		
BS3603	BS3603	BS1600/BS3600	A333 Gr.3			10 Ni 14		
BS3604	BS3604	BS1600/BS3600	A335 P12			13 Cr Mo 44		
BS3604	BS3604	BS1600/BS3600	A335 P22			10 Cr Mo 910		

BS4360 BS4360 BS1600 A672 B65/C65 5L-X52 St. 52.3 Fe 510B St E 355

API Pipes

Size						Weight			Hydrostatic Test Pressure										
Outside Diameter			Wall Thickness			lb/ft	kg/m	kg/ft	API 5L				API 5LX						
									A		B		X42	X46	X52	X56	X60	X65	X70
Nominal Size	in	mm	Sch. No.	in	mm				Std.	Alt.	Std.	Alt.							
½	0.405	10.3	40(Std) 80(XS)	0.068 0.096	1.73 2.41	0.24 0.31	0.36 0.45	-	700 850	-	700 850	-	-	-	-	-	-	-	
¾	0.540	13.7	40(Std) 80(XS)	0.088 0.119	2.24 3.02	0.42 0.54	0.63 0.80	-	700 850	-	700 850	-	-	-	-	-	-	-	
¾	0.675	17.1	40(Std) 80(XS)	0.091 0.126	2.31 3.20	0.57 0.74	0.85 1.10	-	700 850	-	700 850	-	-	-	-	-	-	-	
1	0.840	21.3	40(Std) 80(XS) (XXS)	0.109 0.147 0.294	2.77 3.73 7.47	0.85 1.09 1.71	1.27 1.62 2.55	-	700 850 1000	-	700 850 1000	-	-	-	-	-	-	-	
1¼	1.050	26.7	40(Std) 80(XS) (XXS)	0.113 0.154 0.308	2.87 3.91 7.82	1.13 1.47 2.44	1.68 2.19 3.63	-	700 850 1000	-	700 850 1000	-	-	-	-	-	-	-	
1½	1.315	33.4	40(Std) 80(XS) 160 (XXS)	0.133 0.179 0.250 0.358	3.38 4.55 6.35 9.09	1.68 2.17 2.84 3.66	2.50 3.23 4.23 5.45	0.76 0.99 1.29 1.66	700 850 - 1000	-	700 850 - 1000	-	-	-	-	-	-	-	
1¾	1.660	42.2	40(Std) 80(XS) 160 (XXS)	0.140 0.191 0.250 0.382	3.56 4.85 6.35 9.70	2.27 3.00 3.76 5.21	3.38 4.47 5.60 7.76	1.03 1.36 1.71 2.37	1200 1800 - 2200	-	1300 1900 - 2300	-	-	-	-	-	-	-	
2	1.900	48.3	40(Std) 80(XS) 160 (XXS)	0.145 0.200 0.281 0.400	3.68 5.08 7.14 10.16	2.72 3.63 4.86 6.41	4.05 5.41 7.24 9.55	1.23 1.65 2.21 2.91	1200 1800 - 2200	-	1300 1900 - 2300	-	-	-	-	-	-	-	
2½	2¼	60.3	40(Std) 80(XS) 160 (XXS)	0.083 0.109 0.125 0.141 0.154 0.172 0.188 0.218 0.250 0.281 0.344 0.436	2.11 2.77 3.18 3.58 3.91 4.37 4.78 5.54 6.35 7.14 8.74 11.07	2.03 2.64 3.00 3.36 3.65 4.05 4.39 5.02 5.67 6.28 7.46 9.03	3.02 3.93 4.47 5.00 5.44 6.03 6.54 7.48 8.45 9.35 11.11 13.45	0.92 1.20 1.36 1.53 1.66 1.84 1.99 2.28 2.57 2.85 3.39 4.10	1260 - - - 2330 2500 2500 2500 2500 2500 2500 2500	-	1470 - - - 2500 2500 2500 2500 2500 2500 2500	-	1760 2310 2650 2990 3000 3000 3000 3000 3000 3000 3000 3000	1930 2530 2910 3000 3000 3000 3000 3000 3000 3000 3000 3000	2180 2860 3000 3000 3000 3000 3000 3000 3000 3000 3000 3000	2350 3000 3000 3000 3000 3000 3000 3000 3000 3000 3000 3000	2520 3000 3000 3000 3000 3000 3000 3000 3000 3000 3000 3000	2730 3000 3000 3000 3000 3000 3000 3000 3000 3000 3000 3000	2940 3000 3000 3000 3000 3000 3000 3000 3000 3000 3000 3000
2½	2¾	73.0	40(Std) 80(XS) 160 (XXS)	0.083 0.109 0.125 0.141 0.156 0.172 0.188 0.203 0.216 0.250 0.276 0.375 0.552	2.11 2.77 3.18 3.58 3.96 4.37 4.78 5.16 5.49 6.35 7.01 9.52 14.02	2.47 3.22 3.67 4.12 4.53 4.97 5.40 5.79 6.13 7.01 7.66 10.01 13.69	3.68 4.80 5.47 6.14 6.75 7.40 8.04 8.62 9.13 10.44 11.41 14.91 20.39	1.12 1.46 1.67 1.87 2.06 2.26 2.45 2.63 2.78 3.18 3.48 4.54 6.22	1040 - - - 1950 2150 2350 2500 2500 2500 2500 2500 2500	-	1040 - - - 2280 2500 2500 2500 2500 2500 2500 2500	-	1460 1910 2190 2470 2730 3000 3000 3000 3000 3000 3000 3000 3000	1590 2090 2400 2710 3000 3000 3000 3000 3000 3000 3000 3000 3000	1800 2370 2710 3000 3000 3000 3000 3000 3000 3000 3000 3000 3000	1940 2550 2920 3000 3000 3000 3000 3000 3000 3000 3000 3000 3000	2080 2730 2900 3000 3000 3000 3000 3000 3000 3000 3000 3000 3000	2250 2960 3000 3000 3000 3000 3000 3000 3000 3000 3000 3000 3000	2430 3000 3000 3000 3000 3000 3000 3000 3000 3000 3000 3000 3000
3	3½	88.9	40(Std) 80(XS) 160 (XXS)	0.083 0.109 0.125 0.141 0.156 0.172 0.188 0.216 0.250 0.281 0.300 0.438 0.600	2.11 2.77 3.18 3.58 3.96 4.37 4.78 5.49 6.35 7.14 7.62 11.13 15.24	3.03 3.95 4.51 5.06 5.57 6.11 6.65 7.58 8.68 9.66 10.25 14.32 18.58	4.51 5.88 6.72 7.54 8.30 9.10 9.91 11.29 12.93 14.39 15.27 21.33 27.67	1.38 1.79 2.05 2.30 2.53 2.77 3.02 3.44 3.94 4.39 4.65 6.50 8.44	850 - 1290 1600 1770 1930 2220 2500 2500 2500 2500 2500 2500	-	1000 - 1500 1870 2060 2260 2500 2500 2500 2500 2500 2500	-	1200 1570 1800 2030 2250 2480 2710 3000 3000 3000 3000 3000 3000	1310 1720 1970 2220 2460 2780 3000 3000 3000 3000 3000 3000 3000	1480 1940 2230 2510 2780 3000 3000 3000 3000 3000 3000 3000 3000	1590 2090 2400 2710 3000 3000 3000 3000 3000 3000 3000 3000 3000	1710 2240 2570 2900 3000 3000 3000 3000 3000 3000 3000 3000 3000	1850 2430 2790 3000 3000 3000 3000 3000 3000 3000 3000 3000 3000	1990 2620 3000 3000 3000 3000 3000 3000 3000 3000 3000 3000 3000
3½	4	101.6	40(Std) 80(XS)	0.083 0.109 0.125 0.141 0.156 0.172 0.188 0.226 0.250 0.281 0.318	2.11 2.77 3.18 3.58 3.96 4.37 4.78 5.74 6.35 7.14 8.08	3.47 4.53 5.17 5.81 6.40 7.03 7.65 9.11 10.01 11.16 12.50	5.17 6.75 7.70 8.65 9.53 10.47 11.39 13.57 14.91 16.62 18.62	1.58 2.06 2.35 2.64 2.91 3.19 3.47 4.14 4.54 5.07 5.68	750 980 1120 1270 1400 1550 1690 2030 2250 2530 2800	-	870 1140 1310 1480 1640 1810 1970 2370 2620 2800 2800	-	1050 1370 1580 1700 1970 2170 2370 2850 3000 3000 3000	1150 1500 1720 1950 2150 2370 2590 3000 3000 3000 3000	1290 1700 1950 2200 2430 2680 2930 3000 3000 3000 3000	1390 1830 2100 2370 2540 2890 3000 3000 3000 3000 3000	1490 1960 2250 2540 2750 3000 3000 3000 3000 3000 3000	1620 2130 2440 2750 3000 3000 3000 3000 3000 3000 3000	1740 2290 2630 2960 3000 3000 3000 3000 3000 3000 3000

API Pipes

Size						Weight			Hydrostatic Test Pressure										
Outside Diameter			Wall Thickness			lb/ft	kg/m	kg/ft	API 5L				API 5LX						
									A		B		X42	X46	X52	X56	X60	X65	X70
Nominal Size	in	mm	Sch. No.	in	mm				Std.	Alt.	Std.	Alt.							
½	0.405	10.3	40(Std) 80(XS)	0.068 0.096	1.73 2.41	0.24 0.31	0.36 0.45	-	700 850	-	700 850	-	-	-	-	-	-	-	
¾	0.540	13.7	40(Std) 80(XS)	0.088 0.119	2.24 3.02	0.42 0.54	0.63 0.80	-	700 850	-	700 850	-	-	-	-	-	-	-	
¾	0.675	17.1	40(Std) 80(XS)	0.091 0.126	2.31 3.20	0.57 0.74	0.85 1.10	-	700 850	-	700 850	-	-	-	-	-	-	-	
1	0.840	21.3	40(Std) 80(XS) (XXS)	0.109 0.147 0.294	2.77 3.73 7.47	0.85 1.09 1.71	1.27 1.62 2.55	-	700 850 1000	-	700 850 1000	-	-	-	-	-	-	-	
1	1.050	26.7	40(Std) 80(XS) (XXS)	0.113 0.154 0.308	2.87 3.91 7.82	1.13 1.47 2.44	1.68 2.19 3.63	-	700 850 1000	-	700 850 1000	-	-	-	-	-	-	-	
1	1.315	33.4	40(Std) 80(XS) 160 (XXS)	0.133 0.179 0.250 0.358	3.38 4.55 6.35 9.09	1.68 2.17 2.84 3.66	2.50 3.23 4.23 5.45	0.76 0.99 1.29 1.66	700 850 - 1000	-	700 850 - 1000	-	-	-	-	-	-	-	
1¼	1.660	42.2	40(Std) 80(XS) 160 (XXS)	0.140 0.191 0.250 0.382	3.56 4.85 6.35 9.70	2.27 3.00 3.76 5.21	3.38 4.47 5.60 7.76	1.03 1.36 1.71 2.37	1200 1800 - 2200	-	1300 1900 - 2300	-	-	-	-	-	-	-	
1½	1.900	48.3	40(Std) 80(XS) 160 (XXS)	0.145 0.200 0.281 0.400	3.68 5.08 7.14 10.16	2.72 3.63 4.86 6.41	4.05 5.41 7.24 9.55	1.23 1.65 2.21 2.91	1200 1800 - 2200	-	1300 1900 - 2300	-	-	-	-	-	-	-	
2	2¾	60.3	40(Std) 80(XS) 160 (XXS)	0.083 0.109 0.125 0.141 0.154 0.172 0.188 0.218 0.250 0.281 0.344 0.436	2.11 2.77 3.18 3.58 3.91 4.37 4.78 5.54 6.35 7.14 8.74 11.07	2.03 2.64 3.00 3.36 3.65 4.05 4.39 5.02 5.67 6.28 7.46 9.03	3.02 3.93 4.47 5.00 5.44 6.03 6.54 7.48 8.45 9.35 11.11 13.45	0.92 1.20 1.36 1.53 1.66 1.84 1.99 2.28 2.57 2.85 3.39 4.10	1260 - - - 2330 2500 2500 2500 2500 2500 2500 2500	-	1470 - - - 2500 2500 2500 2500 2500 2500 2500 2500	-	1760 2310 2650 2990 3000 3000 3000 3000 3000 3000 3000 3000	1930 2530 2910 3000 3000 3000 3000 3000 3000 3000 3000 3000	2180 2860 3000 3000 3000 3000 3000 3000 3000 3000 3000 3000	2350 3000 3000 3000 3000 3000 3000 3000 3000 3000 3000 3000	2520 3000 3000 3000 3000 3000 3000 3000 3000 3000 3000 3000	2730 3000 3000 3000 3000 3000 3000 3000 3000 3000 3000 3000	2940 3000 3000 3000 3000 3000 3000 3000 3000 3000 3000 3000
2½	2¾	73.0	40(Std) 80(XS) 160 (XXS)	0.083 0.109 0.125 0.141 0.156 0.172 0.188 0.203 0.216 0.250 0.276 0.375 0.552	2.11 2.77 3.18 3.58 3.96 4.37 4.78 5.16 5.49 6.35 7.01 9.52 14.02	2.47 3.22 3.67 4.12 4.53 4.97 5.40 5.79 6.13 7.01 7.66 10.01 13.69	3.68 4.80 5.47 6.14 6.75 7.40 8.04 8.62 9.13 10.44 11.41 14.91 20.39	1.12 1.46 1.67 1.87 2.06 2.26 2.45 2.63 2.78 3.18 3.48 4.54 6.22	1040 - - - 1950 2150 2350 2500 2500 2500 2500 2500 2500	-	1040 - - - 2280 2500 2500 2500 2500 2500 2500 2500	-	1460 1910 2190 2470 2730 3000 3000 3000 3000 3000 3000 3000 3000	1590 2090 2400 2710 3000 3000 3000 3000 3000 3000 3000 3000 3000	1800 2370 2710 3000 3000 3000 3000 3000 3000 3000 3000 3000 3000	1940 2550 2920 3000 3000 3000 3000 3000 3000 3000 3000 3000 3000	2080 2730 2900 3000 3000 3000 3000 3000 3000 3000 3000 3000 3000	2250 2960 3000 3000 3000 3000 3000 3000 3000 3000 3000 3000 3000	2430 3000 3000 3000 3000 3000 3000 3000 3000 3000 3000 3000 3000
3	3½	88.9	40(Std) 80(XS) 160 (XXS)	0.083 0.109 0.125 0.141 0.156 0.172 0.188 0.216 0.250 0.281 0.300 0.438 0.600	2.11 2.77 3.18 3.58 3.96 4.37 4.78 5.49 6.35 7.14 7.62 11.13 15.24	3.03 3.95 4.51 5.06 5.57 6.11 6.65 7.58 8.68 9.66 10.25 14.32 18.58	4.51 5.88 6.72 7.54 8.30 9.10 9.91 11.29 12.93 14.39 15.27 21.33 27.67	1.38 1.79 2.05 2.30 2.53 2.77 3.02 3.44 3.94 4.39 4.65 6.50 8.44	850 - 1290 1600 1770 1930 2220 2500 2500 2500 2500 2500 2500	-	1000 - 1500 1870 2060 2260 2500 2500 2500 2500 2500 2500	-	1200 1570 1800 2030 2250 2480 2710 3000 3000 3000 3000 3000 3000	1310 1720 1970 2220 2460 2780 3000 3000 3000 3000 3000 3000 3000	1480 1940 2230 2510 2780 3000 3000 3000 3000 3000 3000 3000 3000	1590 2090 2400 2710 3000 3000 3000 3000 3000 3000 3000 3000 3000	1710 2240 2570 2900 3000 3000 3000 3000 3000 3000 3000 3000 3000	1850 2430 2790 3000 3000 3000 3000 3000 3000 3000 3000 3000 3000	1990 2620 3000 3000 3000 3000 3000 3000 3000 3000 3000 3000 3000
3½	4	101.6	40(Std) 80(XS)	0.083 0.109 0.125 0.141 0.156 0.172 0.188 0.226 0.250 0.281 0.318	2.11 2.77 3.18 3.58 3.96 4.37 4.78 5.74 6.35 7.14 8.08	3.47 4.53 5.17 5.81 6.40 7.03 7.65 9.11 10.01 11.16 12.50	5.17 6.75 7.70 8.65 9.53 10.47 11.39 13.57 14.91 16.62 18.62	1.58 2.06 2.35 2.64 2.91 3.19 3.47 4.14 4.54 5.07 5.68	750 980 1120 1270 1400 1550 1690 2030 2250 2530 2800	-	870 1140 1310 1480 1640 1810 1970 2370 2620 2800 2800	-	1050 1370 1580 1700 1970 2170 2370 2850 3000 3000 3000	1150 1500 1720 1950 2150 2370 2590 3000 3000 3000 3000	1290 1700 1950 2200 2430 2680 2930 3000 3000 3000 3000	1390 1830 2100 2370 2540 2890 3000 3000 3000 3000 3000	1490 1960 2250 2540 2750 2890 3000 3000 3000 3000 3000	1620 2130 2440 2750 2960 3000 3000 3000 3000 3000 3000	1740 2290 2630 2960 3000 3000 3000 3000 3000 3000 3000

API Pipes (Continued)

Size						Weight			Hydrostatic Test Pressure							
Outside Diameter			Wall Thickness			lb/ft	kg/m	kg/ft	API 5L				API 5LX			
Nominal Size	in	mm	Sch No	in	mm				A		B		X42	X46	X52	X56
									Std.	Alt.	Std.	Alt.				
4	4½	114.3	40(Std)	0.083	2.11	3.92	5.84	1.78	660		770		930	1020	1150	1240
				0.109	2.77	5.11	7.61	2.32	870		1020					
				0.125	3.18	5.84	8.70	2.65	1000		1170		1400	1530	1730	1870
				0.141	3.58	6.56	9.77	2.98	1130		1320		1580	1730	1960	2110
				0.156	3.96	7.24	10.78	3.29	1250		1460		1750	1910	2160	2330
				0.172	4.37	7.95	11.84	3.61	1380		1610		1930	2110	2390	2570
				0.188	4.78	8.66	12.90	3.93	1500		1750		2110	2310	2610	2810
				0.203	5.16	9.32	13.88	4.23	1620		1890		2270	2490	2810	3000
				0.219	5.56	10.01	14.91	4.54	1750		2040		2450	2690	3000	3000
				0.237	6.02	10.79	16.07	4.90	1900		2210		2650	2910	3000	3000
			60	0.250	6.35	11.35	16.91	5.15	2000		2330		2800	3000	3000	3000
				0.281	7.14	12.66	18.86	5.75	2250		2620		3000	3000	3000	3000
				0.312	7.92	13.96	20.79	6.34	2500		2800		3000	3000	3000	3000
				0.337	8.56	14.98	22.31	6.80	2700		2800		3000	3000	3000	3000
			80(XS)	0.438	11.13	19.00	28.30	8.63	2800		2800		3000	3000	3000	3000
				0.531	13.49	22.51	33.53	10.22	2800		2800		3000	3000	3000	3000
				0.674	17.12	27.54	41.02	12.50	2800		2800		3000	3000	3000	3000
				0.674	17.12	27.54	41.02	12.50	2800		2800		3000	3000	3000	3000
5	5¾	141.3	40(Std)	0.083	2.11	4.86	7.24	2.21	540		630					
				0.125	3.18	7.26	10.81	3.30	810		940					
				0.156	3.96	9.01	13.42	4.09	1010		1180					
				0.188	4.78	10.79	16.07	4.90	1220		1420					
				0.219	5.56	12.50	18.62	5.68	1420		1650					
				0.258	6.55	14.62	21.76	6.63	1670		1950					
				0.281	7.14	15.85	23.61	7.20	1820		2120					
				0.312	7.92	17.50	26.05	7.94	2020		2360					
			80(XS)	0.344	8.74	19.17	28.55	8.70	2230		2600					
				0.375	9.52	20.78	30.94	9.43	2430		2800					
				0.500	12.70	27.03	40.26	12.27	2800		2800					
				0.625	15.88	32.96	49.08	14.96	2800		2800					
			(XXS)	0.750	19.05	38.55	57.41	17.50	2800		2800					
				0.750	19.05	38.55	57.41	17.50	2800		2800					
				0.083	2.11	5.80	8.64	2.63	450	560	530	660	790	860	980	1050
				0.109	2.77	7.59	11.31	3.45	590							
8	8	219.1	20	0.125	3.18	11.35	16.91	5.15	520	650	610	760	910	1000	1130	1220
				0.156	3.96	14.11	21.02	6.41	650	810	760	950	1140	1250	1410	1520
				0.188	4.78	16.94	25.23	7.69	780	980	920	1140	1370	1500	1700	1830
				0.203	5.16	18.26	27.20	8.29					1480	1620	1840	2000
				0.219	5.56	19.66	29.28	8.93	910	1140	1070	1330	1600	1750	1980	2130
				0.250	6.35	22.36	33.31	10.15	1040	1300	1220	1520	1830	2000	2260	2430
				0.277	7.04	24.70	36.79	11.21	1160	1450	1350	1690	2020	2220	2510	2700
				0.312	7.92	27.70	41.26	12.58	1300	1630	1520	1900	2280	2500	2820	3000
			40(Std)	0.322	8.18	28.55	42.53	12.96	1340	1680	1570	1960	2350	2580	2910	3000
				0.344	8.74	30.42	45.31	13.81	1440	1790	1680	2090	2510	2750	3000	3000
				0.375	9.52	33.04	49.21	15.00	1570	1960	1830	2280	2740	3000	3000	3000
				0.406	10.31	35.64	53.09	16.18								
			80(XS)	0.438	11.13	38.30	57.05	17.39	1830	2290	2130	2670	3000	3000	3000	3000
				0.500	12.70	43.39	64.63	19.70	2090	2610	2430	2800	3000	3000	3000	3000
				0.562	14.27	48.40	72.09	21.97	2350	2800	2740	2800	3000	3000	3000	3000
				0.594	15.09	50.95	75.89	23.13								
			100	0.625	15.88	53.40	79.54	24.24	2610	2800	2800	2800	3000	3000	3000	3000
				0.719	18.26	60.71	90.43	27.56	2800	2800	2800	2800	3000	3000	3000	3000
				0.812	20.62	67.76	100.93	30.76								
				0.875	22.22	72.42	107.87	32.88	2800	2800	2800	2800				
			(XXS)	0.906	23.01	74.69	111.25	33.91								
				0.906	23.01	74.69	111.25	33.91								

API Pipes (Continued)

Size						Weight			Hydrostatic Test Pressure							
Outside Diameter			Wall Thickness			lb/ft	kg/m	kg/ft	API 5L				API 5LX			
Nominal Size	in	mm	Sch No	in	mm				A		B		X42	X46	X52	X56
									Std.	Alt.	Std.	Alt.				
10	10 3/4	273.0	20	0.156	3.96	17.65	26.29	8.01	520	650	610	760	1040	1130	1280	1380
				0.188	4.78	21.21	31.59	9.63	630	790	730	920	1250	1370	1550	1660
				0.203	5.16	22.87	34.06	10.38					1350	1480	1670	1800
				0.219	5.56	24.63	36.69	11.18	730	920	860	1070	1450	1590	1800	1940
				0.250	6.35	28.04	41.77	12.73	840	1050	980	1220	1660	1820	2060	2210
				0.279	7.09	31.20	46.47	14.16	930	1170	1090	1360	1850	2030	2290	2470
			30	0.307	7.80	34.24	51.00	15.54	1030	1290	1200	1500	2040	2230	2520	2720
				0.344	8.74	38.23	56.94	17.36	1150	1440	1340	1680	2280	2500	2830	3000
			40(Std)	0.365	9.27	40.48	60.29	18.38	1220	1530	1430	1780	2420	2660	3000	3000
				0.438	11.13	48.24	71.85	21.90	1470	1830	1710	2140	2910	3000	3000	3000
			60(XS)	0.500	12.70	54.74	81.54	24.85	1670	2090	1950	2440	3000	3000	3000	3000
				0.562	14.27	61.15	91.08	27.76	1880	2350	2200	2740	3000	3000	3000	3000
			80	0.594	15.09	64.43	95.97	29.25								
				0.625	15.88	67.58	100.66	30.68	2090	2620	2440	2800	3000	3000	3000	3000
			100	0.719	18.26	77.03	114.74	34.97	2410	2800	2800	2800	3000	3000	3000	3000
				0.812	20.62	86.18	128.37	39.13	2720	2800	2800	2800				
			120	0.844	21.44	89.29	133.00	40.54								
				1.000	25.40	104.13	155.10	47.28								
12	12 3/4	323.8	20	0.172	4.37	23.11	34.42	10.49	490	610	570	710	960	1050	1190	1280
				0.188	4.78	25.22	37.57	11.45	530	660	620	770	1050	1150	1300	1400
				0.203	5.16	27.20	40.51	12.35					1140	1250	1410	1520
				0.219	5.56	29.31	43.66	13.31	620	770	720	900	1230	1340	1520	1640
				0.250	6.35	33.38	49.72	15.15	710	880	820	1030	1400	1530	1730	1870
				0.281	7.14	37.42	55.74	16.99	790	990	930	1160	1570	1720	1950	2100
			30	0.312	7.92	41.45	61.74	18.82	880	1100	1030	1280	1750	1910	2160	2330
				0.330	8.38	43.77	65.20	19.87	930	1160	1090	1360	1850	2020	2290	2460
			(Std)	0.344	8.74	45.58	67.89	20.69	970	1210	1130	1420	1930	2110	2390	2570
				0.375	9.52	49.56	73.82	22.50	1060	1320	1240	1540	2100	2300	2600	2800
			40	0.406	10.31	53.52	79.72	24.30					2270	2490	2810	3000
				0.438	11.13	57.59	85.78	26.15	1240	1550	1440	1800	2450	2690	3000	3000
			(XS)	0.500	12.70	65.42	97.44	29.70	1410	1760	1650	2060	2800	3000	3000	3000
				0.562	14.27	73.15	108.96	33.21	1590	1980	1850	2310	3000	3000	3000	3000
			60	0.625	15.88	80.93	120.55	36.74	1760	2210	2060	2570	3000	3000	3000	3000
				0.688	17.48	88.63	132.01	40.24	1940	2430	2270	2800	3000	3000	3000	3000
			80	0.750	19.05	96.12	143.17	43.64	2120	2650	2470	2800	3000	3000	3000	3000
				0.812	20.62	103.53	154.21	47.00	2290	2800	2670	2800	3000	3000	3000	3000
			100	0.844	21.44	107.32	159.86	48.72								
				0.875	22.22	110.97	165.29	50.38	2470	2800	2800	2800	3000	3000	3000	3000
			120	1.000	25.40	125.49	186.92	56.97								
14	14	355.6	10	0.188	4.78	27.73	41.30	12.59	480	600	560	700	960	1050	1190	1280
				0.203	5.16	29.91	44.55	13.58	520	650	610	760				
				0.210	5.33	30.93	46.07	14.04					1070	1170	1330	1430
				0.219	5.56	32.23	48.01	14.63					1120	1220	1380	1490
				0.250	6.35	36.71	54.68	16.67	640	800	750	940	1280	1400	1580	1700
				0.281	7.14	41.17	61.32	18.69	720	900	840	1050	1430	1570	1770	1910
			20	0.312	7.92	45.61	67.94	20.71	800	1000	940	1170	1590	1740	1970	2120
				0.344	8.74	50.17	74.73	22.78	880	1110	1030	1290	1750	1920	2170	2340
			30(Std)	0.375	9.52	54.57	81.28	24.77	960	1210	1120	1410	1910	2090	2370	2550
				0.406	10.31	58.94	87.79	26.76					2070	2270	2560	2760
			40	0.438	11.13	63.44	94.49	28.80	1130	1410	1310	1640	2230	2450	2770	2980
				0.469	11.91	67.78	100.96	30.77					2390	2620	2960	3000
			(XS)	0.500	12.70	72.09	107.38	32.73	1290	1610	1500	1880	2550	2790	3000	3000
				0.562	14.27	80.66	120.14	36.62	1450	1810	1690	2110	2870	3000	3000	3000
			60	0.594	15.09	85.05	126.68	38.61								
				0.625	15.88	89.28	132.98	40.53	1610	2010	1880	2340	3000	3000	3000	3000
			80	0.688	17.48	97.81	145.69	44.41	1770	2210	2060	2580	3000	3000	3000	3000
				0.750	19.05	106.13	158.08	48.18	1930	2410	2250	2800	3000	3000	3000	3000
			100	0.812	20.62	114.37	170.35	51.92	2090	2610	2440	2800	3000	3000	3000	3000
				0.875	22.22	122.65	182.69	55.68	2250	2800	2520	2800	3000	3000	3000	3000
			120	0.938	23.83	130.85	194.90	59.41	2410	2800	2800	2800	3000	3000	3000	3000
			140	1.000	25.40	138.54	206.80	63.03								
16	16	406.4	10	0.188	4.78	31.75	47.29	14.40	420	530	490	620	840	920	1040	1120
				0.203	5.16	34.25	51.02	15.54	460	570	530	670	910	990	1120	1210
				0.219	5.56	36.91	54.98	16.74	490	620	570	720	980	1070	1210	1300
				0.250	6.35	42.05	62.63	19.07	560	700	660	820	1120	1220	1380	1490
				0.281	7.14	47.17	70.26	21.40	630	790	740	920	1250	1370	1550	1670
				0.312	7.92	52.27	77.86	23.71	700	880	820	1020	1390	1520	1720	1860
			20	0.344	8.74	57.52	85.68	26.09	770	970	900	1130	1540	1680	1900	2050
				0.375	9.52	62.58	93.21	28.39	840	1050	980	1230	1670	1830	2070	2230
			30(Std)	0.406	10.31	67.62	100.72	30.67					1810	1980	2240	2420
																

API Pipes (Continued)

Size						Weight			Hydrostatic Test Pressure							
Outside Diameter			Wall Thickness			lb/ft	kg/m	kg/ft	API 5L				API 5LX			
									A		B		X42	X46	X52	X56
Nominal Size	in	mm	Sch No	in	mm				Std.	Alt.	Std.	Alt.				
16	16	406.4	40(XS)	0.438	11.13	72.80	108.44	33.02	990	1230	1150	1440	1950	2140	2420	2610
				0.469	11.91	77.79	115.87	35.29					2090	2290	2590	2790
				0.500	12.70	82.77	123.29	37.54	1120	1410	1310	1640	2230	2440	2760	2980
				0.562	14.27	92.66	138.02	42.03	1260	1580	1480	1840	2510	2750	3000	3000
				0.625	15.88	102.63	152.87	46.55	1410	1760	1640	2050	2790	3000	3000	3000
				0.656	16.66	107.50	160.12	48.80								
			60	0.688	17.48	112.51	167.58	51.03	1550	1940	1810	2260	3000	3000	3000	3000
				0.750	19.05	122.15	181.94	55.41	1690	2110	1970	2460	3000	3000	3000	3000
				0.812	20.62	131.71	196.18	59.74	1830	2280	2130	2660	3000	3000	3000	3000
				0.844	21.44	136.61	203.48	62.02								
				0.875	22.22	141.34	210.53	64.11	1970	2460	2300	2800	3000	3000	3000	3000
				0.938	23.83	150.89	224.75	68.44	2110	2640	2460	2800	3000	3000	3000	3000
				1.000	25.40	160.20	238.62	72.67	2250	2800	2620	2800	3000	3000	3000	3000
				1.062	26.97	169.43	252.37	76.85	2390	2800	2790	2800	3000	3000	3000	3000
				1.125	28.58	178.72	266.20	81.07	2530	2800	2800	2800	3000	3000	3000	3000
18	18	457.2	10	0.188	4.78	35.76	53.26	16.22	380	470	440	550	750	820	920	990
				0.219	5.56	41.59	61.95	18.87	440	550	510	640	870	950	1080	1160
				0.250	6.35	47.39	70.59	21.50	500	620	580	730	990	1090	1230	1320
			20	0.281	7.14	53.18	79.21	24.12	560	700	660	820	1110	1220	1380	1490
				0.312	7.92	58.94	87.79	26.74	620	780	730	910	1240	1360	1530	1650
				0.344	8.74	64.87	96.62	29.43	690	860	800	1000	1360	1490	1690	1820
			30	0.375	9.52	70.59	105.14	32.02	750	940	880	1090	1490	1630	1840	1980
				0.406	10.31	76.29	113.63	34.61					1610	1760	1990	2150
				0.438	11.13	82.15	122.36	37.26	880	1100	1020	1280	1740	1900	2150	2320
				0.469	11.91	87.81	130.79	39.83					1860	2040	2300	2480
				0.500	12.70	93.45	139.19	42.39	1000	1250	1170	1460	1980	2170	2460	2640
				0.562	14.27	104.67	155.91	47.48	1120	1400	1310	1640	2230	2440	2760	2980
			40	0.625	15.88	115.98	172.75	52.61	1250	1560	1460	1820	2480	2720	3000	3000
				0.688	17.48	127.21	189.48	57.70	1380	1720	1610	2010	2730	2990	3000	3000
				0.750	19.05	138.17	205.80	62.67	1500	1880	1750	2190	2980	3000	3000	3000
20	20	508.0	60	0.812	20.62	149.06	222.02	67.61	1620	2030	1890	2370	3000	3000	3000	3000
				0.875	22.22	160.03	238.36	72.59	1750	2190	2040	2550	3000	3000	3000	3000
				0.938	23.83	170.92	254.59	77.53	1880	2340	2190	2740	3000	3000	3000	3000
			80	1.000	25.40	181.56	270.43	82.36	2000	2500	2330	2800	3000	3000	3000	3000
				1.062	26.97	192.11	286.15	87.14	2120	2660	2490	2990	3000	3000	3000	3000
				1.125	28.58	202.75	302.00	91.97	2250	2800	2620	2800	3000	3000	3000	3000
				1.187	30.15	213.14	317.47	96.68	2370	2800	2770	2800				
				1.188	30.18	213.31	317.73	96.76					3000	3000	3000	3000
				1.250	31.75	223.61	333.07	101.43	2500	2800	2800	2800	3000	3000	3000	3000
			10	0.219	5.56	46.27	68.92	20.99	390	490	460	570	830	910	1020	1100
				0.250	6.35	52.73	78.54	23.92	450	560	520	660	940	1040	1170	1260
				0.281	7.14	59.18	88.15	26.84	510	630	590	740	1060	1160	1320	1420
			20	0.312	7.92	65.60	97.71	29.76	560	700	660	820	1180	1290	1460	1570
				0.344	8.74	72.21	107.56	32.75	620	770	720	900	1300	1420	1610	1730
				0.375	9.52	78.60	117.07	35.65	680	840	790	980	1420	1550	1760	1890
			30	0.406	10.31	84.96	126.55	38.64					1530	1680	1900	2050
				0.438	11.13	91.51	136.30	41.51	790	990	920	1150	1660	1810	2050	2210
				0.469	11.91	97.83	145.72	44.38					1770	1940	2190	2360
				0.500	12.70	104.13	151.13	47.23	900	1120	1050	1310	1890	2070	2340	2520
				0.562	14.27	116.67	173.78	52.92	1010	1260	1180	1480	2120	2330	2630	2750
				0.625	15.88	129.33	192.64	58.66	1120	1410	1310	1640	2360	2590	2750	2750
				0.688	17.48	141.98	211.36	64.37	1240	1550	1440	1810	2600	2750	2750	2750
				0.750	19.05	154.19	229.67	69.94	1350	1690	1580	1970	2750	2750	2750	2750
				0.812	20.62	166.40	247.85	75.48	1460	1830	1710	2130	2750	2750	2750	2750
22	22	558.8	60	0.875	22.22	179.72	266.20	81.07	1580	1970	1840	2300	2750	2750	2750	2750
				0.938	23.83	190.96	284.43	86.62	1690	2110	1970	2460	2750	2750	2750	2750
				1.000	25.40	202.92	302.25	92.04	1800	2250	2100	2620	2750	2750	2750	2750
			80	1.062	26.97	214.80	319.94	97.43	1910	2390	2230	2750	2750	2750	2750	2750
				1.125	28.58	226.78	337.79	102.87	2020	2530	2360	2750	2750	2750	2750	2750
				1.187	30.15	238.50	355.25	108.18	2140	2670	2490	2750				
				1.188	30.15	238.68							2750	2750	2750	2750
				1.250	31.76	250.31	372.84	113.54	2250	2760	2620	2750	2750	2750	2750	2750
				1.312	33.32	261.86	390.04	118.78	2360	2750	2750	2750	2750	2750	2750	2750
				1.375	34.92	273.51	407.39	124.06	2480	2750	2750	2750	2750	2750	2750	2750
			10	0.219	5.56	50.94	75.88	23.11	360	450	420	520	750	820	930	1000
				0.250	6.35	58.07	86.50	26.34	410	510	480	600	860	940	1060	1150
				0.281	7.14	65.18	97.09	29.57	460	570	540	670	970	1060	1200	1290
			20	0.312	7.92	72.27	107.65	32.78	510	640	600	740	1070	1170	1330	1430
				0.344	8.74	79.56	118.50	36.09	560	700	660	820	1180	1290	1460	1580
				0.375	9.52	86.61	129.01	39.29	610	770	720	890	1290	1410	1600	1720

API Pipes (Continued)

Size						Weight			Hydrostatic Test Pressure							
Outside Diameter			Wall Thickness			lb/ft	kg/m	kg/ft	API 5L				API 5LX			
									A		B		X42	X46	X52	X56
Nominal Size	in	mm	Sch No	in	mm				Std.	Alt.	Std.	Alt.				
			30	0.406	10.31	93.63	139.46	42.47					1400	1530	1730	1860
				0.438	11.13	100.86	150.23	45.75	720	900	840	1050	1510	1650	1860	2010
				0.469	11.91	107.85	160.64	48.92					1610	1770	2000	2150
				0.500	12.70	114.81	171.01	52.08	820	1020	950	1190	1720	1880	2130	2290
				0.562	14.27	128.67	191.65	58.36	920	1150	1070	1340	1930	2130	2380	2590

mGas

M GAS STEEL SDN BHD

API Pipes (Continued)

Size						Weight			Hydrostatic Test Pressure							
Outside Diameter			Wall Thickness			lb/ft	kg/m	kg/ft	API 5L				API 5LX			
Nominal Size	in	mm	Sch No	in	mm				A		B		X42	X46	X52	X56
									Std.	Alt.	Std.	Alt.				
28	28	711.2	20	0.344	8.74	101.61	151.35	46.09					930	1020	1150	1240
				0.375	9.52	110.64	164.80	50.19	480	600	560	700	1010	1110	1250	1350
				0.406	10.31	119.65	178.22	54.27					1100	1200	1360	1450
				0.438	11.13	128.93	192.04	58.48	560	700	660	820	1180	1300	1460	1580
				0.469	11.91	137.90	205.40	62.55					1270	1390	1570	1690
				0.500	12.70	146.85	218.73	66.61	640	800	750	940	1350	1480	1670	1800
				0.562	14.27	164.69	245.31	74.70	720	900	840	1050	1520	1660	1880	2020
				0.625	15.88	182.73	272.18	82.89	800	1000	940	1170	1690	1850	2090	2250
			30	0.688	17.48	200.68	298.91	91.03	880	1100	1030	1290	1860	2030	2300	2480
				0.750	19.05	218.27	325.11	99.01	960	1210	1120	1410	2020	2220	2510	2700
				0.812	20.62	235.78	351.19	106.95	1040	1300	1220	1520	2190	2400	2710	2920
				0.875	22.22	253.58	377.56	114.98	1120	1410	1310	1640	2360	2590	2920	3000
				0.938	23.83	271.10	403.80	122.97	1210	1510	1410	1760	2530	2770	3000	3000
				1.000	25.40	288.36	429.51	130.80	1290	1610	1500	1880	2700	2960	3000	3000
30	30	762.0	10	0.250	6.35	79.43	118.31	36.03	300	370	350	440	630	690	780	840
				0.281	7.14	89.19	132.85	40.46	340	420	390	490	710	780	880	940
				0.312	7.92	98.93	147.36	44.87	370	470	440	550	790	860	970	1050
				0.344	8.74	108.95	162.28	49.42					870	950	1070	1160
				0.375	9.52	118.65	176.73	53.82	450	560	520	660	940	1040	1170	1260
				0.406	10.31	128.32	191.13	58.21					1020	1120	1270	1360
				0.438	11.13	138.29	205.98	62.73	530	660	610	770	1100	1210	1370	1470
				0.469	11.91	147.92	220.33	67.10					1180	1290	1460	1580
			20	0.500	12.70	157.53	234.64	71.46	600	750	700	880	1260	1380	1560	1680
				0.562	14.27	176.69	263.18	80.15	670	840	790	980	1420	1550	1750	1890
				0.625	15.88	196.08	292.06	88.94	750	940	880	1090	1580	1720	1950	2100
				0.688	17.48	215.38	320.81	97.70	830	1030	960	1200	1730	1900	2150	2310
				0.750	19.05	234.29	348.97	106.27	900	1120	1060	1310	1890	2070	2340	2520
				0.812	20.62	253.12	377.02	114.82	970	1220	1140	1420	2050	2240	2530	2730
				0.875	22.22	272.17	405.40	123.46	1050	1310	1220	1530	2200	2420	2730	2940
				0.938	23.83	291.14	433.65	132.06	1130	1410	1310	1640	2360	2590	2930	3000
			30	1.000	25.40	309.72	461.33	140.49	1200	1500	1400	1750	2520	2760	3000	3000
				1.062	26.97	328.22	488.88	148.88	1270	1590	1490	1860	2680	2930	3000	3000
				1.125	28.58	346.93	516.75	157.37	1350	1690	1580	1970	2840	3000	3000	3000
				1.188	30.18	365.56	544.60	165.82	1430	1780	1660	2080	2990	3000	3000	3000
				1.250	31.75	383.81	571.68	174.10	1500	1880	1750	2190	3000	3000	3000	3000
32	32	812.8	10	0.250	6.35	84.77	126.26	38.45	280	350	330	410	590	650	730	790
				0.281	7.14	95.19	141.79	43.18	320	400	370	460	660	730	820	890
				0.312	7.92	105.59	157.28	47.90	350	440	410	510	740	810	910	980
				0.344	8.74	116.30	173.23	52.75					810	890	1010	1080
				0.375	9.52	126.66	188.66	57.45	420	530	490	620	890	970	1100	1180
				0.406	10.31	136.99	204.05	62.14					960	1050	1190	1280
				0.438	11.13	147.64	219.91	66.97	490	620	570	720	1030	1130	1280	1380
				0.469	11.91	157.94	235.25	71.64					1110	1210	1370	1480
			20	0.500	12.70	168.21	250.55	76.30	560	700	660	820	1180	1290	1460	1580
				0.562	14.27	188.70	281.07	85.58	530	790	740	920	1330	1450	1640	1770
				0.625	15.88	209.43	311.95	95.00	700	880	820	1030	1480	1620	1830	1970
				0.688	17.48	230.08	342.70	104.36	770	970	900	1130	1630	1790	2010	2170
				0.750	19.05	250.31	372.84	113.54	840	1050	980	1230	1770	1940	2190	2360
				0.812	20.62	270.47	402.87	122.69	910	1140	1070	1330	1920	2100	2380	2560
				0.875	22.22	290.86	433.24	131.93	980	1230	1150	1440	2070	2260	2560	2760
				0.938	23.83	311.17	463.49	141.15	1060	1320	1230	1540	2220	2430	2740	2950
			30	1.000	25.40	331.08	493.14	150.18	1120	1410	1310	1640	2360	2590	2920	3000
				1.062	26.97	350.90	522.74	159.17	1190	1490	1390	1740	2510	2750	3000	3000
40	1.125	28.58	370.96	552.54	168.27	1270	1580	1480	1850	2660	2910	3000	3000			
	1.188	30.18	390.94	582.31	177.33	1340	1670	1560	1950	2810	3000	3000	3000			
1.250	31.75	410.51	611.45	186.21	1410	1760	1640	2050	2950	3000	3000	3000				
34	34	863.6	10	0.250	6.35	90.11	134.22	40.87	260	330	310	390	560	610	690	740
				0.281	7.14	101.19	150.72	45.90	300	370	350	430	620	680	770	830
				0.312	7.92	112.25	167.20	50.92	330	410	390	480	690	760	860	920
				0.344	8.74	123.65	184.18	56.09					760	840	950	1020
				0.375	9.52	134.67	200.59	61.09	400	500	460	580	830	910	1030	1110
				0.406	10.31	145.67	216.98	66.08					900	990	1120	1200
				0.438	11.13	157.00	233.85	71.22	460	580	540	680	970	1070	1210	1300
				0.469	11.91	167.95	250.16	76.18					1040	1140	1290	1390
			20	0.500	12.70	178.89	266.46	81.14	530	660	620	770	1110	1220	1380	1480
				0.562	14.27	200.70	298.94	91.04	600	740	690	870	1250	1370	1550	1670
				0.625	15.88	222.78	331.83	101.05	660	830	770	970	1390	1520	1720	1850
				0.688	17.48	244.77	364.58	111.03	730	910	850	1060	1530	1680	1890	2040
				0.750	19.05	266.32	396.70	120.81	790	990	930	1160	1670	1830	2060	2220
				0.812	20.62	287.81	428.69	130.55	860	1070	1000	1250	1810	1980	2240	2410

API Pipes (Continued)

Size						Weight			Hydrostatic Test Pressure							
Outside Diameter			Wall Thickness			lb/ft	kg/m	kg/ft	API 5L				API 5LX			
									A		B		X42	X46	X52	X56
Nominal Size	in	mm	Sch No	in	mm				Std.	Alt.	Std.	Alt.				
34	34	863.6		0.875	22.22	309.55	461.07	140.41	930	1160	1080	1350	1950	2130	2410	2590
				0.938	23.83	331.21	493.34	150.24	990	1240	1160	1450	2090	2280	2580	2780
				1.000	25.40	352.44	524.96	162.13	1060	1320	1240	1540	2220	2440	2750	2960
				1.062	26.97	373.59	556.46	169.46	1120	1410	1310	1650	2360	2590	2920	3000
				1.125	28.58	394.99	588.34	179.17	1190	1490	1390	1740	2500	2740	3000	3000
				1.188	30.18	416.31	620.09	188.84	1260	1570	1470	1830	2640	2890	3000	3000
				1.250	31.75	437.21	651.22	198.32	1320	1650	1540	1930	2780	3000	3000	3000
36	36	914.4	10	0.250	6.35	95.45	142.17	43.30	250	310	290	360	520	580	650	700
				0.281	7.14	107.20	159.67	48.63	280	350	330	410	590	650	730	790
				0.312	7.92	118.92	177.13	53.94	310	390	360	450	660	720	810	870
				0.344	8.74	131.00	195.12	59.42	340	430	400	500	720	790	890	960
				0.375	9.52	142.68	212.52	64.72	380	470	440	550	790	860	980	1050
				0.406	10.31	154.34	229.89	70.01	420	520	490	600	850	930	1060	1140
				0.438	11.13	166.35	247.78	75.46	460	570	540	660	920	1010	1140	1230
				0.469	11.91	177.97	265.09	80.73	500	620	590	720	980	1080	1220	1310
			20	0.500	12.70	189.57	282.36	85.99	550	680	650	790	1050	1150	1300	1400
				0.562	14.27	212.70	316.82	96.48	600	740	710	860	1120	1230	1380	1480
				0.625	15.88	236.12	351.72	107.11	660	810	780	940	1200	1310	1460	1570
				0.688	17.48	259.42	386.48	117.70	720	880	850	1020	1280	1390	1540	1650
				0.750	19.05	282.35	420.56	128.07	790	960	930	1100	1360	1470	1620	1730
				0.812	20.62	305.16	454.54	138.42	860	1040	1010	1180	1440	1550	1700	1810
				0.875	22.22	328.24	488.91	148.89	940	1120	1090	1260	1520	1630	1780	1890
				0.938	23.83	351.25	523.19	159.33	1020	1200	1170	1340	1600	1710	1860	1970
38	38	965.2	10	1.000	25.40	373.80	556.78	169.56	1100	1280	1250	1420	1680	1790	1940	2050
				1.062	26.97	396.27	590.24	179.75	1180	1360	1330	1500	1760	1870	2020	2130
				1.125	28.58	419.02	624.13	190.07	1260	1440	1410	1580	1840	1950	2100	2210
				1.188	30.18	441.69	657.90	200.35	1340	1520	1490	1660	1920	2030	2180	2290
				1.250	31.75	463.91	690.99	210.43	1420	1600	1570	1740	2000	2110	2260	2370
			20	0.312	7.92	125.58	187.05	56.96	300	370	340	430	620	680	770	830
				0.344	8.74	138.35	206.07	62.76	330	410	380	480	680	750	850	910
				0.375	9.52	150.69	224.45	68.35	360	440	410	520	750	820	920	990
				0.406	10.31	163.01	242.80	73.94	390	480	450	560	810	880	1000	1080
				0.438	11.13	175.71	261.72	79.70	420	520	490	610	870	950	1080	1160
				0.469	11.91	187.99	280.01	85.27	460	560	530	650	930	1020	1160	1240
				0.500	12.70	200.25	298.27	90.83	500	590	560	690	990	1090	1230	1330
				0.562	14.27	224.71	334.71	101.93	560	670	640	780	1120	1220	1380	1490
			30	0.625	15.88	249.48	371.60	113.16	590	740	710	860	1240	1360	1540	1660
				0.688	17.48	274.16	408.36	124.36	650	810	780	940	1320	1440	1630	1750
				0.750	19.05	298.37	444.42	135.34	710	890	860	1020	1400	1520	1710	1830
				0.812	20.62	322.50	480.36	146.29	770	960	930	1100	1480	1600	1800	1920
				0.875	22.22	346.93	516.75	157.37	830	1040	1010	1180	1560	1680	1880	2000
				0.938	23.83	371.28	553.02	168.41	890	1110	1080	1260	1640	1760	1960	2080
				1.000	25.40	395.16	588.59	179.24	950	1180	1150	1330	1720	1840	2040	2160
				1.062	26.97	418.96	624.04	190.04	1010	1260	1230	1410	1800	1920	2120	2240
			40	1.125	28.58	443.05	659.92	200.97	1070	1330	1300	1480	1880	2000	2200	2320
				1.188	30.18	467.06	695.69	211.86	1130	1410	1380	1560	1960	2080	2280	2400
				1.250	31.75	490.61	730.76	222.54	1180	1480	1450	1630	2040	2160	2360	2480
				0.312	7.92	132.25	196.99	59.99	280	350	320	410	590	650	730	790
				0.344	8.74	145.69	217.01	66.08	310	390	360	450	650	710	800	870
				0.375	9.52	158.70	236.38	71.99	340	420	390	480	680	740	830	900
				0.406	10.31	168.28	252.52	77.44	370	450	420	510	710	770	860	930
				0.438	11.13	178.27	268.66	82.89	400	480	450	540	740	800	890	960
42	42	1066.8	10	0.469	11.91	187.99	280.01	85.27	460	560	530	650	930	1020	1160	1240
				0.500	12.70	200.25	298.27	90.83	500	610	580	700	990	1090	1230	1330
				0.562	14.27	224.71	334.71	101.93	560	680	650	780	1120	1220	1380	1490
				0.625	15.88	249.48	371.60	113.16	620	750	720	860	1240	1360	1540	1660
				0.688	17.48	274.16	408.36	124.36	680	820	790	940	1320	1440	1630	1750
				0.750	19.05	298.37	444.42	135.34	740	890	860	1020	1400	1520	1710	1830
				0.812	20.62	322.50	480.36	146.29	800	960	930	1100	1480	1600	1800	1920
				0.875	22.22	346.93	516.75	157.37	870	1040	1010	1180	1560	1680	1880	2000
			20	0.938	23.83	371.28	553.02	168.41	940	1120	1090	1260	1640	1760	1960	2080
				1.000	25.40	395.16	588.59	179.24	1020	1200	1170	1340	1720	1840	2040	2160
				1.062	26.97	418.96	624.04	190.04	1100	1280	1250	1420	1800	1920	2120	2240
				1.125	28.58	443.05	659.92	200.97	1180	1360	1330	1500	1880	2000	2200	2320
				1.188	30.18	467.06	695.69	211.86	1260	1440	1410	1580	1960	2080	2280	2400
				1.250	31.75	490.61	730.76	222.54	1340	1520	1490	1660	2040	2160	2360	2480
				0.312	7.92	132.25	196.99	59.99	280	350	320	410	590	650	730	790
				0.344	8.74	145.69	217.01	66.08	310	390	360	450	650	710	800	870
				0.375	9.52	158.70	236.38	71.99	340	420	390	480	680	740	830	900
			30	0.406	10.31	168.28	252.52	77.44	370	450	420	510	710	770	860	930
				0.438	11.13	178.27	268.66	82.89	400	480	450	540	740	800	890	960
44	44	1130.0	10	0.500	12.70	200.25	298.27	90.83	500	610	580	700	990	1090	1230	1330
				0.562	14.27	224.71	334.71	101.93	560	680	650	780	1120	1220	1380	1490
				0.625	15.88	249.48	371.60	113.16	620	750	720	860	1240	1360	1540	1660
				0.688	17.48	274.16	408.36	124.36	680	820	790	940	1320	1440	1630	1750
				0.750	19.05	298.37	444.42	135.34	740	890	860	1020	1400	1520	1710	1830
				0.812	20.62	322.50	480.36	146.29	800	960	930	1100	1480	1600	1800	1920
				0.875	22.22	346.93	516.75	157.37	870	1040	1010	1180	1560	1680	1880	2000
				0.938	23.83	371.28	553.02	168.41	940	1120	1090	1260	1640	1760	1960	2080
			20	1.000	25.40	395.16	588.59	179.24	1020	1200	1170	1340	1720	1840	2040	2160
				1.062	26.97	418.96	624.04	190.04	1100	1280	1250	1420	1800	1920	2120	2240
				1.125	28.58	443.05	659.92	200.97	1180	1360	1330	1500	1880	2000	2200	2320
46	46	1193.8	10	1.188	30.18	467.06	695.69	211.86	1260	1440	1410	1580	1960	2080	2280	2400
				1.250	31.75	490.61	730.76	222.54	1340	1520	1490	1660	2040	2160	2360	2480
				0.312	7.92	132.25	196.99	59.99	280	350	320	410	590	650	730	790
48	48	1244.6	10	0.344	8.74	145.69	217.01	66.08	310	390	360	450	650	710	800	870
				0.375	9.52	158.70	236.38	71.99	340	420	390	480	680	740	830	900
				0.406	10.31	168.28	252.52	77.44	370	450	420	510	710	770	860	930
50	50	1301.6	10	0.438	11.13	178.27	268.66	82.89	400	480	450	540	740	800	890	960
				0.469	11.91	187.99	280.01	85.27	460	560	530	650	930	1020	1160	1240
				0.500	12.70	200.25	298.27	90.83	500	610	580	700	990	1090	1230	1330
52	52	1357.4	10	0.562	14.27	224.71	334.71	101.93	560	680	650	780	1120	1220	1380	1490
				0.625	15.88	249.48	371.60	113.16	620	750	720	860	1240	1360	1540	1660
				0.688	17.48	274.16	408.36	12								

API Pipes (Continued)

Size						Weight			Hydrostatic Test Pressure							
Outside Diameter			Wall Thickness			lb/ft	kg/m	kg/ft	API 5L				API 5LX			
									A		B		X42	X46	X52	X56
Nominal Size	in	mm	Sch No	in	mm	Std.	Alt.	Std.	Alt.							
				0.469	11.91	208.03	309.86	94.36	400	500	470	590	840	920	1050	1130
				0.500	12.70	221.61	330.09	100.52	430	540	500	520	900	990	1110	1200
				0.562	14.27	248.72	370.47	112.82	480	600	560	700	1010	1110	1250	1350
				0.625	15.88	276.18	411.37	125.28	540	670	620	780	1120	1230	1390	1500
42	42	1066.8		0.688	17.48	303.55	452.14	137.69	590	740	690	860	1240	1360	1530	1650
				0.750	19.05	330.41	492.15	149.87	640	800	750	940	1350	1480	1670	1800
				0.812	20.62	357.19	532.03	162.02	700	870	810	1020	1460	1600	1810	1950
				0.876	22.22	384.31	572.43	174.32	750	940	880	1090	1580	1720	1950	2100
				0.938	23.83	411.35	612.71	186.59	800	1000	940	1170	1690	1850	2090	2250
				1.000	25.40	437.88	652.22	198.62	860	1070	1000	1250	1800	1970	2230	2400
				1.062	26.97	464.32	691.60	210.62	910	1140	1060	1330	1910	2090	2370	2550
				1.125	28.58	491.11	731.51	222.77	960	1210	1130	1410	2030	2220	2510	2700
				1.188	30.18	517.82	771.29	234.88	1020	1270	1190	1480	2140	240	2650	2850
				1.250	31.75	544.01	810.30	246.76	1070	1340	1250	1560	2250	2460	2790	3000
44	44	1117.6		0.344	8.74	160.39	238.90	72.75	280	350	330	410	590	650	730	790
				0.375	9.52	174.72	260.25	79.26	310	380	360	450	640	710	800	860
				0.406	10.31	189.03	281.56	85.74	330	420	390	480	700	760	860	930
				0.438	11.13	203.78	303.53	92.43	360	450	420	520	750	820	930	1000
				0.469	11.91	218.04	324.77	98.90	380	480	450	560	810	880	1000	1070
				0.500	12.70	232.29	346.00	105.37	410	510	480	600	860	940	1060	1150
				0.562	14.27	260.72	388.34	118.26	460	570	540	670	970	1060	1200	1290
				0.625	15.88	289.53	431.25	131.33	510	640	600	750	1070	1180	1330	1430
				0.688	17.48	318.25	474.03	144.36	560	700	660	820	1180	1290	1460	1580
				0.750	19.05	346.43	516.01	157.14	610	770	720	890	1290	1410	1600	1720
46	46	1168.4		0.812	20.62	374.53	557.86	169.89	660	830	780	970	1400	1530	1730	1860
				0.875	22.22	403.00	600.27	182.80	720	890	840	1040	1480	1620	1830	1970
				0.938	23.83	431.39	642.56	195.68	770	960	900	1120	1610	1770	2000	2150
				1.000	25.40	459.24	684.04	208.31	820	1020	950	1190	1720	1880	2130	2290
				1.062	26.97	487.01	725.40	220.92	870	1090	1010	1270	1820	2000	2260	2430
				1.125	28.58	515.14	767.30	233.67	920	1150	1070	1340	1930	2120	2390	2580
				1.188	30.18	543.19	809.08	246.39	970	1210	1130	1420	2040	2240	2530	2720
				1.250	31.75	570.71	850.07	258.87	1020	1280	1190	1490	2150	2350	2660	2860
				0.344	8.74	167.74	249.85	76.09	270	340	310	390	570	620	700	750
				0.375	9.52	182.73	272.18	82.89	290	370	340	430	630	680	760	820
48	48	1219.2		0.406	10.31	197.70	294.47	89.68	320	400	370	460	670	730	830	890
				0.438	11.13	213.13	317.46	96.68	340	430	400	500	720	790	890	960
				0.469	11.91	228.06	339.70	103.45	370	460	430	540	770	840	950	1030
				0.500	12.70	242.97	361.90	110.21	390	490	460	570	820	900	1020	1100
				0.562	14.27	272.73	406.23	123.71	440	550	510	640	920	1010	1140	1230
				0.625	15.88	302.88	451.14	137.39	490	610	570	710	1030	1120	1270	1370
				0.688	17.48	332.95	495.93	151.03	540	670	630	790	1130	1240	1400	1510
				0.750	19.05	362.45	539.87	164.41	590	730	680	860	1230	1350	1530	1640
				0.812	20.62	391.88	583.71	177.76	640	790	740	930	1330	1460	1650	1780
				0.875	22.22	421.69	628.11	191.28	680	860	800	1000	1440	1580	1780	1920
50	50	1270.0		0.938	23.83	451.42	672.39	204.76	730	920	860	1070	1540	1690	1910	2060
				1.000	25.40	480.60	715.85	218.00	780	980	910	1140	1640	1800	2030	2190
				1.062	26.97	509.69	759.18	231.20	830	1040	970	1210	1750	1910	2160	2330
				1.125	28.58	539.17	803.09	244.57	880	1100	1030	1280	1850	2020	2290	2470
				1.188	30.18	568.57	846.89	257.90	930	1160	1080	1360	1950	2140	2420	2600
				1.250	31.75	597.41	889.84	270.99	980	1220	1140	1430	2050	2250	2540	2740
				0.344	8.74	175.08	260.78	79.42	260	320	300	380	540	590	670	720
				0.375	9.52	190.74	284.11	86.52	280	350	330	410	590	650	730	790
				0.406	10.31	206.37	307.39	93.61	300	380	360	440	630	690	780	840
				0.438	11.13	223.07	332.06	100.71	320	410	380	470	670	740	840	900

API Pipes (Continued)

Size						Weight			Hydrostatic Test Pressure							
Outside Diameter			Wall Thickness			lb/ft	kg/m	kg/ft	API 5L				API 5LX			
									A		B		X42	X46	X52	X56
in	in	mm	Sch No	in	mm				Std.	Alt.	Std.	Alt.				
52	52	1320.8		0.375	9.52	206.76	307.97	93.79								
				0.406	10.31	223.72	333.23	101.48								
				0.438	11.13	241.20	359.27	109.41	300	380	350	440	640	700	790	850
				0.469	11.91	258.11	384.45	117.08	320	410	380	470	680	750	840	910
				0.500	12.70	275.01	409.63	124.74	350	430	400	500	730	800	900	970
				0.562	14.27	308.74	459.87	140.04	390	490	450	570	820	890	1010	1090
				0.625	15.88	342.93	510.79	155.55	430	540	500	630	910	1000	1130	1210
				0.688	17.48	377.03	561.69	171.02	480	600	560	690	1000	1100	1240	1330
				0.750	19.05	410.51	611.45	186.21	520	650	610	760	1090	1190	1350	1450
				0.812	20.62	443.91	661.20	201.36	560	700	660	820	1180	1290	1460	1570
				0.875	22.22	477.76	711.62	216.71	610	760	710	880	1270	1390	1580	1700
				0.938	23.83	511.53	761.92	232.03	650	810	760	950	1360	1490	1690	1820
				1.000	25.40	544.68	811.30	247.07	690	870	810	1010	1450	1590	1800	1940
				1.062	26.97	577.75	860.56	262.07	740	920	860	1070	1540	1690	1910	2060
				1.125	28.58	611.26	910.47	277.27	780	970	910	1140	1640	1790	2030	2180
				1.188	30.18	644.69	960.27	292.43	820	1030	960	1200	1730	1890	2140	2300
				1.250	31.75	677.51	1009.15	307.32	870	1080	1010	1260	1820	1990	2250	2420
56	56	1422.4		0.375	9.52	222.78	340.77	101.05								
				0.406	10.31	241.06	359.06	109.34								
				0.438	11.13	259.91	387.14	117.90	280	350	330	410	590	650	730	790
				0.469	11.91	278.15	414.30	126.17	300	380	350	440	630	690	780	840
				0.500	12.70	296.37	441.44	134.43	320	400	380	470	680	740	840	900
				0.562	14.27	332.75	495.63	150.94	360	450	420	530	760	830	940	1010
				0.625	15.88	369.63	550.56	167.66	400	500	470	590	840	920	1040	1120
				0.688	17.48	406.42	60.536	184.35	440	550	520	650	930	1020	1150	1240
				0.750	19.05	442.55	659.18	200.74	480	600	560	700	1010	1110	1250	1350
				0.812	20.62	478.60	712.87	217.09	520	650	610	760	1100	1200	1360	1460
				0.875	22.22	515.14	767.30	233.67	560	700	660	820	1180	1290	1460	1570
				0.938	23.83	551.60	821.61	250.21	600	750	700	880	1270	1390	1570	1690