Multiparty Computation made Practical Using the Virtual Ideal Functionality Framework

Martin Geisler (mg@daimi.au.dk)

BRICS
Department of Computer Science
University of Aarhus
Denmark

ECRYPT Research Meeting June 23–25, 2008

Outline

Background Setting Related Projects

Design Goals

Automatic Parallel Execution Program Counters

Benchmark Results

Multiplications Comparisons


Possible Improvements

Program Counters Memory Overheads Debugging

Conclusion


Setting


Real World




Setting

Real World







Setting




- ► Input
 - Shamir secret sharing




- ► Input
 - ► Shamir secret sharing
- Output
 - ► Reconstruct shares




- Input
 - Shamir secret sharing
- Output
 - ► Reconstruct shares
- Addition
 - ▶ Local addition
 - ▶ No communication



- Input
 - Shamir secret sharing
- Output
 - Reconstruct shares
- Addition
 - Local addition
 - No communication
- Multiplication
 - Local multiplication
 - Resharing




- Input
 - Shamir secret sharing
- Output
 - Reconstruct shares
- Addition
 - Local addition
 - No communication
- Multiplication
 - Local multiplication
 - Resharing
- Comparison
 - Two protocols



- ► Input
 - Shamir secret sharing
- Output
 - Reconstruct shares
- Addition
 - Local addition
 - No communication
- Multiplication
 - Local multiplication
 - Resharing
- Comparison
 - Two protocols

All over arbitrary finite fields.



Related Projects

- ► FairPlay project (Haifa, Israel)
 - Yao-garbled circuits for 2 players
 - Java implementation
 - Working on multiparty computation

Related Projects

- ► FairPlay project (Haifa, Israel)
 - Yao-garbled circuits for 2 players
 - Java implementation
 - Working on multiparty computation
- SCET project (Aarhus, Denmark)
 - General multiparty computations
 - ► C# implementation

Related Projects

- ► FairPlay project (Haifa, Israel)
 - Yao-garbled circuits for 2 players
 - Java implementation
 - Working on multiparty computation
- SCET project (Aarhus, Denmark)
 - General multiparty computations
 - C# implementation
- SIMAP project (Aarhus, Denmark)
 - General multiparty computations
 - Java implementation
 - Some work done on a domain specific language

Outline

Background

Setting

Related Projects

Design Goals

Automatic Parallel Execution Program Counters

Benchmark Results

Multiplications
Comparisons

Possible Improvements

Program Counters Memory Overheads Debugging

Conclusion

VIFF Goals

▶ Easy to use for the programmer:

$$x = 2 * a - b * c$$

VIFF Goals

▶ Easy to use for the programmer:

$$x = 2 * a - b * c$$

Automatically run things in parallel:

```
x = a * b

y = c * d

z = e * f
```

VIFF Goals

▶ Easy to use for the programmer:

$$x = 2 * a - b * c$$

Automatically run things in parallel:

```
x = a * b

y = c * d

z = e * f
```

Extensible with new operations:

```
def max(a, b):

c = a > b

return c * a + (1 - c) * b
```

Parallel Execution

- Networks have significant latency
- ▶ Want to run many operations in parallel
- Including primitive and compound operations

Example: Hamming Distance

```
def xor(a, b):
    assert a.field is b.field
    if a.field is GF256:
        return a + b
    else:
        return a + b - 2 * a * b
```

- ► Straight-forward exclusive-or
- ▶ Fast for $GF(2^8)$ elements
- ▶ Slower for \mathbb{Z}_p elements
- ► (Already part of VIFF)

Example: Hamming Distance

```
 \begin{aligned} \textbf{def } & \mathsf{xor}(\mathsf{a}, \, \mathsf{b}) \\ & \textbf{assert } \mathsf{a}. \mathsf{field } \mathbf{is } \mathsf{b}. \mathsf{field } \\ & \textbf{if } \mathsf{a}. \mathsf{field } \mathbf{is } \mathsf{GF256} ; \\ & \textbf{return } \mathsf{a} + \mathsf{b } \\ & \textbf{else} ; \\ & \textbf{return } \mathsf{a} + \mathsf{b} - 2 * \mathsf{a} * \mathsf{b} \end{aligned}
```


```
 \begin{aligned} & \textbf{def} \; \mathsf{hamming}(\mathsf{s}, \; \mathsf{t}) \colon \\ & \textbf{assert} \; \mathsf{len}(\mathsf{s}) == \mathsf{len}(\mathsf{t}) \\ & \mathsf{distance} = 0 \\ & \textbf{for} \; \mathsf{i} \; \textbf{in} \; \mathsf{range}(\mathsf{len}(\mathsf{s})) \colon \\ & \mathsf{distance} \; += \; \mathsf{xor}(\mathsf{s}[\mathsf{i}], \; \mathsf{t}[\mathsf{i}]) \\ & \textbf{return} \; \mathsf{distance} \end{aligned}
```

- Straight-forward exclusive-or
- ▶ Fast for $GF(2^8)$ elements
- ▶ Slower for \mathbb{Z}_p elements
- ► (Already part of VIFF)

- Hamming distance
- xor calls should run in parallel


Hamming Distance Execution Tree

hamming(s, t) translates to:




Hamming Distance Execution Tree

hamming(s, t) translates to:




xor(a, b) translates to:



VIFF Execution Strategy

- Create execution tree as we go along
- Destroy execution tree from bottom up
 - Each node waits on nodes below
 - Bottom nodes wait on network traffic
- Composable: just plug new operations into tree!

Program Counters



- No parsing execution tree never fully constructed
- ▶ No fixed evaluation order
- ▶ But we must identify results

Program Counters Implementation

- First attempt:
 - Each player increments a global counter
 - ► Fails because of asynchronous execution

Program Counters Implementation

- First attempt:
 - Each player increments a global counter
 - Fails because of asynchronous execution
- Working solution:
 - Manually "weave" a program counter through program
 - ► Tedious, easy to forget to increment program counter

Program Counters Implementation

- First attempt:
 - Each player increments a global counter
 - Fails because of asynchronous execution
- Working solution:
 - Manually "weave" a program counter through program
 - ▶ Tedious, easy to forget to increment program counter
- Current solution:
 - Runtime methods wrapped by a decorator
 - Calculated automatically based on call stack

Outline

Background

Setting

Related Projects

Design Goals

Automatic Parallel Execution Program Counters

Benchmark Results

Multiplications

Comparisons

Possible Improvements

Program Counters


Memory Overheads

Debugging


Conclusion

- ► Tested on 3 machines: USA, Norway, and Denmark
- Results for VIFF 0.4 (VIFF 0.6 is similar or better)
- Tested multiplications and comparisons


- ▶ Tested on 3 machines: USA, Norway, and Denmark
- Results for VIFF 0.4 (VIFF 0.6 is similar or better)
- Tested multiplications and comparisons
- ▶ Tested parallel and serial multiplications




- ▶ Tested on 3 machines: USA, Norway, and Denmark
- Results for VIFF 0.4 (VIFF 0.6 is similar or better)
- Tested multiplications and comparisons
- Tested parallel and serial multiplications




- ▶ Tested on 3 machines: USA, Norway, and Denmark
- ► Results for VIFF 0.4 (VIFF 0.6 is similar or better)
- Tested multiplications and comparisons
- ► Tested parallel and serial multiplications



- ► Tested on 3 machines: USA, Norway, and Denmark
- ► Results for VIFF 0.4 (VIFF 0.6 is similar or better)
- ► Tested multiplications and comparisons
- Tested parallel and serial multiplications




- ► Tested on 3 machines: USA, Norway, and Denmark
- ► Results for VIFF 0.4 (VIFF 0.6 is similar or better)
- Tested multiplications and comparisons
- ► Tested parallel and serial multiplications




Parallel Multiplications

Multiplying random 65-bit numbers:




Serial Multiplications

Multiplying random 65-bit numbers:



Parallel Comparisons

Comparing random 32-bit numbers, 65-bit field modulus:



Outline

Background

Setting

Related Projects

Design Goals

Automatic Parallel Execution Program Counters

Benchmark Results

Multiplications
Comparisons

Possible Improvements

Program Counters Memory Overheads Debugging

Conclusion

Program Counter Overheads

- ▶ They work, but it's a bit magic...
- Exactly when must the program counter be updated?
- Excessive wrapping slows down method calls
- Program counter size depends on stack depth

Memory Overheads

- Python objects have a large memory overhead:
 - Reference count (4 bytes)
 - Object attribute dictionary (144 bytes)
 - ► Allocation overhead (>8 bytes)
 - **>**

Memory Overheads

- Python objects have a large memory overhead:
 - Reference count (4 bytes)
 - Object attribute dictionary (144 bytes)
 - ► Allocation overhead (>8 bytes)
- ▶ 100,000 field elements with 65-bit prime:
 - ► Optimal: ≈800 KB
 - VIFF: ≈40 MB (expanded 50 times)
 - More memory needed for execution tree

Debugging

- ▶ Something went wrong! What now?
- ▶ Debugging asynchronous programs can be hard

Debugging

- Something went wrong! What now?
- Debugging asynchronous programs can be hard
- Need better
 - Logging infrastructure
 - Handling of exceptions

Type Safety

- Python is a strongly typed language
 - ▶ "12" * 3 == "121212" but 12 * 3 == 36
 - ▶ "1" + 12 raises TypeError
- ▶ Types are only checked at runtime

Type Safety

- Python is a strongly typed language
 - ▶ "12" * 3 == "121212" but 12 * 3 == 36
 - ▶ "1" + 12 raises TypeError
- ► Types are only checked at runtime
- ▶ Unit tests help here
- Better input validation

Outline

Background

Setting

Related Projects

Design Goals

Automatic Parallel Execution

Program Counters

Benchmark Results

Multiplications
Comparisons

Possible Improvements

Program Counters Memory Overheads Debugging

Conclusion

Conclusion

- VIFF provides a general framework for MPC
- Automatic parallel execution
- Free Software: LGPL
- ▶ Please see http://viff.dk/
 - Source code
 - Documentation
 - Mailing list
 - Bibliography

Conclusion

- VIFF provides a general framework for MPC
- Automatic parallel execution
- Free Software: LGPL
- ▶ Please see http://viff.dk/
 - Source code
 - Documentation
 - Mailing list
 - Bibliography

Thank you! Questions?