Part d)

i)

```
%function [f,fnames]=extract_hu_moments(mask)
 [M,N]=size(mask);
f=nan(7,1);
 fnames=cell(7,1);
 for i=1:numel(fnames)
    eval(['fnames{i,1}=''phi' num2str(i) ''';'])
[y,x]=meshgrid(N:-1:1,1:M);
\% variables are asigned with the same name as in the text book
m00=sum(sum(mask));
m10=sum(sum(x.*mask));
m01=sum(sum(y.*mask));
xbar=m10/m00:
ybar=m01/m00;
pq=[0 2; 2 0; 0 3; 3 0; 1 2; 2 1; 1 1];
 eta=nan(size(pq,1),1);
 for i=1:size(pq,1)
    p=pq(i,1);
    q=pq(i,2);
    mu=sum(sum(((x-xbar).^p).*((y-ybar).^q).*mask));
    gamma=(p+q)/2+1;
    eta(i,1)=mu/(m00^gamma);
f(1,1)=eta(1)+eta(2);
f(2,1)=(eta(2)-eta(1))^2+4*eta(7)^2;
f(3,1)=(eta(4)-3*eta(5))^2+(3*eta(6)-eta(3))^2;
f(4,1)=(eta(4)+eta(5))^2+(eta(6)+eta(3))^2;
 f(5,1)=(eta(4)-3*eta(5))*(eta(4)+eta(5))*((eta(4)+eta(5))^2-3*(eta(6)+eta(3))^2) + ...
     (3*eta(6)-eta(3))*(eta(6)+eta(3))*(3*(eta(4)+eta(5))^2-(eta(6)+eta(3))^2);
 f(6,1)=(eta(2)-eta(1))*((eta(4)+eta(5))^2-(eta(6)+eta(3))^2) + 4*eta(7)*(eta(4)+eta(5))*(eta(6)+eta(3));
 f(7,1)=(3*eta(6)-eta(3))*(eta(4)+eta(5))*((eta(4)+eta(5))^2-3*(eta(6)+eta(3))^2) + \dots
    (3*eta(5)-eta(4))*(eta(6)+eta(3))*(3*(eta(4)+eta(5))^2-(eta(6)+eta(3))^2);
%end
ii)
```

```
[M,N,~]=size(imread([cd '\101_ObjectCategories\emu\image_0001.jpg']));
ann=load([cd '\Annotations\emu\annotation 0001.mat']);
mask = double(poly2mask(ann.obj\_contour(1,:)+ann.box\_coord(3), ann.obj\_contour(2,:)+ann.box\_coord(1), M, N));
[f,fnames]=extract_hu_moments(mask);
 disp('f Vector:')
 f Vector:
 format shortE
disp(f')
    2.5115e-01 2.2063e-02 6.4386e-03 1.2679e-03 2.5429e-06 1.2366e-05 -2.5802e-06
disp('fnames Cell:')
 fnames Cell:
 disp(fnames')
     'phi1'
               'phi2'
                         'phi3'
                                   'phi4'
                                             'phi5'
                                                       'phi6'
                                                                 'phi7
iii)
```

a function was defined to do the procedure requested in this part. and next section is done with the help of this function

```
%function [f,fnames]=extract_props(mask)
 Struct=regionprops(mask, 'Area', 'ConvexArea', 'Eccentricity', 'EquivDiameter', 'EulerNumber', 'Extent', 'FilledArea', 'MajorAxisLength', ...
                            'MinorAxisLength', 'Perimeter', 'Solidity');
 f=cell2mat(struct2cell(Struct));
 fnames=fieldnames(Struct);
 f=[f(1);f(5);f(4);f(8);f(7);f(10);f(6);f(2);f(3);f(11);f(9)];
 fnames = \{fnames\{1\}; fnames\{4\}; fnames\{4\}; fnames\{8\}; fnames\{10\}; fnames\{6\}; fnames\{2\}; fnames\{3\}; fnames\{11\}; fnames\{9\}\}; fnames\{11\}; f
 %end
```

iv)

```
[M,N,~]=size(imread([cd '\101_ObjectCategories\emu\image_0001.jpg']));
```

```
ann=load([cd '\Annotations\emu\annotation_0001.mat']);
\verb|mask=double(poly2mask(ann.obj_contour(1,:)+ann.box_coord(3),ann.obj_contour(2,:)+ann.box_coord(1),M,N))|;
[f,fnames]=extract_props(mask);
disp('f Vector:')
 f Vector:
format shortE
disp(f')
   2.2924e+04 2.8932e+04 8.6211e-01 1.7084e+02 1.0000e+00 4.6280e-01 2.2924e+04 2.7074e+02 1.3719e+02 7.8864e+02 7.9234e-01
disp('fnames Cell:')
 fnames Cell:
disp(fnames')
    'Area'
              'ConvexArea'
                             'Eccentricity'
                                              'EquivDiameter'
                                                                'EulerNumber'
                                                                                'Extent'
                                                                                           'FilledArea'
                                                                                                           'MajorAxisLength'
                                                                                                                               'MinorAxisLength
```