

More On Go / Personal Fiance

1st. the news

1. Google is working to make blockchains searchable.
2. Facebook has a large development group to create a high-speed blockchain payments system.
3. Kantpoll - Open source election management system based on Ethereum.

2nd. Purpose of a business

1. To make a profit for the owners of the business.

What is "Fiduciary Responsibility". It means that you have been placed / are in a position of legal responsibility for managing somebody else's money.

1. Definitions / Economics

"arbitrage" ::= the simultaneous buying and selling of securities, currency, or commodities in different markets or in derivative forms in order to take advantage of differing prices for the same asset.

1. How Soros broke the Bank of England.

Price Stable Cryptocurrencies (or pegged cryptocurrencies)

Reference

[Soros Broke the Bank of England](#)

Personal Finance

Two Economies in US today. The "high-tech" and the "traditional" economy.

(See Spreadsheet)

Blockchain and Mining

What is Mining and How is it implemented.

What is proof-of-work? What is proof-of-stake? What is a public blockchain / private blockchain?

Diagram of blocks

Diagram of mining

What is the mining process

1. More on Go

Maps do not synchronize automatically. So... Synchronization Primitives:

```
package main

import (
    "fmt"
    "sync"
    "time"
)

// SafeCounter is safe to use concurrently.
type SafeCounter struct {
    v  map[string]int
    mux sync.Mutex
}

// Inc increments the counter for the given key.
func (c *SafeCounter) Inc(key string) {
    c.mux.Lock()
    // Lock so only one goroutine at a time can access the map c.v.
    c.v[key]++
    c.mux.Unlock()
}

// Value returns the current value of the counter for the given key.
func (c *SafeCounter) Value(key string) int {
    c.mux.Lock()
    // Lock so only one goroutine at a time can access the map c.v.
    defer c.mux.Unlock()
    return c.v[key]
}

func main() {
    c := SafeCounter{v: make(map[string]int)}
    for i := 0; i < 1000; i++ {
        go c.Inc("somekey")
    }
}
```

```

    time.Sleep(time.Second)
    fmt.Println(c.Value("somekey"))
}

```

A Go Core/Panic

First the Code

```

package main

import "fmt"

var mm map[string]int

func main() {
    fmt.Println("vim-go")
    mm["bob"] = 3
}

```

Then the bad output.

```
panic: assignment to entry in nil map
```

```

goroutine 1 [running]:
panic(0x10a5540, 0x10d03a0)
    /usr/local/Cellar/go/1.10.3/libexec/src/runtime/panic.go:551 +0x3c1 fp=0xc42005
runtime.mapassign_faststr(0x10a4e80, 0x0, 0x10be68a, 0x3, 0x0)
    /usr/local/Cellar/go/1.10.3/libexec/src/runtime/hashmap_fast.go:696 +0x407 fp=0
main.main()
    /Users/corwin/go/src/github.com/Univ-Wyo-Education/Blockchain-4010-Fall-2018/Le
runtime.main()
    /usr/local/Cellar/go/1.10.3/libexec/src/runtime/proc.go:198 +0x212 fp=0xc42005f
runtime.goexit()
    /usr/local/Cellar/go/1.10.3/libexec/src/runtime/asm_amd64.s:2361 +0x1 fp=0xc420

goroutine 2 [force gc (idle)]:
runtime.gopark(0x10c5580, 0x11397a0, 0x10bfafe, 0xf, 0x10c5414, 0x1)
    /usr/local/Cellar/go/1.10.3/libexec/src/runtime/proc.go:291 +0x11a fp=0xc42004a
runtime.goparkunlock(0x11397a0, 0x10bfafe, 0xf, 0x14, 0x1)
    /usr/local/Cellar/go/1.10.3/libexec/src/runtime/proc.go:297 +0x5e fp=0xc42004a7
runtime.forcegchelper()
    /usr/local/Cellar/go/1.10.3/libexec/src/runtime/proc.go:248 +0xcc fp=0xc42004a7
runtime.goexit()
    /usr/local/Cellar/go/1.10.3/libexec/src/runtime/asm_amd64.s:2361 +0x1 fp=0xc420

```

created by runtime.init.4

/usr/local/Cellar/go/1.10.3/libexec/src/runtime/proc.go:237 +0x35

