

Using Git on OS-X

Munich Cocoaheads

2009-11-12

2009-12-10

©2009 Stephen Riehm


Coming up

- Basic Concepts
 - Daily Git
 - Git with XCode
-
- Non-Obvious Git

project_dir/

.git/

.git/




58206c1725109d441fe846300fd4e57063cc6d6b

blob	size
<pre>// Blah.m // This class does @implementation Bla @synthesize a;</pre>	

56906c1...

tree		size	
ΓW-ΓW-ΓW-	blob	5b1d3...	ReadMe
ΓWXΓWXΓWX	tree	03e78...	Classes
ΓWXΓWXΓWX	tree	cdc8b...	Resources
ΓW-ΓW-ΓW-	blob	cba0a...	Info.plist
ΓWXΓWXΓWX	blob	911e7...	distrib.pl



3500621...

tree		size	
ΓW-ΓW-ΓW-	blob	5b1d3...	ReadMe
ΓWXΓWXΓWX	tree	03e78...	Classes
ΓWXΓWXΓWX	tree	cdc8b...	Resources
ΓW-ΓW-ΓW-	blob	cba0a...	Info.plist
ΓWXΓWXΓWX	blob	911e7...	distrib.pl



56906c1...


commit	size
tree	c4ec5...
previous commit	a149e...
author	Scott
committer	Scott
date	2009-11-10 21:15
commit message	


commit		size
tree	c4ec5...	
previous commit	a149e...	
author	Scott	
committer	Scott	
date	2009-11-10 21:15	
commit message		





56906c1...


tag	size
commit	ae668...
type	commit
tagger	Scott
tag message	

















HEAD and your current branch are automatically updated when you commit a change.







tags are immutable and reliably point to a known state of the entire repository














Git On OS-X





Has Everything



```
~/ > echo "you're going to need the command line :-)"
```

First Steps

```
~/ > $EDITOR ~/.gitconfig
```

```
[core]
```

```
    pager = more
```

```
    excludesfile = /Users/me/.gitignore
```

```
[user]
```

```
    name = My Full Public Identity
```

```
    email = h4x0r@example.com
```

```
[format]
```

```
    pretty = format:%h %ci [%aN] %s
```

pager stops long lists from flying past your nose uncontrollably

excludesfile specifies files should never be checked into a git repository

format:

%h = hash id

%ci = commit date, iso 8601 format

%aN = author name

%s = summary

more info: `git log --help`

```
~/ > $EDITOR ~/.gitignore
```

```
# apple typical files
.DS_Store
.Spotlight-V100
.com.apple.timemachine.supported
.fseventsdbuild

# XCode user state files
*.modelv3
*.pbxuser
*.objc_sync

# other SCM systems
.svn

# editor temporary files
*~
*.swp

# files you generate while building
build/
version.txt
CHANGELOG
```

```
~/ > git help <cmd>
```

```
~/ > git <cmd> --help
```

make sure you install
git's man-pages.


Use the [man](#) branch of
the git repository

<http://git-scm.com>

<http://github.com>

<http://gitready.com>

<http://google.com>




```
~/> cd project
```

```
~/project/ > git init
```

```
Initialized empty Git repository in project_dir/.git/
```

```
~/project/ > git add .
```

```
~/project/ > git commit -m 'initial commit'
```

```
[master (root-commit) 64fb323] initial commit
```

```
1 files changed, 1 insertions(+), 0 deletions(-)
```

```
create mode 100644 hello.txt
```

create your project in XCode
create a new git repository
add your files & directories to git
commit your changes

```
~/project/ > $EDITOR .gitattributes
```

```
*.pbxproj -crlf -diff -merge
```

```
*.nib -crlf -diff -merge
```

```
*.xib -crlf -diff -merge
```

```
*.graffle -crlf -diff -merge
```

```
~/project/ > git add .gitattributes
```

```
~/project/ > git commit -m 'add .gitattributes - prevent accidental merging of special XCode files'
```

```
[master (root-commit) 64fb323] initial commit
```

```
1 files changed, 1 insertions(+), 0 deletions(-)
```

```
create mode 100644 .gitattributes
```

Tell git to treat these files as if they were binaries.

XML files are notorious for being text, but "unmergeable".

`.gitattributes` is project-specific
must be checked into each project separately
will automatically be used by all project members

cloning a repository automatically sets up a remote repository called `origin`.

You can specify a different name for the remote repository with `-o name`

```
~/ > git clone -o cloned_repo URL/project.git
```

```
~/ > cd project
```

```
~/project/ > git checkout -b my_stuff cloned_repo/master
```

cloning a repository automatically sets up a remote repository called `origin`.

You can specify a different name for the remote repository with `-o name`

```
~/ > git clone ~/old_project_dir ~/new_project_dir
```

Daily Work

work work work...

```
~/project/ > git status
```


```
~/project/ > git add file file file directory... or git add -A or git add -u
```


```
~/project/ > git status
```

```
~/project/ > git commit -m 'what I just did'
```

`git add -A`
new files
changed files
removed files

`git add -u`
changed files
removed files





```
git commit -a  
same as  
git add -A; git commit
```

```
~/project/ > git commit -a -m 'what I just did'
```



```
~/project/ > git checkout -b new_branch
```

```
~/project/ > git branch -a
```

```
~/project/ > git branch -d old_branch
```

```
~/project/ > git branch -D old_branch
```

TIP: you can create a new branch AFTER you have already made changes.

Just `checkout -b new_branch` before you `git add`

```
~/project/ > git diff
```

```
~/project/ > git diff --cached
```

```
~/project/ > git diff HEAD
```

```
~/project/ > git diff branch
```

git always merges into the working directory

merged files are added automatically

conflicts are not added - you need to resolve them first

```
~/project/ > git merge other_branch
```

fix conflicts...

```
~/project/ > git add -A
```

```
~/project/ > git commit -m 'merge changes from other_branch'
```

`git reset --hard` updates the cache and the working tree to match the named branch (by default `HEAD`)

```
~/project/ > git reset
```

```
~/project/ > git reset --hard HEAD
```

Multiple Repositories

```
local ~/project/ > ssh me@remote.com
```

```
remote ~/ > mkdir project.git
```

```
remote ~/project.git/ > cd project.git
```

```
remote ~/project.git/ > git init --bare
```

```
remote ~/project.git/ > logout
```

```
local ~/project/ > git remote add public_repo ssh://me@remote.com/~/project.git
```

```
local ~/project/ > git push public_repo release_branch
```

you should NOT publish your private directories (basic security)
create a **bare repository** on a public server
push only the branches your wish to publish

```
~/project/ > git clone --bare . /Volumes/usb_stick/project.git
```

```
~/project/ > git remote add usb_stick /Volumes/usb_stick/project.git
```

```
~/project/ > git push usb_stick
```

USB stick, external disk

great for ad-hoc sharing

great for backup

treat like a public
repository

copying a repository works
just fine - both copies can
synchronise with each
other!

```
~/project/ > cp -R . /Volumes/usb_stick/project
```

```
~/project/ > git remote add usb_stick /Volumes/usb_stick/project
```

```
~/project/ > git push usb_stick
```



```
~/project_dir/ > git remote -v
```

```
public_repo    ssh://me@remote.com/~project.git (fetch)  
public_repo    ssh://me@remote.com/~project.git (push)  
usb_stick      /Volumes/usb_stick/project.git (fetch)  
usb_stick      /Volumes/usb_stick/project.git (push)
```

```
~/project/ > $EDITOR .git/config
```

```
...
```

```
[remote "steve"]
```

```
    url = ssh://steveserve.com/~/.Git/project.git
```

```
    fetch = +refs/heads/*:refs/remotes/steve/*
```

```
[remote "mac"]
```

```
    url = git@github.com:mac/project.git
```

```
    fetch = +refs/heads/*:refs/remotes/mac/*
```

```
[remotes]
```

```
    buddies = steve mac
```

```
...
```

```
~/project/ > git remote update buddies
```

```
Updating steve
```

```
...
```


```
Updating mac
```


```
...
```

Publish your changes via a bare repository

Never push to someone else's repository

Use `git remote update` to track multiple repositories





```
~/project/ > git status
```

```
~/project/ > git diff
```

```
~/project/ > git checkout -b fix
```

```
~/project/ > git commit -am '...'
```

```
~/project/ > git checkout master
```


```
~/project/ > git merge fix
```

```
~/project/ > git push public
```

git checkout



"Read from Disk" will force Xcode not to update your repository



If you get this message, you should:

- Save your work (possibly in a Temporary Directory)
- Close XCode
- Fix up your working directory
- Open XCode again

