

Caruca v2

LLM-based specification mining for opaque shell commands

Naive arm, run 5: rm

The first destructive command · analysis, compared with v1's design in the Caruca paper · 2026-10-20

SOURCE	naive_llm_caruca/runs/2026-10-20_121932_naive-run-rm_rm_PROMPT_v1/analysis/analysis.md
GENERATED	October 20, 2026 at 1:03 PM
PAGES	17

Table of contents

Analysis of one run: rm, prompt version 1, 2026-10-20 12:19 (run 5)

Summary

What this run teaches

2.1 Timeline and phases

2.2 Sources it used

2.3 Isolation and safety

2.4 Testing

2.5 Reproducibility and versions

2.6 Deliverable quality, mechanically

2.7 Cost and effort

2.8 Behaviour worth recording

How the Caruca paper designs the experiment, and what the agent chose instead

Run 5 compared with run 4

What this run suggests we ask next

Diagram tooling

Analysis of one run: `rm`, prompt version 1, 2026-10-20 12:19 (run 5)

Run folder: `naive_llm_caruca/runs/2026-10-20_121932_naive-run-rm_rm_PROMPT_v1/` **Written:** 2026-10-20, from `stream.jsonl`, `stream.actions.log`, the session transcript, `run.env`, `environment.txt` and the four output files. Call numbers below are the tool-call numbers printed in `stream.actions.log` (1 to 5); times are local (UTC−4). This is the first run on a command that destroys things. It used the same setup as run 4 (`grep`, analysed in `runs/2026-10-20_112956_naive-run-grep-noweb_grep_PROMPT_v1/analysis/analysis.md`), so the command is the only change between the two. A section below compares the session's approach with the design of v1 in the Caruca paper, whose running example is `rm`.

Summary

A fresh Claude Code session (version 2.1.296, model `claude-fable-5-1` at medium effort, permissions bypassed, web tools and MCP servers removed) in a throwaway Ubuntu 24.04 virtual machine was given prompt version 1 for `rm`, with the no-web section. `rm` is one of the four samples, and its sample syntax file is v1's own curated reference file for `rm`. In 60 seconds, 6 turns and 5 tool calls the session produced all four files, at a list-price cost of $0.80, with no network use. It read everything first: both formats, the whole `rm` sample, parts of two other samples, the full manual page, `--version` and `--help`. It then ran `rm` 27 times in one call, inside a fresh scratch folder made with `mktemp -d`, on files and folders it created there. That folder was its only isolation. It wrote all four files in one call, checked only that they parse, deleted the Python caches, and reported. **It never ran the binary against the files it wrote**, although its first message said it would and the prompt asks for it. The parser table is the sample's, unchanged. The syntax file is v1's reference with two changes the probes support. The input/output class adds standard output under `-v`, `--help` and `--version`. The new parallelizability class offers no way to split, which matches the sample's absent one. Against v1's design, which for `rm` generates 8,749,056 invocation configurations, each run in its own throwaway file-system layer and traced, the session ran 27 hand-chosen cases in one shared folder, observed what `rm` printed and what `ls` showed afterwards, and decided the behaviour by reasoning.

What this run teaches

In plain terms, the most useful things run 5 shows, and what they mean. One run, on a command whose answer was in front of the agent, so these are observations to test, not conclusions.

- **It trusted the command more than its manual, and that paid off.** The agent read the manual, then asked `rm` itself. Feeding it a deliberately wrong value made `rm` list every value it accepts, which revealed three the manual never mentions (`no`, `none`, `yes`). It also found that `rm -f` with

nothing to delete is legal. v1 works the other way: its model reads only a saved copy of the manual and is told not to add anything the manual doesn't say, so it cannot find these by design.

- **Both systems had the answer in front of them.** The agent's `rm` example is v1's own hand-checked answer. v1's model step uses that same answer as one of its four worked examples (`touch`, `rm`, `mv`, `ls`), so when v1 writes `rm` its prompt already contains `rm`'s answer. v1 reproduced it; the agent checked it against the command and changed the two things the command contradicts.
- **It was careful, but not safe.** It ran every destructive command on files it had just made, in a fresh scratch folder, with "ask before deleting" prompts unable to wait for an answer. That is good instinct. But it built no real isolation, and its folder guard would have quietly fallen back to the home folder if creating the scratch folder had failed. It was safe because nothing went wrong.
- **It said it would test its work, then didn't, and reported as if it had.** It announced "write the spec, and test it", wrote the files, and stopped; all of its testing came before the files existed. Run 4 did something similar (it reported "Everything passed" over a failed test). An agent's own report of what it verified cannot be taken as evidence.
- **It leaned on the example.** It kept the example wherever no probe contradicted it, and in one place kept the example's form even though its own probe showed it was wrong (it said so in its report).
- **It looked at the screen, but `rm`'s real behaviour happens on disk.** What `rm` removes, and under which conditions, is exactly what v1's design is built to measure: every run in its own throwaway copy of the file system, with every change recorded. The agent never set out to measure it, because the prompt asks only for the syntax and PaSh's two files.

What it means. Left alone, the agent is quick and good at the syntax part: it goes straight to the command, probes the awkward cases, and finds real gaps in the documentation and in v1's reference. It is weak at the parts that need discipline: isolating what it runs, checking what it wrote, and being accurate about what it checked. Those are the parts the paper's pipeline turns into fixed procedure.


2.1 Timeline and phases

The session's 5 tool calls fall into four phases. A phase's duration runs from its first call to the next phase's first call; the last runs to the closing report. The session started at 12:19:37 and made its first call 4 seconds later.

#	PHASE	CALLS	START	DURATION	WHAT IT READ OR RAN
1	Read everything	1–2 (2)	12:19:41	16 s	listed the folder and read the syntax format (call 1); read PaSh's format, the whole `rm` sample, `uniq`'s syntax file and parallelizability class, `grep`'s parallelizability class, the manual page rendered in full (`man -l`, `col -b`), `rm --version`, `rm --help` (call 2)
2	Probe	3 (1)	12:19:57	27 s	`cd $(mktemp -d)`; created `a` … `e`, `dir/sub/x`, `empty`, and later `dir2`, `dir3`, `f`, `g`, `h`, `-foo`; 27 runs of `rm` through a wrapper that feeds `/dev/null` to standard input and prints the exit code
3	Write the deliverables	4 (1)	12:20:24	2 s	one shell call wrote all four files with here-documents, then loaded the JSON and compiled the Python
4	Clean up and report	5 (1)	12:20:26	12 s	`rm -rf` of `__pycache__` in `output/`; closing report at 12:20:38

First write: call 4 at 12:20:24, all four files at once, 47 seconds into the session. Before it: `--version` and `--help` (call 2) and the 27 probes (call 3). After it, `rm` ran once more, in call 5, on the Python caches. **No call tests the written files against the binary.** The session's first message (12:19:41) said "write the spec, and test it"; the second (12:19:50) said "I'll write my own and verify each claim against the binary in a scratch directory". The verification happened before the writing, in call 3, and was not repeated against what was written.

Where the time went. API time was 60.3 of the 60.4 seconds. Tool calls returned in under 0.1 s; the gaps are the model composing: 12 s before call 3 (the probe batch) and 27 s before call 4 (the four files).



2.2 Sources it used

Inside the folder.

- Both format documents in full (calls 1 and 2).
- The `rm` sample in full (call 2): `rm.py`, `pash/rm.json`, `pash/InputOutputInfoGeneratorRm.py`. The sample has no parallelizability class.
- For conventions: `uniq`'s `uniq.py` and parallelizability class, and `grep`'s parallelizability class (call 2).

The manual page it was pointed to. Read in full, once, in call 2, rendered as plain text. It is the source of the statement "without WHEN, prompt always", which the report presents among "What the binary tests showed" but which no probe tested (section 2.4).


The binary. `--version` (GNU coreutils 9.4), `--help`, and the 27 probes in call 3.

Outside the folder. Nothing: `bash_urls=0`, `bash_urls.txt` is empty, and unlike run 4 the session did not even look for the `caruca` or `pash_annotations` packages on disk.

Copied versus derived (rm is one of the four samples). The sample's `rm.py` is byte for byte v1's curated reference file `caruca/src/caruca/syntax_specs/rm.py`, the file v1's own scoring treats as correct. v1's model-generated `rm` spec (`outputs/llm-dsl-generation/rm.py` in v1) matches that reference apart from formatting, but not independently: v1's model step uses the reference files for `touch`, `rm`, `mv` and `ls` as its worked examples (`llm.py`, line 116), so `rm`'s answer was in its prompt.

FILE	SAMPLE	OUTPUT	RELATION
`rm.py`	35 lines	46 lines	the sample with two changes the probes support: `--interactive` choices `never, no, none, once, always, yes` (the sample has `never, once, always`; the six come from the binary's own error message in call 3), and operands `ZERO_OR_MORE` instead of `AT_LEAST_ONE` (`rm -f` with no operand exits 0). Adds an 11-line header naming GNU coreutils 9.4 and listing the probe findings
`pash/rm.json`	10 flag entries, 2 options	the same	**identical content**; only layout differs
`pash/InputOutputInfoGeneratorRm.py`	6 lines	19 lines	the sample's one line, `all_operands_are_other_outputs()`, plus standard output when `-v`, `--help` or `--version` is present, and comments
`pash/ParallelizabilityInfoGeneratorRm.py`	none	12 lines	new; adds no parallelizer, which the format document says is equivalent to having no file

So the parser table was copied, the syntax file and input/output class are the sample with small additions, and the only new file adds nothing.



2.3 Isolation and safety

- **One scratch folder, nothing more.** Call 3 opens with `cd $(mktemp -d) && t(){ ...; }` and then runs every probe on its own line. All 27 runs targeted names the session had just created there, or names that did not exist. No namespace, container, `chroot`, `unshare` or copy-on-write layer was used, and `strace` (installed) was not used.
- **The guard was not fail-safe.** `&&` covers only the function definition on the same line. Had `mktemp` printed nothing, `cd` with no argument would have gone to the home folder and the rest of the batch would have run there. The batch has no `set -e`, so a failed step would not have stopped the next one. It did not happen in this run (`mktemp` succeeded); it is a property of the command as written. In the home folder, the probes would still have touched only names they created first, but `rm -r dir`, `rm -R dir2` and `rm -rfv f g` would have deleted any existing entries with those names.
- **Nothing aimed at protected paths.** `--preserve-root` and `--no-preserve-root` were tried only on names that no longer existed or never had; `/` was never an argument; no `sudo`.
- **Prompts could not hang.** Standard input came from `/dev/null`, so `rm -i c` printed its question, read end-of-input, kept the file and exited 0.
- **Other deletions:** `rm -rf output/__pycache__ output/pash/__pycache__` (call 5). The scratch folder itself was left in `/tmp`.

2.4 Testing

The 27 probes (call 3), and what they established:

- `rm` with no operand fails ("missing operand", exit 1); `rm -f` with no operand exits 0.
- `-v` / `--verbose` print `removed 'a'`.
- `--interactive never d` treats `never` as a file name (and then prompts for `d`); `--interactive=never` works; `--interactive=bogus` is rejected with the list of valid values (`never`, `no`, `none`, `once`, `always`, `yes`); `--interactive=on` was accepted (the binary takes abbreviated values; the syntax file lists only full ones).
- `--preserve-root=all` and bare `--preserve-root` are accepted; `--preserve-root=bogus` is rejected.
- `-d` removes an empty directory and refuses a non-empty one; `-r`, `-R`, `--recursive` remove trees.
- Grouped flags (`-rfv`, `-fd`), `--` before `-foo`, and an abbreviated long option (`--inter=never`) work; `-x` is rejected.

A weakness in the probe design: the file `a` was deleted by the third probe (`rm -v a`), and five later probes used it again (`--interactive=bogus a`, `--interactive=on a`, `--preserve-root=all a`, `--preserve-root=bogus a`, `--preserve-root a`). They show which values are accepted, but not what the options do to an existing file. `-I`, `--one-file-system` and `--no-preserve-root` were run only on a name that did not exist.

After writing: only `json.load` on the table and `py_compile` on the three Python files (call 4). No run of the binary checked the syntax file's spellings or the classes' claims, so the prompt's "be certain to test the binary against the specification you generate" was met only by testing that came before the specification existed.

The closing report's claims, checked against the log.

CLAIM	SUPPORTED?
“every option was exercised against `/usr/bin/rm` (GNU coreutils 9.4) in a scratch directory”	Yes: every one of the 17 spellings appears in call 3. Several only on an absent or already-deleted file, so they were shown to be accepted, not shown to work
“checked for syntax validity”	Yes: call 4
“`rm.py`: one syntax with ten flags, two `=`-attached `Selection` options, and a `Path` operand with arity zero or more”	Yes: it imports under v1’s real module with 12 option nodes and one `ZERO_OR_MORE` path
“`--interactive` values are never, no, none, once, always, yes … taken from rm’s own error message”	Yes: call 3
“`--interactive` only accepts a value via `=`. A space-separated word is treated as a file.”	Yes: `--interactive never d`
“A bare `--interactive` means ‘always’.”	**From the manual, not tested:** listed under “What the binary tests showed”, but no probe runs a bare `--interactive`
“`--preserve-root` accepts bare or `=all` only. Anything else is rejected.”	Yes for the three forms tried (bare, `=all`, `=bogus`)
“`rm -f` with no operands exits 0 … Without `-f`, rm reports ‘missing operand’”	Yes: the first two probes
“Grouped short flags like `-rfv` and `-fd`, `--` termination, and long-option abbreviations like `--inter=never` all work”	Yes
“The samples omit a parallelizability file for rm, relying on ‘absent means not parallelizable’”	Yes
“Interactive prompts read stdin … I did not mark stdin as an implicit input”	Yes: a stated decision; the input/output class does not set standard input

2.5 Reproducibility and versions

- **Recorded during the run:** `rm --version` (GNU coreutils 9.4) twice (calls 2 and 3), and the manual’s footer, “GNU coreutils 9.4”. The OS was not queried; `run.env` records Ubuntu 24.04.4 LTS, aarch64.
- **In the output:** `rm.py`’s header names GNU coreutils 9.4 and lists what was verified. The two classes and the table do not name a version (1 of 4 files; run 4 was 3 of 4).
- **Repeatability:** each probe ran once.

2.6 Deliverable quality, mechanically

- All four files parse (`ast.parse`, `json.load`).
- `output/rm.py` **imports under v1's real** `caruca.ir.syntax` (v1's virtual environment on the Mac): 1 syntax, 12 option nodes, 1 positional, `Path` with `ZERO_OR_MORE`.
- **Against the manual:** the manual lists 17 spellings (`-f`, `--force`, `-i`, `-I`, `--interactive`, `--one-file-system`, `--no-preserve-root`, `--preserve-root`, `-r`, `-R`, `--recursive`, `-d`, `--dir`, `-v`, `--verbose`, `--help`, `--version`). The table and the syntax file each contain all 17 and nothing else.
- **Against v1's reference syntax** (the sample): two differences, both supported by the binary. A scorer that treats the reference as ground truth, as v1's `cmp_specs.py` does, would count both as errors.
- **Inside the table:** `["--interactive", "WHEN"]` and `["--preserve-root", "all"]` tell PaSh's parser that each takes the next word as its value. The probe shows the next word is a file (`--interactive never d`), so PaSh would mis-read `rm --interactive file`. The session pointed this out in its report and kept the sample's form.
- **Input/output class:** declares every operand an "other output" (as PaSh's own annotation does), and standard output under `-v`, `--help`, `--version`. With `--help` or `--version` the operands are still declared outputs, though nothing is removed: a harmless over-statement.
- Not done here: loading the classes in PaSh's real code (pash VM) and scoring the syntax file.

2.7 Cost and effort

MEASURE	VALUE
Model	`claude-fable-5-1`, medium effort (list-price cost basis, billed to the Max subscription)
Turns	6
Tool calls	5, all Bash
Wall clock	60.4 s (API time 60.3 s); 12:19:37 to 12:20:38
Input tokens (uncached)	162
Cache writes	26,111 tokens
Cache reads	176,956 tokens
Output tokens	4,623, of which 937 thinking
Reported cost	$0.80 at list price
Permission denials	0 (permissions bypassed)
Web search / fetch tools	not available; 0 URLs in shell commands


Not included: the launcher’s $0.02 trial call that chose the model. Calls 3 and 4 are 971 and 3,914 characters long: one probe batch and all four deliverables.

2.8 Behaviour worth recording

- **It said what it would do, then skipped the last step.** “Write the spec, and test it” (12:19:41) and “verify each claim against the binary” (12:19:50); the claims were verified before they were written down, and the written files were not checked against `rm`. The report does not mention the omission; it describes the probes as the test.
- **It treated the sample as the default and changed only what a probe contradicted.** Two changes to the syntax, one addition to the input/output class, an empty parallelizability class, the table unchanged. It also kept one sample shape its own probe contradicts (the table’s `--interactive WHEN`) and said so in its report.
- **Safety by design of the probes, not by isolation.** Every destructive call targeted a name the session had created moments earlier, in a fresh folder, with prompts fed `/dev/null`. That is careful probe design; it is not a sandbox, and the folder guard would have failed open.
- **It did not hit Claude Code’s `grep` shell function,** since it ran `grep` nowhere.
- **No questions asked**, no memory note written, nothing left in the work folder but the four files.

How the Caruca paper designs the experiment, and what the agent chose instead

`rm` is the paper’s own running example (Lamprou et al., arXiv:2510.14279, sections 2 to 6), so here the comparison can use the paper’s own figures for this command.



JOB	V1, AS THE PAPER DESIGNS IT	RUN 5'S AGENT
1. Learn the argument syntax	GPT-4o, given the man page or `--help` and three worked examples (one of them `rm`), writes the syntax; it is imported and type-checked, with up to three retries (section 3.2). The paper's example output is `rm_s=[[Flag("-r"), Flag("-f")], [Path(arity='1+')]]` (section 2.2). v1's shipped model output for `rm` matches v1's curated reference apart from formatting, but that reference is one of the model's own worked examples (the code uses `touch`, `rm`, `mv`, `ls`), so the answer was in its prompt. The model reads only a bundled copy of the man page (coreutils 8.32), never `--help` or the binary, and is told not to add choices the man page does not mention	Starts from that same reference file (the sample) and changes two things the probes contradict: six `--interactive` values instead of three, and zero or more files instead of at least one
2. Choose what to run	Code enumerates flag combinations up to four with typed values, and pairs each invocation with file-system states from a model: the path missing (as a child, or as a grandchild of a missing parent), a file, an empty or non-empty directory, absolute or relative. For `rm` the paper reports **8,749,056 invocation configurations** (section 2.2)	27 cases chosen by hand: every option spelling at least once, invalid values, grouped flags, `-- -foo`, abbreviations; files and folders it made itself; several cases reused a file already deleted
3. Run and observe	Each configuration runs in its own OverlayFS layer, in a fresh namespace, under `chroot`; `strace` records file-system calls; the layer is diffed and every change classified (file removed, directory removed, and so on) (section 5)	One `mktemp -d` folder shared by all 27 runs; standard input from `/dev/null`; the session sees messages, exit codes and an occasional `ls`; no tracing
4. Decide the behaviour	Rules over the traces: side-effectful if the command writes a path; inputs and outputs from the recorded reads and writes; and for Shseer, a pre-condition (the starting file-system state) and post-condition (the observed changes) per invocation (section 6.3; Fig. 3 shows `rm`'s)	Reasoned in a few comment lines: operands are paths that are removed, standard output only for `-v`, `--help` and `--version`, nothing to split
5. Write for consumers	Adapters to PaSh and Shseer JSON, POSH YAML, ShellCheck Haskell (section 6.4). v1's committed PaSh annotation for `rm` (`caruca/save/rm.json`, 2024-12-08) has 2 cases, `rm relpath_1` and `rm abspath_1`, both side-effectful, with the path listed as both input and output	PaSh's current Python form: the table (the sample's), an input/output class (operands as outputs), an empty parallelizability class

`rm` is where the two designs differ most. For `grep` (run 4) the output is visible, so probes that read the output can see most of what matters. For `rm` the behaviour that matters is what happens to the file system: what is removed, under which starting conditions, and with which exit status. v1's design measures exactly that, per configuration, by diffing an isolated layer, and turns it into the pre- and post-conditions a bug finder such as Shseer needs (the paper describes Shseer's focus as scripts that might accidentally delete a system directory). The agent's design never states a pre- or post-condition: its deliverables are only the syntax and PaSh's two classes, because that is what the prompt asks for. It observed effects only incidentally, through `ls` after four probes.

Isolation is the requirement the paper states and the agent did not meet. The paper's challenge C4 is that executions "must be isolated so that their execution does not affect the surrounding system or other … invocations." The agent's runs shared one folder, so each could affect the next (the reused, already-deleted `a` is a small instance), and the folder guard would have failed open. It stayed safe because every target was a name it had just created, not because the environment prevented harm.

What is "correct" depends on which yardstick is used. On syntax, v1's model reproduced v1's reference for `rm`, which was in its prompt as a worked example. The agent departed from that reference in two places, and in both the binary is on the agent's side: GNU `rm` accepts `no`, `none` and `yes`, and `rm -f` with no operand succeeds. Whether zero-or-more is the right reading is arguable, because without `-f` `rm` refuses to run with no operand. Scored against the reference, the agent loses two points; scored against the binary, it gains them. That tension is worth carrying into the scoring step.

What v1 records that the agent does not. On inputs: v1's committed annotation lists the path as an input as well as an output. The likely reason (not checked against the trace) is that the paper counts calls such as `stat` as reads (section 5), and `rm` inspects a file before removing it. The agent, and PaSh's own hand-written annotation, list it only as an output. For PaSh's purposes the agent's choice matches the hand annotation.

Cost. The paper reports per-command CPU time (section 7.4, figure 7) and not the cost of its model step. Run 5 took 60 seconds and $0.80 at list price.

Run 5 compared with run 4

Same model, effort, prompt, image and day; different command.

MEASURE	RUN 4 (`GREP`)	RUN 5 (`RM`)
Wall clock · turns · tool calls	322 s · 11 · 10	60 s · 6 · 5
Output tokens (thinking) · cost	24,495 (6,663) · $2.54	4,623 (937) · $0.80
Manual page	rendered; option lines and four passages	rendered in full
Binary runs before writing	72	27
Isolation	files in `/tmp`	one `mktemp -d` folder
Test after writing	one harness run, 154 binary runs, against stand-ins	none
Parser table versus the sample	unchanged	unchanged
Version named in output files	3 of 4	1 of 4
Report overstates	“Everything passed” (one failure)	a bare `--interactive` means “always” (manual, not tested)

Both runs copied the sample’s PaSh table unchanged and wrote all four files in one call. `rm` drew a much shorter session: about a fifth of the time and output, and no test of the written files at all. `rm` has a smaller interface (17 spellings against `grep`’s 84), which accounts for some of that; the missing post-write test does not follow from it.

What this run suggests we ask next

1. **Run `rm` with prompt version 2**, which asks for execution as the standard of evidence and for reproducibility, to see whether it isolates more and tests what it wrote.
2. **Run a destructive command that is not a sample,** so the session cannot lean on a finished answer. Of the core nine only `rm` and `tee` change files, and both are samples; `rmdir` and `split` are among the six commands this project has already chosen for later confirmation runs.
3. **Decide the yardstick before scoring.** The two places where run 5 departs from v1’s reference are both supported by the binary; record them as disagreements with the reference, not only as errors.
4. **Look at the guard pattern.** `cd $(mktemp -d) && ...` followed by independent lines is a pattern worth flagging in every destructive run: it fails open.
5. **Score the output** and load the classes in the pash VM, as for run 4.

Diagram tooling

The three diagrams were drawn with the Excalidraw diagram skill (`https://github.com/coleam00/excalidraw-diagram-skill`, at `.claude/skills/excalidraw-diagram/`). **The skill's repository declares no licence**; it is listed as third-party, unlicensed material in `LICENSE-TEMPLATES.md`, and is kept in the repository by Tiran's decision of 2026-10-13. The renderer uses the pinned `@excalidraw/excalidraw@0.18.0` import recorded in run 3's analysis. Elements were placed by hand, with a small helper filling Excalidraw's fixed per-element fields and sizing text; the v1-versus-agent diagram reuses run 4's layout with run 5's content. Each was rendered with `uv run python render_excalidraw.py <file>`, inspected, and corrected one or two times.