


Database Consistency Test

Introduction

This EngineeringPaper.xyz sheet shows how to calculate the maximum stress and displacement for a cantilever beam loaded by a vertical force at its end. The geometry of the beam is shown in the figure below. The beam has a rectangular cross section with height h and width b . The maximum stress in a cantilever with length much larger than its height is due to bending stress that occurs at the base of the beam. For a downward force, the maximum stress will be a tensile force at the top of the beam and a compressive stress at the bottom of the beam. For beam sections that are symmetric top to bottom, the maximum tensile and compressive stresses will have equal magnitude.

μ ρ 你好吗？请问你想把“cats and dogs”翻译成普通话吗？ 🤖😄😊🌴🌳🌲 #



Select Beam Material

$$\text{Aluminum Alloys} \quad \begin{cases} E = 71.7 [GPa] \\ v = 0.34 \\ \rho = 2800 \left[\frac{kg}{m^3} \right] \end{cases}$$

Source: Norton, R. L. "Machine design. A integrated approach, 5th Editi." (2013).

Select Beam Section

$$\text{Rectangle} \left\{ \begin{array}{l} I_x = \frac{b \cdot h^3}{12} \\ c = \frac{h}{2} \\ r = [mm] \\ r_1 = [mm] \\ r_2 = [mm] \\ a = [mm] \\ b = 50[mm] \\ h = 75[mm] \\ b_1 = [mm] \\ h_1 = [mm] \end{array} \right.$$

Source for beam section equations and images: https://en.wikipedia.org/wiki/List_of_second_moments_of_area

Define the Other Beam Parameters

$$l = 500[mm]$$

$$F = 500[N]$$

Define the Deflection and Stress Equations

The maximum displacement of a cantilever beam loaded at its end is defined by [1]:

$$y_{max} = -\frac{F \cdot l^3}{3 \cdot E \cdot I_x}$$

where I_x is the area moment of inertia of the cross section about the x-axis as selected in the table above. The maximum displacement can now be queried:

$$y_{max} = [mm] = -0.165297794307557[mm]$$

The maximum bending stress in a beam section is given by:

$$\sigma_{max} = \frac{M \cdot c}{I_x}$$

where M is the bending moment at the section of interest and c is distance from the neutral axis of the beam to the top or bottom of the beam. The maximum moment occurs at the base of the beam and is defined by:


$$M = l \cdot F$$

where l is the length of the beam. Now that everything is defined, the maximum stress can be queried and converted to [MPa] units:


$$\sigma_{max} = [MPa] = 5.33333333333333[MPa]$$

These results can be compared to the results obtained from a finite element analysis using SolidWorks. The beam has the same dimensions, loading, and material as the rectangular cross-section and the aluminum table options above. The displacement plot

is shown below. The maximum displacement magnitude obtained using finite element analysis is .175 [mm], which is close to the .165 [mm] obtained using the equations above.




Similarly, the maximum stress calculation can be compared to the SolidWorks results. The maximum stress obtained from SolidWorks is 6.5 [MPa] as shown below. Note that this is higher than the 5.3 [MPa] obtained using the beam equation. This is the result of the stress concentration that occurs at the base of the cantilever where it meets the fixed boundary condition. A little further from the fixed boundary condition, the finite element values are close to the calculated values.



[1] Norton, R. L. "Machine design. A integrated approach, 5th Editi." (2013).

$$y = \frac{F}{6 \cdot E \cdot I_x} \cdot (x^3 - 3 \cdot l \cdot x^2)$$



All Colors

one

two

three

four

five

six

seven

nine

ten

eleven

twelve

thirteen

fourteen

fifteen

sixteen

seventeen

eighteen

nineteen

twenty

twenty one

twenty two

twenty three

twenty four

twenty five

twenty six

twenty seven

twenty eight

twenty nine

thirty

thirty one

thirty two

thirty three

thirty four

thirty five

highlight

color and highlight

color and bold

color and bold and italics

color and highlight and bold and italics

no text formatting

Created with EngineeringPaper.xyz