MIDWAY'S



PARTS AND OPERATING MANUAL





TABLE OF CONTENTS

	Page No.
GENERAL INSTRUCTIONS	1-2
MONITOR ADJUSTMENTS	2-4
SWITCH ADJUSTMENTS	5
NO. 866—GALAXIAN FRONT PICTURE	6-7
OPEN BACK PICTURE	8-9
CONTROL ASSEMBLY	10-11
PUSH BUTTON ASSEMBLY	12-13
FLUORESCENT FIXTURE ASSEMBLY	14-15
FRONT DOOR ASSEMBLY	16-17
TRANSFORMER BOARD ASSEMBLY	18-19
GAME LOGIC COMPONENTS LAYOUT - A VERSION	20
GAME LOGIC COMPONENTS LAYOUT - B VERSION	21
GAME LOGIC SCHEMATIC	22
GAME LOGIC CHIP NUMBER & FUNCTION	23-24
MEMORY LOGIC SCHEMATIC	25
WIRING SCHEMATIC - "A" VERSION	26
WIRING SCHEMATIC - "B" VERSION	27
WELLS-GARDNER MONITOR SCHEMATIC	28

WARNING

THIS GAME MUST BE GROUNDED. FAILURE TO DO SO MAY RESULT IN DESTRUCTION TO ELECTRONIC COMPONENTS.

COPYRIGHT @BY MIDWAY MFG. CO. ALL RIGHTS RESERVED.

NO PART OF THIS PUBLICATION MAY BE REPRODUCED BY ANY MECHANICAL, PHOTOGRAPHIC, OR ELECTRONIC PROCESS, OR IN THE FORM OF A PHONOGRAPHIC RECORDING, NOR MAY IT BE TRANSMITTED, OR OTHERWISE COPIED FOR PUBLIC OR PRIVATE USE, WITHOUT PERMISSION FROM THE PUBLISHER.

GENERAL INSTRUCTIONS FOR "GALAXIAN"

INSTALLATION

- 1. Remove shipping cleats located on bottom of cabinet.
- 2. Install four (4) provided leg levelers to bottom of cabinet and level cabinet.
- 3. The power is controlled by a switch located on top of the cabinet. Additional taps have been provided on the transformer to compensate for fluctuating line voltage

LINE VOLTAGE SAFETY SWITCH


A line voltage safety switch has been provided for your protection. It is located on the right rear side of the cabinet in the back door area. When the back door is removed, it opens the circuit to the line voltage. To restore power (when servicing), pull switch fully out.

VOLUME CONTROL

The volume control pot is located on the Game Logic Board (P.C. A082-91352-A000). This pot controls the volume of all sounds and may be varied as desired by rotating pot control.

ADJUSTMENT SWITCHES

Located on Game Logic Board (P.C. A082-91352-A000) and may be adjusted as indicated on separate instruction card in back box area.



TO REMOVE CONTROL PANEL AND MONITOR DISPLAY GLASS

- 1. Open coin door.
- 2. Release two (2) clamps located below Control Panel on each side of cabinet.
- 3. Disconnect control panel jack.
- 4. Remove control panel.
- 5. Remove monitor display glass.

CREDIT PUSH BUTTON SWITCH

Located in cash box area and is readily accessible by opening coin door. This switch is provided as a test aid and awards one credit without advancing coin meter.

TEST SLIDE SWITCH

Located in cash box area and is readily accessible by opening coin door. When placed in "on" position this switch initiates test mode.

GAME BOARD TEST

If game board is good, the following information will be displayed on the screen:

0 K

Coin Adjustment Setting

Bonus Adjustment Setting

No. of Galaxip Per Game Setting

RAM/ROM TEST

If any of the Rams or Roms are faulty, the following information will be displayed on the screen:

"Bad Ram 1" - indicates bad Ram at location 7N or 7P.

"Bad Ram 2" - indicates bad Ram at location 3F or 3H.

"Bad Ram 3" - indicates bad Ram at location 4FH or 5FH.

"Bad Ram" — indicates bad Rom on memory board.

*NOTE:

Early models were not equipped with memory boards. In these models, "Bad Rom" indicates bad Rom at location 7F or 7H.

CONTROL PANEL AND COIN SWITCH TEST

To verify operation of any switch, close switch in question. If the switch is operating properly, a game sound will emit when closure is made.

CAUTION: Be sure to return test switch to game mode when all tests are completed.

M051-00866-A012

MONITOR ADJUSTMENTS


Degaussing:

All monitors are equipped with an automatic degaussing circuit which effectively demagnetizes the picture tube each time the monitor is turned on. The degaussing circuit will operate automatically each time the game is turned on after having been off for at least five (5) minutes. The degaussing is confined to the picture tube since the coils are mounted on the ferrous tube shield. Should any part of the chassis of cabinet become magnetized, it will be necessary to degauss the affected area by means of a manual degaussing coil. Move the coil slowly around the parts to be demagnetized, then slowly withdraw the degaussing coil for a distance of six (6) feet before disconnecting the coil from the A.C. power supply.

Purity Adjustments:


If degaussing fails to improve bad color, check for purity as follows. Position monitor to be facing

either north or south. Purity adjustments are most accurate while observing RED FIELD ONLY. Remove the interface printed circuit connector at the monitor. Turn BLUE and GREEN screen controls (shown below) fully counterclockwise.



To obtain RED field, place service switch in RASTER position. Next, adjust the RED screen control to sufficient brightness to observe purity.

Loosen the yoke and slide the yoke back against the convergence coils assembly. Adjust for a uniform RED area in the center of the screen by spreading or rotating the purity magnet assembly located on the BLUE lateral magnet housing assembly.



Spreading the tube increases the magnet strength and moves beams in a radial direction. Rotating the purity magnets moves beams in a circular path.




Figure 4.—Center Landing Adjustments

After purity has been attained, slide yoke toward the picture tube bell while observing entire screen. Position yoke for the best overall RED screen and tighten yoke. Preactivate BLUE and GREEN guns and observe all three beams. If the screen is not a uniform white, repeat purity adjustments. Place service switch in NORMAL position and reconnect interface connector at monitor.

CONVERGENCE ADJUSTMENTS:


Before performing convergence adjustments, the monitor must be preheated for at least five (5) minutes. The convergence service switch is located to the right of the cash box and is accessed by opening coin door. Turn this switch momentarily "ON" then "OFF". When the crosshatch pattern appears on the screen, turn the service switch back to the "ON" position. The crosshatch pattern will now remain on the screen.

Converge the monitor as follows:

CONVERGENCE


- Use either crosshatch or dot pattern for center convergence.
- Converge center of screen with red, green and blue magnet and the blue lateral magnet.
- Adjust R801 and R802 for convergence (parallelism) of R/G vertical center line.
- Readjust center convergence if necessary.
- Adjust R804 to converge bottom R/G horizontal lines and R803 to converge top R/G horizontal lines at center line of screen.
- Adjust R807 and L801 for straight horizontal blue center line.
- 7. Adjust R806 and R805 for uniform displacement of blue horizontal lines along center vertical lines.
- Converge blue horizontal lines with R/G horizontal lines by adjusting the blue convergence magnet. Adjust red and green magnets if necessary.
- Repeat steps 6 through 8 if necessary.
- Adjust alternately L803 and R809 for right and left side convergence of R/G vertical lines.
- Adjust alternately L804 and R808 for convergence of R/G horizontal center line.
- Converge center of screen and repeat steps 10 and 11 if necessary.
- Minor touch-up adjustments may be made using the appropriate controls.

SERVICE ADJUSTMENTS



STEPS 3 AND 5 ADJUSTMENTS

Figure 8.-Effect of R801, R804, R803 and R802 Adjustment



STEPS 6 AND 7 ADJUSTMENTS
Figure 9.—Effect of R807, L801, R806 and R805 Adjustment




Figure 10.—Effect of L803, R809, L804 and R808 Adjustment


When monitor is satisfactorily converged, return service switch to "OFF" position, (game mode).

SWITCH ADJUSTMENTS

PROGRAM NO. 1

METHOD OF	PLAY	
•	SW. 1	SW. 2
1 COIN = 1 PLAY -	0FF	OFF
2 COINS = 1 PLAY	ON	OFF
1 COIN = 2 PLAYS	OFF	ON
FREE PLAY	ON	ON
BONUS GAI	_AXIP	
•	SW. 3	SW. 4
NO BONUS GALAXIP	OFF	OFF
BONUS GALAXIP AT 4000 PTS.	ON	OFF
BONUS GALAXIP AT 5000 PTS.	OFF	ON
BONUS GALAXIP AT 7000 PTS.	ON	ON
NUMBER OF GALAX	(IP PER GAME	
		SW. 5
3 GALAXIP PER GAME		OFF
5 GALAXIP PER GAME		ON
		M051-00866-A0
PROGRAM NO. 2		
METHOD OF	PLAY	
	SW. 1	SW. 2
1 COIN = 1 PLAY	0FF	OFF
2 COINS = 1 PLAY	ON	OFF
1 COIN = 2 PLAYS	OFF	ON
FREE PLAY	ON	ON
BONUS GAI	_AXIP	
	SW. 3	SW. 4
NO BONUS GALAXIP	OFF	OFF
BONUS GALAXIP AT 3000 PTS.	ON	OFF
BONUS GALAXIP AT 4000 PTS.	OFF	ON
BONUS GALAXIP AT 5000 PTS.	ON	ON
NUMBER OF GALA)	(IP PER GAME	
		SW. 5
2 GALAXIP PER GAME	•	OFF
3 GALAXIP PER GAME		ON
	ı	M051-00866-A0

NO. 866 - GALAXIAN - FRONT PICTURE




MIDWAY MFG. CO.

NO. 866 - GALAXIAN - FRONT PICTURE

177.4	DART NO DESCRIPTION		
ITEM	PART Nº	DESCRIPTION	
1	0866-00901-0000	UPPER DISPLAY PLEXI - 23" x 9" x 3/16"	
2	0866-00103-00XF	PLEXI RETAINING BRKT. (2 REQ'D.)	
3	0866-00900-0000	MAIN DISPLAY PLEXI - 2-1/8" x 23" x 3/16"	
	M052-00050-0005	SPONGE RUBBER TAPE - 1/4 x 23" LG.	
4	0866-00904-0000	T.V. BEZEL	
5	0851-00904-0000	DISPLAY PLEXI (SMOKED) - 17-3/8" x 14"	
	M052-00090-0001	DOUBLE COATED TAPE - 1/2 x 17" LG.	
6	0017-00003-0294	19" COLOR MONITOR - COMPLETE	
7	0866-00902-00XF	CONTROL SHELF OVERLAY	
	0017-00101-0639	#8 - 32 x 1-1/4 CARRIAGE BOLTS (6 REQ'D.)	
	0017-00104-0022	#8 WASHER (6 REQ'D.)	
	0017-00103-0061	#8 - 32 HEX NUT W/SEMS. (6 REQ'D.)	
	0017-00101-0775	#6 x 1/2 PHIL. PAN HD. SCREW (2 REQ'D.)	
8	0866-00903-0000	DECORATIVE CONTROL PANEL	
9	A090-00020-2001	DOUBLE ENTRY COIN DOOR ASSY.	
	A090-00057-0000	COIN DOOR COUNTER METER ASSY.	
10	0090-00002-02GR	COIN DOOR FRAME	
	0017-00101-0555	#6 - 32 x 5/16 HEX HD. S.M.S. (3 REQ'D.)	
		(MOUNTS COIN DOOR TO FRAME)	
11	0017-00102-0048	LEG LEVELERS (4 REQ'D.)	
	0017-00103-0026	LEG LEVELER NUTS (4 REQ'D.)	
12	0098-00900-0200	T-MOLDING - GREEN	
İ		NOT SHOWN LIST	
	0017-00003-0187	6" x 9" SPEAKER - 80HM, 9W.	
	0017-00009-0393	BLACK SPEAKER GRILL W/4, 1-1/2" SCREWS	
	0017-00009-0033	LATCH CLAMP (2 REQ'D.)	
	0603-00131-0000	STRIKE (2 REQ'D.)	
	0586-00036-0000	ON-OFF SWITCH	
	0567-00106-0100	SWITCH MTG. PLATE	
	0017-00101-0025	#8 x 1/2 SLOT. HEX HD. WD. SCR. (4 REQ'D.)	
	A866-00036-0000	TEST SWITCH & BKT. ASSY.	


NO. 866 - GALAXIAN - OPENED BACK PICTURE



NO. 866 – GALAXIAN – OPENED BACK PICTURE ORDER BY PART NUMBER ONLY

	UNDEN	BI PART NUMBER ONLT	
ITEM	PART Nº	DESCRIPTION	
1	0017-00003-0294	19" COLOR MONITOR & CHASSIS - COMPLETE	
2	0866-00109-0000	MONITOR MTG. BRKT.	
	0017-00101-0115	#8 - 32 x 2" HEX MACH. SCREW (5 REQ'D.)	
	0017-00101-0639	#8 - 32 x 1-1/4 CARRIAGE BOLT	
	0017-00101-0628	#8 - 32 x 3/4 CARRIAGE BOLT (4 REQ'D.)	
	0017-00104-0022	#8 WASHER (10 REQ'D.)	
1	0017-00103-0061	#8 - 32 HEX NUT SEMS. (10 REQ'D.)	
3	A866-00035-00XF	INTERLOCK SW. BRKT. ASSY.	
	0017-00032-0071	INTERLOCK SWITCH	
4	A082-91352-A866	GAME LOGIC BOARD ASSY.	
	0624-00902-0600	P.C. SUPPORT BRKT 17" (2 REQ'D.)	
	0624-00902-0300	P.C. SUPPORT BRKT 2-1/2'' (2 REQ'D.)	
5	A866-00048-0000	TRANSFORMER BOARD ASSY.	
6	A866-00054-0000	LOW VOLTAGE CABLE ASSY.	
7	A866-00051-0000	POWER CABLE ASSY HIGH VOLTAGE	
	A866-00053-0000	COIN DOOR CABLE ASSY NOT SHOWN	
	A866-00052-0000	CONTROL PANEL CABLE ASSY NOT SHOWN	
		ADDITIONAL PARTS LIST	
	A084-91353-A866	MEMORY BOARD ASSEMBLY	
	A097-00001-0000	LOCK ASSY BACK DOOR	
	0618-00117-0000	VENT SCREEN (2 REQ'D.)	
	A623-00110-0000	COIN BOX ASSY.	
	A623-00013-0000	COIN BOX COVER ASSY.	
	A624-00001-0000	COIN BOX GUIDE BRKT. ASSY.	
	0624-00101-0000	COIN BOX GUIDE BRKT.	
	0017-00101-0628	#8 - 32 x 3/4 CARRIAGE BOLT (4 REQ'D.)	
	0017-00104-0022	#8 STL. WASHER (4 REQ'D.)	
	0017-00103-0061	#8 - 32 LOCK NUT SEMS. (4 REQ'D.)	
	0866-00905-0000	FISHPAPER SHIELD 4 IN. SQ.	
	0017-00009-0419	PIN EXTRACTOR TOOL (PIN POPPER)	


NO. 866 - GALAXIAN - CONTROL ASSEMBLY



MIDWAY MFG. CO.

NO. 866 - GALAXIAN - CONTROL ASSEMBLY

ITEM	PART Nº	DESCRIPTION
1	A866-00028-0000	HANDLE ASSEMBLY
2	0017-00100-0025	"E"-RING
3	0852-00106-0000	PLATE - FOLLOWER
4	A852-0014-00XF	CONTROL SW. BRKT. & TOP PLATE ASSY.
5	0017-00041-0616	RUBBER BUMPER (2 REQ'D.)
6	A866-00027-0000	PIVOT BRKT. HUB & BEARING ASSY.
7	0852-00701-00XF	PIVOT ROD
8	0017-00103-0011	#10 - 32 LOCK NUT
9	0852-00101-00XF	BRACE MAIN BRKT.
10	0017-00101-0553	#6 - 32 x 1/4 SLT. PAN HD. M.S. (6 REQ'D.)
11	0017-00101-0637	#8 - 32 x 1" CARRIAGE BOLTS (4 REQ'D.)
12	0017-00104-0022	#8 STL. WASHER (4 REQ'D.)
13	0017-00103-0061	#8 - 32 HEX LOCKNUT SEMS. (4 REQ'D.)
14	0852-00103-00XF	SWITCH BRACKET (2 REQ'D.)
15	A852-00016-0000	SWITCH ASSY. (2 REQ'D.)
16	0020-00202-0000	SWITCH PLATE (2 REQ'D.)
17	0017-00101-0737	#5 - 40 x 5/8 PAN HD. M.S. (4 REQ'D.)



NO. 866 - GALAXIAN - PUSH BUTTON ASSY.


ITEM	PART Nº	DESCRIPTION	
1	0017-00009-0384	BUTTON	
2	0010-00593-0000	SPRING	
3 4	0017-00009-0376 0017-00104-0028	BUTTON HOUSING FLAT WASHER (2 REQ'D.)	
5	0017-00104-0025	E-RING	
"	A739-00012-0000	PUSH BUTTON ASSY. (FIRST 5 ITEMS)	
6	0586-00107-0000	MOUNTING BRKT.	
7	0017-00103-0054	PAL NUT	
8	A739-00016-0000	SWITCH ASSY.	
9	0020-00202-0000	SWITCH PLATE	
10	0017-00101-0526	#5 - 40 x 9/16 PHIL. HD. M.S. (2 REQ'D.)	

NO. 866 - GALAXIAN - FLUORESCENT FIXTURE ASSEMBLY OR (D) INCANDESCENT LIGHT ASSEMBLY 0 4 (00) MIDWAY MFG. CO. (M) (5) (**9**

PAGE 14


NO. 866 - GALAXIAN - FLUORESCENT FIXTURE ASSEMBLY OR INCANDESCENT LIGHT ASSEMBLY

ITEM	TEM PART Nº DESCRIPTION	DESCRIPTION
1 1	0017-00003-0043	18 IN. FLUORESCENT LAMP - COOL WHITE
2	0017-00021-0005	FLUORESCENT LOCKS (2 REQ'D.)
3	0017-00031-0036	FLUORESCENT SOCKET (2 REQ'D.)
4	0017-00101-0573	#6 - 32 x 1/2 SLT. RND. HD. M.S. (2 REQ'D.)
5	0866-00108-0000	FLUORESCENT BRKT. ASSY.
6	0017-00021-0096	2 PIN SOCKET CONNECTOR
7	0017-00003-0026	BALLAST
8	0017-00101-0593	#8 - 32 × 1/4 SLT. PAN HD. M.S. (2 REQ'D.)
9	0017-00021-0079	STARTER HOLDER
10	0017-00003-0019	STARTER
11	0017-00101-0528	#5 - 40 x 3/4 R.H.M.S. (2 REQ'D.)
	A866-00039-0000	FLUORESCENT CABLE ASSY NOT SHOWN
ŀ		INCANDESCENT LIGHT ASSEMBLY
		USED AFTER GAME NO. 3,000
	0866-00113-0000	SOCKET MTG. BRKT. (2 REQ'D)
	0017-00003-0135	LAMP SOCKET (2 REQ'D.)
	0017-00003-0309	LAMP 12V., 25W. (2 REQ'D.)
	0017-00101-0626	#8 - 32 × 3/4 SLT. PAN HD. M.S. (4 REQ'D.)
	0017-00103-0061	#8 - 32 HEX NUT W/SEMS. (4 REQ'D.)
j j		



NO. 866 - GALAXIAN - FRONT DOOR ASSY.

ITEM	PART Nº	DESCRIPTION DESCRIPTION		
	10011112	DESCRIPTION		
1	0090-00902-0000	DRESS PLATE		
	0090-00902-0100	DRESS PLATE (W/O PRESS BUTTON TO		
		START GAME)		
2	0017-00101-0552	#6 - 32 x 1/4 CARRIAGE BOLT (2)		
3	0090-00117-03XF	COIN ENTRY PLATE (25¢)		
4	0090-00906-0000	PLASTIC START BUTTON		
5	0010-00007-0000	COMPRESSION SPRING		
6	0090-00013-0200	DOOR ASSY. DOUBLE ENTRY		
7	0017-00005-0050	DOOR LOCK & KEY WITH SCREW & NUT DOUBLE DOOR FRAME		
8 9	0090-00002-02BR 0017-00005-0041	421 N.S. CAM		
10	0017-00003-0041	DOOR SWITCH		
11	0090-00901-0000 0090-00126-01XF	SWITCH BACKUP PLATE		
12	0017-00101-0528	#5 - 40 x 3/4" LNG. M.S.		
13	0090-00903-0040	25¢ WINDOW		
14	0090-00143-0000	COIN PLEX RETAINER		
15	0017-00104-0002	SPLIT LOCK WASHER		
16	0017-00007-0019	KEY HOOK		
17	0017-00103-0005	#6 - 32 HEX NUT		
18	0090-00010-0000	SW. PLATE & OILLITE ASSY.		
19	0017-00100-0018	"E" RING		
20	0090-00131-0000	SWITCH		
21	0090-00104-0000	TOP & BTM. COIN CHUT W/BRKT. ASSY.		
22	0017-00101-0598	#8 - 32 x 5/16 SCREW		
23	0010-00181-0100	SPRING		
24	0090-00129-00XF	PIVOT POST		
25	0010-00134-0000	SPRING		
26	0090-00008-0000	ACCEPTOR FRAME ASSY.		
27	0093-00155-00XF	REJECTOR LEVER		
28	0017-00100-0012	"E" RING		
29	0093-00151-00XF	COIN GUIDE MTG. BRACKET		
30 31	0090-00005-0000 0017-00101-0555	COIN GUIDE ASSY. #6 - 32 x 5/16 SCREW		
32	0017-00101-0555	COIN SWITCH		
33	0017-00005-0035	TRIPWIRE		
34	0017-00007-0132	PUSH-ON RING (BIK)		
35	0017-00007-0132	#4 - 36 x 3/4 SCREW		
36	0090-00128-00XF	SWITCH BRKT DOOR TILT		
"	A090-00061-0000	ANTI-STRING DEVICE ASSY OPTIONAL		
		(REPLACES ITEM 30)		
	A090-00064-0000	ANTI-PENNY DEVICE ASSY OPTIONAL		
(




NO. 866 – GALAXIAN – TRANSFORMER BOARD ASSEMBLY ORDER BY PART NUMBER ONLY

ITEM	PART Nº	DESCRIPTION
IIEM	FARI NY	DEJCRIF HOIA
1	MT00-00082-0000	TRANSFORMER - 115 VOLT
2	MT00-00081-0000	TRANSFORMER - 240 VOLT
3	0017-00003-0114	NOISE FILTER
4	A031-00002-0000	TERMINAL STRIP ASSY.
5	0064-030XX-XXPX	IN4004 400 V. DIODE
6	0720-00001-0200	2 POSITION FUSE CLIP
7	0017-00003-0103	FUSE 1A. SLO-BLO
8	0017-00003-0261	FUSE 1.5A. SLO-BLO
9	0720-00001-0400	4 POSITION FUSE CLIP
10	0017-00003-0169	FUSE 5A. (2 REQ'D.)
11	0017-00003-0001	FUSE 1A. (2 REQ'D.)
12	0017-00101-0637	#8 - 32 x 1-1/4 CARRIAGE BOLT (4 REQ'D.)
	0017-00103-0008	#8 - 32 HEX NUT (4 REQ'D.)
13	0017-00101-0014	#6 x 1/2 SLT. HEX HD. WD. SCR. (12 REQ'D.)
14	0017-00101-0018	#6 x 3/4 SLT. HEX HD. WD. SCR. (4 REQ'D.)
	A866-00049-0000	LINE CORD ASSY NOT SHOWN
]		

PAGE 20

COMPONENT LAYOUT PART NO. MOSI-00866-A002

PAGE 21



GALAXIAN LOGIC BOARD


CHIP NUMBER	FUNCTION
74LS00	Quad Two Input Nand
74LS02	Quad Two Input Nor
7404	Hex Inverter
74LS08	Quad Two Input And
74LS10	Triple Three Input Nand
74LS20	Dual Four Input Nand
74LS30	Eight Input Nand
74LS32	Quad Two Input Or
74LS74	Dual "D" Flip — Flop
74LS86	Quad Two Input Exclusive Or
74LS107	Dual "JK" Flip — Flop
74LS138	Three to Eight Line Decoder
74LS139	Dual Two to Flour Line Decoder
74LS157	Quad Two Input Multiplexer
74LS161	Four Bit Counter
74LS163	Four Bit Counter
74LS164	Eight Bit Shift Register
74LS174	Hex "D" Flip — Flop
74LS175	Quad "D" Flip — Flop
74LS194	Eight Bit Shift Register
74LS259	Eight Big Addressable Latch
74LS273	Octal "D" Flip — Flop
74LS823	Four Bit Binary Adder
74LS245	Octal Bus Transceiver
74LS366	Hex Bus Driver — Inverting
74LS367	Hex Bus Driver
74LS368	Hex Bus Driver — Inverting
74LS377	Octal "D" Flip — Flop


GALAXIAN LOGIC BOARD


CHIP NUMBER FUNCTION 74LS393 **Dual Four Bit Binary Counter** 27LS00 Ram 2114 Ram TMS4045 Ram AM9124 Ram 2102-2 Ram AM9101 Ram 8304 Bus Driver - Bidirectional 8216 Bus Driver - Bidirectional LM324 Quad Operational Amp 555 Timer LM377 Audio Amp Z80 **CPU** 2716 Prom - 16K 1M5610 Prom **78GUIC** Voltage Regulator **ULN2075** Quad Buffer 18.432 X-TAL CD4066 Quad Electronic Switch **D44VM4** Transistor GE6015 Transistor MC14066 Quad Electronic Switch GEA15F Diode - Rectifier A14F Diode - Rectifier IN4148 Diode - Rectifier IN4736A Diode - Zener **D2316EC** 16K Rom


64K Rom

D2364C









NOTES

This space is provided for personal notes