19 – Subagents

AI Training for Beginners

Self-study training: use AI/LLMs safely in everyday life

Version 1.0 • As of: October 2026

File: `19_subagents.md`

https://github.com/mgunthner/AI-Training

License: CC BY-NC-SA 4.0

Contents

19 – Subagents **1**
Key points 1
Example 1
Do / Don’t 2
Safety note 2
Mini checklist 2
Exercise (5 min.) 2
Next 2

19 – Subagents

Definition: Subagents are specialized AI helpers that a main agent (or you) entrusts with parts of a project. Each subagent works on its subtask with its own, clean context.

> **Remember:** One boss, many specialists: the main agent assigns the work, the subagents deliver results.

Key points

- **Core idea:** The main agent coordinates. Subagents handle subtasks – each with its own context window, instead of cramming everything into a single long chat (topic 02).
- **Advantages:**
  - **Context stays manageable:** each helper only knows its own part
  - **Parallelization:** subtasks run at the same time
  - **Specialization:** each subagent gets instructions tailored exactly to its task
- **Disadvantages:**
  - **More cost/tokens:** each subagent needs its own instructions and context
  - **Coordination errors:** results don’t fit together if the requirements are unclear
  - **Harder to trace:** who did what with which specifications?
- **Example split:** research agent (collects material), writing agent (drafts the text), review agent (looks for errors and contradictions).
- **Rule of thumb:** Only split things up if the subtasks are truly independent. Otherwise a single chat is simpler, cheaper and less error-prone.
- **How it relates:** A subagent *executes*. An advisor (topic 20) only *advises*.

Example

Project: create an anonymized case study for a course.

Helper	Task	Gets	Delivers
Research agent	Collect material	Topic list, criteria	Source list with bullet points
Writing agent	Write the text	Source list, style guidelines	Draft

Helper	Task	Gets	Delivers
Review agent	Proofread	Draft, checklist	Error list

Be careful with the handovers: each helper only needs *its* part of the information. The review agent doesn't need the search history – only the draft and the checklist. That keeps the context small – and the costs too.

Do / Don't

Do	Don't
Only split off truly independent subtasks	Start three helpers out of habit
Give each task instructions tailored to it	Give everyone the same unsorted context
Check the handovers between helpers	Let results be passed on unchecked

Safety note

Every subagent with tool access is its own risk (topics 12, 21). Give helpers only the permissions their subtask needs, and keep track of who is allowed to do what.

Mini checklist

- ☐ I can tell the main agent and a subagent apart.
- ☐ I can name two advantages and two disadvantages of splitting work up.
- ☐ I only split up independent subtasks.
- ☐ I give each helper only its part of the context.

Exercise (5 min.)

Take a project from your everyday life (e.g. planning a trip, moving house, a birthday party). Split it across three helpers (research, planning, review). For each one, write down: the task, what it needs to receive, and what it should deliver. Then check: are they really independent? Would one helper do as well?

Next

- Extra exercises: `02_extra_exercises/19_extra_exercises`
- Test: Test E (Agentic systems)
- Related: 16 Agents, 20 Advisor pattern, 02 Tokens & context, 21 Running agents safely

As of: October 2026