



MODUL 15 · DEPLOYMENT & PRODUCTION

Deploy Full-Stack di Vercel

Dari local ke production dalam satu push. Vercel otomatis handle build, CDN, dan scaling.



Persiapan Sebelum Deploy Pertama

Empat hal yang harus siap sebelum push ke Vercel.

```
{
  "scripts": {
    "dev": "next dev",
    "build": "next build",
    "start": "next start",
    "lint": "next lint",

    // ✅ WAJIB: generate Prisma client setiap install
    "postinstall": "prisma generate",

    // Utility scripts
    "db:generate": "prisma generate",
    "db:migrate": "prisma migrate deploy",
    "db:push": "prisma db push",
    "db:studio": "prisma studio",
    "db:seed": "tsx prisma/seed.ts"
  }
}

// — Vercel Build Command —
// Di Vercel Settings → Build & Output Settings:
// Build Command:
// prisma generate && prisma migrate deploy && next build
//
// Atau di vercel.json:
// {
//   "buildCommand":
//     "prisma generate && prisma migrate deploy && next build"
// }
```

Checklist Pre-Deploy

- ✅ postinstall: prisma generate di package.json
- ✅ Build command di Vercel: prisma generate && prisma migrate deploy && next build
- ✅ Semua env vars sudah di Vercel dashboard (bukan .env)
- ✅ Database production siap: URL dan credentials valid
- ✅ OAuth callback URLs di-update: Dev: localhost:3000 Prod: yourdomain.com
- ✅ BETTER_AUTH_URL di-update ke production URL
- ✅ Test: bun run build tidak ada error lokal

Setup Vercel — Import Project & Env Vars

Tiga langkah: import repo, set env vars, trigger deploy pertama.

01

Import Repository

vercel.com → New Project → Import Git Repository. Pilih repo GitHub. Vercel auto-detect Next.js framework.

02

Build Command

Settings → Build & Output Settings. Ubah Build Command: prisma generate && prisma migrate deploy && next build

03

Environment Variables

Settings → Environment Variables. Tambahkan SEMUA secrets: DATABASE_URL, DIRECT_URL, BETTER_AUTH_SECRET, GOOGLE_CLIENT_SECRET, dll.

04

Trigger Deploy

Push ke main branch → Vercel auto-deploy. Atau klik 'Redeploy' di dashboard jika sudah import.

05

Custom Domain

Settings → Domains → Add domain. Update DNS records. Update NEXT_PUBLIC_APP_URL dan BETTER_AUTH_URL ke domain baru.

06

Verify

Buka URL produksi. Test: login, buat post, upload gambar. Cek Vercel Logs jika ada error.

Update OAuth & Better Auth untuk Production

URL callback harus diupdate ke domain production setelah deploy — sering lupa!

● ● ● Google Console — update redirect URIs

```
# Google Cloud Console:
# APIs & Services → Credentials
# → OAuth 2.0 Client ID → Edit

# Authorized JavaScript Origins:
# ✓ http://localhost:3000 (dev)
# ✓ https://yourapp.vercel.app (production)
# ✓ https://yourdomain.com (custom domain)

# Authorized Redirect URIs:
# ✓ http://localhost:3000/api/auth/callback/google
# ✓ https://yourapp.vercel.app/api/auth/callback/google
# ✓ https://yourdomain.com/api/auth/callback/google

# ⚠ Tanpa ini: OAuth login akan error
# "redirect_uri_mismatch" di production!

# Waktu propagasi: 5 menit - beberapa jam
# Sabar jika tidak langsung bekerja.
```

● ● ● Vercel env vars untuk production

```
# Di Vercel → Settings → Environment Variables
# Pastikan ini ter-set untuk Environment: Production

BETTER_AUTH_URL="https://yourdomain.com"
# ↑ BUKAN localhost! URL production!

NEXT_PUBLIC_APP_URL="https://yourdomain.com"

# Database (dari Neon atau provider lain):
DATABASE_URL="postgresql://...neon.tech/db?
sslmode=require"
DIRECT_URL="postgresql://...neon.tech/db?
sslmode=require"

# Auth secrets:
BETTER_AUTH_SECRET="<32+ char random string>"
GOOGLE_CLIENT_ID="xxx.apps.googleusercontent.com"
GOOGLE_CLIENT_SECRET="GOCSPX-xxx"

# Cloudinary:
CLOUDINARY_CLOUD_NAME="your_name"
CLOUDINARY_API_KEY="123456789"
CLOUDINARY_API_SECRET="abc123..."

# Vercel auto redeploy setelah save env vars!
```

K U I S

Evaluasi Pemahaman

Jawab sebelum lanjut.

Q1 — Mengapa 'postinstall: prisma generate' wajib di package.json untuk Vercel?

- A) Prisma butuh generate saat setiap request B) Vercel build container fresh setiap deploy — prisma generate tidak auto-jalan tanpa postinstall C) npm install tidak jalan di Vercel

Q2 — Apa yang terjadi jika BETTER_AUTH_URL masih localhost:3000 saat deploy ke production?

- A) Session tidak bekerja karena cookie domain mismatch — user selalu logout B) Tidak masalah — Better Auth auto-detect C) Error hanya di Chrome

Q3 — Kapan Vercel trigger deployment otomatis?

- A) Hanya manual dari dashboard B) Setiap 24 jam C) Setiap push ke branch yang di-connect (biasanya main) — dan setiap PR mendapat preview URL

Tugas Mandiri

Deploy project ke Vercel untuk pertama kali.

01 Pre-Deploy Check

Jalankan bun run build lokal. Fix semua TypeScript errors. Pastikan tidak ada import yang rusak. Target: build sukses tanpa warning.

02 Vercel Import

vercel.com → New Project → Import repo. Set Build Command: prisma generate && prisma migrate deploy && next build. Tambahkan semua env vars.

03 OAuth Update

Update Google Console: tambahkan production URL ke Authorized Origins dan Redirect URIs. Update BETTER_AUTH_URL di Vercel env vars.

04 Smoke Test

Setelah deploy: test login (email + Google), buat post, upload gambar, cek sitemap.xml, cek /robots.txt. Buka Vercel Logs jika ada error.

💡 Vercel Logs: dashboard → project → Functions tab → lihat real-time logs setiap request. Sangat berguna untuk debug production issues.

Yang Sudah Kita Pelajari

- ✓ postinstall: prisma generate di package.json — wajib agar client ter-generate di Vercel.
- ✓ Build command: prisma generate && prisma migrate deploy && next build.
- ✓ Semua secrets di Vercel dashboard — bukan file yang di-commit.
- ✓ BETTER_AUTH_URL dan OAuth callback URLs harus diupdate ke domain production.
- ✓ Setiap push ke main = auto-deploy. Setiap PR = preview URL otomatis.

→ Selanjutnya: **Bab 3 — Prisma Generate & Migrate Deploy di Pipeline**

