

Lab 01 Revision of programming concepts of C language

Objectives:

- To revise definition and declaration (instantiation) of Structures in C.
- To revise Pointers in C and their use with Structures.
- To revise file handling in C and writing/reading Structure arrays to/from files.

Reading Task 1: Working with Structures in C

In C programming, a struct (or structure) is a collection of variables (can be of different types) under a single name.

Defining a Structure:

Before we can create structure variables, we need to define its data type. To define a structure, the **struct** keyword is used.

Here is an Example:

```
struct Person
{
    char name[50];
    int citNo;
    float salary;
};
```

Here, a derived type **struct Person** is defined. Now, we can create variables of this type.

Creating Structure Variables:

When a struct type is declared, no storage or memory is allocated. To allocate memory of a given structure type and work with it, we need to create variables.

Here's how we create structure variables:

```
struct Person
{
    char name[50];
    int citNo;
    float salary;
};

int main()
{
    struct Person person1, person2, p[20];
    return 0;
}
```

Another way of creating a struct variable is:

```
struct Person
{
    char name[50];
    int citNo;
    float salary;
} person1, person2, p[20];
```

In both cases, two variables person1, person2, and an array variable p having 20 elements of type struct Person are created.

Accessing Members of a structure:

There are two types of operators used for accessing members of a structure.

- Dot (.) - Member operator
- Arrow (->) - Structure pointer operator (will be discussed in the next section)

Suppose, we want to access the salary of person2. Here's how we can do it.

```
person2.salary
```

C Pointers to structures:

Here's how we can create pointers to structures.

```
struct name
{
    member1;
    member2;
    .
    .
};

int main()
{
    struct name *ptr;
}
```

Here, a pointer ***ptr*** of type ***struct name*** is created. That is, ***ptr*** is a pointer to ***struct***.

Access members using Pointer:

To access members of a structure using pointers, we use the Arrow “->” operator.

```
#include <stdio.h>
struct person
{
    int age;
    float weight;
};
int main()
{
    struct person *personPtr, person1;
    personPtr = &person1;
    printf("Enter age: ");
    scanf("%d", &personPtr->age);
    printf("Enter weight: ");
    scanf("%f", &personPtr->weight);
    printf("Displaying:\n");
    printf("Age: %d\n", personPtr->age);
    printf("weight: %f", personPtr->weight);
    return 0;
}
```

In this example, the address of **person1** is stored in the **personPtr** pointer using

personPtr = &person1;

Now, we can access the members of **person1** using the **personPtr** pointer

Dynamic Memory Allocation for structures:

Before you proceed with this section, we recommend you to check C dynamic memory allocation in your programming text book.

Sometimes, the number of struct variables we declared may be insufficient. We may need to allocate memory during run-time. Here's how we can achieve this in C programming.

Example: Dynamic memory allocation of structs

```
#include <stdio.h>
#include <stdlib.h>
struct person {
    int age;
    float weight;
    char name[30];
};
int main()
{
    struct person *ptr;
    int i, n;
    printf("Enter the number of persons: ");
    scanf("%d", &n);
    // allocating memory for n numbers of struct person
    ptr = (struct person*) malloc(n * sizeof(struct person));
    for(i = 0; i < n; ++i)
    {
        printf("Enter first name and age respectively: ");
        // To access members of 1st struct person,
        // ptr->name and ptr->age is used
        // To access members of 2nd struct person,
        // (ptr+1)->name and (ptr+1)->age is used
        scanf("%s %d", (ptr+i)->name, &(ptr+i)->age);
    }
    printf("Displaying Information:\n");
    for(i = 0; i < n; ++i)
        printf("Name: %s\tAge: %d\n", (ptr+i)->name, (ptr+i)->age);
    return 0;
}
```

When we run the program, the output will be:

```
Enter the number of persons: 2
Enter first name and age respectively: Harry 24
Enter first name and age respectively: Gary 32
Displaying Information:
Name: Harry Age: 24
Name: Gary Age: 32
```

In the above example, **n** number of **struct** variables are created where **n** is entered by the user.

To allocate the memory for n number of struct person, we used,

```
ptr = (struct person*) malloc(n * sizeof(struct person));
```

Then, we used the **ptr** pointer to access elements of person.

In-Lab Task 1:

Build and run the program given in Code Listing 1.

In-Lab Task 2:

The program in Code Listing 1 writes a single record to the file. Modify it, to use a function 'write_records_to_file' with following prototype:

```
int write_records_to_file (struct emp * sptr, int num_records, FILE * fptr)
```

This function should write 'num_records' number of structures from a dynamically allocated memory pointed to by 'sptr' to a file pointed to by 'fptr'. It should return the number of structures successfully written to the file.

In-Lab Task 3:

Write functions 'read_records_from_file', and 'print_records' with following prototypes

```
int read_records_from_file(struct emp * sptr, int num_records, FILE * fptr)
void print_records(struct emp * sptr, int num_records);
```

Use these functions to read a previously written file (employees_records2.dat) and display the contents on screen.

Post-Lab Task:

The structures that you write in a file using 'fwrite()' are written in the binary format and cannot be viewed in a text editor properly. Your task is to write the contents of these structures in the text format so that the contents may be viewed in a text editor.

```

#include <stdio.h>
#include <stdlib.h>

/// Define a structure 'emp' to hold data about an employee
struct emp
{
    char name[48]; // Name of the employee
    int age;
    float bs;      // Basic Salary as a floating point number.
};

void flush(void);
int write_records_to_file (struct emp * sptr, int num_records, FILE * fptr);
int read_records_from_file(struct emp * sptr, int num_records, FILE * fptr);
void print_records(struct emp * sptr, int num_records);

int main(void)
{
    FILE *fp ;
    char another = 'Y' ;
    struct emp employee;
    int i = 0;
    int num_rec = 0;

    // Open the file for writing in the Binary Mode
    fp = fopen ( "employees_records.dat", "wb" ) ;

    if ( fp == NULL ) {
        printf ( "Cannot open file\n" ) ;
        exit(0) ;
    }

    while ( another == 'Y' )
    {
        printf ( "\nEnter the name of the Employee: " ) ;
        fgets (employee.name, 48, stdin);
        printf ( "\nEnter the age of the Employee: " ) ;
        scanf("%d", &employee.age);
        printf ( "\nEnter the Basic Salary of the Employee: " ) ;
        scanf("%f", &employee.bs ) ;
        // Writing to file
        fwrite ( &employee, sizeof ( struct emp ), 1, fp );

        flush();

        printf ( "Add another record (Y/N) " );

        another = getchar() ;

        flush();

        i++;
    }
    fclose(fp);
    return(0);
}

```

Code Listing 1