



CyTOS

CYCLE TIME OPTIMISING SOLUTIONS



PRODUCT CATALOGUE

SMART SOLUTIONS.
OPTIMISED PERFORMANCE.



IMPROVE
EFFICIENCY



ENHANCE
PRODUCTIVITY



REDUCE
DOWNTIME



ENSURE
QUALITY



www.cytos.in

OPTIMISE TODAY.
PERFORM TOMORROW.



Overview

CyTOS introduces a wide range of Soft metal machines, which have a capacity to work on Brass, Aluminum or any other soft metal. We are committed to provide you top quality machine of your requirement with reasonable price range. Incorporated with Precision ball-screws help these machines to deliver high accuracy even at larger bed sizes. Drilling, Boring, Milling are the processes which these machines can perform.

Heavy Mild Steel Structure

We provide rigid high quality Mild Steel structure, which has in vibration absorbing property. This structure is an assembly of Mild Steel base and square shaped column on which the z axis is further assembled.

Structure Design

The machine structure is designed in such a way that the vibrations and unbalanced forces during the processes are easily transferred the ground without allowing any effect of vibrations on the machine. These features enables the machine to deliver high accuracy in any job.

CNC Basic	Parameters
Electrical Drive	Stepper motor, Easy Servo Motor, AC Servo
Machine type	Floor Mounted Machine
No. of Spindles	1-5 Nos
Processes	MDF, PVC, Bakelite, Wood, Plastic, Acrylic, Aluminum Drilling and Engraving
	Min width: 1mm
Travel Speed	4000mm/min—10,000mm/min As required
Spindle	1.8Kw @ 40K rpm - 6.5Kw @ 25k RPM
Tool change type	Manual/ Automatic Tool Change
Spindle Type	Water cooled/ air Cooled (Depends on spindle power)
Weight of machine	800 Kg— 1,050 kg
Sheet Clamping Type	T Slot Aluminum Bed
Working Area for Single Spindle	4ft X 4ft X 250mm - 10ft X 10ft X 300mm (X-Y-Z)
Working Area per spindle	X- Axis Travel - 600 mm X- Axis Travel - 750 mm Y- Axis Travel - 2500 mm Y- Axis Travel - 3000 mm Z- Axis Travel - 280mm Z- Axis Travel - 280mm
Collet Size	3 to 10 mm
Ports	USB 2.0 High Speed USB Device
Control Language	Standard NC Programming Language (G-Code, M-Code)
Accuracy	0.1 mm
Repeatability	+/-0.05 mm
Control System	PC Based System
Power supply	Input voltage: 230 - 240V AC Input current: 16A 50Hz
Accessories	Coolant tank, Dust collection arrangement, PC based controller with monitor, CPU

CNC 6060 Drilling And Routing Machine



Overview

CyTOS have been manufacturing High quality of CNC Machines and Systems such as CNC PCB Drilling And Routing Machine, CNC Metal Drilling Machine, CNC PCB Rapid Prototyping Machine and Aluminium PCB Routing Machine.

Performance

Our machines are built using high grade cast iron and steel frame structure. Motion and positions are ensured with the help of guide rails and ball screws, a reliable source of maintaining committed accuracy for long period of time.

CNC 6060 Drilling And Routing Machine

CNC 6060	Parameters
Electrical Drive	Stepper, Easy Servo and AC servo axis Motors
Machine Type	Floor Mounted
No of Spindles	1 - 5 Nos
Process	Drilling And Routing Machine
	Drill Range: 0.2 mm to 3mm
	Routing : 1 mm to 4mm
Travel Speed :	6000 mm/min to 15,000 mm/min
Spindle (RPM)	18,000 RPM - 1,00,000RPM
Spindle (Power)	1.2 Kw - 4.5Kw
Tool Change	Manual and Pneumatic ATC
Drilling Dia. (Min)	0.2 mm
Routing Dia. (Min)	1mm
PCB Clamp Type	Dowel Pin / T Slot Aluminum Bed
Working Area For Single Spindle	X—Axis Travel—600 mm
	Y—axis Travel—600 mm
	Z—axis Travel—100 mm
Collect Size	3 to 6 mm
Ports	USB 2.0 High Speed USB Device
Control Language	Standard NC Programming Language (G-Code, M-Code)
Accuracy	0.05 mm
Repeatability	+/-0.03 mm - 0.05 mm
Type Of Control System	PC Based System
Power Supply	Input Voltage: 230—240V AC Input Current: 16A 50Hz
Accessories	Coolant Tank, Dust Collection Arrangement, PC Based Controller with monitor

CNC 3020 Rapid Prototyping Machine



Overview

CyTOS have been manufacturing High quality of CNC Machines and Systems in CNC PCB Rapid Prototyping Machine and Aluminum PCB Routing Machine. Specially designed for college and training purposes. Key features like auto level, automatic tool change and cameras for visuals have been incorporated in the machine.

Built Quality

Our machines are built using high grade aluminum and steel frame structure. Motion and positions are ensured with the help of guide rails and ball screws, a reliable source of maintaining committed accuracy for long period of time. This model is one of the finest example of compact system with accuracy and performances.

CNC 3020 Drilling And Routing Machine

CNC Basic	Single Spindle
Electrical Drive	Stepper Motor - Easy Servo Motor
Machine type	Table top
Machine size	3ft X 4ft X 5ft
Processes	Drilling & Routing
Travel Speed	6000 mm/min
Spindle	0.8Kw - 1.2 Kw (18000 - 40000 RPM)
Drilling Dia. (Min)	0.4 mm - 3 mm
Routing Dia. (Min.)	1mm - 3mm
Tool change type	Manual / Pneumatic (Button Press) ATC
Spindle Type	Air cooled and Water Cooled both available
Weight of machine	60Kg– 80kg
PCB Clamping Type	Dowel Pin / T Slot Aluminium Bed
Working Area for Single Spindle	X- Axis Travel - 300mm
	Y- Axis Travel - 200 mm
	Z- Axis Travel - 60mm
Collet Size	3 to 6 mm
Ports	USB 2.0 High Speed USB Device
Control Language	Standard NC Programming Language (G-Code, M-Code)
Accuracy	0.05 mm
Repeatability	(99%) +/-0.05 mm
Control System	PC Based System
Power supply	Input voltage: 230 - 240V AC Input current: 16A 50Hz
Accessories	Enclosure, Coolant tank

CNC 3030 Drilling And Routing Machine



CNC Basic	Single Spindle			
Electrical Drive	Stepper motor	Easy Servo Motor	Easy Servo Motor	AC Servo
Machine type	Table top			
Machine size	3ft X 4ft X 5ft			
Processes	Engraving (Rapid Prototype)			
	Min width: 0.3mm			
	Travel Speed: 166 mm/sec	Travel speed: 166 mm/sec	Travel speed: 166 mm/sec	Travel speed: 166 mm/sec
Spindle	28,000 rpm 800 w	40,000 rpm 1.5 Kw	60,000 rpm 1.5 Kw	60,000 rpm 1.5 Kw
Tool change type	Manual	Manual	Pneumatic (Button Press)	ATC
Spindle Type	Air cooled	Water cooled	Water cooled	Water cooled
Weight of machine	250 Kg	300 Kg	350 Kg	370 Kg
PCB Clamping Type	Dowel Pin / T Slot Aluminium Bed			
Working Area for Single Spindle	X- Axis Travel - 300mm			
	Y- Axis Travel - 300 mm			
	Z- Axis Travel - 60mm			
Collet Size	3 to 6 mm			
Ports	USB 2.0 High Speed USB Device			
Control Language	Standard NC Programming Language (G-Code, M-Code)			
Accuracy	0.05 mm			
Repeatability	+/-0.05 mm			
Control System	PC Based System			
Power supply	Input voltage: 230 - 240V AC Input current: 16A 50Hz			
Accessories	Coolant tank, Dust collection arrangement, PC Based controller with monitor, CPU			

Foam Welding Machine



Overview

CyTOS this year introduces a new product in the field of packaging and foam handling. A fully functioned Foam welding machine with automatic controls designed for mass production in foam welding. CyTOS is open to work for its wide range application in size and heating technique areas as per the user requirements.

Performance

Our machines are built using high grade aluminum and steel frame structure. Motion and positions are ensured with the help of guide rails and ball screws, a reliable source of maintaining committed accuracy for long period of time. This model is one of the finest example of compact system with accuracy and performances.

Wood/ Acrylic/Aluminum Router Machine



CNC Basic	Single Spindle			
Electrical Drive	Stepper motor	Easy Servo Motor	Stepper Motor	Easy Servo Motor
Machine type	Floor Mounted Machine			
Machine size	5.5Ft X 10Ft X 6.5Ft		6.5Ft X 12.5Ft X 6.5Ft	
	Wood, Plastic, Acrylic, Aluminum Drilling and Engraving			
	Min width: 1mm			
	Travel Speed: 130 mm/sec	Travel speed: 130 mm/sec	Travel speed: 130 mm/sec	Travel speed: 130 mm/sec
Processes				
Spindle	24000 rpm 3.5 Kw	24,000 rpm 4.5 Kw	24,000 rpm 3.5 Kw	24,000 rpm 4.5 Kw
Tool change type	Manual	Manual	Manual	Manual
Spindle Type	Water cooled	Water cooled	Water cooled	Water cooled
Weight of machine	800 Kg	800 Kg	1050 Kg	1050 Kg
Sheet Clamping Type	T Slot Aluminum Bed			
Working Area for Single Spindle	X- Axis Travel - 1200 mm		X- Axis Travel - 1500 mm	
	Y- Axis Travel - 2500 mm		Y- Axis Travel - 3000 mm	
	Z- Axis Travel - 280 mm		Z- Axis Travel - 280 mm	
Working Area per spindle	X- Axis Travel - 600 mm		X- Axis Travel - 750 mm	
	Y- Axis Travel - 2500 mm		Y- Axis Travel - 3000 mm	
	Z- Axis Travel - 280mm		Z- Axis Travel - 280mm	
Collet Size	3 to 10 mm			
Ports	USB 2.0 High Speed USB Device			
Control Language	Standard NC Programming Language (G-Code, M-Code)			
Accuracy	0.1 mm			
Repeatability	+/-0.05 mm			
Control System	PC Based System			
Power supply	Input voltage: 230 - 240V AC Input current: 16A 50Hz			
Accessories	Coolant tank, Dust collection arrangement, PC Based controller with monitor, CPU			



Overview

CyTOS introduces a wide range of metal machines, which have a capacity to work on MS, SS or any other soft metals as well. We are committed to provide you top quality machine of your requirement with reasonable price range. Drilling, Tapping, Boring, Milling are the processes which these machines can perform.

Heavy Cast Iron Structure

We provide rigid high quality cast iron structure, which has in vibration absorbing property. This structure is an assembly of cast iron base and square shaped column on which the z axis is further assembled.

Structure Design

The machine structure is designed in such a way that the vibrations and unbalanced forces during the processes are easily transferred the ground without allowing any effect of vibrations on the machine.



Overview

CyTOS introduces a wide range of metal machines, which have a capacity to work on MS, SS or any other soft metals as well. We are committed to provide you top quality machine of your requirement with reasonable price range. Drilling, Tapping, Boring, Milling are the processes which these machines can perform.

Parameter	VDM30M	VDM50M	VDM100M
Max. Drilling Size	1 mm – 12mm	1mm - 25 mm	1mm - 50 mm
Process	Drilling	Drilling and Milling	Drilling And Milling
Bed Size (in mm)	300 X 300	500X500	1000 X 1000
Material	Brass, Al, MS	MS, SS, Cast Iron	MS, SS, Cast Iron
Spindle Motor	1.5 Kw(2HP)	2.5 Kw (3.3 HP)	3.5 Kw(5HP) Servo
Axis Motor	Stepper /Easy Stepper	AC Servo Motors	AC Servo Motors
Coolant Pump and Tank	No	Yes	Yes
Controller	PC Based	Delta CNC Controller	Delta CNC Controller
LM Rails	HIWIN	HIWIN	HIWIN
Foundation Type	Table Top	Base Mounted	Base Mounted
Position Accuracy	0.05 mm	0.05 mm	0.05mm
Enclosure	No	Yes	Yes