

Class 10 - Structural Bioinformatics

Melissa (PID: A19149673)

Table of contents

Background	1
PDB Statistics	1
Visualizing the HIV-1 protease structure with Mol-Star	4
Getting started with the bio3D package	7
Predict the flexibility of a given structure	9
Comparative structure analysis of Adenylate Kinase	11

Background

The main repository of high-resolution structural data on biomolecules is called the ****Protein Data Bank*** (PDB).

PDB Statistics

What is in the PDB in terms of molecule type and structure determination method?

Read a CSV file of current PDB stats obtained from <https://www.rcsb.org/stats/summary>

```
pdb <- read.csv ("Data Export Summary.csv")
pdb
```

	Molecular.Type	X.ray	EM	NMR	Integrative	Multiple.methods
1	Protein (only)	180,758	23,111	12,813	348	229
2	Protein/Oligosaccharide	10,488	3,741	34	8	11
3	Protein/NA	9,205	6,751	287	26	8
4	Nucleic acid (only)	3,154	250	1,578	3	15

5		Other	178	27	35	4	0
6	Oligosaccharide (only)		11	0	6	0	1
	Neutron	Other	Total				
1	84	32	217,375				
2	1	0	14,283				
3	0	0	16,277				
4	3	1	5,004				
5	0	0	244				
6	0	4	22				

Q1. What percentage of structures in the PDB are solved by X-Ray and Electron Microscopy.

```
pdb$X.ray
```

```
[1] "180,758" "10,488" "9,205" "3,154" "178" "11"
```

This print out above `pdb$X.ray` is “character” not “numeric”. Therefore I can’t do math with it:

Two functions that can help here are `sub()` and `as.numeric()`

```
# We want to get rid (or sub out) commas:
```

```
x <- pdb$X.ray
tmp <- sub(",", "", x)
sum( as.numeric(tmp))
```

```
[1] 203794
```

We could make a function to do this:

```
rm.comma <- function(x) {
  as.numeric(gsub(",", "", x))
}
```

```
n.tot <- rm.comma(pdb$Total)
n.xray <- rm.comma(pdb$`X-ray`)
n.em <- rm.comma(pdb$EM)

n.xray/n.tot * 100
```

```
numeric(0)
```

```
n.em/n.tot * 100
```

```
[1] 10.631857 26.191976 41.475702 4.996003 11.065574 0.000000
```

We could also use a different input function for this CSV that speaks American (i.e. deals with commas in numbers in a comma separated value file).

```
library(readr)
pdb <- read_csv("Data Export Summary.csv")
```

```
Rows: 6 Columns: 9
```

```
-- Column specification -----
```

```
Delimiter: ","
```

```
chr (1): Molecular Type
```

```
dbl (4): Integrative, Multiple methods, Neutron, Other
```

```
num (4): X-ray, EM, NMR, Total
```

```
i Use `spec()` to retrieve the full column specification for this data.
```

```
i Specify the column types or set `show_col_types = FALSE` to quiet this message.
```

```
n.tot <- sum(pdb$Total)
n.xray <- sum(pdb$`X-ray`)
n.em <- sum(pdb$EM)
```

```
n.xray / n.tot * 100
```

```
[1] 80.48577
```

```
n.em / n.tot * 100
```

```
[1] 13.38046
```

There is about 80% of structures in the PDB that are solved by X-Ray while about 13% are solved using Electron Microscopy.

Q2. What proportion of structures in the PDB are protein?

```
pdb$Total[1]
```

```
[1] 217375
```

```
217375/202556314 * 100
```

```
[1] 0.1073158
```

Key-point: We have a very, very small structural coverage of known proteins (~0.1%). Most structures we know about (~80%) come from one method (X-ray crystallography)


About 98% of structures in the PDB are protein or protein containing complexes.


Q3. Type HIV in the PDB website search box on the home page and determine how many HIV-1 protease structures are in the current PDB?

There are 4,998 HIV-1 protease structures that are in the current PDB.

Visualizing the HIV-1 protease structure with Mol-Star

Main stand alone web version with all features is at <https://molstar.org/viewer/>





Q4. Water molecules normally have 3 atoms. Why do we see just one atom per water molecule in this structure?

We see just one atom per water molecule in this structure since the X-ray crystallography usually detects the oxygen atom of water, while the hydrogen atoms are too small and don't scatter X-rays strongly enough to be resolved clearly.

Q5. There is a critical “conserved” water molecule in the binding site. Can you identify this water molecule? What residue number does this water molecule have

The conserved water molecule in the binding site is HOH.

Q6. Generate and save a figure clearly showing the two distinct chains of HIV-protease along with the ligand. You might also consider showing the catalytic residues ASP 25 in each chain and the critical water (we recommend “Ball & Stick” for these side-chains). Add this figure to your Quarto document. - Discussion Topic: Can you think of a way in which indinavir, or even larger ligands and substrates, could enter the binding site?




Figure 1: Spacefill display of catalytic ASP25 amino acids and key binding site water molecule

Getting started with the bio3D package

```
library(bio3d)
```

```
pdb <- read.pdb("1hsg")
```

Note: Accessing on-line PDB file

```
pdb
```

```
Call: read.pdb(file = "1hsg")
```

```
Total Models#: 1
```

```
Total Atoms#: 1686, XYZs#: 5058 Chains#: 2 (values: A B)
```

```
Protein Atoms#: 1514 (residues/Calpha atoms#: 198)
```

Nucleic acid Atoms#: 0 (residues/phosphate atoms#: 0)

Non-protein/nucleic Atoms#: 172 (residues: 128)

Non-protein/nucleic resid values: [HOH (127), MK1 (1)]

Protein sequence:

```
PQITLWQRPLVTIKIGGQLKEALLDTGADDTVLEEMSLPGRWKPKMIGGIGGFIKVRQYD
QILIEICGHKAIGTVLVGPTPVNIIGRNLLTQIGCTLNFPQITLWQRPLVTIKIGGQLKE
ALLDTGADDTVLEEMSLPGRWKPKMIGGIGGFIKVRQYDQILIEICGHKAIGTVLVGPTP
VNIIGRNLLTQIGCTLNF
```

```
+ attr: atom, xyz, seqres, helix, sheet,
      calpha, remark, call
```

Q7. How many amino acid residues are there in this pdb object?

There are 198 amino acid residues in this PDB structure

Q8. Name one of the two non-protein residues?

One of the two non-protein residues is HOH (water) or MK1 which is the ligand.

Q9. How many protein chains are in this structure?

There are two protein chains, A and B, which are in this structure.

```
attributes(pdb)
```

```
$names
```

```
[1] "atom" "xyz" "seqres" "helix" "sheet" "calpha" "remark" "call"
```

```
$class
```

```
[1] "pdb" "sse"
```

```
head(pdb$atom)
```

	type	eleno	ety	alt	resid	chain	resno	insert	x	y	z	o	b
1	ATOM	1	N	<NA>	PRO	A	1	<NA>	29.361	39.686	5.862	1	38.10
2	ATOM	2	CA	<NA>	PRO	A	1	<NA>	30.307	38.663	5.319	1	40.62
3	ATOM	3	C	<NA>	PRO	A	1	<NA>	29.760	38.071	4.022	1	42.64
4	ATOM	4	O	<NA>	PRO	A	1	<NA>	28.600	38.302	3.676	1	43.40
5	ATOM	5	CB	<NA>	PRO	A	1	<NA>	30.508	37.541	6.342	1	37.87
6	ATOM	6	CG	<NA>	PRO	A	1	<NA>	29.296	37.591	7.162	1	38.40

	segid	elemsy	charge
1	<NA>	N	<NA>
2	<NA>	C	<NA>
3	<NA>	C	<NA>
4	<NA>	O	<NA>
5	<NA>	C	<NA>
6	<NA>	C	<NA>

There are lots of functions that can work with these `pdb` objects:

```
head(pdbseq(pdb))
```

```

  1    2    3    4    5    6
"P" "Q" "I" "T" "L" "W"
```

We can have a quick interactive view

```
library(bio3dview)
view.pdb(pdb)
```

Let's try a custom view

```
view.pdb(pdb,
  colorScheme = "see",
  backgroundColor = "black")
```

Q. Create a custom view of HIV-Pr highlighting the active site ASP residues (`resno=25`), the two chains (in your choice of colors) and the ligand all on a custom color background?

```
active.site <- atom.select(pdb, resno=25)

view.pdb(pdb, cols = c("red", "blue"),
  highlight = active.site,
  highlight.style = "spacefill",
  backgroundColor = "pink")
```

Predict the flexibility of a given structure

Let's do a Normal Mode Analysis (NMA) to predict the flexibility of a give `pdb` object:

```
adk <- read.pdb("6s36")
```

Note: Accessing on-line PDB file
PDB has ALT records, taking A only, rm.alt=TRUE

```
adk
```

```
Call: read.pdb(file = "6s36")
```

```
Total Models#: 1
```

```
Total Atoms#: 1898, XYZs#: 5694 Chains#: 1 (values: A)
```

```
Protein Atoms#: 1654 (residues/Calpha atoms#: 214)
```

```
Nucleic acid Atoms#: 0 (residues/phosphate atoms#: 0)
```

```
Non-protein/nucleic Atoms#: 244 (residues: 244)
```

```
Non-protein/nucleic resid values: [ CL (3), HOH (238), MG (2), NA (1) ]
```

```
Protein sequence:
```

```
MRIILLGAPGAGKGTQAQFIMEKYGIPQISTGDMLRAAVKSGSELGKQAKDIMDAGKLV  
TDELVIALVKERIAQEDCRNGFLDGFPRTPQADAMKEAGINVDYVLEFDVPDELIVDKI  
VGRRVHAPSGRVYHVKFNPPKVEGKDDVTGEELTTRKDDQEETVRKRLVEYHQM  
TAPLIG  
YYSKEAEAGNTKYAKVDGTPVAEVRADLEKILG
```

```
+ attr: atom, xyz, seqres, helix, sheet,  
      calpha, remark, call
```

```
# a quick structure summary
```


```
# Perform flexibility prediction
```

```
m <- nma(adk)
```

```
Building Hessian... Done in 0.013 seconds.
```

```
Diagonalizing Hessian... Done in 0.277 seconds.
```

```
plot(m)
```



Write out the results for viewing in Mol-star:

```
mktrj(m, file="adk_m7.pdb")
```

```
view.nma(m, pdb=adk)
```

Comparative structure analysis of Adenylate Kinase

Q10. Which of the packages above is found only on BioConductor and not CRAN?

The msa package is only found on BioConductor and not CRAN.

Q11. Which of the above packages is not found on BioConductor or CRAN?:

The bio3dview package is not found on CRAN or BioConductor and is installed from GitHub.

Q12. True or False? Functions from the pak package can be used to install packages from GitHub and BitBucket?

True

Our first step is find a sequence for this family. We will use the database ID "1ake_A" here:

```
id <- "1ake_A"

aa <- get.seq(id)
```

Warning in get.seq(id): Removing existing file: seqs.fasta

Fetching... Please wait. Done.

```
aa
```

```

      1      .      .      .      .      .      .      60
pdb|1AKE|A  MRIILLGAPGAGKGTQAQFIMEKYGIPQISTGDMRLAAVKSGSELGKQAKDIMDAGKLV
      1      .      .      .      .      .      .      60

      61      .      .      .      .      .      .      120
pdb|1AKE|A  DELVIALVKERIAQEDCRNGFLLDGFPRTIPQADAMKEAGINVDYVLEFDVPDELIVDRI
      61      .      .      .      .      .      .      120

      121      .      .      .      .      .      .      180
pdb|1AKE|A  VGRRVHAPSGRVYHVKNPPKVEGKDDVTGEELTRKDDQEETVRKRLVEYHQMTAPLIG
      121      .      .      .      .      .      .      180

      181      .      .      .      214
pdb|1AKE|A  YYSKEAEAGNTKYAKVDGTPVAEVRADLEKILG
      181      .      .      .      214
```

Call:

```
read.fasta(file = outfile)
```

Class:

```
fasta
```

Alignment dimensions:

```
1 sequence rows; 214 position columns (214 non-gap, 0 gap)
```

```
+ attr: id, ali, call
```

Q13. How many amino acids are in this sequence, i.e. how long is this sequence?

The sequence contains 214 amino acids.

Search for related sequences in the database

```
blast <- blast.pdb(aa)
```

```
hits <- plot(blast)
```

```
hits <- NULL
```

```
hits$ pdb.id <- c('1AKE_A', '6S36_A', '6RZE_A', '3HPR_A', '1E4V_A', '5EJE_A', '1E4Y_A', '3X2S_A', '6HAP_A')
```

```
# Download related PDB files
```

```
files <- get.pdb(hits$ pdb.id, path="pdb", split=TRUE, gzip=TRUE)
```

```
Warning in get.pdb(hits$ pdb.id, path = "pdb", split = TRUE, gzip = TRUE):  
pdb/1AKE.pdb.gz exists. Skipping download
```

```
Warning in get.pdb(hits$ pdb.id, path = "pdb", split = TRUE, gzip = TRUE):  
pdb/6S36.pdb.gz exists. Skipping download
```

```
Warning in get.pdb(hits$ pdb.id, path = "pdb", split = TRUE, gzip = TRUE):  
pdb/6RZE.pdb.gz exists. Skipping download
```

```
Warning in get.pdb(hits$ pdb.id, path = "pdb", split = TRUE, gzip = TRUE):  
pdb/3HPR.pdb.gz exists. Skipping download
```

```
Warning in get.pdb(hits$ pdb.id, path = "pdb", split = TRUE, gzip = TRUE):  
pdb/1E4V.pdb.gz exists. Skipping download
```

```
Warning in get.pdb(hits$ pdb.id, path = "pdb", split = TRUE, gzip = TRUE):  
pdb/5EJE.pdb.gz exists. Skipping download
```

```
Warning in get.pdb(hits$ pdb.id, path = "pdb", split = TRUE, gzip = TRUE):  
pdb/1E4Y.pdb.gz exists. Skipping download
```

```
Warning in get.pdb(hits$ pdb.id, path = "pdb", split = TRUE, gzip = TRUE):  
pdb/3X2S.pdb.gz exists. Skipping download
```

```
Warning in get.pdb(hits$ pdb.id, path = "pdb", split = TRUE, gzip = TRUE):  
pdb/6HAP.pdb.gz exists. Skipping download
```

Warning in get.pdb(hits\$pdb.id, path = "pdbs", split = TRUE, gzip = TRUE):
pdbs/6HAM.pdb.gz exists. Skipping download

Warning in get.pdb(hits\$pdb.id, path = "pdbs", split = TRUE, gzip = TRUE):
pdbs/4K46.pdb.gz exists. Skipping download

Warning in get.pdb(hits\$pdb.id, path = "pdbs", split = TRUE, gzip = TRUE):
pdbs/3GMT.pdb.gz exists. Skipping download

Warning in get.pdb(hits\$pdb.id, path = "pdbs", split = TRUE, gzip = TRUE):
pdbs/4PZL.pdb.gz exists. Skipping download

	0%
=====	8%
=====	15%
=====	23%
=====	31%
=====	38%
=====	46%
=====	54%
=====	62%
=====	69%
=====	77%
=====	85%
=====	92%
=====	100%

```
# Align related PDBs
pdbs <- pdbaln(files, fit = TRUE, exefile="msa")
```

Reading PDB files:

```
pdbs/split_chain/1AKE_A.pdb
pdbs/split_chain/6S36_A.pdb
pdbs/split_chain/6RZE_A.pdb
pdbs/split_chain/3HPR_A.pdb
pdbs/split_chain/1E4V_A.pdb
pdbs/split_chain/5EJE_A.pdb
pdbs/split_chain/1E4Y_A.pdb
pdbs/split_chain/3X2S_A.pdb
pdbs/split_chain/6HAP_A.pdb
pdbs/split_chain/6HAM_A.pdb
pdbs/split_chain/4K46_A.pdb
pdbs/split_chain/3GMT_A.pdb
pdbs/split_chain/4PZL_A.pdb
  PDB has ALT records, taking A only, rm.alt=TRUE
.   PDB has ALT records, taking A only, rm.alt=TRUE
.   PDB has ALT records, taking A only, rm.alt=TRUE
.   PDB has ALT records, taking A only, rm.alt=TRUE
..  PDB has ALT records, taking A only, rm.alt=TRUE
.... PDB has ALT records, taking A only, rm.alt=TRUE
.   PDB has ALT records, taking A only, rm.alt=TRUE
...
```

Extracting sequences

```
pdb/seq: 1  name: pdbs/split_chain/1AKE_A.pdb
  PDB has ALT records, taking A only, rm.alt=TRUE
pdb/seq: 2  name: pdbs/split_chain/6S36_A.pdb
  PDB has ALT records, taking A only, rm.alt=TRUE
pdb/seq: 3  name: pdbs/split_chain/6RZE_A.pdb
  PDB has ALT records, taking A only, rm.alt=TRUE
pdb/seq: 4  name: pdbs/split_chain/3HPR_A.pdb
  PDB has ALT records, taking A only, rm.alt=TRUE
pdb/seq: 5  name: pdbs/split_chain/1E4V_A.pdb
pdb/seq: 6  name: pdbs/split_chain/5EJE_A.pdb
  PDB has ALT records, taking A only, rm.alt=TRUE
pdb/seq: 7  name: pdbs/split_chain/1E4Y_A.pdb
pdb/seq: 8  name: pdbs/split_chain/3X2S_A.pdb
pdb/seq: 9  name: pdbs/split_chain/6HAP_A.pdb
```

```

pdb/seq: 10  name: pdbs/split_chain/6HAM_A.pdb
  PDB has ALT records, taking A only, rm.alt=TRUE
pdb/seq: 11  name: pdbs/split_chain/4K46_A.pdb
  PDB has ALT records, taking A only, rm.alt=TRUE
pdb/seq: 12  name: pdbs/split_chain/3GMT_A.pdb
pdb/seq: 13  name: pdbs/split_chain/4PZL_A.pdb

```

```

library(bio3dview)
view.pdbs(pdbs)

```

Annotate collected PDB structures

```

# Vector containing PDB database codes
ids <- basename.pdb(pdbs$id)

anno <- pdb.annotate(ids)
unique(anno$source)

```

```

[1] "Escherichia coli"
[2] "Escherichia coli K-12"
[3] "Escherichia coli O139:H28 str. E24377A"
[4] "Escherichia coli str. K-12 substr. MDS42"
[5] "Photobacterium profundum"
[6] "Burkholderia pseudomallei 1710b"
[7] "Francisella tularensis subsp. tularensis SCHU S4"

```

```
anno
```

	structureId	chainId	macromoleculeType	chainLength	experimentalTechnique
1AKE_A	1AKE	A	Protein	214	X-ray
6S36_A	6S36	A	Protein	214	X-ray
6RZE_A	6RZE	A	Protein	214	X-ray
3HPR_A	3HPR	A	Protein	214	X-ray
1E4V_A	1E4V	A	Protein	214	X-ray
5EJE_A	5EJE	A	Protein	214	X-ray

1E4Y_A ray	1E4Y	A	Protein	214	X-
3X2S_A ray	3X2S	A	Protein	214	X-
6HAP_A ray	6HAP	A	Protein	214	X-
6HAM_A ray	6HAM	A	Protein	214	X-
4K46_A ray	4K46	A	Protein	214	X-
3GMT_A ray	3GMT	A	Protein	230	X-
4PZL_A ray	4PZL	A	Protein	242	X-

	resolution	scopDomain	pfam
1AKE_A	2.00	Adenylate kinase	Adenylate kinase, active site lid (ADK_lid)
6S36_A	1.60	<NA>	Adenylate kinase (ADK)
6RZE_A	1.69	<NA>	Adenylate kinase (ADK)
3HPR_A	2.00	<NA>	Adenylate kinase (ADK)
1E4V_A	1.85	Adenylate kinase	Adenylate kinase (ADK)
5EJE_A	1.90	<NA>	Adenylate kinase (ADK)
1E4Y_A	1.85	Adenylate kinase	Adenylate kinase (ADK)
3X2S_A	2.80	<NA>	<NA>
6HAP_A	2.70	<NA>	Adenylate kinase (ADK)
6HAM_A	2.55	<NA>	Adenylate kinase (ADK)
4K46_A	2.01	<NA>	Adenylate kinase (ADK)
3GMT_A	2.10	<NA>	<NA>
4PZL_A	2.10	<NA>	Adenylate kinase (ADK)

	ligandId
1AKE_A	AP5
6S36_A	CL (3),NA,MG (2)
6RZE_A	NA (3),CL (2)
3HPR_A	AP5
1E4V_A	AP5
5EJE_A	AP5,CO
1E4Y_A	AP5
3X2S_A	AP5,MG,JPY (2)
6HAP_A	AP5
6HAM_A	AP5
4K46_A	ADP,AMP,PO4
3GMT_A	SO4 (2)
4PZL_A	CA,FMT,GOL

ligandName

1AKE_A	BIS(ADENOSINE)-5'-
PENTAPHOSPHATE	
6S36_A	CHLORIDE ION (3),SODIUM ION,MAGNESIUM ION (2)
6RZE_A	SODIUM ION (3),CHLORIDE ION (2)
3HPR_A	BIS(ADENOSINE)-5'-
PENTAPHOSPHATE	
1E4V_A	BIS(ADENOSINE)-5'-
PENTAPHOSPHATE	
5EJE_A	BIS(ADENOSINE)-5'-PENTAPHOSPHATE,COBALT (II) ION
1E4Y_A	BIS(ADENOSINE)-5'-
PENTAPHOSPHATE	
3X2S_A	BIS(ADENOSINE)-5'-PENTAPHOSPHATE,MAGNESIUM ION,N-(pyren-1-ylmethyl)acetamide (2)
6HAP_A	BIS(ADENOSINE)-5'-
PENTAPHOSPHATE	
6HAM_A	BIS(ADENOSINE)-5'-
PENTAPHOSPHATE	
4K46_A	ADENOSINE-5'-DIPHOSPHATE,ADENOSINE MONOPHOSPHATE,PHOSPHATE ION
3GMT_A	SULFATE ION (2)
4PZL_A	CALCIUM ION,FORMIC ACID,GLYCEROL

source

1AKE_A	Escherichia coli
6S36_A	Escherichia coli
6RZE_A	Escherichia coli
3HPR_A	Escherichia coli K-12
1E4V_A	Escherichia coli
5EJE_A	Escherichia coli 0139:H28 str. E24377A
1E4Y_A	Escherichia coli
3X2S_A	Escherichia coli str. K-12 substr. MDS42
6HAP_A	Escherichia coli 0139:H28 str. E24377A
6HAM_A	Escherichia coli K-12
4K46_A	Photobacterium profundum
3GMT_A	Burkholderia pseudomallei 1710b
4PZL_A	Francisella tularensis subsp. tularensis SCHU S4

1AKE_A STRUCTURE OF THE COMPLEX BETWEEN ADENYLATE KINASE FROM ESCHERICHIA COLI AND THE INHIBITORS

6S36_A

6RZE_A

3HPR_A

1E4V_A

loop

5EJE_A

1E4Y_A

loop

Cryst


3X2S_A
 conjugated adenylate kinase
 6HAP_A
 6HAM_A
 4K46_A
 3GMT_A
 4PZL_A

The crys

		citation	rObserved	rFree
1AKE_A	Muller, C.W., et al.	J Mol Biology (1992)	0.19600	NA
6S36_A	Rogne, P., et al.	Biochemistry (2019)	0.16320	0.23560
6RZE_A	Rogne, P., et al.	Biochemistry (2019)	0.18650	0.23500
3HPR_A	Schrank, T.P., et al.	Proc Natl Acad Sci U S A (2009)	0.21000	0.24320
1E4V_A	Muller, C.W., et al.	Proteins (1993)	0.19600	NA
5EJE_A	Kovermann, M., et al.	Proc Natl Acad Sci U S A (2017)	0.18890	0.23580
1E4Y_A	Muller, C.W., et al.	Proteins (1993)	0.17800	NA
3X2S_A	Fujii, A., et al.	Bioconjug Chem (2015)	0.20700	0.25600
6HAP_A	Kantaev, R., et al.	J Phys Chem B (2018)	0.22630	0.27760
6HAM_A	Kantaev, R., et al.	J Phys Chem B (2018)	0.20511	0.24325
4K46_A	Cho, Y.-J., et al.	To be published	0.17000	0.22290
3GMT_A	Buchko, G.W., et al.	Biochem Biophys Res Commun (2010)	0.23800	0.29500
4PZL_A	Tan, K., et al.	To be published	0.19360	0.23680

	rWork	spaceGroup
1AKE_A	0.19600	P 21 2 21
6S36_A	0.15940	C 1 2 1
6RZE_A	0.18190	C 1 2 1
3HPR_A	0.20620	P 21 21 2
1E4V_A	0.19600	P 21 2 21
5EJE_A	0.18630	P 21 2 21
1E4Y_A	0.17800	P 1 21 1
3X2S_A	0.20700	P 21 21 21
6HAP_A	0.22370	I 2 2 2
6HAM_A	0.20311	P 43
4K46_A	0.16730	P 21 21 21
3GMT_A	0.23500	P 1 21 1
4PZL_A	0.19130	P 32

```
# Perform PCA
pc.xray <- pca(pdbx)
plot(pc.xray)
```




```
# Calculate RMSD
rd <- rmsd(pdb)
```

Warning in rmsd(pdb): No indices provided, using the 204 non NA positions

```
# Structure-based clustering
hc.rd <- hclust(dist(rd))
grps.rd <- cutree(hc.rd, k=3)

plot(pc.xray, 1:2, col="grey50", bg=grps.rd, pch=21, cex=1)
```



```
# Visualize first principal component  
pc1 <- mktrj(pc.xray, pc=1, file="pc_1.pdb")
```

PCA of all this structural data (x, y and z atom coordinates).

```
pc <- pca (pdbs)  
plot(pc, 1:2)
```

