


Inferential Statistics Concepts

INTRODUCTION TO LINEAR MODELING IN PYTHON




Jason Vestuto
Data Scientist

Probability Distribution



Populations and Statistics



Sampling the Population


Population statistics vs Sample statistics

```
print( len(month_of_temps), month_of_temps.mean(), month_of_temps.std() )  
print( len(decade_of_temps), decade_of_temps.mean(), decade_of_temps.std() )
```


Draw a Random Sample from a Population

```
month_of_temps = np.random.choice(decade_of_temps, size=31)
```


Visualizing Distributions




Visualizing Distributions



Probability and Inference



Visualizing Distributions



Resampling

```
# Resampling as Iteration
num_samples = 20
for ns in range(num_samples):
    sample = np.random.choice(population, num_pts)
    distribution_of_means[ns] = sample.mean()
```

```
# Sample Distribution Statistics
mean_of_means = np.mean(distribution_of_means)
stdev_of_means = np.std(distribution_of_means)
```

Let's practice!

INTRODUCTION TO LINEAR MODELING IN PYTHON


Model Estimation and Likelihood

INTRODUCTION TO LINEAR MODELING IN PYTHON



Jason Vestuto
Data Scientist

Estimation



Estimation

```
# Define gaussian model function
def gaussian_model(x, mu, sigma):
    coeff_part = 1/(np.sqrt(2 * np.pi * sigma**2))
    exp_part = np.exp( - (x - mu)**2 / (2 * sigma**2) )
    return coeff_part*exp_part
```

$$f(x) = \frac{1}{\sigma\sqrt{2\pi}} e^{-\frac{1}{2}\left(\frac{x-\mu}{\sigma}\right)^2}$$


```
# Compute sample statistics
mean = np.mean(sample)
stdev = np.std(sample)
```

```
# Model the population using sample statistics
population_model = gaussian(sample, mu=mean, sigma=stdev)
```


Likelihood vs Probability

- Conditional Probability: $P(\text{outcome A}|\text{given B})$
- Probability: $P(\text{data}|\text{model})$
- Likelihood: $L(\text{model}|\text{data})$

Computing Likelihood



Computing Likelihood



Likelihood from Probabilities

```
# Guess parameters
```

```
mu_guess = np.mean(sample_distances)
```

```
sigma_guess = np.std(sample_distances)
```

```
# For each sample point, compute a probability
```

```
probabilities = np.zeros(len(sample_distances))
```

```
for n, distance in enumerate(sample_distances):
```

```
    probabilities[n] = gaussian_model(distance, mu=mu_guess, sigma=sigma_guess)
```

```
likelihood = np.product(probs)
```

```
loglikelihood = np.sum(np.log(probs))
```

It's Useful to take the log because it's has numerical statistics Better

Maximum Likelihood Estimation

```
# Create an array of mu guesses
```

```
low_guess = sample_mean - 2*sample_stdev
```

```
high_guess = sample_mean + 2*sample_stdev
```

```
mu_guesses = np.linspace(low_guess, high_guess, 101)
```

```
# Compute the loglikelihood for each guess
```

```
loglikelihoods = np.zeros(len(mu_guesses))
```

```
for n, mu_guess in enumerate(mu_guesses):
```


```
    loglikelihoods[n] = compute_loglikelihood(sample_distances, mu=mu_guess, sigma=sample_stdev)
```

```
# Find the best guess
```

```
max_loglikelihood = np.max(loglikelihoods)
```

```
best_mu = mu_guesses[loglikelihoods == max_loglikelihood]
```

Maximum Likelihood Estimation



when model is gaussian the mean matches the answer from least-Square

Let's practice!

INTRODUCTION TO LINEAR MODELING IN PYTHON


Model Uncertainty and Sample Distributions

INTRODUCTION TO LINEAR MODELING IN PYTHON




Jason Vestuto
Data Scientist


Population Unavailable




Sample as Population Model




Sample Statistic



Bootstrap Resampling



Resample Distribution



Bootstrap in Code

```
# Use sample as model for population
population_model = august_daily_highs_for_2017
```

```
# Simulate repeated data acquisitions by resampling the "model"
for nr in range(num_resamples):
    bootstrap_sample = np.random.choice(population_model, size=resample_size, replace=True)
    bootstrap_means[nr] = np.mean(bootstrap_sample)
```

Sampling With Replacement

```
# Compute the mean of the bootstrap resample distribution
estimate_temperature = np.mean(bootstrap_means)
```

```
# Compute standard deviation of the bootstrap resample distribution
estimate_uncertainty = np.std(bootstrap_means)
```

Replacement

```
# Define the sample of notes  
sample = ['A', 'B', 'C', 'D', 'E', 'F', 'G']
```

```
# Replace = True, repeats are allowed  
bootstrap_sample = np.random.choice(sample, size=4, replace=True)  
print(bootstrap_sample)
```

```
C C F G
```

Replacement

```
# Replace = False
```

```
bootstrap_sample = np.random.choice(sample, size=4, replace=False)
```

```
print(bootstrap_sample)
```

Sampling Without Replacement Problems :

1- never get repeated

2- sampling changes the model after every draw

C G A F

```
# Replace = True, more lengths are allowed
```

```
bootstrap_sample = np.random.choice(sample, size=16, replace=True)
```

```
print(bootstrap_sample)
```

C C F G C G A E F D G B B A E C

Let's practice!

INTRODUCTION TO LINEAR MODELING IN PYTHON

Model Errors and Randomness

INTRODUCTION TO LINEAR MODELING IN PYTHON



Jason Vestuto
Data Scientist

Types of Errors


1. Measurement error Mistakes made when collection/recording the data ex: broken sensor
 - e.g.: broken sensor, wrongly recorded measurements
2. Sampling bias Taking draws from one small portion of the population not representing of the rest ex : drawing temperatures only from august when days hottest
 - e.g: temperatures only from August, when days are hottest
3. Random chance variation due to random chance ex : how do we know that the mean slope from model fit is not just due to noise ?

Null Hypothesis


Question: Is our effect due a relationship or due to random chance?

Answer: check the Null Hypothesis.


Ordered Data



Grouping Data



Grouping Data



- Short Duration Group, mean = 5

Test Statistic


```
# Group into early and late times
group_short = sample_distances[times < 5]
group_long = sample_distances[times > 5]
```

```
# Resample distributions
resample_short = np.random.choice(group_short, size=500, replace=True)
resample_long = np.random.choice(group_long, size=500, replace=True)
```


```
# Test Statistic
test_statistic = resample_long - resample_short
```

```
# Effect size as mean of test statistic distribution
effect_size = np.mean(test_statistic)
```

Shuffle and Regrouping



Shuffling and Regrouping



Shuffle and Split

```
# Concatenate and Shuffle
```

```
shuffle_bucket = np.concatenate((group_short, group_long))  
np.random.shuffle(shuffle_bucket)
```

```
# Split in the middle
```

```
slice_index = len(shuffle_bucket)//2  
shuffled_half1 = shuffle_bucket[0:slice_index]  
shuffled_half2 = shuffle_bucket[slice_index+1:]
```


Resample and Test Again

```
# Resample shuffled populations
```

```
shuffled_sample1 = np.random.choice(shuffled_half1, size=500, replace=True)
```

```
shuffled_sample2 = np.random.choice(shuffled_half2, size=500, replace=True)
```

```
# Recompute effect size
```

```
shuffled_test_statistic = shuffled_sample2 - shuffled_sample1
```

```
effect_size = np.mean(shuffled_test_statistic)
```

p-Value



Let's practice!

INTRODUCTION TO LINEAR MODELING IN PYTHON

Looking Back, Looking Forward

INTRODUCTION TO LINEAR MODELING IN PYTHON



Jason Vestuto
Data Scientist

Exploring Linear Relationships

- Motivation by Example Predictions
- Visualizing Linear Relationships
- Quantifying Linear Relationships

Building Linear Models

- Model Parameters
- Slope and Intercept
- Taylor Series
- Model Optimization
- Least-Squares

Model Predictions

- Modeling Real Data
- Limitations and Pitfalls of Predictions
- Goodness-of-Fit

Model Parameter Distributions

- modeling parameters as probability distributions
- samples, populations, and sampling
- maximizing likelihood for parametric shapes
- bootstrap resampling for arbitrary shapes
- test statistics and p-values

Goodbye and Good Luck!

INTRODUCTION TO LINEAR MODELING IN PYTHON