

# Deep Learning Techniques

## DL4. Neural Attention Models

1

### Outline

- **Attention in Neural Machine Translation**
- **Self-attention and Transformer**

2

## Origin of Attention in Machine Translation

- **Example of a training pair**

- Source sentence ( $x$ ): le programme a été mis en œuvre
- Target sentence ( $y$ ): The program has been implemented.

- **Training:** Given parallel corpus  $\mathcal{D} = \{(x, y)\}$ , use a neural network to optimize the model parameter  $\theta$  as

$$\theta^* = \operatorname{argmax}_{\theta} \mathbb{E}_{(x, y) \in \mathcal{D}} \log P_{\theta}(y|x)$$

- **Testing:** Use trained model to predict  $y$  given  $x$

$$y_{\theta^*}(x) = \operatorname{argmax}_y \log P_{\theta^*}(y|x)$$

9/10/2024

@Yiming Yang, 11-741 Lecture on DL Attention

3

3

## Sequence-to-Sequence Model [Sutskever et al., NIPS 2014]

Let's denote  $x = (x_1, x_2, \dots, x_S)$  and  $y = (y_1, y_2, \dots, y_T)$ .

- **Auto-regressive factorization**

$$P_{\theta}(y|x) = \prod_{j=1}^T P_{\theta}(y_j|x, y_{<j}) = \prod_{j=1}^T P_{\theta}(y_j|h_{j-1}) = \frac{\exp(y_j^T h_{j-1})}{\sum_{j'=1}^M \exp(y_{j'}^T h_{j-1})}$$

(  $h_{j-1}$  encodes the information of  $x, y_{<j}$  )

- **Encoder:** producing **source hidden states**  $\mathbf{g} = (g_1, g_2, \dots, g_S)$

$$g_0 = \mathbf{0} \text{ and } g_i = \text{RNN}_{\theta}^{\text{enc}}(x_i, g_{i-1})$$

- **Decoder:** producing **target hidden states**  $\mathbf{h} = (h_1, h_2, \dots, h_T)$

$$h_0 = g_S \text{ and } h_j = \text{RNN}_{\theta}^{\text{dec}}(y_j, h_{j-1})$$

9/10/2024

@Yiming Yang, 11-741 Lecture on DL Attention

4

4

## Seq2seq Model Illustration




Figure 1: One-layer Seq2Seq Model.

Summarizing the whole sentence in single vector  $g_s$

9/10/2024

@Yiming Yang, 11-741 Lecture on DL Attention

5

5

## Alignment-based (Non-neural) MT

**French:** Le programme a ete mise en application

**English:** The programme has been implemented

**Alignment:** locally translate sub-units (words/phrase) of a sentence

$(x_1)$	Le $\Rightarrow$ The	$(y_1)$
$(x_2)$	Programme $\Rightarrow$ program	$(y_2)$
$(x_3)$	a $\Rightarrow$ has	$(y_3)$
$(x_4)$	ete $\Rightarrow$ been	$(y_4)$
$(x_5, x_6, x_7)$	mise en application $\Rightarrow$ implemented	$(y_5)$

**Observation:** Predicting a target word mostly relies on a particular part of the source sentence

9/10/2024

@Yiming Yang, 11-741 Lecture on DL Attention

6

6

## Alignment-based Factorization

### Original Factorization

$$P_{\theta}(y|x) = \prod_{j=1}^T P_{\theta}(y_j | x, y_{<j}) = \prod_{j=1}^T P_{\theta}(y_j | h_{j-1})$$

Compressing all the information in  $x$  by vector  $g_S = h_0$

### Alignment-based Approximation

$$P_{\theta}(y|x) \approx \prod_{j=1}^T P_{\theta}(y_j | \text{Align}(y_j, x), h_{j-1})$$

Localizing the alignment in  $x$  for  $y_j$

e.g., Align(implemented,  $x$ )  $\rightarrow$  (mise en application)

- Dynamic programming is used for cross-language token alignments in traditional MT (Brown et al., CL 1990)


9/10/2024

@Yiming Yang, 11-741 Lecture on DL Attention

7

7

## Seq2Seq with Attention



$$\text{Align}(y_j, x) \approx \text{Attention}(h_{j-1}, g) = \sum_{i=1}^S \frac{\exp(f(h_{j-1}, g_i))}{\sum_{i'=1}^S \exp(f(h_{j-1}, g_{i'}))} g_i \equiv a_{j-1}$$

Why do we use  $h_{j-1}$  instead of  $y_j$ ? Because we do not know  $y_j$  yet in the (testing-phase) decoding when computing the alignment.

9/10/2024

@Yiming Yang, 11-741 Lecture on DL Attention

8

8

## Target Distribution

$$P_{\theta}(y_j | a_{j-1}, h_{j-1}) = \frac{\exp(\phi(y_j, a_{j-1}, h_{j-1}))}{\sum_{m=1}^M \exp(\phi(y_m, a_{j-1}, h_{j-1}))}$$

Design choices:

- 1)  $h'_{j-1} := \text{concat}(a_{j-1}, h_{j-1}) \in \mathbb{R}^{2d}$ ,  $y_j \in \mathbb{R}^{2d}$
- 2)  $h'_{j-1} := \text{MLP}(\text{concat}(a_{j-1}, h_{j-1})) \in \mathbb{R}^d$ ,  $y_j \in \mathbb{R}^d$

Both cases have  $\phi(y_j, w) = \frac{\exp(f(y_j, h'_{j-1}))}{\sum_{m=1}^M \exp(f(y_m, h'_{j-1}))}$

## Soft Alignment via Attention

[D. Bahdanau et al., ICLR 2015]

### Target Word Embedding via Attention

$$h_j := \sum_{i=1}^S \frac{\exp(f(h_{j-1}, g_i))}{\sum_{i'=1}^S \exp(f(h_{j-1}, g_{i'}))} g_i$$

embedding of context  $y_{<j}$

attention from  $g_i$  to  $y_j$

- $f$  is a similarity function (more details later);
- target-token embedding is the weighted sum of the source-token embeddings;
- Attentions (weights) can be viewed as a soft alignment.

## Choices of $f(h, g)$

- Dot-Product (most popular choice)

$$f(h, g) = h^T g$$

- Bilinear

$$f(h, g) = h^T W g$$

- MLP (Multi-Layer Perceptron)

$$f(h, g) = v^T \tanh(W_h h + W_g g + b)$$


9/10/2024

@Yiming Yang, 11-741 Lecture on DL Attention

11

11

## Learned Attention Pattern



9/10/2024

@Yiming Yang, 11-741 Lecture on DL Attention

12

12

## Empirical Results

Performance gain on English-French translation:

Models	BLEU
Seq2Seq w/o Attn	21.50
Seq2Seq with Attn	28.45

**Table 1:** Performance gain with attention. The higher the better.

### What makes attention so good?


- Soft-alignment b/w source-target tokens
- Avoid information bottleneck in RNNs

## Outline

- Attention in Neural Machine Translation
- **Self-attention and Transformer**

# Transformer for seq2seq Modeling

[A Vaswani et al. NeurIPS 2017]



9/10/2024

@Yiming Yang, 11-741 Lecture on DL Attention

15

15

## Attention is all you need

[Vaswani et al., NeurIPS 2017]

- **Query** vectors (target words):  $\mathbf{q} = (q_1, q_2, \dots, q_T) \in \mathbb{R}^{T \times D}$
- **Key** vectors (source words):  $\mathbf{k} = (k_1, k_2, \dots, k_S) \in \mathbb{R}^{S \times D}$
- **Value** vectors (source words):  $\mathbf{v} = (v_1, v_2, \dots, v_S) \in \mathbb{R}^{S \times D}$
- **Attention for target words**

$$q_j = \text{attention}(q_{j-1}, \mathbf{k}, \mathbf{v}) = \sum_{i=1}^S \frac{\exp(f(q_{j-1}, k_i))}{\sum_{i'=1}^S \exp(f(q_{j-1}, k_{i'}))} v_i$$

$$\text{or } \underbrace{\mathbf{q}}_{\mathbb{R}^{T \times D}} = \text{attention}(\underbrace{\mathbf{q}}_{\mathbb{R}^{T \times D}}, \underbrace{\mathbf{k}}_{\mathbb{R}^{T \times S}}, \underbrace{\mathbf{v}}_{\mathbb{R}^{S \times D}}) = \text{Softmax}(\mathbf{q}\mathbf{k}^T) \mathbf{v}$$

row-wise normalized attentions (probabilities)

9/10/2024

@Yiming Yang, 11-741 Lecture on DL Attention

16

16



## Self-Attention

- Denote by  $\mathbf{q}$  a sequence of tokens in one language.
- Use attention to obtain a new sequence in the same language as
 
$$\mathbf{q}' = \text{Attention}(\mathbf{q}, \mathbf{k}, \mathbf{v}) = F(\mathbf{q}) \quad \text{where } \mathbf{q} = \mathbf{k} = \mathbf{v}.$$
- Mapping  $F: \mathbb{R}^{T \times D} \mapsto \mathbb{R}^{T \times D}$  is called **self-attention** (a sequence attends to itself).
- Intuitively, each position gather/retrieve information from all the positions with **pairwise similarities** in calculating a **weighted sum**.


9/10/2024

@Yiming Yang, 11-741 Lecture on DL Attention

17

17

## Self-Attention vs. RNN



- Self-attention **directly connects** each pair of nodes without **information bottleneck** and **vanishing gradient** issues
- As a result, optimizing self-attention models is much easier than optimizing RNNs


9/10/2024

@Yiming Yang, 11-741 Lecture on DL Attention

18

18

## Self-Attention vs. CNN



- Self-attention takes the weighted sum of **all tokens** while CNN takes the weighted sum of **near-by tokens**;
- **Dynamic weights** in self-attention vs. **fixed weights** in CNN during testing, i.e., the former is more flexible than the latter.

9/10/2024

@Yiming Yang, 11-741 Lecture on DL Attention

19

19

## Transformer Encoder

### Four Key Ideas

- 1) **Multi-head self-attention** (**MH-Self-Attn**) for exchanging sequential information
- 2) **Feed-Forward Network** (**FFN**) for position-wise linear and non-linear transformations (ReLU) of hidden vectors
- 3) **Position Embedding** (**PosEmbed**)
- 4) Ease optimization via **residual connection** [5] and **layer normalization** (**LayerNorm**) [1]

9/10/2024

@Yiming Yang, 11-741 Lecture on DL Attention

20

20

## Multi-layer Information Flow in Transformer

- Initialization of hidden states at layer 0

$$\mathbf{h}^0 = \text{WordEmbed}(x) + \text{PosEmbed}(x)$$

- For layer  $m = 1, \dots, L$

$$\mathbf{g}^m = \text{LayerNorm}(\mathbf{h}^{m-1} + \text{MH-Self-Attn}(\mathbf{h}^{m-1}))$$

$$\mathbf{h}_i^m = \text{LayerNorm}(\mathbf{g}_i^m + \text{FFN}(\mathbf{g}_i^m)), \quad \forall i = 1, \dots, T$$

9/10/2024

@Yiming Yang, 11-741 Lecture on DL Attention

21

21

## Multi-head Self Attention

Enhancing Model Flexibility or Expressiveness

**Core Idea:** Computing multiple attentions in parallel with **smaller heads**, which may **focus on different parts of the input**.

- In each layer, with head  $n \in \{1, \dots, N\}$  we compute

- query  $\mathbf{q}_n := \mathbf{h}W_n^q$  with parameters  $W_n^q \in \mathbb{R}^{D \times \frac{D}{N}}$
- key  $\mathbf{k}_n := \mathbf{h}W_n^k$  with parameters  $W_n^k \in \mathbb{R}^{D \times \frac{D}{N}}$
- value  $\mathbf{v}_n := \mathbf{h}W_n^v$  with parameters  $W_n^v \in \mathbb{R}^{D \times \frac{D}{N}}$
- head-specific  $\mathbf{a}_n := \text{Attention}(\mathbf{q}_n, \mathbf{k}_n, \mathbf{v}_n) \in \mathbb{R}^{T \times \frac{D}{N}}$
- Merged attention  $\mathbf{a} := \text{Concat}(\mathbf{a}_1, \mathbf{a}_2, \dots, \mathbf{a}_N) \in \mathbb{R}^{T \times D}$
- Finally, MultiHead(Q,K,V) =  $\mathbf{a}W^o$  with parameters  $W^o \in \mathbb{R}^{D \times D}$

9/10/2024

@Yiming Yang, 11-741 Lecture on DL Attention

22

22

## Feed-Forward Network (FFN)

FFT is a position-wise 2-layer MLP being shared in all positions:

$$\text{FFN}(\mathbf{h}_i) = W_2 \text{ReLU}(W_1 \mathbf{h}_i + \mathbf{b}_1) + \mathbf{b}_2, \quad \forall i = 1, \dots, T$$

- $W_1 \in \mathbb{R}^{M \times D}$  projects the hidden state to MD-dimensional and  $M > 1$  is often referred to as the **expansion rate**;
- $W_2 \in \mathbb{R}^{D \times M}$  projects the hidden state back to D-dimensional;
- The “expansion-squeezing” design is also referred to as “**Inverted Bottleneck**” [8].

9/10/2024

@Yiming Yang, 11-741 Lecture on DL Attention

23

23

## Positional Encoding (PosEmbed)

**Recal:** Attention scores MAY NOT depend on word order

$$\text{Self-Atten}(j, \mathbf{h}) = \sum_{i=1}^S \frac{\exp(f(\mathbf{h}_j, \mathbf{h}_i))}{\sum_{i'=1}^S \exp(f(\mathbf{h}_j, \mathbf{h}_{i'}))} \mathbf{h}_i$$

If  $f$  is a symmetric function (such as dot-prod or cosine), swapping the order of its arguments does not change the similarity value.

**Remedy:** Add position embedding in the hidden states

$$\mathbf{h}^0 = \text{WordEmbed}(x) + \text{PosEmbed}(x)$$

- Position embedding is learned just like word embedding [4];
- Position embedding is based on cosine or sine waves [10].

9/10/2024

@Yiming Yang, 11-741 Lecture on DL Attention

24

24

## Empirical Results

Word (wikitext-103) and character (enwik8) **language modeling**

Models	WikiText-103 (PPL)	Enwik8 (BPC)
Best LSTM Variant	29.9	1.23
Transformer	<b>20.5</b>	<b>1.06</b>

**Table 2:** PPL = perplexity and BPC = bits per character. The lower the better.

**Machine translation**

Models	En-Fr	En-De
LSTM + Attention	40.56	26.03
Transformer	<b>41.8</b>	<b>28.4</b>

**Table 3:** BLEU score on two datasets. The higher the better.

9/10/2024

@Yiming Yang, 11-741 Lecture on DL Attention

25

25

## Concluding Remarks

### □ Attention

- Dynamic information gathering based on pairwise similarity
- Has been plugged into various models (BERT, GPT, etc.)

### □ Transformer

- SOTA performance in many large-scale LM applications
- Performance keeps improving when massive training data are available and **if computation/memory is affordable (many works have focused on Transformer with scalable attention)**

9/10/2024

@Yiming Yang, 11-741 Lecture on DL Attention

26

26

## References

- [1] Jimmy Lei Ba, Jamie Ryan Kiros, and Geoffrey E Hinton.  
**Layer normalization.**  
*arXiv preprint arXiv:1607.06450*, 2016.
- [2] Dzmitry Bahdanau, Kyunghyun Cho, and Yoshua Bengio.  
**Neural machine translation by jointly learning to align and translate.**  
*arXiv preprint arXiv:1409.0473*, 2014.
- [3] Zihang Dai, Zhilin Yang, Yiming Yang, Jaime Carbonell, Quoc V Le, and Ruslan Salakhutdinov.  
**Transformer-xl: Attentive language models beyond a fixed-length context.**  
*arXiv preprint arXiv:1901.02860*, 2019.
- [4] Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova.  
**Bert: Pre-training of deep bidirectional transformers for language understanding.**  
*arXiv preprint arXiv:1810.04805*, 2018.
- [5] Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun.  
**Deep residual learning for image recognition.**  
*In Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 770–778, 2016.
- [6] Nikita Kitaev, Łukasz Kaiser, and Anselm Levskaya.  
**Reformer: The efficient transformer.**  
*arXiv preprint arXiv:2001.04451*, 2020.
- [7] Minh-Thang Luong, Hieu Pham, and Christopher D Manning.  
**Effective approaches to attention-based neural machine translation.**  
*arXiv preprint arXiv:1508.04025*, 2015.

27

27

## References

- [8] Mark Sandler, Andrew Howard, Menglong Zhu, Andrey Zhmoginov, and Liang-Chieh Chen.  
**Mobilenetv2: Inverted residuals and linear bottlenecks.**  
*In Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 4510–4520, 2018.
- [9] Ilya Sutskever, Oriol Vinyals, and Quoc V Le.  
**Sequence to sequence learning with neural networks.**  
*In Advances in neural information processing systems*, pages 3104–3112, 2014.
- [10] Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N Gomez, Łukasz Kaiser, and Illia Polosukhin.  
**Attention is all you need.**  
*In Advances in neural information processing systems*, pages 5998–6008, 2017.

28

28