

DOCUMENT ID	JB1162-50010100-007-0001
PROJECT ID	JB1162




VIEW - BB




ELEVATION (VIEWED FROM FRONT OF BOILER)


ARRANGEMENT OF LP STEAM DRUM



VIEW - AA



DETAIL OF METAL TEMPERATION



DETAIL OF MANHOLE OPENING

DESIGN DATA

CODE OF CONSTRUCTION	I.B.R. (1950) & IT'S LATEST AMMENDMENTS UPTO OCTOBER 2019 (SEE NOTE : 01)
MAXIMUM WORKING PRESSURE	6.0 Kg/Sq. cm (g)
MAXIMUM WORKING TEMPERATURE	164° C
WORKING METAL TEMPERATURE	164° C
HYDRAULIC TEST PRESSURE	9.0 Kg/Sq. cm (g) AT SHOP & AS PER IBR AT SITE
RADIOGRAPHY OF LONG.&CIRCUM.SEAM	100%
STRESS RELIEVING	YES & REFER HEAT TREATMENT CYCLE TABLE
EVAPORATION OF BOILER (M.C.R.)	3.6 TPH
TOTAL HEATING SURFACE AREA OF BOILER (EXCLUDING ECONOMISER)	7365 Sq.m (APPROX.)
HEATING SURFACE AREA OF ECONOMISER (NON STEAMING)	NIL
HEATING SURFACE AREA OF DRUM	NIL (OUT SIDE GAS PATH)
STEAM PRESSURE AT MSSV OUTLET	3.0 Kg/Sq. cm (g)
STEAM TEMPERATURE AT MSSV OUTLET	195°C
WEIGHT OF DRUM	2452.30 Kgs. 01
INSPECTION	DIRECTOR OF BOILERS, UTTAR PRADESH/Lloyds (SEE NOTE : 02)

MATERIAL SPECIFICATIONS :

DESCRIPTION	SIZE	SPECIFICATION	MIN. TENSILITY (Kg/ Sq.mm)	MIN.CALC. THK. (mm)	REMARKS
SHELL BELTS	AS PER MATERIAL LIST	SA 516 Gr.70	49.45	3.37	FOR STEAM DRUM
DISHED ENDS	AS PER MATERIAL LIST	SA 516 Gr.70	49.45	3.4	FOR STEAM DRUM


LIST OF REFERENCE DRAWINGS

DRAWING DOCUMENT ID	DESCRIPTION
JB1162-50010100-006-0001	ARRANGEMENT & DETAIL OF CIRCULAR MANHOLE ON LP STEAM DRUM FOR AQC
JB1162-50010100-009-0001	DETAILS OF LP STEAM DRUM NOZZLES FOR AQC


PWHT CYCLE :- (FOR LP STEAM DRUM)

A) LOADING TEMP. (MAX.)	= 300°C
B) RATE OF HEATING ABOVE 300°C	= 120°C/Hr.
C) SOAKING TEMP.	= 610°±10°C
D) SOAKING TIME (MIN.)	= 30 min.
E) RATE OF COOLING UP TO 300°C	= 120°C/Hr.
F) UNLOADING TEMP.	= 300°C
G) COOLING AFTER UNLOADING	= COOLING IN STILL AIR


IBR CHAPTER - XII
IBR FIG : XII/85E B2



WELD DETAIL OF CLOSING SEAM FOR STEAM DRUM
(SEAM MARK Nos. CS-1 & CS-2)




(MARK Nos. N1, N2)
WELD DETAIL OF NOZZLE TO STEAM DRUM




WELD DETAIL OF LONGITUDINAL SEAM
FOR STEAM DRUM
(SEAM MARK No. LS-10)

IBR CHAPTER - XII
IBR FIG : XII/85E B1




(FOR MARK Nos. N14/1 & N14/2)
WELD DETAIL OF NOZZLE TO DRUM

IBR CHAPTER - XII
IBR FIG : XII/85E B2




(MARK Nos. N4, N5/1, N5/2 , N16, N18, N20, N22, N23, N24, N25, N26, N27, N28, N29, N30, N31, N34, N35, N36, N38 & N39)
WELD DETAIL OF NOZZLE TO STEAM DRUM & DISHED END


IBR CHAPTER-VIII
IBR FIG : VIII 365/13




(MARK No. N15)
WELD DETAIL OF NOZZLE TO DISHED END




STEAM DRUM DISHED END DETAIL




SECTION - CC



WATER LEVELS FOR STEAM DRUM



DETAIL OF STEAM DRUM SLIDING SUPPORT (PERMANENT)



(FRONT OF BOILER)
MANHOLE DOOR ORIENTATION

--	FLATS & BRACKETS ON DRUM	--	--	1	80.26	JB1162-50010100-013-0001
--	FLATS & STUDS INSIDE DRUM	--	--	1	34.45	JB1162-50010100-012-0001
-- (01)	DET. OF DRUM NOZZLE	--	--	1	219.66	JB1162-50010100-009-0001
--	A&D OF MAN HOLE DOOR	--	--	2	516.08	JB1162-50010100-006-0001
66/6	SS PLATE	SA 240 GR 304	PL. 2 THK - 994 X 244	2	7.79	-
66/5	SUPPORT PLATE	IS 2062 E250 A	PL. 12 THK - 363 X 109	8	29.82	-
66/4	SUPPORT PLATE	IS 2062 E250 A	PL. 12 THK - 575 X 230	4	49.83	-
66/3	SUPPORT PLATE	IS 2062 E250 A	PL. 12 THK - 956 X 561	2	73.39	AS DRAWN
66/2	BASE PLATE	IS 2062 E250 A	PL. 12 THK - 1000 X 250	2	47.10	-
66/1	SADDLE PAD	IS 2062 E250 A	PL. 6 THK - 1309 X 250	2	30.83	-
65	CLEAT FOR RING	IS 2062 E250 A	PL. 10 THK - 75 X 50	8	2.36	-
64	LAGGING RING	IS 2062 E250 A	ISA 75 X 50 X 8THK-2105 Lg.	2	31.16	-
63	PAD	SA 516 Gr.70	PL. 8 THK - 100 X 165	1	1.04	FOR METAL TEMPERATURE
10	SHELL	SA 516 Gr.70	PL. 12 THK-4070 X 2500	1	897.09	(958.48 Kg.-MAT.FORECAST WT.)
2	DISHED END	SA 516 Gr.70	PL. 12 THK - 1780x1780	1	215.56	(298.46 Kg.-MAT.FORECAST WT.)
1	DISHED END	SA 516 Gr.70	PL. 12 THK - 1780x1780	1	215.88	(298.46 Kg.-MAT.FORECAST WT.)
P.NO.	PART DESCRIPTION	SPECIFICATION	SIZE	P.QTY	P.WT(kg)	REMARK

ITEM CODE	ITEM DESCRIPTION	I.TYPE	I.GROUP	I.QTY	I.WT (Kg) (TOTAL)	REMARK
SDM001	LP STEAM DRUM WITH ATTACHMENTS	P	B215	1	2452.30 (01)	-

BOILER MAKERS NUMBER I.W.T. No. : 6663-LP

TABLE - 1

S.Nos.	Nozzle Nos.	Nozzle Descriptions	Location of Nozzle	No. of Nozzle	Nozzle Size (OD) (D)mm	Schedule of Nozzle (t)	Nozzle Thickness(t) mm	Connecting Pipe Schedule/ Thickness (mm)	Projection from CL of Drum (L) mm From Dished End seam (L1) mm	Nozzle CL to Drum Vertical Axis (±X) mm	Nozzle CL to Drum Horizontal Axis (±Y) mm	Calculated Nozzle Length (R) mm	Finished Length of the Nozzle (M) mm	M/C Bore for end Preparation (E) mm	Weld Dim. (A) mm	Nozzle Inside Projection (p) mm
1	N1	SAFETY VALVE NOZZLE-1	STEAM DRUM SHELL	1	78	-	14	-	-	-	-	198	198	50	12	0
2	N2	SAFETY VALVE NOZZLE-2	STEAM DRUM SHELL	1	65	-	12.5	-	-	-	-	198	198	40	12	0
3	N4	LP SUPER HEATER STEAM STUB	STEAM DRUM SHELL	1	168.3	SCH.XXS	21.95	SCH.40	822	-	-	250	200	154.08	12	0
4	N5/1&N5/2	LP EVAPORATOR RISER STUB	STEAM DRUM SHELL	2	219.1	SCH.160	23.01	SCH.20	822	-	-	253	203	206.40	12	0
5	N9	FEED INLET THERMAL SLEEVE	STEAM DRUM SHELL	1	114.3	SCH.XXS	17.12	REF.009-0001	1022	-	-	REF.DRG : -009-0001				
6	N14/1&N14/2	FEEDER NOZZLE	STEAM DRUM SHELL	2	168.3	SCH.160	18.26	SCH.40	822	-	-	317	267	154.08	12	55
7	N15	CBD NOZZLE	STEAM DRUM DISHED	1	33.4	SCH.XXS	9.09	SCH.40	580	250	400	491	441	26.64	9	150
8	N16	IBD NOZZLE	STEAM DRUM SHELL	1	48.3	SCH.XXS	10.15	SCH.40	822	-	-	247	197	40.94	10	0
9	N18	AIR VENT NOZZLE	STEAM DRUM SHELL	1	33.4	SCH.XXS	9.09	SCH.40	822	-	-	247	197	26.64	9	0
10	N20	NITROGEN BLANKETING NOZZLE	STEAM DRUM SHELL	1	33.4	SCH.XXS	9.09	SCH.40	822	-	-	247	197	26.64	9	0
11	N22	LEVEL GAUGE NOZZLE (STEAM)	STEAM DRUM DISHED	1	33.4	SCH.XXS	9.09	SCH.40	580	350	340	336	286	26.64	9	0
12	N23	LEVEL GAUGE NOZZLE (WATER)	STEAM DRUM DISHED	1	33.4	SCH.XXS	9.09	SCH.40	580	350	340	336	286	26.64	9	0
13	N24	LEVEL GAUGE NOZZLE (STEAM)	STEAM DRUM DISHED	1	33.4	SCH.XXS	9.09	SCH.40	580	350	340	336	286	26.64	9	0
14	N25	LEVEL GAUGE NOZZLE (WATER)	STEAM DRUM DISHED	1	33.4	SCH.XXS	9.09	SCH.40	580	350	340	336	286	26.64	9	0
15	N26	LEVEL TRANSMITTER (STEAM)	STEAM DRUM SHELL	1	33.4	SCH.XXS	9.09	SCH.40	770	-	305	288	238	26.64	9	0
16	N27	LEVEL TRANSMITTER NOZZLE (WATER)	STEAM DRUM SHELL	1	33.4	SCH.XXS	9.09	SCH.40	770	-	305	288	238	26.64	9	0
17	N28	LEVEL TRANSMITTER (STEAM)	STEAM DRUM DISHED	1	33.4	SCH.XXS	9.09	SCH.40	580	350	305	324	274	26.64	9	0
18	N29	LEVEL TRANSMITTER NOZZLE (WATER)	STEAM DRUM DISHED	1	33.4	SCH.XXS	9.09	SCH.40	580	350	305	324	274	26.64	9	0
19	N30	LEVEL TRANSMITTER (STEAM)	STEAM DRUM SHELL	1	33.4	SCH.XXS	9.09	SCH.40	770	-	305	288	238	26.64	9	0
20	N31	LEVEL TRANSMITTER NOZZLE (WATER)	STEAM DRUM SHELL	1	33.4	SCH.XXS	9.09	SCH.40	770	-	305	288	238	26.64	9	0
21	N34	PRESSURE GAUGE NOZZLE (LOCAL)	STEAM DRUM DISHED	1	33.4	SCH.XXS	9.09	SCH.40	822	-	-	250	200	26.64	9	0
22	N35	REMOTE PRESSURE GAUGE NOZZLE (FLOOR)	STEAM DRUM DISHED	1	33.4	SCH.XXS	9.09	SCH.40	822	-	-	250	200	26.64	9	0
23	N36	PRESSURE TRANSMITTER NOZZLE	STEAM DRUM SHELL	1	33.4	SCH.XXS	9.09	SCH.40	822	-	-	247	197	26.64	9	0
24	N37	HP DOSING NOZZLE WITH THERMAL SLEEVE	STEAM DRUM DISHED	1	115	-	32	REF.009-0001	580	250	400	REF. DRG. 009-0001				
25	N38	PRESSURE TRANSMITTER NOZZLE	STEAM DRUM SHELL	1	33.4	SCH.XXS	9.09	SCH.40	822	-	-	247	197	26.64	9	0
26	N39	SPARE NOZZLE	STEAM DRUM SHELL	1	33.4	SCH.XXS	9.09	-	822	-	-	247	197	-	9	0

NOTES :-

I) GENERAL :

01. THE ZERO DATE OF THIS CONTRACT IS 22.10.2019 HENCE IBR AMMENDMENTS UPTO OCTOBER 2019 HAVE BEEN TAKEN CARE OF WHILE DESIGNING THE EQUIPMENT.
02. INSPECTION BY DIRECTOR OF BOILERS, UTTAR PRADESH/Lloyds CBB Authorisation, form XVIA See Regulation 4C(2). BECAUSE MANUFACTURING OF THIS EQUIPMENT SHALL WILL BE DONE AT ATV PROJECT INDIA LIMITED, MATHURA, UTTAR PRADESH.
03. ALL DIMENSIONS ARE IN 'mm' UNLESS OTHERWISE SPECIFIED.
04. ALL FILLET WELDS ARE 6mm UNLESS OTHERWISE SPECIFIED.
05. FOR DIMENSIONAL TOLERANCE REQUIREMENTS PLEASE REFER DOC. NO. GEN-50990100-DSM-002 AND ITS ASSOCIATED DRAWINGS.
06. CIRCUMFERENTIAL DIMENSION (ON OUTSIDE TRAMMELS ON DRUM) LP STEAM DRUM - 3908 mm
07. LEGEND :

H.W.L	: DENOTES HIGH WATER LEVEL.	ID	: DENOTES INSIDE DIAMETER.
N.W.L	: DENOTES NORMAL WATER LEVEL.	SF	: DENOTES STRAIGHT FACE.
L.W.L	: DENOTES LOW WATER LEVEL.	CR	: DENOTES CROWN RADIUS.
CS-1&CS-2	: DENOTES CLOSING SEAM.	KR	: DENOTES KNUCKLE RADIUS.
TL	: TANGENTIAL LINE.	LS-10	: LONGITUDINAL SEAM.
LP	: LOW PRESSURE.	S.F.P.W	: SET ON FULL PENETRATION WELD

II) SHOP NOTES :

01. ALL CIRCUMFERENTIAL DIMENSIONS ARE MEASURED OUTSIDE OF DRUMS
02. MANHOLE CIRCULAR TYPE SIZE ø410 FOR DRUMS REF. DRG. No. JB1162-50010100-006-0001
03. A MAX. 4^{+3}_{-0} mm FILLET WELD TO BE USED FOR WELDING OF CLEAT BRACKETS AS PER DRG.No : 011-0001 TO 014-0001 AFTER STRESS RELIVING.
04. THIS DRAWING SHALL BE READ IN CONJUNCTION WITH THE FOLLOWING DRGS.
    i. FOR NOZZLE & STUBS DETAILS REFER DRG.No : JB1162-50010100-009-0001
    ii. FOR EXTERNAL AND INTERNAL BAFFLES & PIPE REFER DRG.No : 010-0001 TO 015-0001.
05. ALL WELDING TO BE DONE BY IBR QUALIFIED WELDER USING IBR WELDING PROCEDURES
06. FOR BOILER DRUMS HAVING SHELL THICKNESS 100mm AND ABOVE FOLLOWING ADDITIONAL TESTING SHALL BE CARRIED OUT:
    i. ULTRASONIC EXAMINATION OF ALL BUTT WELD BEFORE AND AFTER PWHT.
    ii. MAGNETIC PARTICLE EXAMINATION OF NOZZLES/STUBS TO SHELL WELDING.
08. ALL THE PADS WELDED ALL-ROUND ON PRESSURE PART SHALL BE PROVIDED WITH 2 Nos 1/8" NPT(F) TELL-TALE HOLES AT 180° APART ON THE PAD TO RELEASE ENTRAPPED AIR/GAS.
09. TOLERANCE FOR FORMED HEADS:- THE INNER SURFACE OF A TORISPHERICAL SHALL NOT DEVIATE OUTSIDE OF THE SPECIFIED SHAPE BY MORE THAN $1\frac{1}{4}$% OF NOMINAL INSIDE DIAMETER & INSIDE THE SPECIFIED SHAPE BY MORE THAN $\frac{5}{8}$% OF NOMINAL INSIDE DIAMETER.
10. SUITABLE STIFFENER ARRANGEMENT SHALL BE PROVIDED AT SHOP FOR NOZZLES AT DISHED END TO AVOID DAMAGE DURING TRANSPORTATION.
11. MANHOLE DOORS ARE TO BE PLACED INSIDE THE DRUM BEFORE ASSEMBLING DRUM ENDS FOR FINAL CIRCUMFERENTIAL WELD AS PER ORIENTATION DETAIL.
12. 2mm THK. SS PLATE SHALL BE PROTECTED USING WOODEN BLANKS DURING TRANSPORTATION.
13. PRIOR TO HYDRAULIC TESTING FOLLOWING SHALL BE CARRIED OUT.
    a) ALL WELD SPATTER, WELD STUBS, SCALE, DIRT ETC SHALL BE REMOVED FROM DRUM.
14. EQUIPMENT SHALL BE THOROUGHLY DRIED/CLEANED AFTER HYDRO TESTING.
15. HYDRO TESTING TO BE CARRIED OUT WITH GASKET THAT IS THE SAME AS THE SPECIFIED SERVICE GASKET.
16. HYDROTEST WATER SHALL NOT CONTAIN MORE THAN 10ppm SUSPENDED SOLIDS.
17. ALL INSIDE EDGES OF NOZZLES AND CONNECTIONS SHALL BE GROUND SMOOTH TO 3 MM RADIUS.
18. STRAY ARCING SHOULD BE AVOIDED. IF ANY STRAY ARCING NOTED SHALL BE DRESSED, MPI & UT CHECKED.
19. FOLLOW APPROVED AND APPLICABLE WPS FOR SELECTION OF WELDING CONSUMABLES,
20. WELD SURFACES SHALL BE FREE FROM CRACKS, UNDERCUTS, UNNECESSARY GRINDING, ABRUPT RIDGES AND VALLEYS.
21. VISUAL INSPECTION OF WELD SHALL BE CARRIED OUT AND NOTED BEFORE OFFERING FOR ANY NON DESTRUCTIVE EXAMINATION.
22. HYDRO TEST WATER QUALITY SHALL BE MAINTAINED WITHIN LIMITS SPECIFIED IN DOCUMENT NO.- BLS-PPA-HYD-01-S1.
23. DRUM TO BE STAMPED AS FOLLOWS :-

ITEM CODE-SDM001-LP STEAM DRUM
ATV PROJECTS INDIA LTD., MATHURA (U.P)
(A/C ISGEC HEAVY ENGINEERING LTD.)
WORKS NO - /IWT NO. 6663-LP
YEAR OF MAKE-
TESTED TO -9.0 Kg/Sq. cm (g)
TESTED ON -
MAXIMUM WORKING PRESSURE - 6.0 Kg/Sq. cm (g)
COMPETENT PERSON'S /
INSPECTING AUTHORITY'S OFFICIAL STAMP
FINAL DATE OF EXAMINATION -

PAINTING NOTES:-

01. FOR PAINTING NOTES REFER SPECIFICATION NO:JB1162-50570900-PSH-0001.

I.W.T. No : 6663-LP

REVN.	ZONE	DESCRIPTION	REVD. BY	CHKD. BY	APPD. BY	DATE
1	~	1. HOLD HAS BEEN REMOVED FOR SAFETY VALVE NOZZLE Nos. N1 & N2 AND CORRESPONDINGLY ITS WELD DETAIL, TABLE - 1 HAS BEEN UPDATED.	V.KAVASKAR	R.G.AMIR	R.ARUNKUMAR	12.02.2020

CONSULTANT	-
CLIENT	M/s. ULTRATECH CEMENT LTD, NATHDWARA CEMENT WORKS

DO NOT SCALE
IF IN DOUBT PLEASE ASK

THIS DESIGN IS THE PROPERTY OF M/S. ISGEC HEAVY ENGINEERING LTD. AND IS ONLY ALLOWED TO BE USED BY EXPRESSED PERMISSION AND LICENSE FROM M/S. ISGEC HEAVY ENGINEERING LTD.

FOR APPROVAL	NO	FOR INFORMATION	NO	FOR PRODUCTION	YES	FOR ERECTION	YES

RESPONSIBLE DEPT.	DRAWN BY	CHECKED BY	APPROVED BY	DATE
MECHANICAL	K.BALAGURU	R.G.AMIR/R.KUMARAN	R.ARUNKUMAR	20.12.2019

TOTAL WEIGHT IN kg.	PROJECT ID	ELEMENT ID	I.W.T. NO.
2452.30 (01)	JB1162	50010100	6663-LP
	YEAR : 2019	SHEET SIZE : A1	SCALE : 1:30

ISGEC BOILERS
(formerly Isgec John Thompson)
Isgec Heavy Engineering Ltd.
Noida 201 301 (U.P.) India

SERVICE	WHR BOILER FOR CLINKER COOLER (AQC)
TITLE	ARRANGEMENT & DETAILS OF LP STEAM DRUM FOR AQC
DRAWING DOCUMENT ID	JB1162-50010100-007-0001
REVISION	01

THIS IS A CAD FILE - DO NOT CORRECT IT MANUALLY

CAD FILE FROM SOFTWARE : CAD