

COMP20003 Algorithms and Data Structures Mergesort

Kris Ehinger
Department of Computing and
Information Systems
University of Melbourne
Semester 2



Mergesort

- Skiena Chapter 4.5




COMP 20003 Algorithms and Data Structures

1-2

Merging

- We have two lists (stored as linked lists or arrays), **each already in sorted order**
- We would like to **merge** them into **one sorted** list that includes every element



COMP 20003 Algorithms and Data Structures

1-3

How do you merge?

- 2 linked lists or arrays
 - **Two pointers** (or indices): to **smallest** element
 - **Compare** elements pointed to
 - **Output smallest and move pointer**
- How many comparisons?
- Code...




COMP 20003 Algorithms and Data Structures

1-4

Sorting using the merge operation

1. If list has **one element**, return
2. **Split** list into two **equal-sized** pieces (recursively, until singleton)
3. **Sort each half**
4. **Merge** two sorted halves



COMP 20003 Algorithms and Data Structures

1-5

Merge Code

```

merge(item C[], item A[], item B[],
      int n, int m) /* n is size of A, m size of B */
{
    // ... merge logic ...
}
  
```

COMP 20003 Algorithms and Data Structures

1-25

Merge Code

```

merge(item C[], item A[], item B[],
      int n, int m) /* n is size of A, m size of B */
{
    int i,j,k;
    for( i=0,j=0,k=0; k < n+m; k++ )
    {
        /* shortcut at the end of A or B */
        if(i == n) { C[k] = B[ j++ ]; continue; }
        if(j == m) { C[k] = A[ i++ ]; continue; }
        if(A[i] <= B[j]) C[k] = A[ i++ ];
        else C[k] = B[ j++ ];
    }
}
  
```

COMP 20003 Algorithms and Data Structures

1-26

Mergesort: topdown (recursive)

```

main() { /* code */ mergesort(A,0,n-1); /* more code */

mergesort(A,first,last)
{
    if( first < last){
        int i;
        item B[], item C[];
        mid = (int)(last-first+1)/2;
        for(i=0;i<mid;i++) B[i] = A[i];
        for(i=mid;i<=last;i++) C[i-mid] = A[i];
        B = mergesort(B,0,mid-1);
        C = mergesort(C,0,mid-1);
        A = merge(B,C);
    }
}
  
```

1-27

Analyzing mergesort

- We are concerned with:
 - Accuracy
 - Does mergesort work?
 - Is it **stable**?
 - Efficiency
 - Does it take **extra space**? How much?
 - **Analyze time efficiency using recurrences**

COMP 2003 Algorithms and Data Structures

1-28

Recurrences

- **Recurrence relation "mathematical def'n":**
 - an equation that recursively defines a sequence
 - each further term of the sequence is defined as a function of the preceding terms

Remember Fibonacci numbers (week 1)

COMP 2003 Algorithms and Data Structures

1-29

Mergesort recurrences

Recurrence for **number of comparisons**:

- Cost of sorting **n** items =
 - **2***Cost of sorting **n/2** items + **merge n items**
- $C(n) = 2C(n/2) + n - 1$ (worst case)
- $C(1) = 0$

COMP 2003 Algorithms and Data Structures

1-30

Solving recurrence

- Approximate **n** as **power of 2**:
 - $C(n) = 2C(n/2) + n - 1$
 - $= 2[2C(n/4) + (n/2 - 1)] + (n - 1)$
 - $= 4C(n/4) + (n - 2) + (n - 1)$
 - $= 8C(n/8) + (n - 4) + (n - 2) + (n - 1)$
 - $= 16C(n/16) + (n - 8) + (n - 4) + (n - 2) + (n - 1)$
 - $2^k C(n / 2^k) + kn - (2^k - 1)$

COMP 2003 Algorithms and Data Structures

1-32


Solving recurrence

- Approximate n as power of 2:
 - $2^k C(n / 2^k) + kn - (2^k - 1)$
 - What is k ?
- Base case: $(n / 2^k) = 1$
 - $n = 2^k$
 - $k = \log_2 n$
- $n C(1) + n \log_2 n - (n - 1)$

COMP 20003 Algorithms and Data Structures

1-33

Intuition



COMP 20003 Algorithms and Data Structures

1-34

Mergesort: Top-down (recursive)

- Top-down mergesort works well with arrays
 - Also with linked lists (pointer to find midpoint of list)
- Worst case $O(n \log n)$
- Average case $O(n \log n)$
- Stable?
- Requires $O(n)$ extra space

COMP 20003 Algorithms and Data Structures

1-35

Bottom-up mergesort

- Break list into n singleton lists
- Insert single lists into a queue
- deQueue the first two items, merge them, and enQueue them




Merged Items go at the end

COMP 20003 Algorithms and Data Structures

1-36

Bottom-up mergesort Example

[4, 2, 5, 3, 0, 1]



COMP 20003 Algorithms and Data Structures

1-37

Mergesort: Implementation

- Top-down mergesort (**recursive**)
- Bottom-up mergesort (**iterative**)
- Demos:
 - <https://www.cs.usfca.edu/~galles/visualization/ComparisonSort.html>
 - <https://www.toptal.com/developers/sorting-algorithms>
 - http://www.youtube.com/watch?v=XaqR3G_NVoo

COMP 20003 Algorithms and Data Structures

1-38

Quicksort vs. Mergesort

	Quicksort	Mergesort
Compare during?	split	merge
Average $O()$	$n \log n$	$n \log n$
Worst $O()$	n^2	$n \log n$
In-place sort?	yes	no
Stable sort?	no	yes

COMP 20003 Algorithms and Data Structures

1-39

Mergesort: Summary

- Analysis similar for recursive and non.
 - $\Theta(n \log n)$
 - **Stable**
 - Reliable, and work with both **arrays** and **lists**
 - Can sort **huge files on disk**
 - Use disk fetching just the portions of data you need
- Would be the **perfect sort**, **except that**:
 - Arrays require **$O(n)$ extra space**
 - Slower than quicksort in practical cases

COMP 20003 Algorithms and Data Structures

1-40