


## PUSH BUTTON MOUNTING CHANGES BETWEEN -01/-03 AND -02/-04

#### HMI POSITION CHANGES BETWEEN -01/-03 AND -02/-04




⑧ SET HEIGHT OF COLLAR HANGER HOOK SO TRAY CAN PASS—UNDER HANGING COLLAR

—BUTTON FINAL  
LOCATION BASED  
ON ERGONOMIC

( 621  
[24]  
TOP OF RAIL

$$\begin{pmatrix} 1463 \\ [58] \end{pmatrix}$$
2232  
[88] —



FINAL  
POSITION  
BASED ON  
APPLICATION



SET HEIGHT OF COLLAR  
HANGER HOOK  
—SO TRAY CAN PASS  
UNDER HANGING  
COLLAR

## BUTTON FINAL LOCATION BASED ON ERGONOMIC

DIMENSIONS ARE IN MM[IN]

|   |  |           |                              |           |
|---|--|-----------|------------------------------|-----------|
|   | 3RD ANGLE PROJECTION<br>© 2024 BERSHKE RECY. INC.<br>ALL RIGHTS RESERVED<br>CONFIDENTIAL AND PROPRIETARY   |           | DESCRIPTION:                 |           |
|   | THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF BERSHKE RECY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF BERSHKE RECY IS PROHIBITED. |           | PACKOUT STATION ASSEMBLY     |           |
| DIMENSIONS ARE IN MILLIMETERS DRAWN IN ACCORDANCE WITH ASME Y14.5-2018  |  |           |                              |           |
| MASS<br>g   | SCALE<br>1:8   | SIZE<br>D | DOCUMENT NUMBER<br>114780-XX | REV:<br>G |
| MATERIAL<br>N/A   |  |           | SHEET<br>G OF C              |           |
| FINISH<br>N/A   |  |           |                              |           |