	规 格	规格书编号 2012091301		
品名	6X6 Radial Taping	型 号	TVDT18-050CR-T	1/10

1.General specification 基本说明

- 1.1 Scope 范围 This specification covers the requirements for single key switches which have no key top(TACT SWITCHES:MECHANICAL CONTACT).此规范含盖单推柄和无推柄的轻触开关要求
- 1.2 Operating Temperature Range 使用温度范围
 -20 to+70℃(normal humidity, normal press.) 正常湿度,标准压力
- 1.3 Storage Temperature Range 保存温度范围 -40 to+85℃(normal humidity, normal press.)
- 1.4 Test Conditions 测试条件

Tests and measurements shall be made in the following standard conditions unless otherwise specified: 测试和计量按下列标准条件除非特殊说明

Normal temperature (temperature 5 to 35℃) 标准温度

Normal humidity (relative humidity 45 to85%) 正常湿气

Normal pressure (pressure 860 to 1060 mbars) 标准压力

In case any question arises from the judgment made, tests shall be conducted in the following conditions:

Temperature $(20\pm 2^{\circ})$ 温度 Relative humidity $(65\pm 5\%)$ 相对湿度 Pressure (860 to 1060 mbars) 压力

2.TYPE OF ACTUATION 动作类型

Tactile feedback 轻触返回

3.CONTACT ARRANGEMENT 1 poles 1 throws 接触形式 1 接点 1 回路

(Details of contact arrangement are given in the assembly drawings.) 细接点形式在装配图中

4.MAXIMUM RATINGS DC <u>12</u> V <u>50</u> mA 最大额定值

DC __1__V __10__ μ A 最小额定值

ZHEJIANG JIANFU ELECTRONICS CO., LTD

	规格书编号 2012091301			
品名	6X6 Radial Taping	型 号	TVDT18-050CR-T	2/10

