Logical partition acquisition for Windows OS <u>CAUTION</u>: NEVER STORE THE DISK IMAGE IN THE TARGET MACHINE. DOING IT WILL DESTROY EVIDENCE. USE AN EXTERNAL STORAGE MEDIA.

## 1 Preparation (on standalone machine)


 A single tool "FTK Imager Lite" is required for this activity. A portable version of this may be downloaded

from: <a href="http://marketing.accessdata.com/ftkimag">http://marketing.accessdata.com/ftkimag</a> erlite3.1.1


- 2. Ensure that you have compression software capable of creating encrypted ZIP archives available in your system. If not, IBM X-Force IRIS recommends using 7-Zip Portable, available from official website: <a href="http://portableapps.com/apps/utilities/7-zip portable">http://portableapps.com/apps/utilities/7-zip portable</a> or any other tool of your choice.
- 3. Prepare storage media, with at least the same size as media in target machine. Tool allows forensic images to be stored on external hard drive attached to target machine. Perform a quick format of a storage media with NFTS file system all data on this media may be irrecoverably lost! If it is not possible to use external storage media, network shared can be used as an alternative.
- 4. Copy "FTK Imager Lite" and if necessary "7zip Portable" onto the media.

# 2 Acquiring Hard Disk Image


 Execute FTK Imager Lite icon in the FTK Imager Lite folder to start the program.




2. Next, select File → Create Disk Image



 Choose Source Evidence Type as "Logical Drive" and click "Next"




4. Select the partition of the drive to be imaged from the drop down with all available logical partitions and click "Finish"



#### IBM X-Force IRIS


5. Now it's time to choose where to store the image file, type of image file to create and other options:




 Click on "Add" to select image file location and type of image to be created. Select Destination image type as "E01" when prompted and click "Next" (See below)



7. In the next screen type details such as case and evidence numbers, description of the activity, Examiner's name and other notes (optional).




8. In the next screen, select the folder where the image file will be stored. Choose the location to be the external media connected to the target computer. Provide a unique name for the image file following the pattern <hostname-drive letterdate> (i.e. client01-C-2018mar03); the extension (.E01 in our case) will be appended automatically. Leave all other options such as Image Fragment Size, Compression, etc. to their default values. Now click on "Finish".




- 9. Now we are ready to start acquiring the disk image. To do this first "check" the following boxes on the screen below before clicking on the "Start" button:
  - a. Verify images after they are created
  - b. Pre-calculate Progress Statistics
  - c. Create directory listings of all files in the image after they are created

v20200507 2/4


#### IBM X-Force IRIS




- 10. Initiate the imaging process by selecting "Start"
- 11. Once the disk imaging process is underway you should see the following progress dialog box:



12. Once the disk image is successfully acquired, you should see the following confirmation box. Click on "Close" on this box:



- 13. Perform steps 3-12 for any additional partitions that may be attached to the Windows systems. Make sure you choose the partition carefully to avoid duplicate images or acquiring image of a wrong drive. Also make sure to choose different folders and/or different image file names to be able to clearly distinguish between images acquired from different physical drives and partitions.
- 3 Preparation for delivery to IBM X-Force IRIS team (on standalone machine)
  - Attach external hard drive with previously acquired forensic image or mount file share containing previously acquired forensic image.
  - 2. Create compressed encrypted archive with below options, eg. using 7-Zip Portable.
  - Open the folder containing previously created evidence files and select all image files and memory dump and click 'Add' from toolbar.
  - 4. In 'Add to Archive' window choose '7z' from 'Archive format' dropdown menu, choose 'Store' from 'Compression level' dropdown menu, set 'Split to volumes, bytes:' to '10g', enter complex (16 characters, mixed case letters, numbers, and special symbols) password in 'Enter password' and 'Reenter password' fields, choose 'AES-256' from 'Encryption method' dropdown menu and tick 'Encrypt file names' checkbox, and click 'OK' button.



 After encryption is completed, use 7-Zip to open newly created file with 7z extension, provide password and click 'OK' button, then click 'Test'

v20200507 3/4

### IBM X-Force IRIS

from toolbar. <u>If test completes without errors, encryption was successful.</u>

- 6. Use method approved within your organization to securely erase file with previously chosen unique and descriptive name and extension <u>E01.</u>
- 7. Newly created 7z file and other files on external hard drive are ready for delivery to IBM X-Force IRIS team via agreed method of delivery.
- 8. Share complex password used to for encryption with IBM X-Force IRIS team <u>using different communication channel</u> then used to share forensic image.

v20200507 4/4