

Documentation

SOFTWARE ENGINEERING FOR DATA SCIENTISTS IN PYTHON



Adam Spannbauer

Machine Learning Engineer at Eastman

Documentation in Python

- Comments

```
# Square the number x
```

- Docstrings

```
"""Square the number x

:param x: number to square
:return: x squared

>>> square(2)
4
"""
```

Comments

```
# This is a valid comment  
x = 2
```

```
y = 3 # This is also a valid comment
```

```
# You can't see me unless you look at the source code  
# Hi future collaborators!!
```

Effective comments

Commenting 'what'

```
# Define people as 5
people = 5

# Multiply people by 3
people * 3
```

Commenting 'why'

```
# There will be 5 people attending the party
people = 5

# We need 3 pieces of pizza per person
people * 3
```

Docstrings

```
def function(x):  
    """High level description of function  
  
    Additional details on function
```

Docstrings

```
def function(x):  
    """High level description of function  
  
    Additional details on function  
  
    :param x: description of parameter x  
    :return: description of return value
```

Example webpage generated from a docstring in the Flask package.

Docstrings

```
def function(x):  
    """High level description of function  
  
    Additional details on function  
  
    :param x: description of parameter x  
    :return: description of return value  
  
    >>> # Example function usage  
    Expected output of example function usage  
    """"  
  
    # function code
```

Example docstring

```
def square(x):  
    """Square the number x  
  
    :param x: number to square  
    :return: x squared  
  
>>> square(2)  
4  
"""  
  
# `x * x` is faster than `x ** 2`  
# reference: https://stackoverflow.com/a/29055266/5731525  
    return x * x
```


Example docstring output

```
help(square)
```

```
square(x)
    Square the number x

:param x: number to square
:return: x squared


>>> square(2)
4
```

Let's Practice

SOFTWARE ENGINEERING FOR DATA SCIENTISTS IN PYTHON

Readability counts

SOFTWARE ENGINEERING FOR DATA SCIENTISTS IN PYTHON



Adam Spannbauer
Machine Learning Engineer

The Zen of Python

```
import this
```

The Zen of Python, by Tim Peters (abridged)

Beautiful is better than ugly.

Explicit is better than implicit.

Simple is better than complex.

The complex is better than complicated.

Readability counts.

If the implementation is hard to explain, it's a bad idea.

If the implementation is easy to explain, it may be a good idea.

Descriptive naming

Poor naming

```
def check(x, y=100):  
    return x >= y
```

Descriptive naming

```
def is_boiling(temp, boiling_point=100):  
    return temp >= boiling_point
```

Going overboard

```
def check_if_temperature_is_above_boiling_point(  
    temperature_to_check,  
    celsius_water_boiling_point=100):  
    return temperature_to_check >= celsius_water_boiling_point
```

Keep it simple

The Zen of Python, by Tim Peters (abridged)

Simple is better than complex.

Complex is better than complicated.



Making a pizza - complex

```
def make_pizza(ingredients):  
    # Make dough  
    dough = mix(ingredients['yeast'],  
                ingredients['flour'],  
                ingredients['water'],  
                ingredients['salt'],  
                ingredients['shortening'])  
  
    kneaded_dough = knead(dough)  
    risen_dough = prove(kneaded_dough)  
  
    # Make sauce  
    sauce_base = sautee(ingredients['onion'],  
                        ingredients['garlic'],  
                        ingredients['olive oil'])  
  
    sauce_mixture = combine(sauce_base,  
                            ingredients['tomato_paste'],  
                            ingredients['water'],  
                            ingredients['spices'])  
  
    sauce = simmer(sauce_mixture)  
    ...
```

Making a pizza - simple

```
def make_pizza(ingredients):  
    dough = make_dough(ingredients)  
    sauce = make_sauce(ingredients)  
    assembled_pizza = assemble_pizza(dough, sauce, ingredients)  
  
    return bake(assembled_pizza)
```


When to refactor

Poor naming

```
def check(x, y=100):  
    return x >= y
```

Descriptive naming

```
def is_boiling(temp, boiling_point=100):  
    return temp >= boiling_point
```

Going overboard

```
def check_if_temperature_is_above_boiling_point(  
    temperature_to_check,  
    celsius_water_boiling_point=100):  
    return temperature_to_check >= celsius_water_boiling_point
```

Let's Practice

SOFTWARE ENGINEERING FOR DATA SCIENTISTS IN PYTHON

Unit testing

SOFTWARE ENGINEERING FOR DATA SCIENTISTS IN PYTHON



Adam Spannbauer

Machine Learning Engineer at Eastman

Why testing?

- Confirm code is working as intended
- Ensure changes in one function don't break another
- Protect against changes in a dependency

Testing in Python

- `doctest`
- `pytest`




pytest

Using doctest


```
def square(x):  
    """Square the number x  
  
    :param x: number to square  
    :return: x squared  
  
    >>> square(3)  
    9  
    """  
    return x ** x  
  
import doctest  
doctest.testmod()
```

```
Failed example:  
    square(3)  
Expected:  
    9  
Got:  
    27
```

pytest structure



pytest structure



Writing unit tests

working in `workdir/tests/test_document.py`

```
from text_analyzer import Document

# Test tokens attribute on Document object
def test_document_tokens():
    doc = Document('a e i o u')

    assert doc.tokens == ['a', 'e', 'i', 'o', 'u']

# Test edge case of blank document
def test_document_empty():
    doc = Document('')

    assert doc.tokens == []
    assert doc.word_counts == Counter()
```

Writing unit tests

```
# Create 2 identical Document objects
doc_a = Document('a e i o u')
doc_b = Document('a e i o u')

# Check if objects are ==
print(doc_a == doc_b)
# Check if attributes are ==
print(doc_a.tokens == doc_b.tokens)
print(doc_a.word_counts == doc_b.word_counts)
```

False

True

True

Running pytest

working with `terminal`

```
datacamp@server:~/work_dir $ pytest
```

```
collected 2 items
```

```
tests/test_document.py .. [100%]
```

```
===== 2 passed in 0.61 seconds =====
```

Running pytest

working with `terminal`

```
datacamp@server:~/work_dir $ pytest tests/test_document.py
```

```
collected 2 items

tests/test_document.py ..                [100%]

===== 2 passed in 0.61 seconds =====
```

Failing tests

working with `terminal`

```
datacamp@server:~/work_dir $ pytest
```

```
collected 2 items
```

```
tests/test_document.py F.
```

```
===== FAILURES =====
```

```
_____ test_document_tokens _____
```

```
def test_document_tokens(): doc = Document('a e i o u')
```

```
assert doc.tokens == ['a', 'e', 'i', 'o']
```

```
E AssertionError: assert ['a', 'e', 'i', 'o', 'u'] == ['a', 'e', 'i', 'o']
```

```
E Left contains more items, first extra item: 'u'
```

```
E Use -v to get the full diff
```

```
tests/test_document.py:7: AssertionError
```

```
===== 1 failed in 0.57 seconds =====
```

Let's Practice

SOFTWARE ENGINEERING FOR DATA SCIENTISTS IN PYTHON

Documentation & testing in practice

SOFTWARE ENGINEERING FOR DATA SCIENTISTS IN PYTHON



Adam Spannbauer

Machine Learning Engineer at Eastman

Documenting projects with Sphinx

text_analyzer

Navigation

Classes

Utility Functions

Quick search

Classes

class text_analyzer.**Document**(text)

Analyze text data

Parameters: **text** – text to analyze

Variables:

- **text** – Contains the text originally passed to the instance on creation
- **tokens** – Parsed list of words from `text`
- **word_counts** – `Counter` object containing counts of hashtags used in text

plot_counts(attribute='word_counts', n_most_common=5)

Plot most common elements of a `collections.Counter` instance attribute

Parameters:

- **attribute** – name of `Counter` attribute to use as object to plot
- **n_most_common** – number of elements to plot (using `Counter.most_common()`)

Returns: None; a plot is shown using `matplotlib`

```
>>> doc = Document("duck duck goose is fun")
>>> doc.plot_counts('word_counts', n_most_common=5)
```


Documenting classes

```
class Document:
    """Analyze text data

    :param text: text to analyze

    :ivar text: text originally passed to the instance on creation
    :ivar tokens: Parsed list of words from text
    :ivar word_counts: Counter containing counts of hashtags used in text
    """
    def __init__(self, text):
        ...
```

Continuous integration testing




DataCamp / text_analyzer  build failing

Current Branches Build History Pull Requests > [Build #230](#)

More options 

✖ new_feature update SocialMedia class

🔗 #230 failed

🔗 Commit 3080c4a 

🕒 Ran for 1 min 13 sec

🔗 Compare 43dc3ba . . 3080c4a 



📅 11 days ago

🔗 Branch new_feature 

 DataCamp

🔗 </> Python: 3.6

Continuous integration testing

 DataCamp / text_analyzer  build passing

Current

Branches

Build History

Pull Requests

Build #231

More options

✓ new_feature fix bug in SocialMedia

Commit 09eb5e9

Compare 3080c4a...09eb5e9

Branch new_feature

DataCamp

Python: 3.6

#231 passed

Ran for 1 min 39 sec

11 days ago

Links and additional tools

- [Sphinx](#) - Generate beautiful documentation
- [Travis CI](#) - Continuously test your code
- [GitHub](#) & [GitLab](#) - Host your projects with git
- [Codecov](#) - Discover where to improve your projects tests
- [Code Climate](#) - Analyze your code for improvements in readability

Let's Practice

SOFTWARE ENGINEERING FOR DATA SCIENTISTS IN PYTHON

Final Thoughts

SOFTWARE ENGINEERING FOR DATA SCIENTISTS IN PYTHON



Adam Spannbauer

Machine Learning Engineer at Eastman

Looking Back

- Modularity

```
def function()  
    ...
```

```
class Class:  
    ...
```



Looking Back

- Modularity
- Documentation

```
"""docstrings"""
```

```
# Comments
```



Looking Back


- Modularity
- Documentation
- Automated testing



```
def f(x):  
    """  
  
    >>> f(x)  
    expected output  
    """  
    ...
```



Data Science & Software Engineering



Good Luck!

SOFTWARE ENGINEERING FOR DATA SCIENTISTS IN PYTHON