

Welcome to this course!

FUNCTIONS FOR MANIPULATING DATA IN SQL SERVER



Ana Voicu
Data Engineer

Topics covered

- The most important data types
- Functions for these types:
 - Date and time functions
 - String functions
 - Functions for numeric operations

Categories of data types

- Exact numerics
- Approximate numerics
- Date and time
- Character strings
- Unicode character strings
- Binary strings
- *Other data types*

Exact numerics

- Whole numbers
 - smallint
 - tinyint
 - int
 - bigint
- Decimal numbers
 - numeric
 - decimal
 - money
 - smallmoney

Exact numerics - integers

Numbers without a decimal point

Data type	Storage
bigint	8 Bytes
int	4 Bytes
smallint	2 Bytes
tinyint	1 Byte

Exact numerics - decimals

1234567.675

S (scale) = number of decimal digits stored to the right of the decimal point

P (precision) = maximum total number of decimal digits that will be stored

Precision	Storage
1 – 9	5 Bytes
10 – 19	9 Bytes
20 – 28	13 Bytes
29 - 38	17 Bytes

Approximate numerics

- Float
- Real
- Store **approximate** numeric values

Date and time data types

Data type	Format	Accuracy
time	hh:mm:ss[.nnnnnnnn]	100 nanoseconds
date	YYYY-MM-DD	1 day
smalldatetime	YYYY-MM-DD hh:mm:ss	1 minute
datetime	YYYY-MM-DD hh:mm:ss[.nnn]	0.00333 second
datetime2	YYYY-MM-DD hh:mm:ss[.nnnnnnnn]	100 nanoseconds

Character and Unicode character data types

Character data types store character strings (ASCII)

- char
- varchar
- text

Unicode data types are used for storing Unicode data (non-ASCII)

- nchar
- nvarchar
- ntext

Other data types

- binary
- image
- cursor
- rowversion
- uniqueidentifier
- xml
- Spatial Geometry / Geography Types

Let's see what you know!

FUNCTIONS FOR MANIPULATING DATA IN SQL SERVER

Implicit conversion

FUNCTIONS FOR MANIPULATING DATA IN SQL SERVER



Ana Voicu
Data Engineer

Data comparison

Keep in mind: for comparing two values, they need to be of the same type.

Otherwise:

- SQL Server converts from one type to another (**IMPLICIT**)
- The developer explicitly converts the data (**EXPLICIT**)

Example of possible conversions

```
SELECT  
  company  
  bean_type,  
  cocoa_percent  
FROM ratings;
```

Example of possible conversions

```
SELECT
  company
  bean_type,
  cocoa_percent
FROM ratings
WHERE cocoa_percent > 0.5;
```

company	bean_type	cocoa_percent
Amedei	Blend	0.7000
Bonnat	Trinitario	0.7500
...

Example of possible conversions

```
SELECT
  company
  bean_type,
  cocoa_percent
FROM ratings
WHERE cocoa_percent > -2;
```

company	bean_type	cocoa_percent
Amedei	Blend	0.7000
Bonnat	Trinitario	0.7500
...

Example of possible conversions

```
SELECT
  company
  bean_type,
  cocoa_percent
FROM ratings
WHERE cocoa_percent > GETDATE();
```

company	bean_type	cocoa_percent
...

Example of possible conversions

```
SELECT
  company
  bean_type,
  cocoa_percent
FROM ratings
WHERE cocoa_percent > 'A';
```

```
| result |
|-----|
| Error converting data type varchar to numeric. |
```

Example of possible conversions

```
SELECT
  company
  bean_type,
  cocoa_percent
FROM ratings
WHERE cocoa_percent > '0.5';
```

company	bean_type	cocoa_percent
Amedei	Blend	0.7000
Bonnat	Trinitario	0.7500
...

Data type precedence

1. user-defined data types (**highest**)
2. datetime
3. date
4. float
5. decimal
6. int
7. bit
8. nvarchar (including nvarchar(max))
9. varchar (including varchar(max))
10. binary (**lowest**)

Data type precedence

! [Data type precedence, from highest to lowest

Implicit conversion between data types

To → From ↓	DATETIME	FLOAT	DECIMAL	INT	BIT	NVARCHAR	VARCHAR
DATETIME		✗	✗	✗	✗	✓	✓
FLOAT	✓		✓	✓	✓	✓	✓
DECIMAL	✓	✓		✓	✓	✓	✓
INT	✓	✓	✓		✓	✓	✓
BIT	✓	✓	✓	✓		✓	✓
NVARCHAR	✓	✓	✓	✓	✓		✓
VARCHAR	✓	✓	✓	✓	✓	✓	

Performance impact of implicit conversion

- Implicit conversion is done for each row of the query
- Implicit conversion can be prevented with a good database schema design.

Let's practice!

FUNCTIONS FOR MANIPULATING DATA IN SQL SERVER

Explicit conversion

FUNCTIONS FOR MANIPULATING DATA IN SQL SERVER



Ana Voicu
Data Engineer

Implicit and explicit conversion

- **IMPLICIT** - performed automatically, behind the scenes
- **EXPLICIT** - performed with the functions `CAST()` and `CONVERT()`
 - `CAST()` and `CONVERT()` are used to convert from one data type to another

CAST()

```
CAST(expression AS data_type [(length)])
```

SELECT

```
CAST(3.14 AS int) AS DECIMAL_TO_INT,  
CAST('3.14' AS decimal(3,2)) AS STRING_TO_DECIMAL,  
CAST(GETDATE() AS nvarchar(20)) AS DATE_TO_STRING,  
CAST(GETDATE() AS float) AS DATE_TO_FLOAT;
```

DECIMAL_TO_INT	STRING_TO_DECIMAL	DATE_TO_STRING	DATE_TO_FLOAT
3	3.14	Apr 11 2019 1:01PM	43531.7052687886

CONVERT()

```
CONVERT(data_type [(length)], expression [,style])
```

SELECT

```
CONVERT(int, 3.14) AS DECIMAL_TO_INT,  
CONVERT(decimal(3,2), '3.14') AS STRING_TO_DECIMAL,  
CONVERT(nvarchar(20), GETDATE(), 104) AS DATE_TO_STRING,  
CONVERT(float, GETDATE()) AS DATE_TO_FLOAT;
```

DECIMAL_TO_INT	STRING_TO_DECIMAL	DATE_TO_STRING	DATE_TO_FLOAT
3	3.14	11.04.2019	43531.7052687886

CAST() vs. CONVERT()

- `CAST()` comes from the SQL standard and `CONVERT()` is SQL Server specific
- `CAST()` is available in most database products
- `CONVERT()` performs slightly better in SQL Server

Let's practice!

FUNCTIONS FOR MANIPULATING DATA IN SQL SERVER