

Introduction to C Programming

Module 15.5: Practice Day 02

(Codeforces Links and Practice Questions)

Topics:

1. Pointer and Functions
2. Sorting

Codeforces Links:

1. **A. Add**
   Solution link: A Add

2. **B. Print**
   Solution link: B Print

3. **G. Max and MIN**
   Solution link: G Max and Min

4. **T. Sort Numbers**
   Solution link: T Sort Numbers

5. **D. Positions in array**
   Solution link: D Positions in array

6. **N. Check Code**
   Solution link: N Check Code

[Scroll down for more problems]

Practice Problem 1

Question: Write a function named **my_abs()** that receives an integer value as parameter and returns the absolute value of that. Absolute value means if the value is negative it will be converted to positive value. Then print the value in the main function.

Sample Input	Sample Output
5	5
-7	7

Practice Problem 2

Question: Write a function named **my_len()** which receives a string as a parameter and then counts the length of that string and returns that count. Don't use **strlen()** function to get the length of the string. After receiving that count in the main function print it.

Note: The string will not have any spaces.

Sample Input	Sample Output
hello	5

Practice Problem 3

Question: Write a function named **count_odd()** which receives an array of integers and the size of that array and counts the number of odd elements in that array and returns that. Call that function in the main function and print the count there.

Sample Input	Sample Output
5 1 5 4 10 2	2

Practice Problem 4

Question: Make a function named **change_it()** which receives an array of integers and the size of that integer. In the function you need to change the value of the last index of that array and assign 100 there. You don't need to return anything. After that print the array in the main function and see if it is updated.

Sample Input	Sample Output
5 10 20 30 40 50	10 20 30 40 100
3 1 2 3	1 2 100

Practice Problem 5

Question: Write a function named **swap_it()** which will receive addresses of two integer variables. That means you need to receive them as integer pointers in the function parameter. In the function you need to swap the values of each other, you know that you can access the values of them by using dereferencing. You don't need to return anything. After the function calls print the values of those two variables in the main function and see if anything happens!

Sample Input	Sample Output
10 20	20 10