

Accounting for Heterogeneity Across Multiple Imaging Sites Using Multi-Task Learning

No Author Given

No Institute Given

Abstract. Combining imaging data from multiple sites has the potential to increase statistical power in clinical studies. However, while pooling multiple data sources increases sample size, it also increases unwanted variance due to inconsistencies across sites, e.g., different scanners, protocols, and demographics. In this paper, we present an approach for combining multi-site imaging data in classification tasks that takes this heterogeneity into account. The idea is to treat the classification problem as a multi-task learning problem, where each imaging site is treated as a “task”. We employ a regularized support vector machine (SVM) that allows for differences in decision boundaries at individual sites, while at the same time leveraging the similarities in the decision boundaries across sites. We demonstrate the effectiveness of this approach in the classification of autism from multi-site functional magnetic resonance imaging (fMRI) from the Autism Brain Imaging Data Exchange (ABIDE). The proposed method achieves state-of-the-art accuracy and outperforms a comparable SVM classifier applied to pooled data as well as individual SVM classifiers applied per site.

1 Introduction

Recent years have seen a movement towards combining neuroimaging data collected across multiple sites. Such multi-site data has the potential to accelerate scientific discovery by increasing sample sizes, providing broader ranges of participant demographics, and making data publicly available. Different approaches include large, coordinated multi-site neuroimaging studies, such as the Alzheimer’s Disease Neuroimaging Initiative (ADNI) [?], as well as data sharing initiatives that combine multiple single-site studies, such as the Autism Brain Imaging Data Exchange (ABIDE) [4]. Analysis using these datasets, however, is not straightforward, due to differences across site scanners, protocols, populations, and diagnosis techniques. Treating a multi-site study as a single, homogeneous data set fails to account for this variability, which can be detrimental to the statistical power and counteract the gains made by increasing the sample size.

An alternative approach is to perform separate statistical analyses at individual sites and combine the results in a meta-analysis. This is often formulated as a random effects model [3], where each site is regarded as a random treatment effect. While this can be an effective way to combine statistical tests of low-dimensional summary measures, it is less applicable to learning problems on

high-dimensional data such as images. For instance, applying independent classifiers at each site and then combining them post-hoc misses the opportunity that the classifiers could benefit from sharing information across sites during learning. Also, meta-analysis is not free of subjectivity of data variability, thus this method of combined analysis is also faulty [6].

In this paper, we propose an approach for combining multiple imaging studies in classification problems. The idea is to treat the problem as a multi-task learning problem, where classifiers for each site are estimated jointly, with a regularization that favors similarity across sites. This allows classifiers to share information during learning, but also provides the flexibility for them differ at each site as needed. This is the key principle in multi-task learning: heterogeneity across similar tasks (or, in our case, sites) can be accounted for while using a common mean to account for similarities between the different tasks. We specifically employ a regularized support vector machine (SVM) introduced by Evgeniou and Pontil [5]. As a driving problem, we apply this method to the classification of autism from functional magnetic resonance imaging (fMRI) from the ABIDE database.

Several groups have reported classification results using the ABIDE data, in each case treating the pooled collection of images across all sites as a single homogeneous dataset during classification. Nielsen, et al. [11] combines the ABIDE dataset with a whole-brain approach, using a leave-one-out classifier to compute a classification score for each left-out subject based on age, gender and handedness. The correlations for each connection in turn were fit with a linear model, separating controls from ASDs, which was then adjusted by the difference between the subject’s site mean for that connection and the overall mean. This approach yielded a maximum overall accuracy of 60.0% despite finding significant positive correlation between the classification score and several of the phenotypic behavioral measures [11]. A different study used histogram of gradients and applied this to several multi-site imaging studies which was able to achieve 61.7% accuracy on the ABIDE dataset and 62.6% on the ADHD-200 dataset [7]. While [11] accounted for the site differences during feature generation and selection, both studies approached the differences across imaging sites as noise instead of extra data that can be leveraged when classifying an aggregate data set.

2 Methods

Classification of multi-site imaging data can be thought of as a multi-task learning problem where each site, s , is treated as a separate task, t . For a dataset with S sites, the corresponding multi-task problem will have a set of $T = S$ tasks and a function $F(t)$ that describes the relationship between each task. Prior to using any sort of machine learning, however, nuisance factors (e.g. age) should be ***removed? from the data to ideally isolate differences across all data that are exclusive to the ***disease, disorder?**** being studied.

2.1 Multi-Task Learning

Evgeniou and Pontil [5] introduce a method of multi-task learning based on kernel methods typically used for single task learning. This method relies on minimizing regularization functions, such as that for SVM, to capture both overall similarity between tasks and individual task differences. The traditional minimization for a soft margin SVM is

$$\frac{1}{2}w^2 + CF \left(\sum_{i=1}^t \xi_i \right), \quad (1)$$

where C is a constant and $F(\mu)$ is a monotonic convex function with $F(0) = 0$ [2]. In the case of SVMs, the weight vector w is used to define the hyperplane, $(w \cdot x + b)$, which is the boundary between groups.

For multi-task learning, the relationship between T tasks must be described, which can be framed as a hierarchical model. This assumes that each task function comes from a class of probability distributions. The relationship is defined as

$$w_t = w_0 + v_t, \quad (2)$$

where w_0 is the mean of the data and each task t has its own weight vector, v_t . Multi-task learning allows for simultaneous learning of the mean of all tasks, w_0 , and each task weight vector, v_t , so the minimization function then becomes

$$C \sum_{t=1}^T \sum_{i=1}^m \xi_{it} + \frac{\lambda_1}{T} \sum_{t=1}^T \|v_t\|^2 + \lambda_2 \|w_0\|^2, \quad (3)$$

where λ_1, λ_2 are positive regularization parameters, and C is still a constant. For high similarity between tasks, the v_t will be small in relation to w_0 ; this relationship is described by the hyperparameters λ_1, λ_2 that must be chosen by the user.

The dual of equation 3 can be found by defining a set of functions $f_t(x) = w_t \cdot x$ which can be simplified to $F(x, t) = f_t(x)$. This can be described by a kernel function $\phi((x, t))$ which allows us to relate the dual of a multi-task learning problem to the dual of Equation 1.

$$\max_{\alpha_{it}} \left\{ \sum_{i=1}^m \sum_{t=1}^T \alpha_{it} - \sum_{i=1}^m \sum_{s=1}^T \sum_{j=1}^m \sum_{t=1}^T \alpha_{is} y_{is} \alpha_{jt} y_{jt} \phi((x, t)) \right\} \quad (4)$$

where

$$\phi((x, t)) = \left(\frac{x}{\sqrt{\mu}}, \underbrace{0, \dots, 0}_{t-1}, x, \underbrace{0, \dots, 0}_{T-t} \right), \quad \text{for } \mu = \frac{T\lambda_2}{\lambda_1}. \quad (5)$$

As you can see in Equation 4, this is the same dual problem as for a single task-SVM, with the data transformed by $\phi((x, t))$ into the multi-task kernel space.

2.2 Feature Selection

Data extraction in imaging studies typically leads to very high dimensional data spaces. For f-MRI, a typical choice for data is the pairwise correlation between n predefined regions of the brain. This yields a dataspace of $\frac{n(n+1)}{2}$ dimensionality, which, even for a relatively small number of regions, can be computationally expensive. The multi-task learning above further increases dimensionality with the number of tasks. For a feature space $x \in \mathbb{R}^d$, the multi-task kernel $\phi((x, t))$ would yield a feature space of $d(t + 1)$ dimensions. Feature selection can and should be employed to remove redundancy and increase relevancy of the data while reducing computation time [8].

One approach is to use the values of the weight vector w to choose the most relevant features. Recall that the decision boundary in an SVM is defined by $w \cdot x$, so the highest magnitudes in the weight vector denote the features that best define the decision boundary between groups. This approach requires choosing a user defined n size subset of features which introduces another parameter and layer of complexity but overall reduces computation time by dramatically reducing the dimensionality of the feature space.

3 Evaluation

3.1 Data

The Autism Brain Imaging Data Exchange (ABIDE) database is an online consortium of resting-state functional-MRI data from 17 international sites, resulting in brain imaging data for 539 individuals with ASD and 573 typically developing (TD) controls [4]. All ASD subjects were diagnosed by either the Autism Diagnosis Observation Schedule-General (ADOS-G) or the Autism Diagnostic Interview-Revised tests and removed from the study if other co-morbid disorders were present [9] [10] [4]. Further inclusion details can be found at (put url? citation to... website? or the abide paper?)

Preprocessing All data was preprocessed using the Functional Connectomes-1000 preprocessing scripts [1]. This includes:

1. MRI Deoblique, reorient, skull strip
2. f-MRI Reorient, motion correct, skull strip, smooth
3. registration
4. Segmentation - csf, white matter
5. extracting global signal, from csf and wm
6. extract time series, Z-transform correlations
7. spatial smoothing, register to atlas
8. some sort of regression

Twelve subjects were removed because of failure during the preprocessing. Two Oregon subjects were missing the resting fMRI file and 10 UCLA subjects were missing the anatomical scan file which is required in step 1 of the preprocessing pipeline above. This resulted in 1100 subjects for analysis, 530 ASD and 570 TD controls.

- Colcombe, et al. Toward discovery science of human brain function. *Proceedings of the National Academy of Sciences*, 107(10):4734–4739, 2010.
2. Corinna Cortes and Vladimir Vapnik. Support-vector networks. *Machine learning*, 20(3):273–297, 1995.
3. Rebecca DerSimonian and Nan Laird. Meta-analysis in clinical trials. *Controlled clinical trials*, 7(3):177–188, 1986.
4. A Di Martino, CG Yan, Q Li, E Denio, FX Castellanos, K Alaerts, JS Anderson, M Assaf, SY Bookheimer, M Dapretto, et al. The autism brain imaging data exchange: towards a large-scale evaluation of the intrinsic brain architecture in autism. *Molecular psychiatry*, 2013.
5. Theodoros Evgeniou and Massimiliano Pontil. Regularized multi-task learning. In *Proceedings of the tenth ACM SIGKDD international conference on Knowledge discovery and data mining*, pages 109–117. ACM, 2004.
6. Hans J Eysenck. Meta-analysis and its problems. *BMJ: British Medical Journal*, 309(6957):789, 1994.
7. Sina Ghiassian, Russell Greiner, Ping Jin, and Matthew RG Brown. Learning to classify psychiatric disorders based on fmri images: Autism vs healthy and adhd vs healthy.
8. Isabelle Guyon and André Elisseeff. An introduction to variable and feature selection. *The Journal of Machine Learning Research*, 3:1157–1182, 2003.
9. Catherine Lord, Susan Risi, Linda Lambrecht, Edwin H Cook Jr, Bennett L Leventhal, Pamela C DiLavore, Andrew Pickles, and Michael Rutter. The autism diagnostic observation schedulegeneric: A standard measure of social and communication deficits associated with the spectrum of autism. *Journal of autism and developmental disorders*, 30(3):205–223, 2000.
10. Catherine Lord, Michael Rutter, and Ann Le Couteur. Autism diagnostic interview-revised: a revised version of a diagnostic interview for caregivers of individuals with possible pervasive developmental disorders. *Journal of autism and developmental disorders*, 24(5):659–685, 1994.
11. Jared A Nielsen, Brandon A Zielinski, P Thomas Fletcher, Andrew L Alexander, Nicholas Lange, Erin D Bigler, Janet E Lainhart, and Jeffrey S Anderson. Multisite functional connectivity mri classification of autism: Abide results. *Frontiers in human neuroscience*, 7, 2013.
12. Jonathan D Power, Alexander L Cohen, Steven M Nelson, Gagan S Wig, Kelly Anne Barnes, Jessica A Church, Alecia C Vogel, Timothy O Laumann, Fran M Miezin, Bradley L Schlaggar, et al. Functional network organization of the human brain. *Neuron*, 72(4):665–678, 2011.