



SSG030NVEJXS1YL000 SSG050NVEJXS1YL000

ROI...Reimagined

HUEBSCH stacked washer-extractor/tumble dryer, featuring the Quantum Touch control, is a unique product that truly delivers return on investment.

- Designed to produce maximum ROI per square foot for laundries where space is at a premium
- Offers all the benefits of a HUEBSCH 30-pound washer-extractor and tumbler dryer (50-pound version also available)
- A flush-mounted soap dispenser contributes to the machine's sleek, modern design, that includes stainless steel with chrome accents
- Minimal front fasteners gives quick access to key washer-extractor components to improve serviceability
- Tumble dryer features two cycle modifiers for additional profit potential
- Great product for owners to differentiate their store from the competition. The stack provides customers an all-in-one option, with no need to use a laundry cart to transfer loads across the store to the tumble dryer section.





Stacked Washer-Extractor/Tumble Dryers

Touch Control

Reimagine your laundry experience with the **HUEBSCH** Touch display. Clear, easy to use, easy to understand directions with profitable cycle modifiers enhance your customers' experience and increase return on investment.

- User-friendly screens with operating instructions built in as part of the control
- Washer-Extractor:
15 total cycle options, 3 basic cycles, 1 custom cycle, 3 basic temperature options
- Tumble Dryer:
5 basic cycles (high, medium, low, delicate, no heat)
- Easy-to-understand cycle modifier prompts will encourage your customers to customize their dry
- Flexible pricing & additional revenue opportunities with customizable cycle modifiers, time-of-day pricing and lucky cycle options
- 30+ languages available
- On-screen timer so your customers know exactly how much time their cycle will take
- Speed Cycle option for those who want to get in and out quickly
- Flexible Payment Options - Coin, Card, Mobile, Cash



Take your business to new levels of efficiency and profitability with advanced analytics and customer data—all integrated into the same platform with the rest of your business management tools. Know how often each customer visits, which machines they use, how they pay, and use that information to increase your revenue through stronger customer relationships and a more rewarding laundry experience.



Stacked Washer-Extractor/Tumble Dryers

			30		50	
			Washer-Extractor	Tumble Dryer	Washer-Extractor	Tumble Dryer
Control Option			Quantum Touch		Quantum Touch	
Capacity - lb (kg)			30 (13) x 2		50 (23) x 2	
Overall Width - in (mm)			31.4 (797)		34.4 (875)	
Overall Depth - in (mm)			45.5 (1152)		51.3 (1302)	
Overall Height - in (mm)			79.7 (2023)		84.3 (2141)	
Cylinder Diameter - in (mm)			24.0 (610)	30.0 (762)	26.3 (668)	33.0 (838)
Cylinder Depth - in (mm)			16.0 (406)	26.0 (660)	20.3 (515)	30.0 (762)
Cylinder Volume - cu. ft (liters)			4.2 (119)	10.6 (300)	6.3 (178)	14.8 (419)
Reversing Cylinder			-	Standard	-	Standard
Door Opening Size - in (mm)			14.3 (363)	22.6 (574)	16.3 (414)	26.9 (683)
Door Bottom to Floor - in (mm)			14.0 (356)	51.3 (1303)	14.6 (370)	52.3 (1328)
Water Inlet Connection - in (mm)			2 x 0.75 (19)	-	2 x 0.75 (19)	-
Drain Diameter - in (mm)			1 x 3 (76)	-	1 x 3 (76)	-
Drain Height to Floor - in (mm)			4.3 (108)	-	4.5 (115)	-
Heat Input Power - Btu/hr (kW, Mj/hr.)			-	73,000 (21.4, 77.0)	-	95,000 (27.8, 100)
Gas Connection - in			-	1/2 NPT	-	1/2 NPT
Air Outlet - in (mm)			-	8.0 (200) Elliptical	-	10.0 (250) Elliptical
Airflow - cfm (l/sec)			-	400 (190)	-	600 (285)
Motor - HP (kW)	Fan		-	0.5 (0.4)	-	0.5 (0.4)
	Drive		1 (0.75)	0.3 (0.2)	2 (1.5)	0.5 (0.4)
Total # of Speeds			9	-	9	-
Cylinder Speeds - RPM (G-Force)	Gentle		34 (0.4)	-	33 (0.4)	-
	Wash		48 (0.8)	-	46 (0.8)	-
	Distribution		86 (2.5)	-	82 (2.5)	-
	Very Low		282 (27)	-	269 (27)	-
	Low		485 (80)	-	464 (80)	-
	Medium		542 (100)	-	518 (100)	-
	High		606 (125)	-	579 (125)	-
	Very High		664 (150)	-	635 (150)	-
	Ultra High		766 (200)	-	733 (200)	-
Electrical Specs - amps	B	100-120V/50/60/1	15	15	-	-
	X	200-240V/50/60/1/3	15	10	15	10
	P	380-415V/50/60/3	15	10	15	10
Shipping Dimensions Approx. - in (mm)	Width		34.5 (876)		35.5 (902)	
	Depth		47.0 (1194)		54.0 (1372)	
	Height		83.0 (2108)		89.0 (2261)	
Net Weight - lb (kg)			770 (349)		910 (413)	
Shipping Weight - lb (kg)			787 (357)		930 (422)	
Agency Approvals			UL _{US} CSA		UL _{US} CSA	

For the most accurate information, the installation guide should be used for all design and construction purposes.
 Due to continuous product improvements, design and specifications subject to change without notice.
 The quality management systems of Alliance Laundry Systems are registered to ISO 9001.