

AUDSPECT

Breach & Attack Simulation Platform

Adversary Simulation Assessment Report

Active Directory Credential Access Drill (PurpleSharp)

RISK: HIGH RISK

Prepared for	DESKTOP-5TVEBSI
Endpoint	Windows/amd64 (10.0.19045)
Environment	Production
Assessment date	30 June 2026, 11:06 UTC
Report generated	30 June 2026, 11:07 UTC
Run reference	18bdd72a

1. Executive Summary

PRODUCTION ENVIRONMENT

This assessment executed live adversary techniques against a production endpoint. Endpoint changes were reverted where the snapshot system captured them — see section 7 (Changes & Cleanup Verification).

This report presents the results of an automated breach & attack simulation executed against DESKTOP-5TVEBSI (Windows/amd64 (10.0.19045)) on 30 June 2026. The assessment ran 13 MITRE ATT&CK-aligned techniques to measure how effectively the endpoint's security controls prevent real adversary behaviour.

Of the techniques executed, 6 were prevented or blocked by a security control and 7 executed successfully without being stopped. This yields a prevention effectiveness of 50% and an overall risk classification of High Risk (risk score 70/100). Consecutive failures across adjacent kill-chain phases amplified exposure by 1.3×, indicating an attacker could chain multiple steps with limited resistance.

7 critical or high-severity technique(s) were not prevented and require prioritised remediation (see Key Findings). Testing exercised 3 of the 14 MITRE ATT&CK Enterprise tactics across 13 technique(s) — this is the breadth of THIS run, not a measure of overall MITRE ATT&CK coverage. Broadening scenario coverage in future runs will increase assurance. Prioritised recommendations are provided in section 8.

Overall posture: High Risk (risk score 70 / 100, Baseline)

13 techniques · 6 prevented · 7 succeeded · 0 errored · 0 skipped · 7 critical/high finding(s)

Trend vs Previous Assessment

This is the first scored assessment for this endpoint — a prevention trend will appear once a second assessment completes.

Prevention & Detection

7 technique(s) executed without being prevented. A FAIL means a prevention control did not stop execution — not that the attacker's end objective was independently verified. Of those that executed:

Detection results unavailable: no host telemetry was collected during this run.

This is a measurement gap, not proof the techniques evaded detection. Confirm the agent build collects event-log telemetry and that Microsoft Defender (or Sysmon) is enabled on the endpoint, then re-run. The figures below reflect prevention only; the detection split cannot be trusted until telemetry is collected.

0 Detected

an alert fired (Microsoft Defender) — a SOC would see this

0 Logged only

telemetry exists but no alert was raised

7 Undetected

detection not measured — no telemetry collected this run (see caveat above)

Business-Objective Risk

What an attacker could achieve against this endpoint, by objective — derived from the tested techniques in each area (execution errors excluded).

Credential Theft

HIGH RISK

5 of 7 technique(s) unprevented

Privilege Escalation

LOW RISK

0 of 3 technique(s) unprevented

Lateral Movement

HIGH RISK

2 of 3 technique(s) unprevented

2. Assessment Scorecard

PREVENTION

50%

techniques blocked (higher is better)

DETECTION

N/A

no telemetry — not measurable

EXPOSURE

High

posture band (lower is better)

PENETRATION

7 / 13

53% of executed got through

Attack Surface Age: Exposed weakness present for 0 days · Days weakness: T1021.002 (SMB Signing Required) · Status: WITHIN-SLA

Endpoint Stability Check — Health Impact: Negligible

Before Running: CPU: 1.9% · RAM: 5.6 GB · Disk: 53.7% | After Running: CPU: 2.3% · RAM: 5.6 GB · Disk: 53.7%

Detection Source Ranking

PRODUCT	DETECTIONS	MIN TIME-TO-DETECT	AVG TIME-TO-DETECT
1. Trellix	18	4s	8s
2. Defender	14	2s	4s
3. SIEM	5	12s	25s

Assessment Insights

MOST PROTECTED

Privilege Escalation (100%)

LEAST PROTECTED

Credential Access (28%)

No host telemetry was collected this run — detection effectiveness could not be measured (the agent may be offline or an older build). Undetected counts reflect missing measurement, not confirmed evasion.

Control Maturity by Category

Maturity (0–10) per control family, from this run's prevention rate — a management view of which controls held and which need investment. Derived from tested techniques only.

Privilege Escalation Controls		10 / 10
Credential Access Controls		3 / 10
Lateral Movement Controls		3 / 10
Detection Controls		not measured (no telemetry)

3. Methodology & Scope

Framework	MITRE ATT&CK (Enterprise)
Engines	Custom checks
Target endpoint	DESKTOP-5TVEBSI — Windows/amd64 (10.0.19045)
Asset class	Workstation (inferred from OS)
Environment	Production
Business criticality	High — production endpoint
Security context	AV: Windows Defender, Microsoft Defender (real-time protection ON)
Techniques executed	13
Tactics exercised	3 of 14 ATT&CK tactics
Window	30 Jun 2026 11:06 UTC

Security context lists the AV/EDR products detected on the endpoint (presence only). Detection by third-party EDR is not locally observable and is therefore never asserted in this report.

Each technique is scored as PASS when a security control prevented or blocked it, FAIL when it executed without being stopped, ERROR when the test itself could not execute correctly (malformed content, timeout, missing prerequisite, scheduler contention), or SKIPPED when it was not run. Only PASS and FAIL count toward the score: a FAIL is a finding — the simulated adversary behaviour succeeded against this endpoint — while ERROR and SKIPPED are excluded because they reflect a test-execution problem, not the endpoint's defences.

4. ATT&CK Tactic Breakdown

Privilege Escalation		100%	3 pass · 0 fail
Credential Access		28%	2 pass · 5 fail
Lateral Movement		33%	1 pass · 2 fail

5. Key Findings

Top Risk Drivers

Techniques whose failures account for the most lost prevention points (the points each accounts for, not a promised gain from any single fix).

1.	T1003.001 LSA Protection (RunAsPPL) (Credential Access)	22.7 PTS · 3F · CRITICAL
2.	T1558.003 Kerberos RC4 Disabled (Anti-Kerberoasting) (Credential Access)	6.8 PTS · 1F · HIGH
3.	T1558.004 NTLM Relay Restrictions (Credential Access)	6.8 PTS · 1F · HIGH
4.	T1021.002 SMB Signing Required (Lateral Movement)	6.8 PTS · 1F · HIGH
5.	T1557.001 LLMNR/NetBIOS Poisoning (Lateral Movement)	6.8 PTS · 1F · HIGH

Realized Attack Path

The unprevented techniques from this run, ordered by kill-chain phase. An attacker chaining these consecutive phases met limited resistance — this is the path the endpoint's gaps actually permit, derived from observed FAILs (no inferred causal links).

Credential Access

T1003.001 — LSA Protection (RunAsPPL) · T1558.003 — Kerberos RC4 Disabled (Anti-Kerberoasting) · T1558.004 — NTLM Relay Restrictions

Lateral Movement

T1021.002 — SMB Signing Required · T1557.001 — LLMNR/NetBIOS Poisoning

CRITICAL	F-01 T1003.001 — LSA Protection (RunAsPPL) Credential Access
What happened	RunAsPPL not set — LSASS process is unprotected against credential dumping.
Business Impact	LSASS credentials enable Pass-the-Hash or Pass-the-Ticket attacks against every Windows endpoint in the domain. An attacker can silently reach domain controllers without triggering additional authentication prompts.
Remediation	Set HKLM\SYSTEM\CurrentControlSet\Control\Lsa\RunAsPPL = 1 and reboot.
Priority	Critical
Owner	Active Directory / Identity Team
How to Verify	Run LSASS dump test — result must change to BLOCKED. Enable Credential Guard via Group Policy (Device Guard) and confirm with Get-WinEvent -FilterHashtable @{LogName='System'; Id=12}. Verify Event ID 4656 fires in Windows Security log on any LSASS handle attempt.
Threat Intelligence (MITRE ATT&CK)	
Known threat actors	APT1, APT28, APT3, APT32, APT33, APT39, APT41, APT5, Agrius, Aquatic Panda, +5 more
Associated malware/tools	Bad Rabbit, Cobalt Strike, CozyCar, Daserf, Emotet, Empire, GreyEnergy, Impacket, LaZagne, Lizar, +5 more
Mitigations (ATT&CK)	Behavior Prevention on Endpoint; Credential Access Protection; Operating System Configuration; Password Policies; Privileged Account Management; Privileged Process Integrity; +1 more
Platforms	Windows
Detection data sources	Command: Command Execution; File: File Creation; Logon Session: Logon Session Creation; Process: OS API Execution; Process: Process Access; Process: Process Creation; Windows Registry: Windows Registry Key Modification
Windows telemetry (Sysmon/WEL)	Sysmon 1, Windows Security 4688, PowerShell 4104, Sysmon 11, Windows Security 4624, Windows Security 4625, Sysmon 10, Sysmon 12-14, Windows Security 4657
ATT&CK version	v1.5 · created 2020-02-11 · updated 2024-08-13
ATT&CK reference	https://attack.mitre.org/techniques/T1003/001
Illustrative (analyst-curated, not authoritative)	OWASP E-522 — Insufficiently Protected Credentials
Analyst note	LSASS credential theft is a top precursor to lateral movement in BFSI intrusions; prioritise Credential Guard / LSA protection.

HIGH

F-02 T1558.003 — Kerberos RC4 Disabled (Anti-Kerberoasting) — Active Directory Credential Access Drill (PurpleSharp)

Credential Access

What happened Kerberos SupportedEncryptionTypes not set — RC4 (weak, Kerberoastable) allowed by default.

Business Impact Credentials harvested here can authenticate as legitimate users across Active Directory, enabling silent lateral movement and potentially domain-wide access within minutes.

Remediation Set SupportedEncryptionTypes = 24 (AES128+AES256 only) and set msDS-SupportedEncryptionTypes on service accounts.

Priority High **Owner** Active Directory / Identity Team

How to Verify Enable Credential Guard and audit credential access events (Event IDs 4648, 4776, 4768). Re-run credential access technique — result must change to BLOCKED.

Threat Intelligence (MITRE ATT&CK)

Known threat actors APT29, FIN7, Indrik Spider, Operation Wocao, UNC2452, Wizard Spider
Associated malware/tools Brute Ratel C4, Empire, Impacket, PowerSploit, Rubeus, SILENTTRINITY
Mitigations (ATT&CK) Encrypt Sensitive Information; Password Policies; Privileged Account Management
Platforms Windows
Detection data sources Active Directory: Active Directory Credential Request
ATT&CK version v1.2 · created 2020-02-11 · updated 2024-09-23
ATT&CK reference <https://attack.mitre.org/techniques/T1558/003>

HIGH

F-03 T1558.004 — NTLM Relay Restrictions

Credential Access

What happened RestrictNTLM not configured — NTLM relay attacks not prevented.

Business Impact Credentials harvested here can authenticate as legitimate users across Active Directory, enabling silent lateral movement and potentially domain-wide access within minutes.

Remediation Configure HKLM\SYSTEM\CurrentControlSet\Control\Lsa\RestrictNTLMInDomain and enable EPA.

Priority High **Owner** Active Directory / Identity Team

How to Verify Enable Credential Guard and audit credential access events (Event IDs 4648, 4776, 4768). Re-run credential access technique — result must change to BLOCKED.

Threat Intelligence (MITRE ATT&CK)

Associated malware/tools Rubeus
Mitigations (ATT&CK) Audit; Encrypt Sensitive Information; Password Policies
Platforms Windows
Detection data sources Active Directory: Active Directory Credential Request
ATT&CK version v1.1 · created 2020-08-24 · updated 2024-10-15
ATT&CK reference <https://attack.mitre.org/techniques/T1558/004>

HIGH

F-04 T1021.002 — SMB Signing Required

Lateral Movement

What happened RequireSecuritySignature = 0x0 — SMB relay attacks possible.

Business Impact An attacker can pivot from this endpoint to other systems on the network, expanding the breach blast radius. In BFSI environments this can reach core banking systems and payment infrastructure.

Remediation Set HKLM\SYSTEM\CurrentControlSet\Services\LanmanServer\Parameters\RequireSecuritySignature = 1.

Priority High **Owner** Network Security Team

How to Verify Restrict SMB/WinRM/RDP between non-admin workstations via firewall policy. Re-run lateral movement technique — connection must be blocked or alerted.

Threat Intelligence (MITRE ATT&CK)

Known threat actors APT28, APT29, APT3, APT32, APT39, APT41, Aquatic Panda, Blue Mockingbird, Chimera, Cinnamon Tempest, +5 more
Associated malware/tools Anchor, BlackEnergy, Brute Ratel C4, Cobalt Strike, Conficker, Conti, Diavol, Duqu, Emotet, HermeticWizard, +5 more
Mitigations (ATT&CK) Filter Network Traffic; Limit Access to Resource Over Network; Password Policies; Privileged Account Management
Platforms Windows
Detection data sources Command: Command Execution; Logon Session: Logon Session Creation; Network Share: Network Share Access; Network Traffic: Network Connection Creation; Network Traffic: Network Traffic Flow; Process: Process Creation
Windows telemetry (Sysmon/WEL) Sysmon 1, Windows Security 4688, PowerShell 4104, Windows Security 4624, Windows Security 4625, Sysmon 3, Windows Security 5156
ATT&CK version v1.2 · created 2020-02-11 · updated 2023-07-28
ATT&CK reference <https://attack.mitre.org/techniques/T1021/002>

Lateral Movement

What happened LLMNR not disabled via GPO — susceptible to credential capture via Responder/Inveigh.

Business Impact An attacker can pivot from this endpoint to other systems on the network, expanding the breach blast radius. In BFSI environments this can reach core banking systems and payment infrastructure.

Remediation Disable LLMNR via GPO: Computer Config . DNS Client . Turn off multicast name resolution.

Priority High **Owner** Network Security Team

How to Verify Block SMB/WinRM/RDP between non-admin workstations via firewall policy. Re-run lateral movement technique — connection must be blocked or alerted.

Threat Intelligence (MITRE ATT&CK)

Known threat actors Lazarus Group, Wizard Spider

Associated malware/tools Empire, Impacket, PoshC2, Pupy, Responder

Mitigations (ATT&CK) Disable or Remove Feature or Program; Filter Network Traffic; Network Intrusion Prevention; Network Segmentation

Platforms Windows

Detection data sources Network Traffic: Network Traffic Content; Network Traffic: Network Traffic Flow; Service: Service Creation; Windows Registry: Windows Registry Key Modification

Windows telemetry (Sysmon/WEL) Sysmon 3, Windows Security 5156, System 7045, Windows Security 4697, Sysmon 12-14, Windows Security 4657

ATT&CK version v1.4 · created 2020-02-11 · updated 2023-04-25

ATT&CK reference <https://attack.mitre.org/techniques/T1557/001>

Adversary Knowledge Graph

Threat actors and malware known (per MITRE ATT&CK) to use the techniques that went unprevented in this run, ranked by how many of those techniques they cover — the real-world adversaries these gaps expose you to.

Threat actors that use these techniques

APT28	2 technique(s): T1003.001, T1021.002
APT29	2 technique(s): T1021.002, T1558.003
APT3	2 technique(s): T1003.001, T1021.002
APT32	2 technique(s): T1003.001, T1021.002
APT39	2 technique(s): T1003.001, T1021.002
APT41	2 technique(s): T1003.001, T1021.002
Aquatic Panda	2 technique(s): T1003.001, T1021.002
Blue Mockingbird	2 technique(s): T1003.001, T1021.002

Malware / tools that implement these techniques

Empire	3 technique(s): T1003.001, T1557.001, T1558.003
Impacket	3 technique(s): T1003.001, T1557.001, T1558.003
Brute Ratel C4	2 technique(s): T1021.002, T1558.003
Cobalt Strike	2 technique(s): T1003.001, T1021.002
Emotet	2 technique(s): T1003.001, T1021.002
Net Crawler	2 technique(s): T1003.001, T1021.002
NotPetya	2 technique(s): T1003.001, T1021.002
Rubeus	2 technique(s): T1558.003, T1558.004

Threat-intelligence context derived from MITRE ATT&CK®. © The MITRE Corporation. ATT&CK® is a registered trademark of The MITRE Corporation.

6. Detailed Technique Results

Results are grouped by ATT&CK technique. Each technique shows how many of its tests executed, were blocked, or errored. ERROR tests (a BAS execution problem, not a security outcome) are summarised in the counts and excluded from scoring.

T1003.001 — LSA Protection (RunAsPPL)

Credential Access · Critical · Policy Configuration Check

4 test(s): 3 executed · 1 blocked · 0 errored · 0 skipped

Threat impact Attackers dump credentials from LSASS memory (Mimikatz) to obtain hashes and plaintext passwords.

Remediation Set HKLM\SYSTEM\CurrentControlSet\Control\Lsa\RunAsPPL = 1 and reboot.

FAIL

RunAsPPL not set — LSASS process is unprotected against credential dumping.

Detection: No detection telemetry observed

PASS

WDigest UseLogonCredential = 0 — plaintext credentials not cached.

Blocked by: an active security control (not identifiable from local telemetry)

Detection: No detection telemetry observed

FAIL

LSASS process access auditing not configured — ProcDump/Mimikatz credential dumps are undetected.

Detection: No detection telemetry observed

T1558.003 — Kerberos RC4 Disabled (Anti-Kerberoasting)

Credential Access · High · Policy Configuration Check

1 test(s): 1 executed · 0 blocked · 0 errored · 0 skipped

Threat impact

Kerberoasting harvests RC4-encrypted TGS tickets crackable offline in hours; AES-256 tickets are not feasibly crackable.

Remediation

Set SupportedEncryptionTypes = 24 (AES128+AES256 only) and set msDS-SupportedEncryptionTypes on service accounts.

FAIL

Kerberos SupportedEncryptionTypes not set — RC4 (weak, Kerberoastable) allowed by default.

Detection: No detection telemetry observed

T1552.002 — AutoLogon Credentials in Registry

Credential Access · Critical · Policy Configuration Check

1 test(s): 0 executed · 1 blocked · 0 errored · 0 skipped

Threat impact

AutoLogon stores credentials in plaintext in the registry, readable by any local process.

Remediation

Disable AutoLogon: clear HKLM\...\Winlogon\AutoAdminLogon and DefaultPassword.

PASS

AutoLogon disabled — no plaintext credentials stored in registry.

Blocked by: an active security control (not identifiable from local telemetry)

T1558.004 — NTLM Relay Restrictions

Credential Access · High · Policy Configuration Check

1 test(s): 1 executed · 0 blocked · 0 errored · 0 skipped

Threat impact

Unrestricted NTLM allows relay attacks to authenticate as domain users without knowing passwords.

Remediation

Configure HKLM\SYSTEM\CurrentControlSet\Control\Lsa\RestrictNTLMInDomain and enable EPA.

FAIL

RestrictNTLM not configured — NTLM relay attacks not prevented.

Detection: No detection telemetry observed

T1550.002 — Pass-the-Hash Mitigation (Restricted Admin Mode)

Lateral Movement · High · Policy Configuration Check

1 test(s): 0 executed · 1 blocked · 0 errored · 0 skipped

Threat impact

Without Restricted Admin Mode, Mimikatz-extracted NTLM hashes allow RDP lateral movement to any reachable host.

Remediation

Enable Restricted Admin Mode: HKLM\...\Lsa\DisableRestrictedAdmin = 0. Implement credential tiering.

PASS

Restricted Admin Mode enabled (DisableRestrictedAdmin=0) — Pass-the-Hash over RDP mitigated.

Blocked by: an active security control (not identifiable from local telemetry)

T1021.002 — SMB Signing Required

Lateral Movement · High · Policy Configuration Check

1 test(s): 1 executed · 0 blocked · 0 errored · 0 skipped

Threat impact

Without SMB signing, relay attacks can authenticate as other users across the network.

Remediation

Set HKLM\SYSTEM\CurrentControlSet\Services\LanmanServer\Parameters\RequireSecuritySignature = 1.

FAIL

RequireSecuritySignature = 0x0 — SMB relay attacks possible.

Detection: No detection telemetry observed

T1557.001 — LLMNR/NetBIOS Poisoning

Lateral Movement · High · Policy Configuration Check

1 test(s): 1 executed · 0 blocked · 0 errored · 0 skipped

Threat impact

LLMNR and NetBIOS can be poisoned (Responder) to capture NTLM hashes on local network.

Remediation

Disable LLMNR via GPO: Computer Config . DNS Client . Turn off multicast name resolution.

FAIL

LLMNR not disabled via GPO — susceptible to credential capture via Responder/Inveigh.

Detection: No detection telemetry observed

Privilege Escalation · Critical · Policy Configuration Check

3 test(s): 0 executed · 3 blocked · 0 errored · 0 skipped

Threat impact	Disabled UAC allows any process to silently elevate to Administrator without user consent.
Remediation	Enable UAC: HKLM\SOFTWARE\Microsoft\Windows\CurrentVersion\Policies\System\EnableLUA = 1.
PASS	UAC is enabled (EnableLUA = 1). Blocked by: an active security control (not identifiable from local telemetry)
PASS	LocalAccountTokenFilterPolicy not set — default (0) applies, remote admin tokens filtered. Blocked by: an active security control (not identifiable from local telemetry)
PASS	AlwaysInstallElevated not enabled — MSI privilege escalation path blocked. Blocked by: an active security control (not identifiable from local telemetry)

7. Changes & Cleanup Verification

No endpoint changes were captured for reversal during this run — the snapshot/revert system recorded no residual registry or file artifacts to roll back.

Scope note: residual-artifact tracking covers changes captured by the pre-run snapshot (registry keys and files the engine instruments). Out-of-band changes a technique may make outside that scope are not tracked here — verify manually for high-impact techniques run in production.

8. Action Plan

Ordered by the prevention-score points each tactic's failures account for (severity-weighted, the same weighting as the headline score). The points quantify current exposure — not a guaranteed score gain.

- Credential Access — Credential Theft** 36.4 PTS · 5F
Enable Credential Guard / LSASS protection, restrict debug privileges, and alert on LSASS access.
- Lateral Movement — Lateral Movement** 13.6 PTS · 2F
Segment the network, require SMB signing, and disable legacy remote-exec paths (PsExec/WMI) where unused.

Additional Guidance

- Prevention score indicates significant control gaps. Review failed techniques and apply vendor hardening guides.
- Critical tactic 'credential-access' has 5 failing technique(s). Address immediately — this tactic has the highest attacker value in BFSI environments.
- Critical tactic 'lateral-movement' has 2 failing technique(s). Address immediately — this tactic has the highest attacker value in BFSI environments.
- Tactic coverage is below 50%. Run additional scenarios (ART full sweep, Caldera lateral movement) to exercise more of the ATT&CK kill chain before next audit.

9. Appendix — Metric Definitions

PASS	A security control prevented or blocked the simulated technique. More passes is better.
FAIL	A prevention control did not stop the technique from executing — a finding requiring attention. This means execution was permitted; it does NOT independently verify the attacker's end objective was achieved (e.g. that credentials were actually exfiltrated), which is technique-specific. Check the Detection line for whether the execution was also detected.
Detection	Whether the executed technique was seen by locally-observable telemetry: Detected (a Microsoft Defender alert fired), Logged only (Sysmon/Security telemetry exists but no alert), or Undetected (no telemetry). Third-party EDR detection is not locally observable and is never asserted.

Blocked by	The control credited with blocking a technique, when local evidence (a Microsoft Defender event or a recognisable block signature in the output) supports it. Where no control can be evidenced locally, the report states that an active control blocked it without naming a product — it never guesses.
Trend	Change in prevention effectiveness versus the previous scored assessment for this endpoint, with a short history. Appears once a second assessment has completed.
Threat Intelligence	Per-technique context from MITRE ATT&CK® (threat actors, malware/tools, mitigations) — authoritative, published by MITRE. CVE/KEV/OWASP/CWE shown as 'illustrative' are analyst-curated context, not an authoritative per-technique mapping, and should be read as examples, not an exhaustive list.
ERROR	The test could not execute correctly (malformed content, timeout, missing prerequisite, scheduler contention). A BAS execution problem, not a security outcome — excluded from scoring.
SKIPPED	The technique was deliberately not run (e.g. external payload not shipped) and was excluded from scoring.
Policy Configuration Check	A passive audit that inspects a security setting (registry key, policy, service state) without running an attack — it confirms whether a control is correctly configured.
Active Adversary Behavioral Test	An ART or Caldera test that actually executes the technique on the endpoint — it confirms whether deployed controls stop a live attack, not just whether they are configured.
Prevention	Severity-weighted percentage of techniques that were prevented. Higher is better.
Exposure	Tactic-weighted failure rate, amplified by consecutive kill-chain failures. Lower is better.
Tactic Breadth	Breadth of THIS run: how many of the 14 MITRE ATT&CK Enterprise tactics it exercised. Not a measure of overall MITRE ATT&CK technique coverage — running more Atomics in a tactic does not increase ATT&CK coverage.
Defense Rate	Share of tested tactics in which every technique was blocked (zero failures).
Kill-chain amplifier	Multiplier (1.0–2.5×) reflecting consecutive unprevented kill-chain phases.
Risk classification	Overall posture band derived from the amplified exposure score.