Lab 2 - Greedy regret heuristics

Author: Michał Żurawski 160252

Description of the problem

Each instance contains nodes with coordinates (x, y) and a cost. Select exactly half of the nodes (rounded up) and connect them into a closed cycle. Minimise **cycle length + sum of the costs of the selected nodes**. Distances are Euclidean, rounded to the nearest integer.

Algorithms

Four greedy construction methods, 200 runs each (run i starts from node i). They grow the solution like lab 1's nearest neighbor (any position) and greedy cycle, and differ only in **which node is inserted next**.

Intuition

Plain greedy takes the cheapest insertion right now. A node that fits well in only one place loses it once another node takes that place, and later has to go somewhere much worse. The **regret** of a node is how much we lose if its best position is gone and the second best must be used, so the most "urgent" node (highest regret) is inserted first, and nodes that fit well in several places can wait.

Example: u has insertion increases 10, 50, 60 → regret 40; v has 8, 9, 30 → regret 1. Greedy picks v (8 < 10), regret picks u: if u waits it pays at least 50, while v still has 9.

Pure regret ignores the node cost, so it happily takes expensive nodes. **2-regret + best change** also rewards cheap insertions.

Core calculations

For every unused node u and every place (a, b) it could be inserted (path: also the two ends, cycle: every edge):

`Δ(u, a, b) = d(a, u) + d(u, b) − d(a, b)`


`regret(u) = second smallest Δ − smallest Δ`

`best_change(u) = smallest Δ + cost(u)`

`score(u) = α · regret(u) − β · best_change(u)`

The node with the highest score is inserted at its smallest-Δ place.

Method	α	β
2-regret	1	0
2-regret + best change	1	1



Pseudocode

Simplified from `python/solver.py`. Nearest neighbor and greedy cycle share the loop; they differ in the starting tour and in how the insertion increases are listed (`path_insertion_increases` / `cycle_insertion_increases`).

```
def regret_heuristic(start, weights):               # weights = (α, β)
    tour = [start]                                  # greedy cycle: + nearest partner
    while len(tour) < k:
        node, position = regret_insertion(tour, weights)
        tour.insert(position, node)
    return tour


def regret_insertion(tour, weights):
    regret_weight, change_weight = weights
    for u in unused_nodes:
        increases = insertion_increases(tour, u)     # Δ of every position
        position, cheapest, second_cheapest = two_cheapest(increases)
        regret = second_cheapest − cheapest
        best_change = cheapest + cost[u]
        score = regret_weight ∗ regret − change_weight ∗ best_change
    return the u with the highest score, and its position
```

Results


Objective = cycle length + sum of node costs, over 200 runs per method. Each cell is av (min – max); the best value of each kind per instance is in bold.
All best solutions were checked with the solution checker (the same computation as the lecturer's Solution checker.xlsx): **yes**.
Results are identical in all implemented languages: **yes**.

Method	TSPA	TSPB
Random solution	263514 (237131 – 287973)	206802 (188214 – 231879)
Nearest neighbor (end only)	87477 (84362 – 90075)	59397 (56007 – 63166)
Nearest neighbor (any position)	74347 (72328 – 77022)	59475 (52915 – 66164)
Greedy cycle	73797 (72590 – **75281**)	59709 (53016 – 63736)
Nearest neighbor (any position), 2-regret	122861 (111527 – 133181)	74763 (69032 – 80767)
Nearest neighbor (any position), 2-regret + best change	75561 (72419 – 78504)	**55698** (**50485** – **61406**)
Greedy cycle, 2-regret	121007 (112654 – 130924)	73403 (69455 – 78142)
Greedy cycle, 2-regret + best change	**73350** (**72011** – 75532)	57751 (52906 – 63326)


Visualisation (Instance TSPA)




Random solution
237131 (length 140636 + cost 96495)




Nearest neighbor (end only)
84362 (length 31319 + cost 53043)




Nearest neighbor (any position)
72328 (length 21816 + cost 50512)




Greedy cycle
72590 (length 21570 + cost 51020)




Nearest neighbor (any position), 2-regret
111527 (length 19974 + cost 91553)



Nearest neighbor (any position), 2-regret + best change
72419 (length 20127 + cost 52292)




Greedy cycle, 2-regret
112654 (length 21632 + cost 91022)




Greedy cycle, 2-regret + best change
72011 (length 20248 + cost 51763)


Visualisation (Instance TSPB)




Random solution
188214 (length 138112 + cost 50102)




Nearest neighbor (end only)
56007 (length 24632 + cost 31375)




Nearest neighbor (any position)
52915 (length 20068 + cost 32847)




Greedy cycle
53016 (length 16704 + cost 36312)




Nearest neighbor (any position), 2-regret
69032 (length 21267 + cost 47765)



Nearest neighbor (any position), 2-regret + best change
50485 (length 18835 + cost 31650)



Greedy cycle, 2-regret
69455 (length 20736 + cost 48719)



Greedy cycle, 2-regret + best change
52906 (length 16675 + cost 36231)


Running time

Average time of one run of the algorithm only, over the same runs as above. The fastest language in each row is in bold.

Instance TSPA

Method	Python	C	C++	Rust
Random solution	0.0776 ms	0.0004 ms	0.0003 ms	**0.0003 ms**
Nearest neighbor (end only)	0.3740 ms	**0.0140 ms**	0.0204 ms	0.0235 ms
Nearest neighbor (any position)	24.39 ms	0.5342 ms	**0.4811 ms**	0.5672 ms
Greedy cycle	22.58 ms	0.6874 ms	**0.4626 ms**	0.6487 ms
Nearest neighbor (any position), 2-regret	42.75 ms	**0.6887 ms**	2.96 ms	3.21 ms
Nearest neighbor (any position), 2-regret + best change	44.34 ms	**0.6788 ms**	2.86 ms	3.14 ms
Greedy cycle, 2-regret	43.19 ms	**0.9425 ms**	2.80 ms	1.41 ms
Greedy cycle, 2-regret + best change	43.23 ms	**1.00 ms**	2.78 ms	1.39 ms


Pareto plot (Instance TSPA)



Instance TSPB

Method	Python	C	C++	Rust
Random solution	0.0702 ms	**0.0004 ms**	0.0005 ms	0.0005 ms
Nearest neighbor (end only)	0.3600 ms	**0.0156 ms**	0.0240 ms	0.0183 ms
Nearest neighbor (any position)	23.51 ms	0.5293 ms	**0.5159 ms**	0.5616 ms
Greedy cycle	21.92 ms	0.5417 ms	**0.4642 ms**	0.6392 ms
Nearest neighbor (any position), 2-regret	44.36 ms	**0.6792 ms**	2.78 ms	3.66 ms
Nearest neighbor (any position), 2-regret + best change	43.22 ms	**0.7049 ms**	2.91 ms	3.14 ms
Greedy cycle, 2-regret	43.15 ms	**0.9417 ms**	2.80 ms	1.48 ms
Greedy cycle, 2-regret + best change	42.78 ms	**0.9413 ms**	2.76 ms	1.40 ms

Pareto plot (Instance TSPB)



Best solutions (0-based node indices)

Instance TSPA

Nearest neighbor (any position), 2-regret
199, 82, 116, 119, 11, 49, 108, 152, 123, 160, 12, 97, 120, 92, 171, 166, 183, 10, 22, 98, 27, 87, 141, 23, 180, 28, 156, 16, 190, 74, 144, 179, 177, 36, 99, 41, 61, 135, 181, 58, 84, 134, 65, 158, 111, 182, 105, 57, 64, 107, 88, 78, 26, 75, 170, 159, 130, 117, 113, 106, 150, 0, 176, 174, 8, 142, 85, 128, 3, 1, 59, 46, 86, 55, 17, 29, 19, 163, 24, 136, 186, 109, 34, 62, 154, 39, 175, 115, 5, 112, 139, 18, 4, 76, 132, 68, 44, 14, 38, 80

Nearest neighbor (any position), 2-regret + best change
171, 2, 189, 187, 30, 141, 87, 45, 73, 135, 114, 181, 192, 158, 58, 84, 134, 72, 176, 174, 150, 106, 113, 89, 42, 151, 138, 182, 57, 64, 107, 88, 78, 193, 153, 75, 170, 146, 159, 130, 47, 93, 50, 3, 169, 1, 59, 178, 101, 55, 29, 163, 136, 186, 164, 142, 8, 9, 54, 33, 131, 36, 177, 52, 179, 53, 140, 144, 67, 16, 51, 35, 185, 102, 28, 180, 132, 76, 4, 71, 157, 91, 80, 100, 123, 83, 160, 152, 108, 49, 60, 116, 149, 63, 168, 97, 127, 69, 129, 104

Greedy cycle, 2-regret
190, 52, 177, 140, 61, 45, 67, 35, 102, 180, 145, 23, 162, 68, 132, 76, 4, 71, 91, 137, 126, 48, 199, 77, 82, 63, 49, 108, 152, 100, 123, 160, 12, 161, 97, 188, 129, 110, 92, 171, 166, 183, 10, 27, 70, 98, 25, 114, 118, 181, 192, 158, 58, 84, 134, 72, 0, 151, 106, 89, 124, 57, 64, 107, 193, 75, 170, 159, 130, 117, 93, 81, 85, 142, 164, 169, 47, 37, 147, 21, 155, 101, 17, 29, 19, 163, 24, 136, 186, 109, 34, 62, 154, 39, 175, 5, 112, 139, 133, 51

Greedy cycle, 2-regret + best change
80, 91, 157, 71, 4, 76, 132, 180, 28, 102, 185, 35, 51, 16, 67, 144, 140, 53, 179, 52, 177, 36, 131, 33, 54, 9, 8, 142, 164, 186, 136, 163, 29, 55, 101, 178, 1, 169, 3, 50, 93, 47, 130, 159, 146, 170, 75, 153, 193, 78, 88, 107, 64, 57, 182, 138, 151, 42, 89, 113, 106, 150, 174, 176, 72, 134, 84, 58, 158, 192, 181, 114, 135, 73, 45, 87, 141, 189, 2, 171, 187, 30, 161, 127, 97, 160, 83, 123, 100, 152, 108, 49, 11, 168, 63, 149, 116, 60, 31, 48

Instance TSPB

Nearest neighbor (any position), 2-regret
57, 44, 89, 32, 43, 48, 58, 198, 121, 195, 50, 42, 116, 37, 13, 149, 145, 65, 178, 103, 132, 1, 108, 62, 175, 134, 157, 60, 141, 155, 113, 115, 19, 177, 125, 26, 161, 154, 140, 47, 38, 21, 168, 136, 8, 95, 128, 122, 151, 111, 3, 137, 72, 86, 0, 185, 104, 162, 54, 127, 129, 52, 182, 150, 84, 66, 35, 24, 25, 73, 59, 101, 179, 88, 163, 99, 171, 17, 74, 20, 14, 2, 93, 23, 110, 118, 131, 148, 10, 196, 193, 61, 105, 169, 165, 199, 70, 190, 194, 12

Nearest neighbor (any position), 2-regret + best change
65, 145, 28, 149, 13, 146, 37, 116, 147, 42, 50, 130, 63, 121, 198, 96, 48, 156, 89, 57, 185, 76, 104, 162, 54, 192, 80, 127, 129, 90, 153, 14, 2, 20, 74, 17, 171, 99, 88, 179, 87, 82, 51, 85, 59, 73, 167, 181, 152, 34, 24, 67, 66, 27, 98, 151, 122, 3, 184, 46, 72, 117, 8, 120, 133, 136, 172, 160, 69, 124, 21, 183, 30, 38, 47, 154, 140, 64, 33, 40, 141, 155, 71, 60, 157, 45, 134, 175, 62, 36, 197, 6, 115, 170, 125, 177, 29, 132, 174, 1

Greedy cycle, 2-regret
152, 25, 98, 151, 122, 3, 109, 46, 72, 166, 92, 8, 172, 189, 124, 4, 49, 33, 47, 140, 154, 161, 26, 125, 170, 115, 113, 155, 141, 60, 157, 45, 134, 175, 62, 91, 36, 197, 132, 103, 178, 65, 145, 28, 149, 13, 37, 116, 42, 50, 130, 195, 121, 198, 96, 48, 164, 43, 32, 89, 44, 83, 57, 79, 0, 135, 162, 119, 104, 77, 12, 194, 190, 70, 199, 165, 169, 105, 61, 193, 196, 10, 148, 131, 118, 110, 23, 93, 9, 14, 20, 74, 17, 171, 99, 163, 88, 82, 167, 85

Greedy cycle, 2-regret + best change
60, 157, 45, 134, 175, 71, 113, 36, 197, 132, 29, 6, 180, 115, 170, 177, 125, 26, 97, 154, 140, 47, 38, 21, 30, 183, 191, 130, 63, 121, 198, 96, 48, 43, 156, 32, 89, 57, 79, 185, 104, 54, 196, 114, 10, 90, 14, 2, 74, 20, 153, 129, 127, 80, 192, 162, 76, 135, 27, 11, 66, 67, 24, 34, 152, 181, 126, 88, 179, 87, 82, 167, 51, 85, 59, 73, 98, 151, 122, 173, 3, 184, 86, 46, 72, 117, 8, 120, 133, 136, 172, 160, 69, 124, 4, 64, 33, 155, 141, 40

Source code

labs/lab2 (Python, C, C++, Rust)

Conclusions

- Pure 2-regret is even worse than lab 1 solutions because it ignores node costs; adding the best change fixes this.
- 2-regret + best change beats the lab 1 methods.
- 2-regret solutions run much longer than lab 1 solutions.