Technical report — Gegenprobe: one schema and a converter for Swiss parliamentary answers

Track 2A — OpenParlData · Online · Team 444 — Roman (+ Claude Code agents, §7) · Evidence site https://gegenprobe.mi11ion.io

maturity	components
ready to apply · ready to deploy	census and Bern repair lists (relinks: one OPD decision, its hash rule) · nightly job (three real nights on standard GitHub runners; the ledger fix's real two-night re-run dispatched 12 Oct 00:30 UTC, run in progress)
audited · tested prototype	source-adapter lists · rules-only converter
feasibility study · drafts for the eCH group	review mode, whole and virtual affairs · schema v0.1 and v0.2 (P8's roles)

1. Summary

A common schema for Swiss parliamentary business works if its fields carry roles, and the proposed repairs, keyed on OpenParlData (OPD) ids, would raise the share of interventions with a recorded government answer that have answer text from 81.6% to 92.3%. Of the 17 fields, 10 need roles (8 robust, 2 fragile), 1 is body-specific, and 6 are defined once in v0.1 (their meaning is the next test). "Answer date" is the government's decision in some parliaments, the letter or registration date in others and the submission date in a few; schema v0.1 gives every date its role, every value its source (page and character span, or the OPD record) and every empty field a typed reason. **Sovereign and cheap to run:** the default runs no model and only reads public sources (OPD's exports, Bern's open data, Fedlex, the parliaments' sites); Apertus runs through the Public AI gateway or locally (8B GGUF, CPU); a first network night took 86 min, the next 6.6 min; at ten times OPD's whole export the rules need about 5 CPU-hours.

1. **Schema.** Roles, not only for dates: in 7 parliaments OPD's "answer" event is mostly the submission date. A pre-registered meaning test on 66 affairs from 11 parliaments (P8) finds roles in fields v0.1 defined once: sole, joint or group authorship; co-signatory lists that include authors of record; one harmonised type for different instruments; language tags naming the other official language; in Vernier and Lausanne a submission date printed nowhere. Meaning is measured for 11 of 17 fields (Table 1). Schema v0.2 ships P8's roles and validates 171 affairs, 105 of them the converter's own records.
2. **Census.** Of 91,268 interventions with a recorded government answer, 81.6% have answer text attached today, 85.6% with the repairs from what OPD already holds, 88.3% after its hash decision for the Bern relinks and **92.3%** with the checked fetches. At most 13,150 written answers lack text on their intervention; 2,177 of the "missing" answers were in OPD all along under a heading the census lexicon does not list; in Bern a linking bug, confirmed by OPD (correspondence, 10 Oct 2026), leaves most answers unlinked.
3. **Ready for OPD.** Repairs proposed for **9,720** answers, keyed on OPD ids, among them Bern's 2,421 ready relinks (of 2,459 candidates; 38 for review) and 48 ready fetches with a self-checking dry-run SQL plan (and a guarded plan for the tag rows); separately, 554 Bern `begin_date` corrections; per-parliament lists from 50 model-free source adapters, 27 with counted repairs (judged by blind AI annotators: 197/200 are the executive's answer, the date wrong or unsupported in 15); 9 OPD vocabulary labels wrong as published (e.g. "Votaziun" on 9,887 affairs); a Fedlex resolver for 29,946 federal documents that store Fedlex's "JavaScript required" page. Schemas v0.1 and v0.2 ship as standalone pydantic files for OPD's workbench (`schema/`).
4. **Apertus.** As a closed-set verifier of the review queue (P7, pre-registered), its promotions are answers whose printed answer date passes the date check in 95.8%, **+22.7 points** over a no-model date match (H4, [10.2, 34.3], weighted, as registered; unweighted +7.5), and blind AI annotators judged **120/120** sampled promotions the government's answer (H1, Wilson 95% [96.9, 100]); post hoc, the date it picks is the gold date in 113/120 promotions, against 127/157 for a no-model rule. It fills a tier of **214** review-queue answers. In 15 parliaments nobody wrote rules for it finds 24/29 answer dates (P2; rules 2/29) and is exact on 53/62 documents, against 44/62 for the best no-model baseline (post hoc). On submitters both model routes beat the rules (P5: rules 12/40, pointer 24/40, free generation 34/40). Every date it extracts is printed in the document, with page and span.

2. Architecture

Census (`census/`) streams the OPD exports once into a per-affair *answer-link status* (`attached | agenda | parentless | absent | image_only | oral`), the feasibility matrix and a comparability measure; a derived layer (`census/corrected.py`) places every registered gap row once the repair routes have looked (Fig. 1). **Repair** (`repair/`): deterministic routes per cause, each row checked (affair number or title, answer heading, date against OPD's answer event), as lists keyed on OPD ids; a nightly job (`deploy/nightly/`) re-runs the Bern route. **Converter** (`convert/`, `qa/`): OPD metadata and events, then frozen DE/FR/IT anchor rules, then the Apertus closed-set pointer on the residue; modes `rules_only` (default, no model) and `review` (suggestions with page, span and margin, flagged `needs_review`). **Schema and validator** (`schema/`, `validate/`): Pydantic schema v0.1, normative; a value carries `{value, role, page, char_start, char_end, quote, route, rule, model_build, θ, margin}`, a null its typed reason (`not_in_corpus`, `unlinked`, `oral`, … in `data/schema/null_reasons.json`); `QAItem` pairs question *n* with its answer passage.




Figure 1. The registered 16,749 placed once each (`results/census/corrected.json`). Still to find: 5,077 (943 of them already waiting for a person).

3. Use of Apertus

Closed form only. Apertus never writes a value. (i) *Verifier* (P7, `repair/adapters/adjudicate.py`): for an adapter review row it answers "does this document print the executive's answer to this intervention (number, title)?" (yes vs no scored after a JSON prefix, θ_A = 8) and picks the answer date among the printed dates or none (θ_B = 10); a row is promoted only if both pass and the date passes the adapters' own date rule. (ii) *Pointer* (`convert/pointer.py`, prompts `src/prompts/{de,fr,it}`): the document (first 12,000 characters) and the question in the user message, the assistant turn prefilled with a JSON prefix, `null` and every distinct printed date scored by summed log-probability; null if `lp(null) − logsumexp(lp(dates)) > θ`. Code locates every span (`pointer.locate`: the occurrence nearest an answer anchor, else the first). θ does not transfer across builds, so it is fitted per build on dev documents and frozen (θ = 10.40, AUROC 0.99). The same form picks labels and, in `qa/`, the question a paragraph answers, the recommendation sentence or the submitter's printed name. **Why closed:** asked freely, Apertus dates 15/15 (8B) and 14/15 (70B) Bern interventions that have no answer. **Design:** Apertus suggestions go to a reviewer; rules run unattended.

Which model. Evaluation used **Apertus v1.5 70B weights served by Public AI** under the name `swiss-ai/apertus-v1.5-8b` (inferred from the served fingerprint `tp8-pp2-…` and 760/792 greedy outputs byte-identical to the `-70b` name); the response `model` is checked on every call. The **8B** (`swiss-ai/Apertus-v1.5-8B`, a community 4-bit GGUF, sha256-pinned) runs locally on CPU with its own θ = 16.73 (exploratory): on P2's unseen parliaments it finds 15 of 21 answer dates (70B 16), and the registered P2-H2 test over the rules gives 13 vs 0; its two-stage reader v2 cuts dates on answerless documents from 18/34 to 5/34 (P6; v2 51/67 vs v1 48/67; rules then v2 55/67 vs rules 54/67). **Recommendation:** `rules_only` unattended; for suggestions the 8B where no text may leave the machine, the 70B for accuracy on infrastructure the operator chooses. Review mode stops (exit 3) on a served build θ was not fitted on.

Cost (`results/report/cost_end_to_end.json`, one core, no GPU). Fetch, extraction and checks about 2.1 s per document plus 6.9 s per OCR page (about 527 hours for the whole export from outside OPD); the rules process 480 documents per second (0.5 CPU-hours for all 902,754 documents in OPD's export). Review mode: USD 0.59 per 1,000 residue documents on the 70B. The 8B takes 180 s per document on 4 vCPUs. For the whole export (about 569k residue documents, an upper bound) review mode would cost about USD 336 on the 70B or 28,400 machine-hours on the 8B; at ten times OPD's volume the rules need about 5 CPU-hours. Review

load per night (estimate): 18.2 answers a day in 2025 (28.6 in the busiest month) at residue share 0.63 give 11.5 documents, about 34 minutes on the 8B (54 in the busiest month).

4. Data and operations

Data. OPD bulk exports (snapshot 6 Oct 2026; CC BY 4.0, "Source: OpenParlData.ch"; OPD's API robots.txt disallows `/v1/`), Bern open data, Fedlex, parliament sites, fetched politely (≥ 1.2 s per host and process). `data/` and `results/` are CDLA-Permissive-2.0 and carry OPD's attribution. **Sovereignty.** No third-party processor by default; besides the public sources, Hugging Face once for the pinned 8B, and a review-model endpoint (Public AI, or the local 8B, where no text leaves the machine) and an alert relay only if the operator sets them. **Operations.** `make run` and the nightly unit run the image read-only, as a non-root uid, with `--cap-drop ALL`; PDFs are capped at 50 MB and 600 s. On GitHub runners: one real night under systemd (83 min, Bern list reproduced on live data), then **two consecutive real nights in the recommended Docker setup** (Actions run 38098822336): night 1 took 86 min and streamed 6.4 GB; night 2 took 6.6 min (12 bodies re-scanned), 0 alerts; the ledger-status bug that night 2 exposed is fixed and covered by a two-night test. **robots.txt:** we found, audited and fixed our own robots.txt bug; every fetch path now fails closed (disclosure: `docs/incidents.md`).

5. Results without a model: schema verdict, census, repair

Table 1. The 17 fields. *Class*: role split = one label covers several roles, measured on OPD's labels (`results/census/comparability.json`) or on the documents (P8, `results/p8/`); fragile = not under both P8 checks; shared = one v0.1 definition. *Source* of the split (committed results only): practice = parliaments work differently, the standard encodes the role; OPD = likely an OPD data or tagging error OPD can correct; both; open = the labels cannot tell practice from harmonisation. *Where it lives*: parliaments where OPD metadata carries it · carries it for part of the affairs · only the PDF · not in OPD's data (`results/census/matrix.json`).

field	class	source	evidence	where it lives (meta · mixed · PDF · none)
answer date	role split	both	decided, dispatched or registered; in 7 of 54 bodies the submission date	**metadata**: 53 · 1 · 0 · 0
procedural history	role split	open	35 event labels, several date roles	**metadata**: 78 · 9 · 1 · 1
type	role split	both	42 of 1,038 raw labels map to two types; P8: the instrument	partly: 61 · 24 · 2 · 2
procedural state	role split	open	32 labels ambiguous	partly: 41 · 27 · 18 · 3
decision outcome	role split	practice	3 labels ambiguous	partly: 7 · 31 · 33 · 6
submitter	role split	practice; OPD in GR	P8: sole, joint or group author	partly: 23 · 61 · 5 · 0
co-signatories	role split	practice	P8: includes authors of record	PDF only: 0 · 2 · 72 · 12
language	role split	OPD	P8: tag names the other language	partly: 14 · 53 · 20 · 2
addressed body	split, fragile	practice	P8: the council (Bellinzona)	partly: 12 · 10 · 54 · 10
government recommendation	split, fragile	both	P8: by stage	partly: 3 · 8 · 56 · 10
submission date	body-specific in 2	OPD	P8: Vernier, Lausanne	**metadata**: 89 · 0 · 0 · 0
answer-link status	shared	—	defined once in v0.1	**metadata**: 54 · 0 · 0 · 0
decision date	shared	—	defined once in v0.1	partly: 7 · 30 · 34 · 6
Q/A pairing	shared	—	defined once in v0.1	partly: 22 · 25 · 4 · 3
usable text	shared	—	defined once in v0.1	partly: 41 · 42 · 0 · 6
dispatch date	shared	—	defined once in v0.1	PDF only: 0 · 0 · 47 · 7
related affairs	shared	—	defined once in v0.1	PDF only: 0 · 0 · 76 · 13

4 fields are in OPD's metadata almost everywhere, 13 partly or only in the PDF. The recommendation's string check (0 of 183 raw labels map to two concepts) covers the labels OPD has harmonised (29.1% of all events carry no harmonised id). Three further *concepts* are body-specific: oral answers in question time (23.6% of question-time answers), executive business that answers no member's affair, and councils that publish only meeting documents (16 bodies; v0.1 marks affairs rebuilt from minutes `virtual`, P4).




Figure 2. Where each field comes from, per parliament. Orange = not in OPD's data for that parliament (the parliament may still publish it).

Cross-parliamentary question. Of the 91,268 interventions with a recorded government answer, 81.6% have answer text attached in OPD (the registered count); 82.3% also count the 592 answers OPD files under an agenda item of the affair (not sample-checked; they are among the 9,720, which add 9,128 beyond 82.3%); 85.6% with the repairs from what OPD already holds, 88.3% after the Bern relinks, 92.3% with the checked fetches (`results/report/r9_numbers.json`). Answer times are not one quantity: per group of parliaments (descriptive: each group holds different parliaments), the median is 112 days where OPD's "answer" date is the verified decision date (Bern, Ticino), 79 on a government's weekly sitting, 39 for diffuse, publication-like dates; in 7 parliaments the "answer" is the submission date.

Repair. *Bern*: of 3,532 answers the canton publishes OPD attaches 229 (6.5%), although 96.1% are in OPD and linkable without a model. 2,459 relink candidates = 2,421 that pass every check against OPD's own copy (affair number, heading, decision date = OPD's answer event [97.9, 98.9]) + 38 to review. The document `hash` is sha256(body_key + parent_type + url) (49,810 of 49,810 rows), so relinking changes each identifier and file URL unless OPD keeps the old one; the plan carries both values. *Source adapters* (`docs/adapters.md`): readers for 50 parliaments (27 yield counted rows) verify 6,613 answers by affair number or title, the parliament's answer formula and a date check, in three tiers (own date equals an OPD event 5,161; a printed date equals an OPD answer event 1,056; documented window 396). 2,177 of them are already in OPD with text under a heading the census lexicon does not list: the repair is a category on the document (`tag_answer`). Listed separately: 282 Jura answers matched by identity and wording only, and 917 review rows (214 of them recovered by Apertus into the tier `promoted_by_apertus`, §6). **Blind audit v3** (`results/repair/adapters/audit3/`): 200 counted rows and 60 decoys, shuffled into packets without the pipeline's verdict, the key hashed on GitHub first. Claude Opus judged 197/200 counted rows to be the executive's answer (Wilson 95.7% to 99.5%), and the date wrong or unsupported on 15. It rejected 60% of the failed decoys but only 1.5% of the counted rows; a second auditor from another vendor (Qwen-SEA-LION) accepted 200/200, and the two agree on 252 of 260 packets.

6. Evaluation: nine pre-registrations

Design. Each test froze code, prompts and θ by sha256 before any label was committed (P1's hypothesis script followed its labels, D4). Unit (P1, P2, P6): one document's answer date, strict. Arms on identical inputs: **rules**; **pointer**; **cascade** (rules, then the pointer on the residue); **naive** free generation, plain and null-allowed; trivial baselines. **Gold, no human labelling by design:** two blind agent annotators (Claude Opus, Sonnet), a third breaks ties, quotes verified by code, raw files committed; all 84 annotator sessions of P1–P7 ended before GitHub received their labels (`results/eval/annotation_sessions.json`). P1's rules were committed with its sample (D12), so P2 is the clean out-of-sample test of the rules.

Table 2. The nine tests, in registration order.

test	n	what it tests	registered result	note
P1	154 documents, parliaments with rules	answer date: rules vs Apertus	**partial**: H3 held; H1 null safety failed (7/90); H2 Branch B	rules alone 135/154, so no model by default
P2	62 documents, 15 parliaments without rules	rules transfer; pointer vs rules	**3 of 4 held**; H3 null safety failed (4/33)	pointer 24/29 dates, rules 2/29
P3	29 whole affairs, 10 parliaments	7 fields: metadata, rules, Apertus	**partial**: no field unattended; Apertus recall held, precision below	feasibility study (D3-5)
P3b	36 fresh affairs, 9 parliaments	replication of P3	**held**: replicated (S1, S2)	S2 lenient; type 35/36; addressed body 2/33
P4	120 agenda items, 6 sittings	affairs rebuilt from minutes	**partial**: H2, H4 held; H1, H3 failed	recall 99/120, precision 99/99
P5	40 fresh affairs, 10 parliaments	Q/A pairs, people, recommendation	**partial** tier (H1); H2, H5 held; H4 as rules vs free generation; H3 no gain	*not yet* when parliaments are resampled
P6	68 fresh documents, 8 parliaments	answer-date reader v2 vs free prompting	**no hypothesis held**	free prompt 62/68, v2 59/68
P7	478 review rows, 190 blind packets	Apertus as verifier of the review queue	**H1 holds** (120/120); H4 supported; H3 not supported	214 of 917 rows promoted
P8	66 fresh affairs, 11 parliaments	meaning of 7 fields v0.1 defines once	**none uniform**: 6 role split, 1 body-specific	5 robust; meaning measured for 11 of 17

Unattended (95% lower bound ≥ 0.80, document-level intervals): the rules' answer date where rules exist (P1, helped by right nulls: dates found 47/64), the type on whole affairs (P3b, 35/36), and in P5 question detection (recall 167/187, precision 167/175), the reasoning span (37/40) and co-signatory precision (101/103). **Cross-checks.** `Qwen-SEA-LION-v4-32B-IT` (AI Singapore) relabelled P1, P2, P6 and P7 blind: date κ 0.80, 0.87 and 0.86, P7's is-answer labels 185/190; no registered decision changes. Non-LLM checks: OPD's event matches 37 of 44 checkable P1 dates; P6: 10/10, every gold quote on its page (34/34). Holm over all 20 registered confirmatory tests of P1–P7: the 9 that held survive (`results/eval/posthoc_r8_multiplicity.json`); whole parliaments are resampled as well.

P1 arm (154 documents)	exact [95% CI]	answered: found /64	wrong printed date	invented	answerless dated /90
rules only (default)	**135/154 [81.5, 92]**	47	4	0	2
pointer	130/154 [77.9, 89.3]	46	16	0	6
cascade	139/154 [84.6, 94]	56	11	0	7
naive, null-allowed	134/154 [80.8, 91.4]	47	11	0	3
trivial: latest date, answer-typed docs	*131/154 [78.6, 89.8]*	*44*	*16*	*0*	*3*

P1: H1 null safety failed (the cascade dates 7 of 90 answerless documents, 6 of them council reports; upper bound 15.2% vs 10%); H2 gave Branch B (cascade alone right on 5, rules alone on 1, p = 0.22), so Apertus left the unattended path for an opt-in review suggestion (D6); H3 held (AUROC 0.969). The 8B cascade: 119/154, 25 of 90 answerless dated.

P2 arm (62 documents)	exact [CI]	answered: found /29 [CI]	wrong date	invented	answerless dated /33
rules only	35/62 [44.1, 68.1]	**2/29** [1.9, 22]	2	0	0
pointer	**53/62** [74.7, 92.2]	**24/29** [65.5, 92.4]	8	0	4
naive, null-allowed, re-parsed (D2-4)	54/62	24/29	7	1	3
trivial: latest printed date	*24/62*	*22/29*	*38*	*0*	*31*
trivial: latest date, answer-typed docs	*44/62*	*18/29*	*13*	*0*	*7*

P2: the rules collapse off their home layouts (47/64 → 2/29). H2 held: on all 62 documents the pointer beats the rules on 22 and loses on 4 ($p = 5.3 \times 10^{-4}$); resampling the 15 parliaments, the gain is [-0.02, 0.54], so it sits in a few parliaments. "Answerless" means no qualifying answer date: the pointer's 4 such dates all fall on documents that contain an answer but print no qualifying date; of the 25 with no answer at all it dates none (post hoc; with P6's v2 none of 53 across P2 and P6; P6's v1 dated 1 of 28). Against the free prompt with null allowed: ahead on 2, behind on 1. Against the best no-model baseline (post hoc): 53/62 vs 44/62. **By stratum** (post hoc, `results/eval/breadth_p1_p2.json`): the rules are exact on 17/22 to 21/22 documents in each of P1's seven language × level strata, scanned Ticino answers included (21/22, 11/12 dates found through OCR); on P2 the pointer finds answer dates in every language (DE 9/13, FR 10/11, IT 5/5).

P3/P3b/P4. Default (metadata + rules) on 29 affairs: type 27/29, answer date 22/27, 27/27 with Apertus suggestions. P3b replicated by its registered criteria; its answer date (C 20/35) fell below P3's interval, 3 wrong dates from a Luzern rule that overrode OPD's correct date (the product path now keeps OPD's date and flags the record); with Apertus 31/35. P4: 99 of 120 agenda items as virtual affairs, precision 99/99, no decision invented (0/36). **P5.** Rules-only pairing: precision 118/143 = 0.83, recall 118/176 = 0.67, *partial* with document-level intervals, *not yet* when parliaments are resampled (precision [0.66, 0.97]); Valais 0/11. H2: rules beat paragraph order 116:5. H4, read as rules vs free generation: 79:11 (the pointer never fired, H3). Recommendation 34/40 by rules; submitter rules 12/40, pointer 24/40, free generation 34/40.

P6 arm (68 documents, 34 answered)	exact	answered: found	answerless dated	printed nowhere
free prompt, null allowed	**62/68**	32/34	4/34	0
cascade v2 (rules, then v2)	60/68	31/34	5/34	0
v2	59/68	30/34	5/34	0
rules only	54/68	20/34	0/34	0
trivial: latest date, answer-typed docs	*51/68*	*25/34*	*8/34*	*0*
model-free cascade (post hoc)	*55/68*			*0*

P6 — reader v2 (an answer-present gate, then the gold guide's decision-before-letter-date rule). No registered hypothesis held: v2 vs free prompting 1:4 (p = 0.38); v2 dates 5/34 answerless documents (upper bound 30.1% vs 15%), all 5 on documents that contain an answer without a qualifying date; v2 vs v1 5:2 (p = 0.45). On all 68 documents cascade v2 beats the rules on 11 and loses on 5 (p = 0.21); the model-free cascade scores 55/68 (cascade v2 ahead on 5, behind on 0, p = 0.06).

P7 — Apertus as verifier of the review queue (`eval/prereg8/`, LOCK8 before the draw). Test frame: 478 eligible review rows outside every audit; 190 blind packets, gold A1 Opus / A2 Sonnet. H1 (primary): promotion precision 120/120, Wilson lower bound 96.9% ≥ 0.90: **holds**. H4: dated precision 95.8% vs 73.2% for a trivial exact-date match, +22.7 points [10.2, 34.3], weighted, as registered (unweighted +7.5): **supported**. H3: the rows free generation with a printed-date filter adds are 28/30 right: **not supported**. Base rate: 86.7% of eligible queue rows are answers, but only 40.9% are answers whose own date passes the rule, so the gain is the date check. *Post hoc* (`results/p7/`): the metric measures how often promotions are date-checkable, not the date picked. A model-free rule accepting any printed date of the same closed set reaches 76.2%: P7 +19.6 points [8.4, 30.9] (parliament-cluster [0.9, 42.8]); Apertus's chosen date is the gold date in 113/120 promotions, the rule's first passing date in 127/157. The rule recovers more rows with less precision (attainable recall 88% vs 66%; 369 vs 214 queue rows). Without Frauenfeld (109 of 214 promotions) 48/48. Applied to the whole queue, 214 of 917 rows go to the tier `promoted_by_apertus`, a pre-sorted batch for review.

P8 — what the shared fields mean (`eval/prereg9/`, LOCK9 before the draw). Blind annotators labelled what seven fields denote in the two documents OPD links per affair. Share in v0.1's meaning, pooled (parliament-cluster 95% interval): submitter 35/65 [33.3%, 75.0%], co-signatories 10/41 [6.8%, 46.3%], submission date 44/57 [57.1%, 91.8%], type 55/64 [76.2%, 95.3%], language 34/36 [83.3%, 100.0%], each verdict unchanged on agreed labels only and on Qwen's labels; addressed body (57/60) and recommendation (31/34) are fragile. Qwen's κ on the submitter, 0.24, is mostly interpretive: it calls the first of several equal authors the "first signatory" (18 affairs). Ticino's robots.txt disallows its documents, hence 11 parliaments.

What the tests say. Apertus earns its place on parliaments the rules were not written for (P2: 24/29 vs 2/29; P3: 27/27 vs 22/27 answer dates with its suggestions) and as a closed-set verifier with a date check (P7). **Provenance by construction:** no arm that picks from printed dates returned a date printed nowhere (P1, P2, P6), at accuracy close to Apertus asked freely with null allowed (P2 53 vs 54 of 62; P6 59 vs 62 of 68); the closed set adds a page, span and margin to every value. **Null safety** is left to the reviewer: the registered null-safety tests on the 70B failed (P1-H1, P2-H3, P6-H2), which is why the default runs no model.

7. Next steps, reproducibility, declarations

Next steps. Answer dates are tested in depth and Q/A pairs on 40 affairs; next come tables, annexes and images inside answers, and gold sets with federal documents and Italian in P6's design (P4 covers one commune). With OPD: its hash decision for the relinks and the 30-row spot-check kit (`results/opd_spotcheck/`); with the eCH group: `QAItem`, the five gaps and the meaning test for the six fields defined once. **Reproducibility.** `make run` (Docker, CPU, clean checkout) recomputes the census and the Bern join, re-derives the P1 rules arm from the source PDFs and the P1/P2 Apertus decisions from the model cache, replays P1–P8 from committed files (nine LOCKs verified), and runs the claims check (every claim recomputed and found where listed; every number in this summary bound to its claim by an anchor phrase). **Declarations.** Claude Code agents (Anthropic) wrote most code, documentation and the gold labels. Public AI (may route outside Switzerland) served evaluation only. Report CC-BY-4.0; standards in `docs/mapping.md`.