

ERRURS

F

R

-

T

S

MAGNET 2-DUALS - TRANSLES

```

import { pipe } from 'fp-ts/function';
import * as E from 'fp-ts/Either';

type State = E.Either<Error, Idle | Moving>
const initialState: State = pipe(idle(), E.right);

const reducer: Reducer<State, Action> = (state: State | undefined, action: Action) => {
  if (!state) return initialState //mandatory by Redux
  // ⚠️ `chain` is `flatMap` or `bind` name in fp-ts;
  // be carefull bind is js Function.prototype.bind ... naming are hard
  return E.chain(
    // 😞 TS inference is bad, you will often need to help the typer
    (state: Idle | Moving): E.Either<Error, Idle | Moving> => {
      switch (state.type) {
        case "idle": {
          // ⚠️ Redux action MUST be tagged on a `type` attribute
          switch (action.type) {
            case "face": return pipe(idle(), E.right); // idle () |> E.right
            case "start": return pipe(moving(), E.right);
            default: return pipe(new Error("Illegal Action from Idle"),
                                , E.left); // 😎
          }
        }
        case "moving": {
          switch (action.type) {
            case "stop": return pipe(idle(), E.right);
            default: return pipe(new Error("Illegal Action from Moving"),
                                , E.left); // 😎
          }
        }
      }
    }
  )(state)
}

```

Design simpliste pour exemple

Que faire quand le state est en erreur ?

Action Init?

Reinit auto ?

Conserver le state avant erreur ?

**Dans un state plus complexe,
on ne veut pas forcément tout
dans un Either : c'est ok!**

ERREURS

FP-TS

Design simpliste pour exemple

Que faire quand le state est en erreur ?

Action Init?

Reinit auto ?

Conserver le state avant erreur ?

**Dans un state plus complexe,
on ne veut pas forcément tout
dans un Either : c'est ok!**

ÉCOSYSTÈME REACT

NOTRE ENVIRONNEMENT DE TP

Une application plus complexe nécessite de pouvoir chaîner les actions et de gérer des actions asynchrone

Nous utiliserons:

- redux-loop qui implémente le pattern Elm dans une vision puriste
- fp-ts pour disposer des types Option et Either
- Fast Check pour les PBT

Interdiction d'utiliser l'état local !