

s Drone Payload Structure Design and Analysis

In this project, you are optimizing drone arm design, including geometry and material selection, to maximize payload capacity while ensuring structural integrity under motor-induced loads. You will use MATLAB to perform force balance analysis and finite element modeling to quantitatively support your design solution.

Use this Live Script as a template to get started on your project solution. You may include helper functions at the bottom of this document or as separate files. For a tutorial on how to use Live Scripts, check out this [video](#).

Suggested Tasks

1. Gather your starter assumptions and load the material properties into MATLAB.
2. Propose at least two drone arm designs
3. Perform a thrust-to-weight analysis to evaluate each of your designs across all material options. Your design must meet a minimum payload requirement and safety standards.
4. Perform finite element analysis across all design and material options.
5. Recommend a final design solution.

Table of Contents

Break Down the Problem	1
Task 1: Gather your starter assumptions and load material properties	2
Task 2: Propose at least two drone arm designs	3
Task 3: Perform thrust-to-weight analysis across all design and material options	6
Task 4: Perform finite element analysis across all design and material options	8
Interpretation of Results - Final Recommended Design Solution	19

Break Down the Problem

In the space below, define the problem statement:

The problem statement is defined as designing a quadcopter drone capable of maximizing payload capacity by proposing lightweight solutions that have structural integrity to withstand forces in flight while meeting safety requirements.

List the requirements, constraints, and success criteria for the project:

For this project we must:

- Propose to different drone arm designs.
- Perform thrust-weight-analysis for each design and material options.
- Our design must support a 0.5 kg payload and meet a thrust-to-weight ratio of at least 2:1.
- Perform finite element analysis.
- Propose final design recommendation.

What is your proposed solution?

Our proposed solution is a hollow tube design and a beam of trusses design to maximize our payload capacity while remaining lightweight. We will use MATLAB and CAD to perform analysis and create 3D models of our designs.

List the steps you will need to take to achieve your proposed solution:

- Create drawings with dimensions and key details.
- Write matlab function to test thrust-to-weight analysis to ensure safety.
- Draw 3D models in CAD with out proposed dimensions.
- Upload our STL files to matlab and run a FEA on both of our separate designs to compare results such as max stress, factor of safety, and max displacement.
- Make a final recommendation based on the results.

What challenges do you face in the process of achieving the solution?

The challenges we might face are understanding drone flight basics and correctly applying motor loads to our model in FEA, interpreting results and evaluating tradeoff between strength and weight in order to propose our final recommendation.

Task 1: Gather your starter assumptions and load material properties

Load the provided `droneArmMaterials.mat` file into MATLAB. This contains a data struct with the material properties for six different materials commonly used for drones (carbon fiber composite, aluminum alloy, fiberglass composite, PLA plastic, ABS plastic, and wood). For each material, you have been provided the following information:

- Density (ρ), in $\frac{\text{kg}}{\text{m}^3}$
- Young's Modulus (E) in Pa
- Poisson's ratio (ν), unitless
- Yield strength, in Pa
- Average cost per meter in US dollars

For this project, you can assume the following design parameters:

- Quadcopter drone with 4 motors and 4 propellers
- Each motor can provide up to 1kg thrust
- Acceleration due to gravity: $g = 9.81 \frac{\text{m}}{\text{s}^2}$
- Total weight of the drone components without the arms or the payload: 1kg

The breakdown of the weight of each drone component is as follow:

- Battery = 0.3kg
- Each motor = 65g, 4 motors = 0.26kg
- Each propeller = 10g, 4 propellers = 0.04 kg
- Each electronic speed controller = 30g, 4 electronic speed controllers = 0.12 kg
- Flight controller and electronics = 0.05kg
- Receiver/GPS = 0.03kg
- Drone frame (center body) excluding arms = 0.2kg

```
% ----- Load "droneArmMaterials.mat" -----
matPath = fullfile(pwd, 'data', 'droneArmMaterials.mat');
data = load(matPath);
materials = data.materials;

% ----- Drone Specifications -----
numMotors = 4; % Number of motors
numPropellers = 4; % Number of propellers
numElecContr = 4; % Number of electronic speed controllers (ESCs)
numArms = 4; % Number of frame arms
g = 9.81; % Acceleration due to gravity [m/s^2]

% ----- Mass Breakdown -----
thrustPerMotor = 1.0; % thrust of 1 motor [kg]
massBattery = 0.3; % mass of battery [kg]
massPerMotor = 0.065; % mass of 1 motor [kg]
massPerPropeller = 0.01; % mass of 1 propeller [kg]
massPerElecContr = 0.03; % mass of 1 ESC [kg]
massContr = 0.05; % mass of flight controller and electronics [kg]
massGPS = 0.03; % mass of receiver/gps [kg]
massCB = 0.2; % mass of center body excluding arms [kg]
massBase = 1.0; % total weight of the drone components without the arms or the
payload [kg]
```

Task 2: Propose at least two drone arm designs

Develop at least two distinct drone arm designs by drawing clear, neatly labeled sketches that show key geometric features, including:

- Overall shape (e.g. beam, tube, truss structure)
- Dimensions (length, width, thickness)
- Motor mount location
- Where the arm connects to the drone body

The two designs should be meaningfully different from each other (e.g. different geometries or structural strategies) and not just small variations of the same idea.

Navigate to the 'Insert' tab and insert pictures of your sketches in the space below (hand-drawn or digital). Include a short design description for each sketch that includes:

- Geometry (e.g. solid beam, hollow tube, beam with trusses)
- Why you chose this design
- How it might perform under load

Hollow Tube Design

material: carbon fiber composite (CFRP)
 $\rho = 1600 \text{ kg/m}^3$

notes:

- The outer diameter determines the structural stiffness and load capacity.
 - standard diameter range between 10mm and 40mm
- The inner diameter is the empty space inside the tube.
 - A larger inside diameter lowers the arm's weight and gives you a place to put the motor wires.
- The length is how long the arm needs to be so the propellers have enough room to spin safely.
- Thin Walls (0.5-1mm): Very lightweight. Best for racing drones.
- Medium Walls (1-2mm): Good balance of weight and strength. Best for standard commercial and camera drones.
- Thick Walls (2mm+): Highly durable and impact resistant. Best for industrial drones that need to carry heavy loads or survive tough environments.

1st trial of calculations:

thickness (t); $t = 2 \text{ mm}$

outer diameter (d_{out}); $d_{\text{out}} = 30 \text{ mm}$

inner diameter (d_{in}); $d_{\text{in}} = d_{\text{out}} - 2t = 30 \text{ mm} - 2(2 \text{ mm})$
 $d_{\text{in}} = 24 \text{ mm}$

cross sectional area (A); $A = \pi/4 (d_{\text{out}}^2 - d_{\text{in}}^2) = \pi/4 ((30 \text{ mm})^2 - (24 \text{ mm})^2)$
 $A = 81\pi \approx 254.5 \text{ mm}^2$

length (l); $l = 300 \text{ mm}$

volume (V); $V = A \cdot l = 81\pi \text{ mm}^2 \cdot 300 \text{ mm} = 24,300\pi \text{ mm}^3 \approx 7.6341 \times 10^{-5} \text{ m}^3$

carbon fiber density (ρ); $\rho = 1600 \text{ kg/m}^3$

mass (m); $m = V \cdot \rho = (7.63 \times 10^{-5} \text{ m}^3) \cdot (1600 \text{ kg/m}^3)$

$$m = 0.122 \text{ kg}$$

mass total of all 4 arms (m_{arms}); $m_{\text{arms}} = 4(0.122 \text{ kg})$

$$m_{\text{arms}} = 0.489 \text{ kg}$$

minimum payload of 0.5kg?

total mass w/o payload (m_{empty}); $m_{\text{empty}} = 1 \text{ kg} + 0.489 \text{ kg}$

$$m_{\text{empty}} = 1.489 \text{ kg}$$

total mass w/ payload (m_{tot}); $m_{\text{tot}} = 1.489 \text{ kg} + 0.500 \text{ kg}$

$$m_{\text{tot}} = 1.989 \text{ kg}$$


total thrust of all motors (F_{thrust}); $F_{\text{thrust}} = 11.0 \text{ kg}$

minimum payload of 0.5kg (✓)

$$\rightarrow 0.511 \text{ kg}$$

thrust-to-weight ratio of at least 2:1 (✓)

$$\rightarrow 4.0 : 1.989$$



VOLUME (from CAD): 22968.89 mm^3
 $= 2.297 \times 10^{-5} \text{ m}^3$

This drone arm design is a beam with trusses that is structured to withstand stresses while reducing weight. I chose this design for its simplicity and strength. The beam is thick enough to handle damage that may occur during flight and the truss cutouts ensure the arm doesn't bend with fatigue. The overall length and width matches common dimensions of drones with this arm design.

Task 3: Perform thrust-to-weight analysis across all design and material options

Write a MATLAB function that will perform a thrust-to-weight analysis across all design and material options. This analysis will help you evaluate which drone arm design and which material optimizes payload capacity while meeting suggested safety requirements.

- Your design must support a minimum payload of 0.5kg.
- Your design must meet a thrust-to-weight ratio of at least 2:1 to ensure safe and stable flight. This safety standard is widely used in drone design. Conceptually, it means that the drone's maximum thrust must be at least twice its weight. This ensures stable hovering and maneuvering with a safety margin. Note that the thrust-to-weight safety margin is a system-level safety standard for drone flight that is distinct from the structural safety factor of the drone arms (which you will evaluate later through finite element analysis).
- Your goal is calculate maximum payload capacity for each design and material option (i.e. what is the heaviest payload your drone design could carry while still allowing the drone to safely take off?)

Ensure that the results of your analysis can be readily interpreted, e.g. in the form of a summary table or plot.

Note: if you have two drone arm designs, the expected output should be 12 payload capacity estimates (2 designs across 6 materials options).

```

% ===== Geometry and Volume =====
% Design 1: Hollow Tube Design
dOuter = 0.030; % Outer diameter [m]
dInner = 0.024; % Inner diameter [m]
thickArm = 0.003; % Wall thickness [m]
lengthArm = 0.300; % Arm length [m]

crossAreaTube = (pi/4) * ((dOuter)^2-(dInner)^2); % Cross sectional area [m^2]
volHollowTube = crossAreaTube * lengthArm; % Total volume of 1 arm [m^3]

% Design 2: Truss Design
volTruss = 0.00002297; % Taken from CAD [m^3]

% ===== Setting up Structure Arrays =====
% Design 1: Hollow Tube Design
designs(1).Name = 'HOLLOW TUBE DESIGN RESULT TABLE';
designs(1).Volume = volHollowTube;

% Design 2: Truss Design
designs(2).Name = 'TRUSS DESIGN RESULT TABLE';
designs(2).Volume = volTruss;

% ===== Pre Allocated Arrays =====
for i = 1:numel(designs)
    volArm = designs(i).Volume;

    numMaterials = numel(materials); % The number of elements (materials) in
    "droneArmMaterials.mat" data file
    matNameArr = strings(numMaterials, 1); % Column array for material names
    densityArr = zeros(numMaterials, 1); % Column array for densities
    massArmArr = zeros(numMaterials, 1); % Column array for single arm masses
    massEmptyArr = zeros(numMaterials, 1); % Column array for empty drone masses
    massPayloadArr = zeros(numMaterials, 1); % Column array for max payload
    capacities
    passStatusArr = false(numMaterials, 1); % Boolean array for payload requirement
    check

    % ===== Payload Analysis Loop =====
    for j = 1:numMaterials
        matNameArr(j) = materials(j).name;
        densityArr(j) = materials(j).rho_kg_m3;
        massArmArr(j) = volArm * densityArr(j); % Mass of 1 arm [kg]
        massEmptyArr(j) = massBase + (massArmArr(j) * numArms); % Total empty drone
        mass [kg]
        massPayloadArr(j) = (thrustPerMotor * (numMotors / 2)) - massEmptyArr(j); %
        Max payload capacity [kg]
        passStatusArr(j) = massPayloadArr(j) >= 0.5; % Check if payload is minimum
        0.5 kg [true/false]
    end
% ===== Summary Result Table =====

```

```

matResultTable = table(matNameArr, densityArr, massArmArr, massEmptyArr,
massPayloadArr, passStatusArr, ...
    'VariableNames', {'Material', 'Density (kg/m^3)', 'Single Arm Mass (kg)',
'Empty Drone Mass (kg)', 'Max Payload (kg)', 'Pass'});
disp([designs(i).Name]);
disp(matResultTable);
fprintf('\n');
end

```

HOLLOW TUBE DESIGN RESULT TABLE

Material	Density (kg/m ³)	Single Arm Mass (kg)	Empty Drone Mass (kg)	Max Payload (kg)
"Carbon Fiber Composite (CFRP)"	1600	0.12215	1.4886	0.51
"Aluminum Alloy"	2700	0.20612	1.8245	0.17
"Fiberglass Composite (GFRP)"	1900	0.14505	1.5802	0.42
"PLA Plastic"	1250	0.095426	1.3817	0.61
"ABS Plastic"	1050	0.080158	1.3206	0.67
"Wood (Birch)"	600	0.045804	1.1832	0.83

TRUSS DESIGN RESULT TABLE

Material	Density (kg/m ³)	Single Arm Mass (kg)	Empty Drone Mass (kg)	Max Payload (kg)
"Carbon Fiber Composite (CFRP)"	1600	0.036752	1.147	0.85
"Aluminum Alloy"	2700	0.062019	1.2481	0.75
"Fiberglass Composite (GFRP)"	1900	0.043643	1.1746	0.82
"PLA Plastic"	1250	0.028712	1.1148	0.88
"ABS Plastic"	1050	0.024118	1.0965	0.90
"Wood (Birch)"	600	0.013782	1.0551	0.94

Task 4: Perform finite element analysis across all design and material options

Perform finite element analysis (FEA) across all design and material options to evaluate the structural safety factor of your drone arm design. To simplify the task, you will perform the FEA only on a single drone arm.

Using a CAD software of your choice, first create a 3D model of one drone arm for each of your designs. Be sure your model can be exported as a STEP or STL file for analysis in MATLAB.

- Recommended CAD software options: Tinkercad, Onshape, Fusion 360, Solidworks (most have free versions)

Import your model into MATLAB and perform FEA. In your FEA model, you should model and apply two loads to the drone arm: upward thrust force from the motor and downward weight of the motor.

- Helpful resources: [online tutorial](#), documentation for [Structural Mechanics](#) and [Partial Differentiation Equation Toolbox](#), and [example workflow](#)


For each design and material combination, you should report the overall maximum displacement, maximum stress, and factor of safety and include visualizations of the x-, y-, and z-displacement and Von Mises stress. Ensure that your results are presented for easy interpretation (e.g. present a table with numerical results, clearly labeled subplots for the visualizations).

- The factor of safety compares how strong a material is to how much stress it experiences, indicating whether a design is safe under the given loads. For this project use the equation: $FoS = \frac{\text{Material Yield Strength (Pa)}}{\text{Maximum von Mises Stress}}$. Yield strength indicates how much stress a given material can withstand before permanently deforming. Maximum von Mises stress (derived from your FEA model) is a measure of how much stress your design experiences under the applied loads.
- A typical engineering safety margin for FoS is ~1.5-2+
- This [example](#) demonstrates the plots you are asked to include in your results

```
% ===== Hollow Tube FEA =====
% ----- Load and Create 3D Simulation Model -----
stlPathTube = fullfile('models', 'drone_arm_tube.stl');
gmTube = fegeometry(stlPathTube);
gmTube = scale(gmTube, 0.001); % Converts millimeters to meters

tubeModel = femodel(AnalysisType = 'structuralStatic', Geometry = gmTube);


% ----- Plot Geometry and Face Labels -----
% Front View (shows F1)
figure;
pdegplot(tubeModel, FaceLabels = 'on', FaceAlpha = 0.5, FaceColor = 'blue'); %
Transparent faces (FaceAlpha = 0.5) to identify Face IDs
view(50, 18);
xlim([-0.03, 0.03]); ylim([-0.2, 0.13]); zlim([-0.02, 0.04]); camzoom(1.19);
title('Tube Drone Arm with Face Labels');
```



```
% Rear View (shows F2)
figure;
pdegplot(tubeModel, FaceLabels = 'on', FaceAlpha = 0.5, FaceColor = 'blue');
```

```
view(-130, 20); camzoom(1.20);
xlim([-0.04, 0.04]); ylim([-0.2, 0.13]); zlim([-0.04, 0.04]);
title('Tube Drone Arm with Face Labels, Rear View');
```

Tube Drone Arm with Face Labels, Rear View



```
% ----- Boundary Conditions -----
tubeModel.FaceBC(1) = faceBC(Constraint = "fixed"); % Fix face connecting to drone
body (Face 1)


thrustForce = thrustPerMotor * g; % Upward thrust from motor [N]
motorWeight = -(massPerMotor * g); % Downward weight due to motor [N]
netForce = thrustForce + motorWeight; % Net upward force along +Z [N]
netTractionTube = netForce / crossAreaTube; % Convert force to surface traction [N/
m^2]

tubeModel.FaceLoad(2) = faceLoad(SurfaceTraction = [0; 0; netTractionTube]); %
Apply net surface load to Face 2 (face where motor mounts)

% ----- Generate Mesh -----
tubeModel = generateMesh(tubeModel);

figure;
pdemesh(tubeModel);
title("Hollow Tube Mesh, Quadratic Tetrahedral Elements");
view(50, 18); xlim([-0.03, 0.03]); ylim([-0.2, 0.13]); zlim([-0.02, 0.04]);
axis on; grid on; camzoom(1.19);
```

Hollow Tube Mesh, Quadratic Tetrahedral Elements



```
% ----- Pre Allocated Arrays -----
dispMaxTubeArr = zeros(numMaterials, 1); % Column array for max displacement
stressMaxTubeArr = zeros(numMaterials, 1); % Column array for max stress
yieldStrArr = zeros(numMaterials, 1); % Column array for yield strength
fosTubeArr = zeros(numMaterials, 1); % Column array for Factor of Safety

% ----- Loop Through All Materials -----
for j = 1:numMaterials
    matNameArr(j) = materials(j).name;
    yieldStrArr(j) = materials(j).yieldStrength_Pa;

    tubeModel.MaterialProperties = materialProperties( ...
        YoungsModulus = materials(j).E_Pa, ...
        PoissonsRatio = materials(j).nu, ...
        MassDensity = materials(j).rho_kg_m3);

    resultTube{j} = solve(tubeModel); % Solve FEA


    uxTube = resultTube{j}.Displacement.ux; % Displacement along x-axis
    uyTube = resultTube{j}.Displacement.uy; % Displacement along y-axis
    uzTube = resultTube{j}.Displacement.uz; % Displacement along z-axis

    dispMagTube = sqrt(uxTube.^2 + uyTube.^2 + uzTube.^2); % Magnitude of
displacement [m]
    dispMaxTubeArr(j) = max(dispMagTube);
    stressMaxTubeArr(j) = max(resultTube{j}.VonMisesStress);
    fosTubeArr(j) = yieldStrArr(j) / stressMaxTubeArr(j);
end
```

```
% ----- Visualization Plots for Carbon Fiber Composite
```


```
% X-Displacement
```

```
figure;  
pdeplot3D(resultTube{1}.Mesh, ColorMapData = resultTube{1}.Displacement.ux);  
title('x-displacement (m)');  
colormap('jet');
```




```
% Y-Displacement
```


```
figure;  
pdeplot3D(resultTube{1}.Mesh, ColorMapData = resultTube{1}.Displacement.uy);  
title('y-displacement (m)');  
colormap('jet');
```



```
% Z-Displacement
figure;
pdeplot3D(resultTube{1}.Mesh, ColorMapData = resultTube{1}.Displacement.uz);
title('z-displacement (m)');
colormap('jet');
```



```
% Von Mises Stress
figure;
pdeplot3D(resultTube{1}.Mesh, ColorMapData = resultTube{1}.VonMisesStress);
title('Von Mises Stress (Pa)');
colormap('jet');
```



```
% ----- Hollow Tube FEA Table -----
feaResultTableTube = table(matNameArr, dispMaxTubeArr, stressMaxTubeArr,
yieldStrArr, fosTubeArr, ...
    'VariableNames', {'Material', 'Max Displacement (m)', 'Max Stress (Pa)', 'Yield
Strength (Pa)', 'Factor of Safety'});
disp('HOLLOW TUBE FEA RESULTS');
```

HOLLOW TUBE FEA RESULTS


```
disp(feaResultTableTube);
```

Material	Max Displacement (m)	Max Stress (Pa)	Yield Strength (Pa)	Factor of Safety
"Carbon Fiber Composite (CFRP)"	5.4872e-05	1.8766e+06	6e+08	319.73
"Aluminum Alloy"	5.5613e-05	1.8947e+06	2.75e+08	145.14
"Fiberglass Composite (GFRP)"	0.00015373	1.8663e+06	3e+08	160.74
"PLA Plastic"	0.0010951	1.9167e+06	6e+07	31.30
"ABS Plastic"	0.0019172	1.9089e+06	4e+07	20.95
"Wood (Birch)"	0.00038343	1.9089e+06	8e+07	41.92


```
fprintf('\n');
% ===== TRUSS ARM FEA =====
% ----- Load and Create 3D Simulation Model -----
stlPathTruss = fullfile('models', 'Drone arm (truss) v2.stl');
gmTruss = fegeometry(stlPathTruss);
gmTruss = scale(gmTruss, 0.001);
trussModel = femodel(AnalysisType = 'structuralStatic', Geometry = gmTruss);

% ----- Plot Geometry -----
% Front View (shows F1)
figure;
pdegplot(trussModel, 'FaceLabels', 'on', 'FaceAlpha', 0.5, FaceColor = 'blue');
```

```
title('Truss Arm with Face Labels');  
xlabel('x'); ylabel('y'); zlabel('z'); grid on;  
xlim([-0.04 0.22]); ylim([-0.04 0.03]); zlim([-0.05 0.05]); view([30 15]);
```



```
% Rear View (shows F2)
figure;
pdegplot(trussModel, 'FaceLabels', 'on', 'FaceAlpha', 0.7, FaceColor = 'blue');
title('Truss Arm with Face Labels, Rear View');
xlabel('x'); ylabel('y'); zlabel('z'); grid on;
xlim([-0.04 0.22]); ylim([-0.04 0.03]); zlim([-0.05 0.05]); view([173.1313 9.0246]);
```



```
% ----- Boundary Conditions -----
```

```

trussModel.FaceBC(33) = faceBC(Constraint = 'fixed'); % Fix face connecting to
drone body (Face 33)


crossAreaTruss = 0.02124756; % Taken from CAD [m^2]
netTractionTruss = netForce / crossAreaTruss;

trussModel.FaceLoad(2) = faceLoad(SurfaceTraction = [0; 0; netTractionTruss]); %
Apply net surface load to Face 2 (face where motor mounts)

% ----- Generate Mesh -----
trussModel = generateMesh(trussModel);

figure;
pdemesh(trussModel);
title("Mesh with Quadratic Tetrahedral Elements");
view(50, 18); axis on; grid on; camzoom(1.19);
xlim([-0.04 0.22]); ylim([-0.04 0.03]); zlim([-0.05 0.05]); view([30 15]);

```



```

% ----- Pre Allocated Arrays -----
dispMaxTrussArr = zeros(numMaterials, 1); % Column array for max displacement
stressMaxTrussArr = zeros(numMaterials, 1); % Column array for max stress
fosTrussArr = zeros(numMaterials, 1); % Column array for Factor of Safety

% ----- Loop Through All Materials -----
for j = 1:numMaterials
    matNameArr(j) = materials(j).name;
    yieldStrArr(j) = materials(j).yieldStrength_Pa;

    trussModel.MaterialProperties = materialProperties( ...
        YoungsModulus = materials(j).E_Pa, ...
        PoissonsRatio = materials(j).nu, ...

```

```

    MassDensity = materials(j).rho_kg_m3);


    resultsTruss{j} = solve(trussModel); % Solve FEA

    uxTruss = resultsTruss{j}.Displacement.ux; % Displacement along x-axis
    uyTruss = resultsTruss{j}.Displacement.uy; % Displacement along y-axis
    uzTruss = resultsTruss{j}.Displacement.uz; % Displacement along z-axis

    dispMagTruss = sqrt(uxTruss.^2 + uyTruss.^2 + uzTruss.^2); % Magnitude of
displacement [m]
    dispMaxTrussArr(j) = max(dispMagTruss);
    stressMaxTrussArr(j) = max(resultsTruss{j}.VonMisesStress);
    fosTrussArr(j) = yieldStrArr(j) / stressMaxTrussArr(j);
end

% ----- Visualization Plots for Carbon Fiber Composite
-----
figure;
pdeplot3D(resultsTruss{1}.Mesh, ColorMapData = resultsTruss{1}.Displacement.ux);
title('x-displacement (m)');
colormap('jet');


```




```

figure;
pdeplot3D(resultsTruss{1}.Mesh, ColorMapData = resultsTruss{1}.Displacement.uy);
title('y-displacement (m)');
colormap('jet');


```



```
figure;
pdeplot3D(resultsTruss{1}.Mesh, ColorMapData = resultsTruss{1}.Displacement.uz);
title('z-displacement (m)');
colormap('jet');
```



```
figure;
pdeplot3D(resultsTruss{1}.Mesh, ColorMapData = resultsTruss{1}.VonMisesStress);
title('Von Mises Stress (Pa)');
colormap('jet');
```



```
% ----- Truss FEA Table -----
feaResultTableTruss = table(matNameArr, dispMaxTrussArr, stressMaxTrussArr,
yieldStrArr, fosTrussArr, ...
    'VariableNames', {'Material', 'Max Displacement (m)', 'Max Stress (Pa)', 'Yield
Strength (Pa)', 'Factor of Safety'});
disp('TRUSS FEA RESULTS');
```

TRUSS FEA RESULTS

```
disp(feaResultTableTruss);
```

Material	Max Displacement (m)	Max Stress (Pa)	Yield Strength (Pa)	Factor of Safety
"Carbon Fiber Composite (CFRP)"	1.8531e-05	1.5005e+06	6e+08	399.87
"Aluminum Alloy"	1.8557e-05	1.4883e+06	2.75e+08	184.78
"Fiberglass Composite (GFRP)"	5.228e-05	1.5088e+06	3e+08	198.87
"PLA Plastic"	0.00036031	1.476e+06	6e+07	40.65
"ABS Plastic"	0.00063392	1.4801e+06	4e+07	27.02
"Wood (Birch)"	0.00012678	1.4801e+06	8e+07	54.04

```
fprintf('\n');
```

Interpretation of Results - Final Recommended Design Solution

Using the results of your thrust-to-weight analysis and finite element analysis, recommend a final drone arm design that meets all required constraints. Your recommendation should clearly identify the selected design (arm geometry and material choice), make use of quantitative results to justify your decisions, demonstrate that the design meets the constraints, explain the trade-offs considered, and include comparisons to alternative designs.

What are some limitations of your work?

What are practical next steps?