

Loading the data

In [1]:

```
# importing required libraries
import pandas as pd
```

In [2]:

```
#Loading the data
data = pd.read_csv('titanic_train.csv')
data.head()
```

Out[2]:

	PassengerId	Survived	Pclass	Name	Sex	Age	SibSp	Parch	Ticket	Fare	Cabin	Embarked
0	1	0	3	Braund, Mr. Owen Harris	male	22.0	1	0	A/5 21171	7.2500	NaN	S
1	2	1	1	Cumings, Mrs. John Bradley (Florence Briggs Th...)	female	38.0	1	0	PC 17599	71.2833	C85	C
2	3	1	3	Heikkinen, Miss. Laina	female	26.0	0	0	STON/O2. 3101282	7.9250	NaN	S
3	4	1	1	Futrelle, Mrs. Jacques Heath (Lily May Peel)	female	35.0	1	0	113803	53.1000	C123	S
4	5	0	3	Allen, Mr. William Henry	male	35.0	0	0	373450	8.0500	NaN	S

Missing Values

In [3]:

```
#missing values in the data
data.isnull().sum()
```

Out[3]:

```
PassengerId      0
Survived          0
Pclass           0
Name             0
Sex              0
Age             177
SibSp            0
Parch            0
Ticket           0
Fare             0
Cabin           687
Embarked         2
dtype: int64
```

- Age and Cabin have a very high number of missing values
- Embarked has very low number of missing values

Deleting Data points with missing values

In [13]:

```
# Age variable without missing values treatment
data['Age'].head(6)
```

Out[13]:

```
0    22.0
1    38.0
2    26.0
3    35.0
4    35.0
5     NaN
Name: Age, dtype: float64
```

In [12]:

```
# dropping all rows with missing values

data_row_del = data.dropna(axis=0)
data_row_del['Age'].head(6)
```

Out[12]:

```
1    38.0
3    35.0
6    54.0
10   4.0
11   58.0
21   34.0
Name: Age, dtype: float64
```

- Have deleted rows, if any one column/ feature has missing values in that row

In [6]:

```
# shape before and after removing missing values

data.shape, data_row_del.shape
```

Out[6]:

```
((891, 12), (183, 12))
```

- Significant loss of information
- Only three columns had missing values

Deleting columns with missing values

In [7]:

```
## isnull with ratio  
  
(data.isnull().sum())/891
```

Out[7]:

```
PassengerId    0.000000  
Survived        0.000000  
Pclass          0.000000  
Name            0.000000  
Sex             0.000000  
Age            0.198653  
SibSp           0.000000  
Parch           0.000000  
Ticket          0.000000  
Fare            0.000000  
Cabin           0.771044  
Embarked        0.002245  
dtype: float64
```

In [8]:

```
data.head(10)
```

Out[8]:

	PassengerId	Survived	Pclass	Name	Sex	Age	SibSp	Parch	Ticket	Fare	Cabin	Embarked
0	1	0	3	Braund, Mr. Owen Harris	male	22.0	1	0	A/5 21171	7.2500	NaN	S
1	2	1	1	Cumings, Mrs. John Bradley (Florence Briggs Th...)	female	38.0	1	0	PC 17599	71.2833	C85	C
2	3	1	3	Heikkinen, Miss. Laina	female	26.0	0	0	STON/O2. 3101282	7.9250	NaN	S
3	4	1	1	Futrelle, Mrs. Jacques Heath (Lily May Peel)	female	35.0	1	0	113803	53.1000	C123	S
4	5	0	3	Allen, Mr. William Henry	male	35.0	0	0	373450	8.0500	NaN	S
5	6	0	3	Moran, Mr. James	male	NaN	0	0	330877	8.4583	NaN	Q
6	7	0	1	McCarthy, Mr. Timothy J	male	54.0	0	0	17463	51.8625	E46	S
7	8	0	3	Palsson, Master. Gosta Leonard	male	2.0	3	1	349909	21.0750	NaN	S
8	9	1	3	Johnson, Mrs. Oscar W (Elisabeth Vilhelmina Berg)	female	27.0	0	2	347742	11.1333	NaN	S
9	10	1	2	Nasser, Mrs. Nicholas (Adele Achem)	female	14.0	1	0	237736	30.0708	NaN	C

In [9]:

```
# dropping all columns with missing values

data_col_del = data.dropna(thresh = 500, axis=1)
data_col_del.head()
```

Out[9]:

	PassengerId	Survived	Pclass	Name	Sex	Age	SibSp	Parch	Ticket	Fare	Embarked
0	1	0	3	Braund, Mr. Owen Harris	male	22.0	1	0	A/5 21171	7.2500	S
1	2	1	1	Cumings, Mrs. John Bradley (Florence Briggs Th...	female	38.0	1	0	PC 17599	71.2833	C
2	3	1	3	Heikkinen, Miss. Laina	female	26.0	0	0	STON/O2. 3101282	7.9250	S
3	4	1	1	Futrelle, Mrs. Jacques Heath (Lily May Peel)	female	35.0	1	0	113803	53.1000	S
4	5	0	3	Allen, Mr. William Henry	male	35.0	0	0	373450	8.0500	S

In [10]:

```
# shape before and after removing missing values

data.shape, data_col_del.shape
```

Out[10]:

((891, 12), (891, 11))

- A better way to deal with missing values without loss of information?