

PRODUCTION READINESS REPORT

Default App Init and Registry Bootstrap

Pushed CLI, registry-directory, and kit registry changes summarized for production review.

May 18

DATE

100%

PASS RATE

81

INIT FILES

0

MISSING FILES

Executive Summary

Decision

Default interactive init should install the lean layout/app wrapper and only the shared runtime files required for that wrapper to compile and run.

Production Meaning

The bootstrap is smaller and more predictable. Real UI components and asset-heavy choices install only when the user explicitly selects them.

What Should Install by Default

Default	Items	Reason
YES	Lean layout/app wrapper: <code>app.dart</code> , <code>shadcn_ui.dart</code> , and <code>component_theme_global_configs.dart</code> .	Users need a working app shell immediately after init.
YES	Shared runtime support: localization base, theme, overlay, constants, and required utilities.	Runtime dependencies of <code>ShadcnApp</code> , not optional UI components.
NO	<code>layout/scaffold</code> , <code>display/divider</code> , and utility localization component folders.	They are real components and should be installed when explicitly requested.
NO	Font and icon assets when the user presses Enter at the optional prompt.	Prevents silent app bundle growth during init.

Before vs Now

Before

The `layout/app` component exported `scaffold/divider` symbols and declared dependencies on `scaffold`, `divider`, and `shadcn_localizations`. `Init` could therefore pull more UI surface than a `bootstrap` command should.

Now

`layout/app` is a lean wrapper with no component dependencies. The registry `init` action copies only wrapper files plus shared runtime support required by `ShadcnApp`.

Changed Files and Effects

Repo	Files / Area	What changed	Effect
Kit	<code>layout/app/app.dart</code>	Removed <code>scaffold</code> and <code>divider</code> exports.	The app wrapper no longer exposes unrelated component APIs by default.
Kit	<code>layout/app/meta.json</code> <code>components.json</code>	Removed <code>scaffold/divider/localization</code> component dependencies; kept required shared dependencies.	Installing app no longer cascades into unrelated component installs.
Registry Directory	<code>registries/registries.json</code>	Added explicit app wrapper copy action and overlay runtime files; removed localization extension from default <code>init</code> .	Interactive <code>init</code> creates the app shell without extra UI components or extension helpers.
CLI Reports	<code>qa_reports/default-app-init...</code>	Added manual QA evidence and this summary report.	The change is auditable without digging through terminal logs.

Verification Flow

1. Fresh Project Created a clean Flutter project so previous local files could not hide missing output.	2. Interactive Init Ran local CLI against local registry-directory and kit registry, accepted defaults, skipped optional assets.	3. Assertions Checked required files, checked forbidden files, analyzed generated app code, and validated the registry.
---	--	---

QA Scorecard

Check	Result	Evidence
JSON syntax	PASS	Kit app manifest, aggregate manifest, and registry-directory JSON passed jq.
Interactive init	PASS	Default paths accepted, optional assets skipped, init completed with 81 files and 1 directory.
Forbidden output	PASS	No scaffold, divider, localization-extension, or font asset output appeared in the default install.
Generated app analysis	PASS	flutter analyze lib reported no issues after using ShadcnApp.
Registry validation	PASS	validate --json: 133 components, 1834 files, 0 missing dependencies, 0 missing files.

Pushed Branch Evidence

Repository	Branch	Commit	Summary
flutter_shadcn_kit	branch-v1-default-app-init	2b179e5b	Make default app bootstrap lean: 3 files changed, 4 insertions, 19 deletions.
registry-directory	branch-v1-registry-directory-minimal-init	88026bd	Install lean app wrapper during init: 1 file changed, 36 insertions, 2 deletions.
flutter_shadcn_cli	branch-v1-default-app-init-report	c7d647a	Add default app init QA report: 1 file changed, 115 insertions.

Final Result

The default init path is now a controlled bootstrap. It gives users a working shadcn app wrapper and required shared runtime, while keeping optional assets and real UI components out until explicitly selected or installed.