


RB 100 RL-E

Core drill dimensions	Ø 12.0 - 100.0 mm / Ø 20.0 - 50.0 mm (cutting depth 110 mm)
Cutting depth	50.0 mm / 110.0 mm
Twist drill	Ø 1.0 - 16.0 mm with drill chuck Up to Ø 32.0 mm with MT3 DIN 345
Counterboring	Ø 10.0 - 55.0 mm
Tapping	with tapping chucks: Up to M30 with tapping attachment: Up to M30
Arbors	MT3
Stroke	245 mm
Height adjustment	116 mm
4-speed gearbox	right / left 1. Step 50 - 150 rpm 2. Step 75 - 230 rpm 3. Step 100 - 310 rpm 4. Step 160 - 490 rpm
Power consumption	2,500 W (230 V) 2,400 W (110 V)
Voltage	230 V 50/60 Hz 110 V 50/60 Hz
Magnetic adhesion strength	20.000 N
Tool force (10 mm)	4.000 N
Magnetic base	92 x 238 mm, 30° adjustable right and left, 10 mm front and back
Weight	28.0 kg

Motor	
Smooth start	✓
Full-wave control electronics	✓
Right/left run	✓
Overload protection	✓
Oil bath gearbox	✓
Mech. Slip clutch	✓
Slides	
Infinitely adjustable	✓
Operation	
Soft-touch grips	✓
Membrane keyboard	✓
Magnet	
Metal rings	✓

Made in Germany ✓

Scope of delivery

- Metal core drilling machine RB 100 RL-E
- Coolant device
- MT3 tool holder with internal cooling
- Carrying case
- Chip hook
- Seat belt
- Drill spray
- **incl. 1 core drill free**



MADE IN GERMANY

Prod.-No.

ALFRA Rotabest® RB 100 RL-E	230 Volt	18634
ALFRA Rotabest® RB 100 RL-E	110 Volt	18634.110