

Panasonic

Welding Machine
Robot
Laser Welding System

Thyristor-controlled CO₂/MAG Welding Machine

KR2 Series

Popular Model with Outstanding Performance and Wide Application

- Non-remote control cable design
- Convincing high reliability
- Good welding performance
- Various kinds of protection functions, convenient functions and good expandability.



350KR2



200KR2



500KR2

Panasonic pursues Only one in welding

● Non-remote control cable design

By carrying the remote controller on the wire feeder and improvement of control circuit, the original two pieces of cable was integrated to one piece. This realized light weight, improved mobility and decreased wire breaking trouble.

● Convincing high reliability

- High insulation strength (Class H), high temperature resistance and good dust proof structure are adopted in main transformer and reactor.
- IP (International Protection) class of enclosure is IP21S and it effectively prevents the affection and interference of the main circuit to the control circuit. And moisture-proof, drip-proof and dust-proof structure enables the operation under adverse circumstances.

The special patented technology preventing the damage of main transformer further improves the safety performance and reliability of the machine.

● Good welding performance

- KR2 adopts the special control circuit which realizes low spatter welding in short circuit transfer and spray transfer of CO₂/MAG welding.
- The arc starting circuit ensures high rate of success of arc start, which reaches to almost 100% under any operating mode within the technical specifications. It is also possible to be equipped with various automatic welding systems.

● Various kinds of protection functions, convenient functions and good expandability.

- Overheat protection
- Under-voltage protection
- Output over-current protection
- Lighting-proof circuit
- Adjustable burn-back time
- Pre-flow on-off selection
- Current detection terminal for peripheral equipment
- Individual and Simple Unitary mode

● Specifications

Model		YD-200KR	YD-350KR	YD-500KR
Control method	—	Thyristor		
Input power source frequency	Hz	50/60		
Rated input capacity	KVA/ KW	7.6/6.5	18.1/16.2	31.9/28.1
Rated duty cycle	%	60	50	60
Output current range	A	50~220	60~380	60~550
Crater current range	V	16.5~25	17~33	17~41.5
Crater voltage range	A	50~220	60~380	60~550
Output voltage range	V	16.5~25	17~33	17~41.5
Method of welding	—	Individual/Unitary		
Enclosure protection class	—	IP21S		
Insulation class	—	H		
Cooling mode	—	Forced air cooling		
Applicable welding wire type	—	Solid / FCW		
Applicable welding wire diameter	mm	Solid. 8/1.0/1.2		Solid 1.2/1.4/1.6
	mm	FCW 1.2		FCW 1.2/1.4/1.6
Overall dimensions (W×D×H)	mm	376×675×747		436×675×762
Mass	kg	89	117	158
Wire feeder		YW-20KB3	YW-35KB3	YW-50KB3
Applicable welding wire diameter	mm	0.8/1.0/(1.2)		1.2/1.6
Length of cable	m	1.8		
Welding torch		YT-20CS4	YT-35CS4	YT-50CS4
Rated current	A	200	350	500
Applicable welding wire diameter	mm	0.8/1.0/(1.2)	(0.8)/1.0/1.2	1.2/1.6
Length of torch cable	m	3		
Gas regulator		YX-25CD1		

 **Safety precautions** ● Before attempting to use any welding product, always read the manual to ensure correct use.

Panasonic®

Panasonic Welding Systems(Tangshan)Co.,Ltd.
Tel: (0315) 3206066 3206060 Fax: (0315) 3206018
Service hotline: (0315) 3206016 4006125816
Technique consulting: (0315)3206012
Website: <http://pwst.panasonic.cn>
E-mail: sales@tsmi.cn

The color is subject to be different to the real product. The specifications are subject to change without notice.
Advertiser: Panasonic Welding Systems (Tangshan) Co., Ltd.
Address: No.9 Qingnan Road, New & Hi-tech Development Zone, Tangshan, Hebei, China
Printed by Tangshan October Printing Co., Ltd.
Address: No.2 Tanggu Road, Tangshan, Hebei, China

Printed in May.2016

