

Welding Cable

| Double Insulated | Extra Flexible

| Orange & Black Jacket

• 10 Sq. mm. to 400 Sq. mm • 600 Volts

• -30°C to +90°C

FEATURES.....

- Based on CENELEC HD 22-6 31, VDE 0282, IEC 245-6, IS 473, BS 638-4
- Outstanding toughness & durability
- High resistance to cuts, tears & abrasion
- Resistance to oil, solvents and chemicals
- Excellent ozone and weather resistant
- Fire Retardant

APPLICATIONS.....

- **Welding:** Designed for the secondary (high current) connection to automatic or hand - held metal arc welding electrodes. It is suitable for flexible use under rugged conditions, on assembly lines and conveyor systems, in machine tool and automatically operated line and spot welding machines.
- **Power:** Earthings / return leads, power feeds to electrolytic plating process, Busbar connection, transformers, generators, aircraft servicing equipments etc.

CONSTRUCTION.....

Conductor: High conductivity, bare annealed copper flexible conductor.

Sheath: Double Sheathed with a specially developed Thermoplastic Elastomeric (TPR/TPE)

Orange / Black Coloured

VOLATGE DROP.....

When total cable lengths in excess of 15 mtrs. Are involved, it may be necessary to use cables of larger cross section to ensure that the voltage drop is not excessive and welding currents is maintained at adequate levels.



An ISO 9001:2008 Company



CURRENT RATINGS.....

The maximum current ratings of flexible welding cables for different duty cycles are based on an ambient air temperature of 25°C and a maximum conductor temperature of 90°C. The percentages duty cycles given in the table are based on a cycle time of 5 minutes. The typical duty cycles for various welding processes and applications are as follows:

- Automobile Welding : up to 100%
- Semi-automatic welding : 30% to 85%
- Manual Welding : 0% to 60%
- Very intermittent or Occasional Welding : up to 20%

sqmm	Nominal insulation thickness	Nominal sheath thickness	Overall cable diameter		Max conductor resistance at 20°C	Current rating					
			Lower limit	Upper limit		Welding applications					Non Welding Application
						Duty Cycle					
						100%	85%	60%	30%	20%	
mm	mm	mm	mm	mm	Ω/km	amp	amp	amp	amp	amp	amp
10	1.2	1.8	7.8	10	1.91	105	115	135	190	235	110
16	1.2	1.9	9	11.5	1.21	135	145	175	245	302	138
25	1.4	2	10	13	0.780	180	195	230	330	402	187
35	1.4	2.2	11.5	14.5	0.554	225	245	290	410	503	233
50	1.6	2.4	13	17	0.386	285	310	370	520	637	295
70	1.6	2.6	15	19	0.272	355	385	460	650	794	372
95	1.8	2.8	17.5	21.5	0.206	430	470	560	790	961	449
120	1.8	3	19.5	24	0.161	500	540	650	910	1118	523
150	2	3.2	21.5	26	0.129	580	620	740	1040	1297	608
185	2.2	3.4	23	29	0.106	660	715	850	1200	1476	690
240	2.4	3.5	27	32	0.0801	710	770	916	1296	1587	744
300	2.6	3.6	30	35	0.0641	800	850	1035	1450	1790	840
400	2.8	3.8	33	39	0.0486	925	1000	1195	1690	2070	970

Ambient temperature °C	20°	25°	30°	35°	40°	45°	50°	55°	60°	65°
Rating Factor	1.04	1.00	0.96	0.91	0.87	0.82	0.76	0.69	0.64	0.57

* Customisation is available upon request: Colour of Sleeve; Size of Cable; Printing