

NE697: Introduction to Geant4

C++ Geant4 Intro

October 5th, 2021
Dr. Micah Folsom




THE UNIVERSITY OF
TENNESSEE
KNOXVILLE



Today's Agenda

- Administrative items?
- Assignment 3 solution
- Do we need more C++ practice?
- exampleB1 detailed breakdown

Assignment 3



C++ to Revisit

- Is there anything you want me to cover again?
- More demos or just more practice?
 - Maybe more assignments, then we spend some chunk of class time working and discussing? So kind of like a lab class...
- Debugging demo session – common errors/issues that people encountered?

Assignment 4

- Expand MC1D
 - New interaction: “scattering”, skip 1 unit
 - 5 command-line args instead of 3
 - Scatter probability (skip one unit)
 - Start position on the track
 - Isotropic source – particles can go either direction (50/50)
 - Update .csv to contain type of interaction (“a”, “s”)
- ...or something else? A different program? A few smaller programs?

Geant4 Resources

- Application Developer's Guide
 - <https://geant4-userdoc.web.cern.ch/UsersGuides/ForApplicationDeveloper/html/index.html>
 - **Read this!!!**
- Doxygen documentation (source code browsing)
 - <https://geant4.kek.jp/Reference/>
- Examples
 - https://geant4-userdoc.web.cern.ch/Doxygen/examples_doc/html/index.html

Geant4 Example B1

- [DEMO]
 - Code and slides side-by-side breakdown

Geant4: RunManager

- G4RunManager (G4MTRunManager)
- Initialize() (/run/initialize)
- Remember run() from our MC1D assignment?
 - BeamOn() (/run/beamOn)
- SetUserAction() is deprecated
- SetUserInitialization() -> ActionInitialization

Public Member Functions

```
G4RunManager ()
virtual ~G4RunManager ()
virtual void BeamOn (G4int n_event, const char *macroFile=0, G4int n_select=-1)
virtual void Initialize ()
virtual void DefineWorldVolume (G4VPhysicalVolume *worldVol, G4bool topologyIsChanged=true)
virtual void AbortRun (G4bool softAbort=false)
virtual void AbortEvent ()
virtual void InitializeGeometry ()
virtual void InitializePhysics ()
virtual G4bool ConfirmBeamOnCondition ()
virtual void RunInitialization ()
virtual void DoEventLoop (G4int n_event, const char *macroFile=0, G4int n_select=-1)
virtual void RunTermination ()
virtual void InitializeEventLoop (G4int n_event, const char *macroFile=0, G4int n_select=-1)
virtual void ProcessOneEvent (G4int i_event)
virtual void TerminateOneEvent ()
virtual void TerminateEventLoop ()
virtual G4Event * GenerateEvent (G4int i_event)
virtual void AnalyzeEvent (G4Event *anEvent)
virtual void DumpRegion (const G4String &name) const
virtual void DumpRegion (G4Region *region=0) const
virtual void rndmSaveThisRun ()
virtual void rndmSaveThisEvent ()
virtual void RestoreRandomNumberStatus (const G4String &fileN)
virtual void SetUserInitialization (G4VUserDetectorConstruction *userInit)
virtual void SetUserInitialization (G4VUserPhysicsList *userInit)
virtual void SetUserAction (G4UserRunAction *userAction)
virtual void SetUserAction (G4VUserPrimaryGeneratorAction *userAction)
virtual void SetUserAction (G4UserEventAction *userAction)
virtual void SetUserAction (G4UserStackingAction *userAction)
virtual void SetUserAction (G4UserTrackingAction *userAction)
virtual void SetUserAction (G4UserSteppingAction *userAction)
const G4VUserDetectorConstruction * GetUserDetectorConstruction () const
const G4VUserPhysicsList * GetUserPhysicsList () const
const G4UserRunAction * GetUserRunAction () const
const G4VUserPrimaryGeneratorAction * GetUserPrimaryGeneratorAction () const
const G4UserEventAction * GetUserEventAction () const
const G4UserStackingAction * GetUserStackingAction () const
const G4UserTrackingAction * GetUserTrackingAction () const
const G4UserSteppingAction * GetUserSteppingAction () const
void SetNumberOfAdditionalWaitingStacks (G4int iAdd)
const G4String & GetVersionString () const
void SetPrimaryTransformer (G4PrimaryTransformer *pt)
void StoreRandomNumberStatusToG4Event (G4int vl)
G4int GetFlagRandomNumberStatusToG4Event () const
void SetRandomNumberStore (G4bool flag)
G4bool GetRandomNumberStore () const
void SetRandomNumberStoreDir (const G4String &dir)
const G4String & GetRandomNumberStoreDir () const
const G4String & GetRandomNumberStatusForThisRun () const
const G4String & GetRandomNumberStatusForThisEvent () const
void GeometryHasBeenModified ()
void PhysicsHasBeenModified ()
void CutOffHasBeenModified ()
void ReOptimizeMotherOf (G4VPhysicalVolume *)
void ReOptimize (G4LogicalVolume *)
void SetVerboseLevel (G4int vl)
G4int GetVerboseLevel () const
void SetGeometryToBeOptimized (G4bool vl)
G4bool GetGeometryToBeOptimized ()
void SetNumberOfEventsToBeStored (G4int val)
const G4Run * GetCurrentRun () const
const G4Event * GetCurrentEvent () const
const G4Event * GetPreviousEvent (G4int i) const
void SetRunIDCounter (G4int i)
G4int GetNumberOfParallelWorld () const
void SetNumberOfEventsToBeProcessed (G4int val)
void SetDCtable (G4DCtable *DCtbl)
void ConstructScoringWorlds ()
```


Geant4: ActionInitialization

Public Member Functions

	G4VUserActionInitialization ()
virtual	~G4VUserActionInitialization ()
virtual void	Build () const =0
virtual void	BuildForMaster () const
virtual G4VSteppingVerbose *	InitializeSteppingVerbose () const

- Used for “registering” user-defined action classes with Geant4
 - Register: give Geant4 a pointer to an instance of the object
 - Using inheritance; Geant4 keeps a **G4VUserActionInitialization***
- Build() is called by each thread
- BuildForMaster() is called by the master thread (often just RunAction)

Geant4: RunAction

- Used for Run management
- Functions called at the start and stop of a Run
- Allows us to provide a custom Run object (inherits from G4Run)
- Note “const G4Run*”: cannot change Run objects in these functions!
 - Reminder, same as G4Run const*
- We’ll revisit the Run objects later

Public Member Functions

	G4UserRunAction ()
virtual	~G4UserRunAction ()
virtual G4Run *	GenerateRun ()
virtual void	BeginOfRunAction (const G4Run *aRun)
virtual void	EndOfRunAction (const G4Run *aRun)
virtual void	SetMaster (G4bool val=true)
G4bool	IsMaster () const

Protected Attributes

G4bool	isMaster
---------------	-----------------

Geant4: EventAction

- Used for Event management
- Functions called at the start and stop of an Event
- Often used for printing periodic updates (event number)
- EndOfEventAction() historically used for getting Event hit information (now done in Run::RecordEvent())

Public Member Functions

	G4UserEventAction ()
virtual	~G4UserEventAction ()
virtual void	SetEventManager (G4EventManager *value)
virtual void	BeginOfEventAction (const G4Event *anEvent)
virtual void	EndOfEventAction (const G4Event *anEvent)

Geant4: PrimaryGeneratorAction

- Sets the primary particle properties for the G4Event
 - Which, how many, position, direction, energy, etc
- GeneratePrimaries() is usually a pass-through to a particle gun's GeneratePrimaryVertex()
- G4GeneralParticleSource (GPS) built-in option

Public Member Functions

	<u>G4VUserPrimaryGeneratorAction ()</u>
virtual	<u>~G4VUserPrimaryGeneratorAction ()</u>
virtual void	<u>GeneratePrimaries (G4Event *anEvent)=0</u>

Geant4: DetectorConstruction

Public Member Functions

	G4VUserDetectorConstruction ()
virtual	~G4VUserDetectorConstruction ()
virtual G4VPhysicalVolume *	Construct ()=0
virtual void	ConstructSDandField ()
virtual void	CloneSD ()
virtual void	CloneF ()
void	RegisterParallelWorld (G4VUserParallelWorld *)
G4int	ConstructParallelGeometries ()
void	ConstructParallelSD ()
G4int	GetNumberOfParallelWorld () const
G4VUserParallelWorld *	GetParallelWorld (G4int i) const

- Interface for providing geometry to Geant4
- Also handles SensitiveDetectors (more on this later)
- Parallel geometries (I've never used these)
- Construct() returns your top level simulation physical volume (“world”)

Geant4: Physics Lists

- We can define what physics we want, how we want
- We usually want to use the physics we all know* and love
- Most people 1) copy from a similar example and then modify or 2) use a built-in
- Completely dependent on details of the use case

Public Member Functions

```
G4VUserPhysicsList ()
virtual ~G4VUserPhysicsList ()
G4VUserPhysicsList (const G4VUserPhysicsList &)
G4VUserPhysicsList & operator= (const G4VUserPhysicsList &)
virtual void ConstructParticle ()=0
void Construct ()
virtual void ConstructProcess ()=0
void UseCoupledTransportation (G4bool vl=true)
virtual void SetCuts ()
void SetDefaultCutValue (G4double newCutValue)
G4double GetDefaultCutValue () const
void BuildPhysicsTable ()
void PreparePhysicsTable (G4ParticleDefinition *)
void BuildPhysicsTable (G4ParticleDefinition *)
G4bool StorePhysicsTable (const G4String &directory=".")
G4bool IsPhysicsTableRetrieved () const
G4bool IsStoredInAscii () const
const G4String & GetPhysicsTableDirectory () const
void SetPhysicsTableRetrieved (const G4String &directory="")
void SetStoredInAscii ()
void ResetPhysicsTableRetrieved ()
void ResetStoredInAscii ()
void DumpList () const
void DumpCutValuesTable (G4int flag=1)
void DumpCutValuesTableIfRequested ()
void SetVerboseLevel (G4int value)
G4int GetVerboseLevel () const
void SetCutsWithDefault ()
void SetCutValue (G4double aCut, const G4String &pname)
G4double GetCutValue (const G4String &pname) const
void SetCutValue (G4double aCut, const G4String &pname, const G4String &mname)
void SetParticleCuts (G4double cut, G4ParticleDefinition *particle, G4Region *region=0)
void SetParticleCuts (G4double cut, const G4String &particleName, G4Region *region=0)
void SetCutsForRegion (G4double aCut, const G4String &mname)
void ResetCuts ()
void SetApplyCuts (G4bool value, const G4String &name)
G4bool GetApplyCuts (const G4String &name) const
void RemoveProcessManager ()
void AddProcessManager (G4ParticleDefinition *newParticle, G4ProcessManager *newManager=0)
void CheckParticleList ()
void DisableCheckParticleList ()
G4int GetInstanceID () const
virtual void InitializeWorker ()
virtual void TerminateWorker ()
```

Assignment 4

- Questions, discussion, time to get started?