Chapters 9.3-9

Riccardo Miccini[1]   Eren Can [1]

[1]Technical University of Denmark
Digital Communication

November 19, 2016

Modulation Schemes not Requiring Coherent References

- In this section, now we consider two modulation schemes that you do not need to require the acquisition of a local reference signal in phase coherence with the received carrier.

Differential Phase-Shift Keying (DPSK)

- The implementation of a such a scheme presupposes two things;
  1. The unknown phase perturbation on the signal varies slowly that the phase is constant from one signalling interval to next.
  2. The phase during a given signalling interval bears a known relationship to the phase during the preceding signalling interval bears a known relationship to the phase during the preceding signalling interval.

Table 9.3 Differential Encoding Example

Message sequence:		1	0	0	1	1	1	0	0	0
Encoded sequence:	1	1	0	1	1	1	1	0	1	0
Reference digit:	↑									
Transmitted phase:	0	0	π	0	0	0	0	π	0	π

Differential Encoding Message Sequence

- An arbitrary reference binary digit is being selected as an initial digit of the sequence
- For each digit , the present digit used as a reference
- 0 in the message sequence is encoded as a transition from state of reference digit to the opposite state in the encoded message sequence
- 1 encoded as no change of state

Figure 9.16
Block diagram of a DPSK modulator

Comparison of Digital Modulation Systems

- .

Multipath Interference

- .

Equalization

- .

Equalization by Zero Forcing

- .

Equalization by Minimum Mean-Squared Error

- .

Tap Weight Ajustment (LMS Algorithm)

- .