

Exam presentation

Assignment 2.1 and 3

Riccardo Miccini¹

¹Technical University of Denmark
Digital Communication

December 15, 2016

Overview

- Assignment 2
 - Eye diagrams
 -
 -
- Assignment 3
 - Link budget model
 - SNR and P_E
 - Alternative modulations

Eye diagram

- Plot composed by overlaying segments of different bit sequences
- Can be generated with an oscilloscope
- Shows effects of *inter-symbol interference*
- Provides a qualitative measure of the system performance

Eye diagram characteristics




Figure: Eye diagram of BPSK signal

- A Difference between high and low levels
- A_j Difference between A and the eye opening
- T_j Deviations from ideal timing
- T_b Bit time period

Eye diagram at different bandwidths




Figure: Eye diagram for normalized bandwidths 0.3, 0.7, 1.2

- Low BW: high amplitude and timing jitter
- High BW: no ISI, chances of higher noise

Link budget model

- A way of estimating the power of a received signal
- Takes into account all the gains and losses of transmitter, channel, and receiver

$$P_R = \left(\frac{\lambda}{4\pi d} \right)^2 \frac{P_T G_T G_R}{L_0}; \quad (1)$$

- In decibels:

$$P_{R,dB} = 20 \log_{10} \left(\frac{4\pi d}{\lambda} \right) + ERP_{dB} + G_{R,dB} - L_{0,dB}; \quad (2)$$

Link budget model variables

$(\frac{4\pi d}{\lambda})^2$ Free-space loss

$ERP = P_T G_T$ Effective radiated power

G_R Gain of receiver antenna

L_0 Other losses, link budget margin

SNR calculation

- Signal-to-noise ratio in decibels:

$$SNR_{dB} = P_{R,dB} - P_{int,dB} \quad (3)$$

P_R Calculated using link budget model

P_{int} Noise power, proportional to the receiver noise temperature and the transmission bandwidth







P_E calculation

- Bit error probability for BSFK transmissions:

$$P_E = Q \left(\sqrt{\frac{2E_b}{N_0}} \right) \quad (4)$$

- 1 ratio E_b/N_0 derived from $SNR \Rightarrow \frac{E_b}{N_0 BT_b}$
- 2 For binary BPSK, $B = 2/T_b$
- 3 Factor BT_b is 2, or 3 dB

Impact of d , λ , B



Impact of P_T

- P_E for P_T at 50 W, 5 W, and 500 mW:

$$1.4062\text{e-}05 \quad 9.2684\text{e-}02 \quad 3.3768\text{e-}01 \quad (5)$$




Figure: P_E over values of P_T

Alternative modulation: ASK



Alternative modulation: FSK

