

Planning and Executing Humanoid Gaits in a World of Stairs

Candidate: Michele Cipriano

Thesis Advisor: Prof. Giuseppe Oriolo

January 21, 2020



SAPIENZA
UNIVERSITÀ DI ROMA

Master Degree in Artificial Intelligence and Robotics

Department of Computer, Control and Management Engineering

Sapienza University of Rome

Introduction

Abstract. Humanoid Robot Locomotion Problem.

Block Scheme

- `elevation_mapping`: autonomously build a map \mathcal{M}_z
- RRT-based footstep planner: generate a footstep sequence $\{f^j\}$ together with swing foot trajectories $\{p_{\text{swg}}^*\}$
- variable-height CoM IS-MPC: realize a stable trajectory p_{CoM}^*




Figure 1: Block scheme of the approach.

Variable Height CoM IS-MPC: 3D Motion Model

- LIP model not suitable for gait generation over uneven terrain
- constraint vertical motion such that

$$\frac{\ddot{z}_c + g}{z_c - z_z} = \omega^2$$

- CoM dynamics become

$$\ddot{x}_c = \omega^2(x_c - x_z)$$

$$\ddot{y}_c = \omega^2(y_c - y_z)$$

$$\ddot{z}_c = \omega^2(z_c - z_z) - g$$




Figure 2: ZMP, CoP and COM are colinear.

Variable Height CoM IS-MPC: MPC Formulation

- constrain ZMP into subregion of polyhedral cone (box)

$$R_{k+i}^T \begin{pmatrix} x_z^{k+i} - x_f^{k+i} \\ y_z^{k+i} - y_f^{k+i} \\ z_z^{k+i} - y_f^{k+i} \end{pmatrix} \leq \frac{1}{2} \begin{pmatrix} \tilde{d}_x^z \\ \tilde{d}_y^z \\ d_z^z \end{pmatrix}$$

- bound CoM wrt ZMP (LIP stability)

$$\frac{1}{\omega} \frac{1 - e^{-\delta\omega}}{1 - e^{-N\delta\omega}} \sum_{i=0}^{N-1} e^{-i\delta\omega} \dot{x}_z^{k+i} = x_c^k + \frac{\dot{x}_c^k}{\omega} - x_z^k \text{ internal to polyhedral cone.}$$

- solve QP problem using MPC scheme




Figure 3: CoP internal to support polygon equivalent to ZMP internal to polyhedral cone.

Variable Height CoM IS-MPC: Stair Climbing




Figure 4: NAO going down the stairs.

Variable Height CoM IS-MPC: Stair Climbing




Figure 5: CoM/ZMP plot (z-axis).

RRT-based Footstep Planning

- Rapidly-Exploring Random Tree

- R1 maximum footsteps height variation $|z_f^j - z_f^{j-1}| \leq \Delta z_{\max}$

- R2 footstep is fully in contact with the ground

- R3 swing foot trajectory p_{swg}^j is collision free

- footstep planner iteration

1. $p_{\text{rand}} \leftarrow \text{Rand}(\mathcal{M}_z)$
2. $v_{\text{near}} \leftarrow \text{Nearest}(p_{\text{rand}}, \gamma, \mathcal{T})$
3. $f_{\text{cand}} \leftarrow \text{Rand}(U)$
4. if f_{cand} feasible wrt R1-R2 then
5. $p_{\text{swg}}^{\text{cand}} \leftarrow \text{BuildTrajectory}(\cdot)$
6. $\mathcal{T}.\text{add}(v_{\text{new}}, v_{\text{near}})$ if $p_{\text{swg}}^{\text{cand}}$ satisfies R3

RRT-based Footstep Planning: Catalogue of Primitives




Figure 6: NAO's catalogue of primitives U .

RRT-based Footstep Planning: Obstacle Avoidance




Figure 7: NAO avoiding an obstacle.

RRT-based Footstep Planning: Obstacle Avoidance

tree size: 488 – solution size: 31 – runtime: 70 ms




Figure 8: Footstep plan generated for the scenario “Obstacle Avoidance”.

Elevation Map Generation: Framework

elevation_mapping

- robot-centric grid-based map: \mathcal{M}_z
- height estimate $\mathcal{N}(\hat{h}_i, \sigma_{h_i}^2)$ for each cell i
- Kalman filter given new height and motion measurements
- map fusion: $(\hat{h}_i, h_{i,\min}, h_{i,\max})$ such that $h_i \in [h_{i,\min}, h_{i,\max}]$ with 95% confidence
- dynamic environments using visibility check based on ray tracing

Elevation Map Generation: Settings

- NAO humanoid robot
- ASUS Xtion Pro (**depth sensor**)
- working range: 0.5–3.5 m
- elevation map extended with **safe zone**
- *unknown World of Stairs* environment



Figure 9: NAO with ASUS Xtion Pro placed on its head.

Stair Climbing in Unknown Environment




Figure 10: NAO climbing the stairs in an unknown environment.

Stair Climbing in Unknown Environment: Footstep Plan

tree size: 454 – solution size: 10 – runtime: 331 ms




Figure 11: Footstep plan generated for the scenario “Stair Climbing in Unknown Environment”.

Video

Conclusion

Results. Future Works.

Q&A

References

-  A. Zamparelli, N. Scianca, L. Lanari, and G. Oriolo, "Humanoid Gait Generation on Uneven Ground using Intrinsically Stable MPC," *IFAC-PapersOnLine*, vol. 51, pp. 393–398, 01 2018.
-  P. Ferrari, N. Scianca, L. Lanari, and G. Oriolo, "An integrated motion planner/controller for humanoid robots on uneven ground," in *18th European Control Conference, ECC 2019, Naples, Italy, June 25-28, 2019*, pp. 1598–1603, 2019.
-  P. Fankhauser, M. Bloesch, and M. Hutter, "Probabilistic terrain mapping for mobile robots with uncertain localization," *IEEE Robotics and Automation Letters (RA-L)*, vol. 3, no. 4, pp. 3019–3026, 2018.