Xacta.io JSON Data Dictionary
2.0
April 2025

Telos Corporation | 19886 Ashburn Road, Ashburn, Virginia, USA 20147-2358 | 1.800.70.TELOS | 1.800.708.3567 | www.telos.com

© 2025 Telos Corporation. All rights reserved.

Xacta® is a premier suite of cyber risk management and automation software solutions developed by Telos Corporation ("Telos") and launched in August 2000. Xacta content is protected under the copyright laws of the United States of America and is the property of Telos or the party credited as the provider of the content. Copyright © 2000 – 2025. All Rights Reserved.

Xacta has been developed at private expense and embodies certain trade secrets and other confidential, proprietary, and commercially-sensitive information that Telos safeguards through various measures implemented to maintain confidentiality and prevent unauthorized use or disclosure.

Access to and use of Xacta is subject to the terms of a license agreement with Telos (a "License") and is restricted to Authorized Users of the Customer (the "Licensee") that has been granted a License from Telos. **"Authorized Users"** means the employees, consultants, contractors, agents, or other designees of the Licensee who are authorized by the Licensee to use Xacta in accordance with the license granted by Telos and who have been supplied user login keys and credentials by the Licensee or Telos.

If the Licensee of Xacta software solutions and/or documentation is the U.S. Government or an agency thereof, or anyone licensing Xacta on behalf of the U.S Government, the following notice is applicable:

> U.S. GOVERNMENT END USERS: Xacta software solutions and/or documentation delivered to U.S. Government end users are "**commercial computer software**" and "**restricted computer software**" as these terms are used in applicable Federal Acquisition Regulation (FAR) and Defense Federal Acquisition Regulation Supplement (DFARS) clauses, and agency-specific supplemental regulations. As such, the use, duplication, disclosure, modification, and adaptation of the Xacta software solutions and/or documentation, and rights in technical data, shall be subject to the terms and restrictions set forth in the License applicable to the Xacta software solutions, and restrictions set forth in applicable FAR and DFARS clauses. See, *e.g.*, FAR 12.211 (Technical Data), FAR 12.212 (Software), FAR 52-227-14 (Rights in Data-General), FAR 52-227-19 (Commercial Computer Software License), DFARS 252.227-7015 (Technical Data – Commercial Items), and DFARS 227.7202-3 (Rights in Commercial Computer Software or Computer Software Documentation). No other rights are granted to the U.S. Government.

No Xacta user or other party may, without the express written permission of Telos or other rights owner, as applicable: 1) reverse engineer or otherwise attempt to discover the source code, object code or underlying structure, ideas, know-how or algorithms of Xacta; 2) copy, reproduce, distribute, publish, display, perform, modify, create derivative works, transmit, or in any way exploit the content of Xacta; 3) distribute any part of Xacta content over any network, including a local area network, or sell or offer it for sale, or; 4) use Xacta source code or content to construct any kind of database or to develop or enhance a competing Governance, Risk and Compliance (GRC) solution. Furthermore, no user or other party may alter or remove any copyright or other notice from Xacta or Xacta content.

Xacta is a registered trademark of Telos Corporation. All other registered trademarks and unregistered common law trademarks that appear in Xacta content are the property of their respective holders.

This document is furnished for informational purposes only. The material presented in this document is believed to be accurate at the time of release. However, Telos assumes no liability in connection with this document except as set forth in the License under which the document is furnished.

Contents

Overview 5
Xacta® JSON Data List 6
cpus 7
osList 7
endpointData 9
cloudInfo 10
testResults 11
softwares 13
drivelist 14
netAdapters 14
Sample Xacta® JSON Data Content 16
Related Topics 22

© 2025 Telos Corporation. All rights reserved.

Change History

Version Number	Date of Last Revision	Comments
1.0	04/25/2023	New document
2.0	04/16/2025	Updated cover page and copyright page

© 2025 Telos Corporation. All rights reserved.

Overview

This article is applicable to the following:

Product	License Type	Release/Build Number	OS	Database
Xacta.io		1.10 and higher		

This article provides a list of data within in an Xacta® JSON file. Xacta® JSON format provides significant flexibility when working with structural datasets that can transform your data in a variety of ways. This allows users to import asset or vulnerability data into Xacta.io. For more on information on importing and converting to Xacta® JSON, see the Importing Assets section of the Xacta.io User Guide and Converting to Xacta® JSON Using Python.

An Xacta® JSON file contains information on multiple assets and their test results, operating systems, hardware, etc. Please see screenshot below for sample Xacta® JSON file content; see also **Sample Xacta JSON Content** for another Xacta® JSON file content sample.


```
{
    "hostName":"Test Instance - FQDN: test.instance.gov",
    "dataSource":"Kubernetes STIG Checklist",
    "scannerVersion":"Stig version 2.15 for Windows",
    "netAdapters":{
        "ipAddress":"[redacted]2",
        "macAddress":""
    },
    "testResults":[
        {
            "vendorId":"V-223005",
            "testName":"ENFORCE_ENCODING_IN_GET_WRITER must be set to true.",
            "notes":"Check Content: From the Tomcat server as a privileged user, run the following command:\n\nsudo grep -i  enforce_encoding
            /etc/systemd/system/tomcat.service \n\nIf there are no results, or if the
            org.apache.catalina.connector.response.ENFORCE_ENCODING_IN_GET_WRITER is not =\"true\", this is a finding.",
            "description":"Some clients try to guess the character encoding of text media when the mandated default of ISO-8859-1 should be
            used. Some browsers will interpret as UTF-7 when the characters are safe for ISO-8859-1. This can create the potential for a XSS
            attack. To defend against this, enforce_encoding_in_get_writer must be set to true.",
            "result":"N/A",
            "rawResult":"N/A",
        }
        ],
            "contents":[
            "contents":[
                {
                    "name":"CCI-000366",
                    "type":"CCI"
                },
                {
                    "name":"CM-6 b",
                    "type":"IAC"
                }
            ],
            "riskFactor":"Medium",
            "scannedWithCredentialsFlag":true,
            "complianceCheckName":"TCAT-AS-001690",
            "resultData":{
                "Group Title":"SRG-APP-000516-AS-000237",
                "Rule ID":"SV-223005r615938_rule",
                "IA Controls":"",
                "Fix Text":"From the Tomcat server as a privileged user: \n\nEdit the /etc/systemd/system/tomcat.service file, and either add
                or edit the org.apache.catalina.connector.response.ENFORCE_ENCODING_IN_GET_WRITER setting.\n\nSet the
                org.apache.catalina.connector.response.ENFORCE_ENCODING_IN_GET_WRITER=true \n\nEXAMPLE:\nEnvironment='CATALINA_OPTS
                -Dorg.apache.catalina.connector.response.ENFORCE_ENCODING_IN_GET_WRITER=true'\n\nRestart the Tomcat server:\nsudo systemctl
                restart tomcat\nsudo systemctl daemon-reload",
                "False Positives":"",
                "False Negatives":"",
                "Documentable":"false",
                "Mitigations":"",
                "Potential Impact":"",
                "Third Party Tools":"",
                "Mitigation Control":"",
                "Responsibility":"",
                "Severity Override Guidance":"",
                "Check Content Reference":"M",
                "Classification":"M",
                "STIG":"Apache Tomcat Application Sever 9 Security Technical Implementation Guide :: Version 2, Release: 4 Benchmark Date: 27
                Jan 2022",
                "Comments":"",
                "Finding Details":"",
                "Severity Override":"",
                "Severity Override Justification":""
            }
        }
    ]
},
```


© 2025 Telos Corporation. All rights reserved.

It is important to note that the contents of an Xacta® JSON file depends on the scanner tool used, where the asset being scanned is hosted, and what the scanner tool has gathered. For example, cloudInfo data will only be provided for any assets hosted in a cloud environment and will not be available for On-Premises assets.

Users must also keep in mind that not all data in an Xacta® JSON file will be displayed or has an equivalent Xacta.io field. Please refer to **Xacta JSON Data List** for more information on the content of an Xacta® JSON file.

Xacta® JSON Data List

An Xacta® JSON file contains information, depending whether the assets come from a cloud environment or has an anti-virus application. Refer to the table below for the list of Xacta® JSON data and its description and associated Xacta.io field.

Xacta® JSON Data	Data Type	Description	Xacta.io Field
dataSource	String	This refers to the scanner tool providing the data. ***Note:*** *If there are testresults provided, datasource is required.*	
hostName	String	This refers to the asset identifier or the name of the asset's host. Note that the value must be unique within the boundary. ***Important:*** *This is a required value.*	Host Name
ramSize	Integer	This refers to the RAM size of the asset. This is not required data.	
scanDate	String	This refers to the date when the scan was executed by the tool.	Last Updated
scannerVersion	String	This refers to the version or type of the scanner tool.	

© 2025 Telos Corporation. All rights reserved.

Xacta® JSON Data	Data Type	Description	Xacta.io Field
systemName	String	This refers to the accreditation boundary where the asset belongs. This is not required data.	System Name

cpus

Xacta® JSON Data	Data Type	Description	Xacta.io Field
cpus	Collection	This refers to CPU information of the scanned asset. This is not a required value. The succeeding rows list the data typically included in the cpus Collection.	Asset Info tab
model	String	This refers to the model of the CPU.	
clock	String	This refers to the clock of the CPU.	
biosManufacturer	String	This refers to the manufacturer of the asset. This is not required data.	
biosDate	String	This refers to how old the asset could be. This is not required data.	

osList

Xacta® JSON Data	Data Type	Description	Xacta.io Field
osList	Collection	This refers to the information on operating system (OS) or kernel of the asset. This is not required data. The succeeding rows list the data typically included in the osList Collection.	OS Software tab
name	String	This refers to the name of operating system.	Name
build	String	This refers to the build of operating system.	Build

© 2025 Telos Corporation. All rights reserved.

Xacta® JSON Data	Data Type	Description	Xacta.io Field
version	String	This refers to the version of operating system.	Version
patch	String	This refers to the patch of operating system.	Patch
family	String	This refers to the family of operating system.	
cpe	String	This refers to the CPE of operating system.	CPE
vendorInfo	String	This refers to the vendor information of hardware model. This is not required data.	Vendor
systemModel	String	This refers to the information of hardware model. This is not required data.	
serial	String	This refers to the serial number of the hardware. This is not required data.	
poc	String	This refers to the point of contact (POC) for the host, if it is known. This is not required data. ***Important:*** *The email address field uniquely identifies a POC; each unique email introduced in the Xacta JSON will be created as new POC record.*	POC
name	String	This refers to the name of the asset's POC.	Name under Asset Info tab > Point of Contact section
organization	String	This refers to the organization of the asset's POC.	Organization under Asset Info tab > Point of Contact section
email	String	This refers to the email of the asset's POC. ***Note:*** *If poc data is*	Email under Asset Info tab > Point of Contact section

© 2025 Telos Corporation. All rights reserved.

Xacta® JSON Data	Data Type	Description	Xacta.io Field
		provided, this is a required data.	
phone	String	This refers to the phone of the asset's POC.	Phone under Asset Info tab > Point of Contact section
location	String	This refers to the location of the asset's POC.	Location under Asset Info tab > Point of Contact section

endpointData

Xacta® JSON Data	Data Type	Description	Xacta.io Field
endpointData	Collection	Used if there is AV data collected. This is not required data. This is not required data. The succeeding rows list the data typically included in the endpoint Collection.	
virusScanProductVersion	String	The refers to the version of the anti-virus scanner product.	
virusScanPatchNum	String	This refers to the anti-virus scanner product patch number.	
antiSpywareVersion	String	This refers to the anti-Spyware tool's version number.	
datVersion	String	This refers to the version of the anti-virus software's DAT.	Import Validation Report > DAT
hipVersion	String	This refers to the version of anti-virus software's HIP.	Import Validation Report > HIPS
hipPatchNum	String	This refers to the patch number of HIP	
hipStatus	String	This refers to the status of HIP.	
firewallStatus	String	This refers to the status of the firewall.	
lastScan	String	This refers to the date when the anti-virus tool completed the scanning.	
lastDefinitionDate	String	This refers to the date when the virus	

© 2025 Telos Corporation. All rights reserved.

Xacta® JSON Data	Data Type	Description	Xacta.io Field
		definition was last updated.	

cloudInfo

Xacta® JSON Data	Data Type	Description	Xacta.io Field
cloudInfo	Collection	This is only displayed when the scanned asset is hosted in a cloud environment. Refer to the succeeding rows below under the cloudInfo section for the data that is typically included in the cloudinfo data collection.	
cloudResourceId	String	This refers to the cloud resource ID. ***Note:*** *Assets must have unique cloudResourceID. In instances where the asset being imported has the same cloudResourceID with an existing asset in the Xacta.io application, the system will override the existing asset with the imported asset with the same cloudResourceID.*	Resource ID
cloudType	String	This refers to the cloud type.	Type
cloudAccountId	String	This refers to the cloud account ID.	Account ID
resourceName	String	This refers to the cloud resource name.	Resource Name
region	String	This refers to the cloud region where the asset belongs.	Region

© 2025 Telos Corporation. All rights reserved.

Xacta® JSON Data	Data Type	Description	Xacta.io Field
resourceType	String	This refers to the cloud resource type.	
resourceData	String	This refers to the cloud resource data. ***Note:*** *Any valid JSON object can be provided for resourceData. For example:* *"resourceData": { "anyField1":"sample value", "anyField2": true, "anyField3": ["this", "is", "an", "array"] }*	

testResults

Xacta® JSON Data	Data Type	Description	Xacta.io Field
testResults	Collection	This refers to the results of the tests executed by the scanner tool. This is not a required value but users may want to leverage if there are test results in the scan. This is not required data. The succeeding rows lists the testResults Collection.	
vendorID	String	This refers to the unique identifier of the test and it is used to track changes over time like plugins. For testResults data, this is required.	Vendor (ID)
testName	String	This refers to the human-readable name of test. For testResults data, this is required. Note that if only test name is provided, the isTestNameTestIdentifier	Name

© 2025 Telos Corporation. All rights reserved.

Xacta® JSON Data	Data Type	Description	Xacta.io Field
		data should be set to True. Result is required.	
notes	String	This refers to any information or notes provided by the tester. This is not a required data.	
description	String	This refers to the description of the test. This is not a required data.	Test Details > Description
result	String	This refers to the result of the test. This is required.	Scan Result/Results
rawResult	String	This refers to the raw result of the test. The data should be in Xacta.io format: {"Pass", "Fail", "N/A"}. This is not a required data.	Raw Result
contents	Collection	This refers to mapping information to any regulation or content. Note that a new array should be created for each content associated with the test and should be under the testResults collection. This is not a required data. This is not required data. The succeeding rows list the data typically included in the contents Collection. ***Note:*** *If content is added, make sure that values for name and type should be provided.*	
name	String	This refers to the content text; e.g., CVE-123-45677, AC-2.a, etc. ***Note:*** *If contents data is provided, this is required.*	Test Details > Controls

© 2025 Telos Corporation. All rights reserved.

Xacta® JSON Data	Data Type	Description	Xacta.io Field
type	String	This refers to information on where the content goes in Xacta.io and how it is used in Xacta.io. For example, {0:"CVE", 1:"CCE", 2:"CCI", 3:"V", 4:"CWE", 5:"IAC", 6:"ALERT", 7:"CPE"}. ***Note:*** *If contents data is provided, this is required.*	
port	Integer	This refers to the port of the scanned asset.	Test Data > Port
protocol	String	This refers to the protocol. This is not a required value.	Test Data > Protocol
runTime	String	This refers to the date and time the scan was executed. This is not a required value.	Scan Date
scannedWithCredentialsFlag	Boolean	This indicates whether the scanning was done with credentials flag. This is used for the scan history report, and it can show quality of the scan. This is not a required data.	Cred/Scan Credentialing

softwares

Xacta® JSON Data	Data Type	Description	Xacta.io Field
softwares	Collection	This populates software inventory for host, and will populate data in Xacta 360. This is not a required data. The succeeding rows list the data typically included in the softwares Collection.	Asset Details > Hardware
name	String	This refers to the name of the software in the asset.	Model

© 2025 Telos Corporation. All rights reserved.

Xacta® JSON Data	Data Type	Description	Xacta.io Field
		Note: *If there is a software data, this is a required data.*	
version	String	This refers to the version of the software in the asset.	
vendor	String	This refers to the vendor of the software in the asset.	Vendor Info
cpe	String	This refers to the CPE of the software in the asset.	CPE

drivelist

Xacta® JSON Data	Data Type	Description	Xacta.io Field
driveList	Collection	This populates Drives field in the Hardware list of an asset. This is not required. The succeeding rows list the data typically included in the driveList Collection.	Drives
model	String	This refers to the model of the hardware drive.	
sizeInMB	Integer	This refers to the size of the drive or storage in MB.	

netAdapters

Xacta® JSON Data	Data Type	Description	Xacta.io Field
netAdapters	Collection	This populates IP address for host, and will populate data in Xacta 360. This is not required. The succeeding rows list the data typically included in the	Net Adapters

© 2025 Telos Corporation. All rights reserved.

Xacta® JSON Data	Data Type	Description	Xacta.io Field
		netAdapters Collection.	
ipAddress	String	This refers to the IP address of the net adapter.	IP Address
macAddress	String	This refers to the MAC address of the net adapter.	MAC Address
dnsAddress	String	This refers to the DNS address of the net adapter.	DNS

© 2025 Telos Corporation. All rights reserved.

Sample Xacta® JSON Data Content

Below is a sample Xacta® JSON Data file content that includes osList, testData, cloudInfo, and software information:


```
[
{
  "hostName": "testInstance2",
  "dataSource": "Qualys",
  "ramSize": 16021788,
  "scanDate": 1425015828000,
  "vendorInfo":"Vendor information of the Hardware ModelAAA",
  "cpus": [
    {
      "model": "AMD Ryzen 5",
      "clock": "3500Mhz"
    },
    {
      "model": "Intel i7",
      "clock": "3500Mhz"
    }
  ],
  "osList": [
    {
      "name": "Microsoft Windows 7 Enterprise",
      "family": "WINDOWS"
    }
  ],
  "testResults": [
    {
      "vendorId": "V-1",
      "testName": "RHEL 8-test1",
      "notes": "Notes 1",
      "description": "Description 1",

      "rawResult": "Pass",
     }
     ],
     "contents": [
        {
          "name": "CCI-000015",
          "type": "CCI"
        },
        {
          "name": "CCI-000054",
          "type": "CCI"
        },
```


© 2025 Telos Corporation. All rights reserved.

```
      {
        "name": "CCI-001814",
        "type": "CCI"
      },
      {
        "name": "AC-17",
        "type": "IAC"
      },
      {
        "name": "AC-6 (9)",
        "type": "IAC"
      },
      {
        "name": "CCI-000015",
        "type": "CCI"
      },
      {
        "name": "CCI-000054",
        "type": "CCI"
      },
      {
        "name": "CCI-001453",
        "type": "CCI"
      },
      {
        "name": "AC-17 (1)",
        "type": "IAC"
      },
      {
        "name": "CCI-000139",
        "type": "CCI"
      }
    ],
    "riskFactor": "High",
    "scannedWithCredentialsFlag": true
  },
  {
    "vendorId": "V-2",
    "testName": "RHEL 8-test2",
    "notes": "Notes 2",
    "description": "Description 2",

    "rawResult": "N/A",

  }
  ],
    "contents": [
      {
        "name": "AC-3",
```


© 2025 Telos Corporation. All rights reserved.

```
        "type": "IAC"
      },
      {
        "name": "CM-6 b",
        "type": "IAC"
      },
      {
        "name": "CM-6 b",
        "type": "IAC"
      },
      {
        "name": "CM-6 b",
        "type": "IAC"
      },
      {
        "name": "CCI-000068",
        "type": "CCI"
      },
      {
        "name": "AC-17 (2)",
        "type": "IAC"
      },
      {
        "name": "AC-3",
        "type": "IAC"
      },
      {
        "name": "CCI-000054",
        "type": "CCI"
      },
      {
        "name": "AC-17 (2)",
        "type": "IAC"
      },
      {
        "name": "AU-5 a",
        "type": "IAC"
      }
    ],
    "scannedWithCredentialsFlag": true
  },

  {
    "vendorId": "V-500",
    "testName": "RHEL 8-test500",
    "notes": "Notes 500",
    "description": "Description 500",

    "rawResult": "Pass",
```


© 2025 Telos Corporation. All rights reserved.

```
      }
    ],
      "contents": [
        {
          "name": "AC-3",
          "type": "IAC"
        },
        {
          "name": "CCI-001814",
          "type": "CCI"
        },
        {
          "name": "AC-17 (2)",
          "type": "IAC"
        },
        {
          "name": "CCI-000015",
          "type": "CCI"
        },
        {
          "name": "CCI-001814",
          "type": "CCI"
        },
        {
          "name": "CCI-001453",
          "type": "CCI"
        },
        {
          "name": "CCI-000015",
          "type": "CCI"
        },
        {
          "name": "AU-5 a",
          "type": "IAC"
        },
        {
          "name": "AC-2 (1)",
          "type": "IAC"
        },
        {
          "name": "CCI-001453",
          "type": "CCI"
        }
      ],
      "scannedWithCredentialsFlag": true
    }
  ],
  "softwares": [
    {
```


© 2025 Telos Corporation. All rights reserved.

```
      "name": "Internet Explorer",
      "vendor": "Microsoft",
      "version": "11",
      "cpe": "cpe:2.3:a:microsoft:internet_explorer:11:-:*:*:*:*:*:*"
    },
    {
      "name": "Dolby Audio X2 (DAX2)",
      "vendor": "Dolby",
      "version": "1.3",
      "cpe": "cpe:/a:dolby:dolby_audio_x2:1.3"
    },
    {
      "name": "openssl",
      "vendor": "openssl",
      "version": "3.1",
      "cpe": "cpe:/a:openssl:openssl"
    },
    {
      "name": "Internet Explorer",
      "vendor": "Microsoft",
      "version": "11",
      "cpe": "cpe:2.3:a:microsoft:internet_explorer:11:-:*:*:*:*:*:*"
    },
    {
      "name": "Dolibarr ERP CRM",
      "vendor": "Dolibarr",
      "version": "2.7.0",
      "cpe": "cpe:/a:dolibarr:dolibarr:2.7.0"
    },
    {
      "name": "Dolibarr ERP CRM",
      "vendor": "Dolibarr",
      "version": "2.7.0",
      "cpe": "cpe:/a:dolibarr:dolibarr:2.7.0"
    },
    {
      "name": "Dolibarr ERP CRM",
      "vendor": "Dolibarr",
      "version": "2.7.0",
      "cpe": "cpe:/a:dolibarr:dolibarr:2.7.0"
    },
    {
      "name": "Python",
      "vendor": "Python",
      "version": "3.8",
      "cpe": "cpe:2.3:a:python:python:3.10.3:*:*:*:*:*:*:*"
    },
    {
      "name": "Fortinet FortiOS",
```


© 2025 Telos Corporation. All rights reserved.

```
      "vendor": "Fortinet",
      "version": "4.1.4",
      "cpe": "cpe:/o:fortinet:fortios:4.1.4"
    },
    {
      "name": "openssl",
      "vendor": "openssl",
      "version": "3.1",
      "cpe": "cpe:/a:openssl:openssl"
    }
  ],
  "netAdapters": [
    {
      "ipAddress": "250.13.208.239",
      "macAddress": "0a:69:ac:94:fa:4c",
      "dnsAddress": "ip-250.13.208.239.internal"
    },
    {
      "ipAddress": "84.80.74.89",
      "macAddress": "0a:69:ac:d0:c5:a4",
      "dnsAddress": "ip-84.80.74.89.internal"
    },
    {
      "ipAddress": "34.42.103.14",
      "macAddress": "0a:69:ac:a4:62:f8"
    },
    {
      "ipAddress": "188.41.109.21",
      "macAddress": "0a:69:ac:66:ba:9c"
    }
  ],
  "biosManufacturer": "AMI",
  "biosDate": "2020",
  "biosVersion": "1.42",
  "systemModel": "Latitude E6400",
  "serial": "1234578ULdRdrDe",
  "scannerVersion": "3",
  "systemName": "Cloud Service Provider Vulnerability Management (API)",
  "driveList": [
    {
      "model": "Buffalo",
      "sizeInMB": 2000
    },
    {
      "model": "Buffalo",
      "sizeInMB": 2000
    }
  ],
  "poc": {
```


© 2025 Telos Corporation. All rights reserved.

```
      "name": "James Brown",
      "organization": "Company",
      "email": "james.brown@company.com",
      "phone": "58887345",
      "title": "Mr.",
      "location": "Frizz VA"
    },
    "cloudInfo": {
      "cloudresourceId": "i-1234567890abcdef0",
      "cloudType": 0,
      "cloudAccountId": "0662773",
      "region": "us-east-1",
      "resourceType": "ec2-instance",
      "resourceData": {
        "amiId": "ami-12345",
        "instanceId": "12345",
        "instanceType": "mid",
        "hostnameLocal": "hostnamelocal",
        "hostnamePublic": "hostnamePUblic",
        "ipLocal": "1.1.1.1",
        "ipPublic": "8.8.8.8"
      },
      "resourceName": "ec2-IPaddress-1.2.3.4"
    }

  }
]
```


Related Topics

- Xacta.io User Guide
- Xacta.io API Guide
- Converting to Xacta® JSON Data Using Python

© 2025 Telos Corporation. All rights reserved.