Xacta.io Mapping Guide
4.0
May 2025

Telos Corporation | 19886 Ashburn Road, Ashburn, Virginia, USA 20147-2358 | 1.800.70.TELOS | 1.800.708.3567 | www.telos.com

© 2025 Telos Corporation. All rights reserved.

Xacta® is a premier suite of cyber risk management and automation software solutions developed by Telos Corporation ("Telos") and launched in August 2000. Xacta content is protected under the copyright laws of the United States of America and is the property of Telos or the party credited as the provider of the content. Copyright © 2000 – 2025. All Rights Reserved.

Xacta has been developed at private expense and embodies certain trade secrets and other confidential, proprietary, and commercially-sensitive information that Telos safeguards through various measures implemented to maintain confidentiality and prevent unauthorized use or disclosure.

Access to and use of Xacta is subject to the terms of a license agreement with Telos (a "License") and is restricted to Authorized Users of the Customer (the "Licensee") that has been granted a License from Telos. **"Authorized Users"** means the employees, consultants, contractors, agents, or other designees of the Licensee who are authorized by the Licensee to use Xacta in accordance with the license granted by Telos and who have been supplied user login keys and credentials by the Licensee or Telos.

If the Licensee of Xacta software solutions and/or documentation is the U.S. Government or an agency thereof, or anyone licensing Xacta on behalf of the U.S Government, the following notice is applicable:

> U.S. GOVERNMENT END USERS: Xacta software solutions and/or documentation delivered to U.S. Government end users are "**commercial computer software**" and "**restricted computer software**" as these terms are used in applicable Federal Acquisition Regulation (FAR) and Defense Federal Acquisition Regulation Supplement (DFARS) clauses, and agency-specific supplemental regulations. As such, the use, duplication, disclosure, modification, and adaptation of the Xacta software solutions and/or documentation, and rights in technical data, shall be subject to the terms and restrictions set forth in the License applicable to the Xacta software solutions, and restrictions set forth in applicable FAR and DFARS clauses. See, *e.g.*, FAR 12.211 (Technical Data), FAR 12.212 (Software), FAR 52-227-14 (Rights in Data-General), FAR 52-227-19 (Commercial Computer Software License), DFARS 252.227-7015 (Technical Data – Commercial Items), and DFARS 227.7202-3 (Rights in Commercial Computer Software or Computer Software Documentation). No other rights are granted to the U.S. Government.

No Xacta user or other party may, without the express written permission of Telos or other rights owner, as applicable: 1) reverse engineer or otherwise attempt to discover the source code, object code or underlying structure, ideas, know-how or algorithms of Xacta; 2) copy, reproduce, distribute, publish, display, perform, modify, create derivative works, transmit, or in any way exploit the content of Xacta; 3) distribute any part of Xacta content over any network, including a local area network, or sell or offer it for sale, or; 4) use Xacta source code or content to construct any kind of database or to develop or enhance a competing Governance, Risk and Compliance (GRC) solution. Furthermore, no user or other party may alter or remove any copyright or other notice from Xacta or Xacta content.

Xacta is a registered trademark of Telos Corporation. All other registered trademarks and unregistered common law trademarks that appear in Xacta content are the property of their respective holders.

This document is furnished for informational purposes only. The material presented in this document is believed to be accurate at the time of release. However, Telos assumes no liability in connection with this document except as set forth in the License under which the document is furnished.

Contents

Overview 5
Mapping Scanner Data with Xacta.io 6
Amazon Inspector 6
AWS Config 7
McAfee 7
Nessus 9
Nexpose (Rapid7) 13
Qualys 13
Qualys (Azure) 14
Splunk 14
Symantec 16
Tenable.sc 17

© 2025 Telos Corporation. All rights reserved.

Change History

Version Number	Date of Last Revision	Comments
1.0	04/29/2021	New document
2.0	01/09/2022	Add information regarding Notes values
3.0	04/16/2024	Add information re: Asset Role; Add Qualys (Azure)
4.0	04/04/2025	Add information re: JSON imports; Updated cover page and copy right page

© 2025 Telos Corporation. All rights reserved.

Overview

This article is applicable to the following:

Product	License Type	Release / Build Number	OS	Database
Xacta.io		Xacta.io 1.4.1 and higher		

This article aims to provide users information on how each data from different scanners supported by Xacta.io are mapped to a specific Xacta.io field. These scanner data are retrieved by Xacta.io from Splunk, which uses a Common Information Model (CIM) tool that helps normalize data to match a common standard using the same field names; for more information, please refer to the Configuring Splunk Integration article.

Xacta.io supports the following data from the following asset and vulnerability scanners; how each data is mapped to a specific Xacta.io field is detailed in the **Mapping Scanner Data with Xacta.io**:

- **Amazon Inspector**
- **AWS Config**
- **McAfee**
- **Nessus**
- **Nexpose (Rapid7)**
- **Qualys**
- **Qualys (Azure)**
- **Splunk**
- **Symantec**
- **Tenable.sc**

© 2025 Telos Corporation. All rights reserved.

Mapping Scanner Data with Xacta.io

Each scanner data is mapped to a specific Xacta.io field, which allows users to easily determine where the scanner data will be displayed in Xacta.io when it is imported in the application. It is important to note that only scan data in XML, JSON, CSV, ZIP, and GZIP formats can be imported into Xacta.io; please refer to the Xacta.io User Guide for more information. For JSON imports, note that Scan Results other than "pass" or "n/a" will be reflected as "fail".

Below are the lists of the Xacta.io fields and their corresponding fields from each scanner. The Scanner Data column lists the data retrieved from the scanner. For example, the Amazon Inspector data named *numericSeverity* will be displayed in the Scan Result field of Xacta.io.

Important: *Values displayed in the Notes field are pulled from the corresponding scanner tag. For example, in Qualys scanner data, all values included within or in the <RESULT> under <VULN_INFO> tag will also be displayed in the Notes field.*

Amazon Inspector

Xacta.io Fields	Scanner Data
Host Name	Findings > networkInterfaces[0]> privateDnsName
Scan Date	Findings > createdAt
Asset Roles	Refers to the roles assigned to assets to categorize how the assets are used in the system. Note that the asset role must exist in the application in order for the Asset Role mapping to appear on import.
Cloud	
Resource Name	Findings > assetAttributes > agentID
Resource Type	Findings > assetType
TestResult	
Test Name	Findings > Id
Result Data	Refers to any of the following scanner data; any of these information will be displayed in the Test Data field: • Findings > Severity (raw value, no translation applied) • Findings > recommendation
Scan Result	Findings > numericSeverity
Notes	Findings > Description
Content	Findings > attributes > value where findings > attributes > key = "CVE-ID"

© 2025 Telos Corporation. All rights reserved.

Xacta.io Fields	Scanner Data
Description	Findings > Description
Protocol	Findings > attributes > value where findings > attributes > key = “PROTOCOL”
Port	Findings > attributes > value where findings > attributes > key = “PORT”
Peered VPC	Findings > attributes > value where findings > attributes > key = “PCX_VPC”
Run Time	Findings > createdAt
Scanned with Credentials Flag	“No”
Risk Factor	Findings > severity The mapping value for Risk Factor are as follows: • Critical = Critical • High = High • Medium = Medium • Low = Low • Informational = None • Undefined = Unknown ***Note:*** *This is not applicable to Network Reachability Rules Package.*

AWS Config

Xacta.io Fields	Scanner Data
Host Name	privateDnsName
Scan Date	configurationItemCaptureTime
Scanner Version	configurationItemVersion
Cloud	
Cloud Resource ID (ARN)	ARN
Cloud Account ID (AWS Account ID)	awsAccountId
Resource Name	resourceName
Region	awsRegion
Resource Type	resourceType
Cloud Resource Data	All raw data for the resource

McAfee

Xacta.io Fields	Scanner Data
Host Name	System Name

© 2025 Telos Corporation. All rights reserved.

Xacta.io Fields	Scanner Data
System Name	Group Notes
Scan Date	Last Detected Time
Scanner Version	Product Version (VirusScan Enterprise)
Vendor Data	
Model	System Model
Vendor Info	System Manufacturer
Serial	System Serial Number
Operating System	
OS Name	OS Type
OS Build	OS Build Number
OS Version	OS Version
OS Patch	OS Service Pack Version
OS Family	OS Type (parse to determine Unix, Mac, Windows, etc)
Software	
Software Name	Software
Software Version	Software Version
Endpoint Data	
Virus Scan Product Version	Product Version (VirusScan Enterprise)
Virus Scan Engine Version	Engine Version (VirusScan Enterprise)
Virus Scan Patch Num	Hotfix/Patch Version (VirusScan Enterprise)
AntiSpyware Version	Product Version (AntiSpyware)
DAT Version	DAT Version (VirusScan Enterprise)
HIP Version	Product Version (Host Intrusion Prevention)
HIP Patch Num	Hotfix/Patch Version (Host Intrusion Prevention)
HIPStatus	Host IPS Status (Host IPS)
HIP Firewall Status	Firewall Status (Host IPS)
Last Definition Date	Last Detected Time
TestResult (*Note that each record is a new result)*	
Vendor ID	The value displayed depends on the dictionary used. If CVE is populated, the value displayed is *FaultlineID.* If the CCE is populated, the value displayed is the value of the CCE. If there are no CVE or CCE, the Vendor ID value is *FaultlineID*.
Test Name	FaultlineID Title *(Note that faultlineID will be used if faultlineID Title is not present)*
Result Data	Result
Scan Result	Result is displayed as value if CVEs exist or both CVE and CCE do not exist. If the value is Vulnerable, indicate it as test failure. If no CVE exist and CCE exists, test passes if CCE Compliance is pass.
Raw Result	Result is displayed as value if CVE is present or both CVE and CCE are not present. CCE Compliance is displayed as value when CCE is present and CVE is not.
Content	For CVE is displayed as value if it does not equal CVE-MAP-NOMATCH, split by comma.

© 2025 Telos Corporation. All rights reserved.

Xacta.io Fields	Scanner Data
	The value is Content Name if the content type is CVE. For CCE, the value is the content name if the content type is CCE.
Run Time	Last Detected Time
Scanned with Credentials Flag	The value for this field is True

Nessus

Xacta.io Fields	Scanner Data
Host Name	Returns the content of *<tag name="netbios-name">*, *<tag name="hostname">* or *<tag name="host-fqdn">* from the ReportHost name attribute. If none of the above are available, the hostname value will be the same as the IP.
Scan Date	Returns the content of *<tag name="HOST_START">*
Vendor Data	
Serial	Returns the content of *<tag name ="aws-instance-xxxx">* or *<tag name="aws-instance-xxxx-xxxx">*.
Operating System	
OS name	Returns the content of *<tag name="operating-system">*. The Name attribute of tag that starts with *cpe-* then parse out OS information out of CPE if CPE starts with *cpe:/o*. If this condition is met, the value should be the parsed CPE value from *plugin_output*.
OS build	Parsed from CPE (refer to OS name)
OS version	Parsed from CPE (refer to OS name)
OS patch	Parsed from CPE (refer to OS name)
OS family	Returns the content of *<tag name="operating-system">* (parse to determine UNIX, Mac, Windows, etc.)
Cloud	
Cloud Account ID (AWS Account ID)	Returns the content of *<tag name="aws-instance-accountid">*
Resource Name	Returns the content of *<tag name="aws-instance-instanceid">*.
Region	Returns the content of *<tag name="aws-instance-region">*
Resource Type	EC2
Cloud Resource Data	The value will be based from the following tags: • *<tag name="aws-intance-xxxx">* • *<tag name="aws-instance-xxxx-xxxx">*
NetAdapater	

© 2025 Telos Corporation. All rights reserved.

Xacta.io Fields	Scanner Data
IP	Returns the name attribute of ReportHost *<tag name="host-ip">*
Mac Address	Returns the content of *<tag name="mac-address">*
Software	
Name	Returns the name attribute of tag that starts with *cpe-* then parse out OS information out of CPE if CPE starts with *cpe:/a*. If the vedor ID is 20811, the value for OS name is *plugin_output*
Version	The version value displayed is parsed from CPE app name. If the Vendor ID is 28011, the value for OS name is *plugin_output*
Vendor	Parsed from CPE app name
CPE	Returns the content of tag when name attribute starts with CPE and the CPE starts with *cpe:/a*
Endpoint Data *(Note that if the Vendor ID is 16193, the value for OS name is* plugin_output*)*	
Virus Scan Product Version	Returns the content of *regex:(((mcafee virusscan enterprise)|(symantec endpoint protection))\s*:\s*\d+\.\d+\.\d+\.\d+)* ***Note:*** *Use the first match group with no spaces.*
Virus Scan Engine Version	Returns the content of *regex: (engine version\s*:\s*\d+\.\d+)*
AntiSypware Version	Returns the content of *regex:(((mcafee virusscan enterprise)|(symantec endpoint protection))\s*:\s*\d+\.\d+\.\d+\.\d+)* ***Note:*** *Use the first match group with no spaces.*
DAT Version	Returns the content of *regex: (DAT version\s*:\s*\d+\.\d+)*
Last Definition Date	Returns the content of *regex: (updated date\s*:\s*\d+\.\d+)* ***Note:*** *The format of the date will be in YYYY/MM/DD for McAfee and YYYYMMDD for Symantec. The tag content will contain the word McAfee if it was from McAfee and Savce if it is from Symantec.*
TestResult	
Vendor ID	pluginID attribute under ReportItem tag
Test Name	The test name value displayed is the ReportItem pluginName attribute. If compliance-check-name exists, use value from this tag (replace out \t), set to auto-generated vendorID
Result Data	Refers to any of the following scanner data: • compliance-info • compliance-reference • risk_factor • plugin_output

© 2025 Telos Corporation. All rights reserved.

Xacta.io Fields	Scanner Data
	• compliance-audit-file • compliance-check-id • compliance-actual-value
Test Data	Refers to any of the following scanner data; any of these information will be displayed in the Test Data field: • ReportItem pluginFamily attribute • Synopsis • Stig_severity • Xref • Plugin_modification_date • Plugin_publication_date • patch_publication_date • Vuln_publication_date • Exploitability_ease • Exploit_available • Exploit_framework_canvas • Exploit_framework_metasploit • Exploit_framework_core • Metasploit_name • Canvas_package • Cvss_vector • Cvss_base_score • Cvss_temporal_score • Plugin_type
Scan Result	If compliance-result or pci-dss-compliance tag exists, test failed if the value is either *Warning, Skipped, Failed, or Error*. Otherwise, set to fail if the Severity is > = 1. If the compliance-tag exists, the value of N/A is set when compliance tag is INFO.
Raw Result	If the compliance-tag does not exist, the raw result value is the value of the severity. If

© 2025 Telos Corporation. All rights reserved.

Xacta.io Fields	Scanner Data
	severity value is not within 0 to 4, the value will be *Cleared*. If the compliance-tag exists, use value from the compliance-result or pci-dss-compliance severity mapping to result: 0=info 1=low 2=medium 3=high 4=critical
Notes	Solution
Content	The content type displayed for CVE is CVE while the content type displayed for CWE is CWE. For compliance-check-name, find any CCEs from the content and add it with the content type of CCE. For compliance-info, find any CCI and add it with the content type of the CCI. For controls, find any controls and add it with the content type of IAC. For compliance-reference, parse out controls where controls type is in *(800-53, ISO/IEC-2700, 8500.2, Vuln-ID, PCI-DSSv3.1, 800-171, CSF, ITSG-33, HIPAA)* and add as content type for IAC. For xref-, parse out IAVA: and IAVAB: and add as content where content type is Alert.
Description	Description
Protocol	ReportItem protocol attribute
Port	ReportItem port attribute
Run Time	Returns the content of *<tag name="HOST_START">*
Scanned with Credentials Flag	*<tag name="Credentialed_Scan">* is set to true if any of the following values are contained in the tag: *Yes, True, or Success*
Skipped Flag	Compliance-tag exists, but value is not recognized if it is not within *Warning, Skipped, Failed, Passed, Cleared, Error, or Info*.
Error Running Test Flag	Description = Syntax error
Risk Factor	Risk_factor
Compliance Name	Compliance-check-name

© 2025 Telos Corporation. All rights reserved.

Nexpose (Rapid7)

Xacta.io Fields	Scanner Data
Host Name	Asset Names
Operating System	
OS name	Asset OS Name
OS family	Asset OS Family
NetAdapater	
IP	Asset IP Address
TestResult	
Vendor ID	Vulnerability ID
Test Name	Vulnerability Title
Result Data	Vulnerable Since
Test Data	Vulnerability Solution, Published On, Service Name
Scan Result	The Vulnerability Test Result Codes will be translated into IO Scan Results and will be mapped to IO values as follows: • VE, VV, VP, = Fail (IO) • NP, NV = Pass (IO) • EE, EV, EP, UK, SD, SV, ER, DS, OV, NT = N/A (IO)
Raw Result	Vulnerability Test Result Code
Notes	Vulnerability Proof
Content	Vulnerability CVE IDs
Description	Vulnerability Description
Protocol	Service Protocol
Port	Service Port
Skipped Flagged	TRUE
Risk Factor	Vulnerability Severity Level

Qualys

Xacta.io Fields	Scanner Data
Host Name	*<NETBIOS_HOSTNAME>*
Scan Date	*<GENERATION_DATETIME>*
Operating System	
OS name	*<OPERATING_SYSTEM>*
TestResult	
Vendor ID	*<QID>*
Test Name	*<Title>*
Test Data	Solution, Threat, Impact, PCI Flag

© 2025 Telos Corporation. All rights reserved.

Xacta.io Fields	Scanner Data
Scan Result	PCI 0 = Pass; PCI 1 = Fail
Raw Result	PCI 0 = Pass; PCI 1 = Fail
Notes	*<RESULT> under <VULN_INFO>*
Content	*<CVE_ID><ID>*
Description	*<THREAT>*
Protocol	*<VULN_INFO><PROTOCOL>*
Port	*<VULN_INFO><PORT>*

Qualys (Azure)

Xacta.io Fields	Scanner Data
Host Name	*<NETBIOS_HOSTNAME>*
Scan Date	*<GENERATION_DATETIME>*
Operating System	
OS name	*<OPERATING_SYSTEM>*
TestResult	
Vendor ID	*<QID>*
Test Name	*<Title>*
Test Data	Solution, Threat, Impact, PCI Flag
Scan Result	PCI 0 = Pass; PCI 1 = Fail
Raw Result	PCI 0 = Pass; PCI 1 = Fail
Notes	*<RESULT> under <VULN_INFO>*
Content	*<CVE_ID><ID>*
Description	*<THREAT>*
Protocol	*<VULN_INFO><PROTOCOL>*
Port	*<VULN_INFO><PORT>*

Splunk

Xacta.io Fields	Scanner Data
Host Name	asset_ds.hostName
System Name	asset_ds.systemName
Scan Date	asset_ds.scanDate
Scanner Version	asset_ds.scannerVersion
Ram Size	asset_ds.ramSize
Vendor Data	
Vendor Info	vendorInformation.vendorInfo
Model	vendorInformation.systemModel
Serial	vendorInformation.serial
BIOS	
manufacturer	bios.biosManufacturer

© 2025 Telos Corporation. All rights reserved.

Xacta.io Fields	Scanner Data
Date	bios.biosDate
Version	bios.biosVersion
CPU	
Model	cpu.cpuModel
Clock	cpu.cpuClock
Operating System	
OS Name	os.osName
OS Build	os.osBuild
OS Version	os.osVersion
OS Patch	os.osPatch
OS family	os.osFamily
OS CPE	os.osCPE
External ID	cloud.externalId
Cloud	
Cloud Resource ID (ARN)	cloud.cloudResourceId
Cloud Account ID (AWS Account ID)	cloud.cloudAccountId
Resource Name	cloud.resourceName
Region	cloud.region
Resource Type	cloud.resourceType
Cloud Resource Data	cloud.resrouceData
POC	
POC Name	poc.pocName
POC Org	poc.pocOrganization
POC Phone	poc.pocPhone
POC Email	poc.pocEmail
POC Location	poc.pocLocation
POC Title	poc.pocTitle
NetAdapter	
IP	netAdapater.ipAddress
MAC Address	netAdapater.macAddress
Software	
Name	software.softwareName
Version	software.softwareVersion
Vendor	software.softwareVendor
CPE	software.softwareCpe
Endpoint Data	
Virus Scan Product Version	endpointData.virusScanProductVersion
Virus Scan Engine Version	endpointData.virusScanEngineVersion
Virus Scan Patch Num	endpointData.virusScanPatchNum
AntiSpyware Version	endpointData.antiSpywareVersion
DAT Version	endpointData.datversion
HIP Version	endpointData.hipVersion
HIP Patch Num	endpointdata.hipPatchNum
HIP Status	endpointData.hipStatus
HIP Firewall Status	endpointData.firewallStatus
Last Definition Date	endpointData.lastDefinitionDate
Last Scan	endpointData.lastScan
TestResult	
Vendor ID	testResult.vendorId
Test Name	testResult.testName

© 2025 Telos Corporation. All rights reserved.

Xacta.io Fields	Scanner Data
Result Data	testResult.resultData
Test Data	testResult.testData
Scan Result	testResult.result
Raw Result	testResult.rawResult
Notes	testResult.notes
Content	testResult.content
Description	testResult.description
Protocol	testResult.protocol
Port	testResult.port
Run Time	testResult.runTime
Scanned With Credentials Flag	testResult.scannedWithCredentialsFlag
Error Running Test Flag	testResult.errorRunningTestFlag
Risk Factor	testResult.riskFactor
Compliance Name	testResult.complianceCheckName

Symantec

Xacta.io Fields	Scanner Data
Host Name	COMPUTER_NAME
System Name	GROUPNAME
Scan Date	LAST_SCAN_TIME
Scanner Version	AGENT_VERSION
Operating System	
OS name	OPERATION_SYSTEM
OS patch	SERVICE_PACK
OS family	OPERATION_SYSTEM
NetAdapter	
IP	IP_ADDR1
Endpoint Data	
Virus Scan Product Version	AGENT_VERSION
Virus Scan Engine Version	CIDS_ENGINE_VERSION
Virus Scan Patch Num	AGENT_VERSION
AntiSpyware Version	AGENT_VERSION
DAT Version	PATTERNDATE
HIP Version	CIDS_ENGINE_VERSION
HIP Patch Num	CIDS_ENGINE_VERSION

© 2025 Telos Corporation. All rights reserved.

Xacta.io Fields	Scanner Data
HIP Status	CIDS_DRV_ONOFF
HIP Firewall Status	FIREWALL_ONOFF
Last Definition Date	LAST_UPDATE_TIME
Last Scan	LAST_SCAN_TIME

Tenable.sc

Xacta.io Fields	Scanner Data
Host Name	Returns the content of <tag name="netbios-name">, <tag name="hostname"> or <tag name="host-fqdn"> from the ReportHost name attribute. If none of the above are available, the hostname value will be the same as the IP.
Scan Date	Returns the content of <tag name="HOST_START">
Operating System	
OS name	Returns the content of <tag name="operating-system">. The Name attribute of tag that starts with cpe- then parse out OS information out of CPE if CPE starts with cpe:/o. If this condition is met, the value should be the parsed CPE value from plugin_output.
OS build	Parsed from CPE (refer to OS name)
NetAdapater	
IP	Returns the name attribute of ReportHost *<tag name="host-ip">*
Mac Address	Returns the content of *<tag name="mac-address">*
Software	
Name	<plugin_output>
Version	<plugin_output>
CPE	Returns the content of tag when name attribute starts with CPE and the CPE starts with cpe:/a
Endpoint	
Last Scan	<tag_name="HOST_END">
TestResults	
Vendor ID	pluginID attribute under ReportItem tag.
Test Name	The test name value displayed is the ReportItem pluginName attribute. If compliance-check-name exists, use value from this tag (replace out \t), set to auto-generated vendorID.
Result Data	Refers to any of the following scanner data:

© 2025 Telos Corporation. All rights reserved.

Xacta.io Fields	Scanner Data
	• compliance-info • compliance-reference • risk_factor • plugin_output • compliance-audit-file • compliance-check-id • compliance-actual-value
Test Data	Refers to any of the following scanner data; any of these information will be displayed in the Test Data field: • ReportItem pluginFamily attribute • Synopsis • Stig_severity • Xref • Plugin_modification_date • Plugin_publication_date • patch_publication_date • Vuln_publication_date • Exploitability_ease • Exploit_available • Exploit_framework_canvas • Exploit_framework_metasploit • Exploit_framework_core • Metasploit_name • Canvas_package • Cvss_vector

© 2025 Telos Corporation. All rights reserved.

Xacta.io Fields	Scanner Data
	• Cvss_base_score • Cvss_temporal_score • Plugin_type
Scan Result	If compliance-result or pci-dss-compliance tag exists, test failed if the value is either *Warning, Skipped, Failed, or Error*. Otherwise, set to fail if the Severity is > = 1. If the compliance-tag exists, the value of N/A is set when compliance tag is INFO.
Raw Result	If the compliance-tag does not exist, the raw result value is the value of the severity. If severity value is not within 0 to 4, the value will be *Cleared*. If the compliance-tag exists, use value from the compliance-result or pci-dss-compliance severity mapping to result: 0=info 1=low 2=medium 3=high 4=critical
Content	The content type displayed for CVE is CVE while the content type displayed for CWE is CWE. For compliance-check-name, find any CCEs from the content and add it with the content type of CCE. For compliance-info, find any CCI and add it with the content type of the CCI. For controls, find any controls and add it with the content type of IAC. For compliance-reference, parse out controls where controls type is in *(800-53, ISO/IEC-2700, 8500.2, Vuln-ID, PCI-DSSv3.1, 800-171, CSF, ITSG-33, HIPAA)* and add as content type for IAC. For xref-, parse out IAVA: and IAVAB: and add as content where content type is Alert.
Description	Gets all the Plugins matching the filters, if provided.
Protocol	ReportItem protocol attribute
Run Time	Returns the content of *<tag name="HOST_START">*
Scanned with Credentials Flag	*<tag name="Credentialed_Scan">* is set to true if any of the following values are contained in the tag: *Yes, True, or Success*
Risk Factor	severity=""

© 2025 Telos Corporation. All rights reserved.