Gamma Ray

Schlumberger

Company: Lynx Petroleum Consultants, Inc.
Well: Hunton Energy Corp. Lynx Petroleum Consultants, Inc. Hunton Energy Corp.
Field: Wildcat
County: Hemphill
State: Texas

Other Services: Dual Induction Focused Log, Compensated Neutron Density Log, Borehole Compensated Sonic Log, Microlog

Permanent Datum:	Ground Level	Elev.:	2,457 ft
Log Measured From:	Kelly Bushing		15 ft above Perm. Datum
Drilling Measured From:	Kelly Bushing		
API Serial No.			
Date	1-Jan-1900		
Run No.	ONE		
Depth-Driller	9,000 ft		
Depth-Logger	9,000 ft		
Bottom Log Interval	9,000 ft		
Top Log Interval	8,500 ft		
Casing-Driller	8 5/8 @ 1,500 ft		
Casing-Logger			
Bit Size	7 7/8 in		
Type Fluid in Hole	Gel Chem		
Density	9.0 lb/gal		
Viscosity	40 s		
Fluid Loss	8.0 cc		
Source of Sample	Flowline		
Rm @ Meas. Temp.	0.08 @ 75 °F		
Rmf @ Meas. Temp.	0.06 @ 75 °F		
Rmc @ Meas. Temp.	0.12 @ 75 °F		
Source: Rmf / Rmc	Measured / Calculated		
Rm @ BHT	0.05 @ 150 °F		
Time Since Circulation	12 hrs		
Time Since Stop in Hole	1 hr		
Max. Rec. Temp.	150 °F		
Equipment Location	Pampa, Texas		
Recorded By	Jones		
Witnessed By	Smith		

Run No.	Bit Size	Depth Drilled	Depth In	Depth Out	Hours	Type Bit	Type Mud	Wt.	Vis.	Pv	Yp	Gels	Cl	Ph	Fl
ONE	7 7/8	9,000	1,500	9,000	90	Rock	Gel Chem	9.0	40	12	8	2/4	1,000	10.5	8.0

Remarks: Primary Service

GAMMA RAY	DATA	GAMMA RAY
PRESSURE INTENSIFIER INDICATOR		PRESSURE INTENSIFIER INDICATOR

Checksum: 0 0 0