

LOMBA KOMPETENSI SISWA PENDIDIKAN MENENGAH TINGKAT WILAYAH JAKARTA TIMUR 2 TAHUN 2026



TEST PROJECT WINDOWS

IT NETWORK SYSTEMS ADMINISTRATION

Introduction

You have been appointed as the system administrator for lksjkt.id and lab.lksjkt.id. In this organization, Microsoft technologies are primarily used to provide centralized management, file services, and web services. At the same time, Ansible is utilized to automate system configuration, deployment, and routine administrative tasks.

Your role is to ensure all services are properly configured, integrated, and operational within the given time constraints. Attention to detail and time management are critical to your success in this assignment.

All configuration on Windows Server and Client MUST BE PERSISTS AFTER REBOOT!

Credential Information

Windows

Username: User / Administrator

Password: Skills39!Jakarta

Linux

Username: root / user

Password: Skills39!Jakarta

Description of project and tasks

Basic Configuration

Configure hostname, FQDN and IP address on all hosts refer to the information table and set the timezone to (UTC+07:00) Bangkok, Hanoi, Jakarta. Also configure appropriate DNS servers on each host.

Active Directory

CORE.lksjkt.id

1. Configure this server as the initial domain controller for a new forest named **lksjkt.id**.
2. Configure Active Directory Sites and Services:
 - a. Rename the default site into **LKSJKT-ID**
 - b. Create and associate the following IP subnets with the LKSJKT site:
 - i. **192.168.1.0/24**
 - ii. **192.168.2.0/24**
 - c. Only **CORE** server assigned to the LKSJKT site.
3. Create the following **Organizational Units (OU)** inside the **lksjkt.id** domain:
 - a. Employee
 - b. Finance
 - c. Engineer
 - d. Manager
4. Inside each newly created OU, create a **security group** with the same name as its corresponding OU (e.g., create a group named Finance inside the Finance OU).
5. Create **Active Directory user accounts** according to the table below. Use PowerShell script to create all user accounts. Use password **Skills39!Jakarta** and make sure users do not need to change their password at the next logon.

Username Format	Total Accounts	Target OU
employee-001 - employee-514	514	Employee
engineer-001 - engineer-182	182	Engineer
finance-001 - finance-056	56	Finance

manager-001 - manager-015	15	Manager
---------------------------	----	---------

6. Configure **group membership** for all created users. Each user must be a member of the security group that corresponds with their OU (e.g., all users in the Finance OU must be members of the Finance group).
7. For users in the Finance and Manager groups, configure their home folder to be **\\lksjkt.id\CSDrive\Home\%username%** and mapped into the H: drive letter.
8. Configure **SRV.lksjkt.id**, **FW.lksjkt.id** and **WORKSTATION.lksjkt.id** as the domain members of **lksjkt.id**
9. Configure group policy called **LKSJKT GPO**. This policy must be applied only to the WORKSTATION with specification below:
 - a. Disable the first sign-in animation for users logging onto the workstation.
 - b. Enable folder redirection for Documents and Desktop to each home dir on network path **\\lksjkt.id\CSDrive\Home\%username%** and make sure the file is available offline
 - c. For any user logging into the workstation, automatically map the network path **\\lksjkt.id\CSDrive\Group** to drive letter **G:**

DC.lab.lksjkt.id

1. Promote this server as a new domain controller for a new child domain named **lab.lksjkt.id** in the existing **lksjkt.id** forest.
2. Configure **Active Directory Sites and Services**:
 - a. Create a new site named **LAB-LKSJKT**
 - b. Create and associate the IP subnet **172.172.1.0/24** with the **LAB-LKSJKT** site.
 - c. Only DC server assigned to the **LAB-LKSJKT** site.
3. Inside the **lab.lksjkt.id** domain, create the following **Organizational Units (OU)**:
 - a. Operator
 - b. Member
4. Inside each created OU, **create a security group** with the same name as its corresponding OU.
5. Create Active Directory user accounts according to the table below. Use password **Skills39!Jakarta** and make sure users do not need to change their password at the next logon.

Username Format	Total Accounts	Target OU
operator10 - operator20	11	Operator
member100 - member105	6	Member

6. Configure **group membership** for all created users. Each user must be a member of the security group corresponding to their OU.

DNS Service

CORE.lksjkt.id

1. Create the following Forward DNS records in the **lksjkt.id** zone: Type Record Name Value / Target

Type	Record Name	Value / Target
A	CORE	192.168.1.1
A	SRV	192.168.1.100
A	FW	192.168.1.254
A	CLIENT-GW	192.168.2.254
CNAME	CSDRIVE	SRV.lksjkt.id
CNAME	FILE	SRV.lksjkt.id
CNAME	www	SRV.lksjkt.id
CNAME	Internal	SRV.lksjkt.id
CNAME	Extra	SRV.lksjkt.id
CNAME	DC	CORE.lksjkt.id

2. Create the following Static Reverse DNS (PTR) records:

Record Name	IP Address
CORE.lksjkt.id	192.168.1.1
SRV.lksjkt.id	192.168.1.100
FW.lksjkt.id	192.168.1.254
CLIENT-GW.lksjkt.id	192.168.2.254

3. Make sure WORKSTATION IP address automatically created on reverse DNS zone.

DC.lab.lksjkt.id

1. Create the following Forward DNS records in the lab.lksjkt.id zone:

Type	Record Name	Value / Target
A	DC	172.172.1.100

2. Configure a DNS forwarder pointing to the IP address of **CORE.lksjkt.id**.

DHCP Service

FW.lksjkt.id

1. Install and configure **DHCP** services on this server. Create a new DHCP scope with the following specifications:

Scope Name	lksjkt.id_Client
Range	192.168.2.10 - 192.168.2.200
Subnet Mask	255.255.255.0
Excluded Address Range	192.168.2.110 - 192.168.2.120
DNS Servers	192.168.1.1, 172.172.1.100
Domain Name	lksjkt.id
Gateway	192.168.2.254
Lease Time	1 day, 49 minutes, 49 seconds

2. Configure the DHCP server to always perform **dynamic DNS updates** for clients.
3. Configure this server in Active Directory as an **authoritative** DHCP server for the lksjkt.id domain.

IIS Web Service

SRV.lksjkt.id

1. Install and configure the **Internet Information Services** (IIS) web server role on this server.
2. All websites created on this server must be secured using a pre-installed certificate with appropriate subject name for **HTTPS connections**.
3. Create and configure websites according to the specifications in the table below:

Website Name (Binding)	Path	Default Index File
internal.lksjkt.id	c:\www\internal	Internal.html
www.lksjkt.id	c:\www\public	Index.html
extra.lksjkt.id	c:\www\extra	Extra.html

4. Set website content to “**Welcome to {site name} site**”. (example for internal: “Welcome to Internal site”)
5. Configure **Windows Authentication** for **internal.lksjkt.id** and make sure domain users can access this site after authentication.

DC.lab.lksjkt.id

1. **Install Internet Information Services** (IIS) web server role on this server for future website deployment using playbook.
2. For easier management, install and configure **IIS Management Service**.

Shared Folder

SRV.lksjkt.id

1. Create a new root directory for all shared folders at the following path: **C:\Shared Folder**
2. Create two shared folders refer to the list below:
 - a. Shared folder named **Home** pointing to the **C:\Shared Folder\Home** directory.
This share will be used for users' personal home folders mounted as home drives.
 - b. Shared folder named **Group** pointing to the **C:\Shared Folder\Group** directory.
This share will be used for group-specific data.
3. On **Group** shared folder, create folder with NTFS permission refer to the list below:
 - a. **Employee** directory with **Employee & Manager** group has Full permission.
 - b. **Engineer** directory with **Engineer & Manager** group has Full permission
 - c. **Finance** directory with **Finance & Manager** group has Full permission
 - d. **Manager** directory with only **Manager** group has Full permission
4. Configure permissions on the **Home** shared folder so that each user can only access their own personal folder within the share.
5. On all created shared folders, remove the default **Everyone** account share permission.

File Server Resource Manager

SRV.lksjkt.id

1. Configure Quota Management to enforce storage limits:
 - a. Apply a **50MB** hard limit to each user's personal folder inside the **Home** shared folder.
 - b. Apply a **100MB** hard limit quota directly to each group folder inside the **Group** shared folder.
2. Configure File Screening to control file types:
 - a. On the **Home** folder, apply a file screen to **block executable** files from being saved.
 - b. On the **Group** folder, apply a file screen that only permits files with the **.txt** and **.doc** extensions to be saved.

Distributed File System

SRV.lksjkt.id

1. Configure a new domain-based DFS Namespace with name **CSDrive**
2. Create the following folders within the CSDrive namespace with their respective targets:
 - a. **\\ksjkt.id\CSDrive\Home** targeting **\\SRV.lksjkt.id\Home**
 - b. **\\ksjkt.id\CSDrive\Group** targeting **\\SRV.lksjkt.id\Group**
3. Configure this server as the primary member for DFS replication. Set up replication for the following folders:

Source Directory	Target Directory
C:\Shared Folder\Group\Manager	C:\Backup\Manager
C:\Shared Folder\Group\Finance	C:\Backup\Finance
C:\Shared Folder\Group\Engineer	C:\Replica\Engineer
C:\Shared Folder\Group\Employee	C:\Replica\Employee

FW.lksjkt.id

1. Add this server as a second namespace server for the **\\ksjkt.id\CSDrive** namespace to provide redundancy.
2. Configure this server as the target replication server for the DFS replication configured on **SRV.lksjkt.id**.
3. Ensure that DFS Replication is configured to **synchronize** automatically and continuously between the primary member and this target server.

Routing and Remote Access

FW.lksjkt.id

1. Install and configure the **Routing and Remote Access** service.
2. Configure **Routing** to allow clients, server from both sites to be reachable.

Ansible Automation

ansible-srv

The **ansible-srv** host is **Linux Debian VM** that can be used as configuration management for **Windows servers** in the **lksjkt.id** and **lab.lksjkt.id** domain.

Your task is to create and execute Ansible playbooks to automate the following administrative tasks.

All playbooks should be created in the **/etc/ansible/playbooks/** directory with **.yml** format!

1. Checking Playbook

As an introduction, create a playbook named **check.yml**. This playbook must perform the following actions on all Windows hosts defined in the inventory file:

- a. Ensure the directory **C:\LKSJKT** exists
- b. Create a file at **C:\LKSJKT\ansible_ready.txt**
- c. The content of the file must be the text: Ansible Connected

2. Website Deployment

Create a playbook named **deploy_website.yml** that targets **DC.lab.lksjkt.id**. This playbook must be able to deploy a new website by using a variable for the site name.

- a. The playbook should accept the following variable **site_name** as the website name.

Example execution:


```
ansible-playbook /etc/ansible/playbooks/deploy_website.yml \
-e site_name=test.lab.lksjkt.id
```

- b. The created playbook must perform this step:
 - i. Create a DNS A record in the **lab.lksjkt.id** zone for the **site_name**, pointing to the IP address of **DC.lab.lksjkt.id**. Based on example execution, DNS A record **test.lab.lksjkt.id** will be created pointing to **172.172.1.100**

- ii. Create a root directory for the website at **C:\project_website\site_name**. Based on example execution, **C:\project_website\test.lab.lksjkt.id** will be created.
- iii. Configure default index content to the value of **site_name**. Based on example execution, content of index.html for created website will be **test.lab.lksjkt.id**
- iv. Create a new IIS website that listens on HTTP, using the **site_name** as the hostname and the corresponding directory for its content.

Appendix

Topology



Addressing Table

Hostname	FQDN	IP Address
CORE	CORE.lksjkt.id	192.168.1.1/24
SRV	SRV.lksjkt.id	192.168.1.100/24
FW	FW.lksjkt.id	Ethernet0: 172.172.1.1/24 Ethernet1: 192.168.1.254/24 Ethernet2: 192.168.2.254/24
DC	DC.lab.lksjkt.id	172.172.1.100/24
WORKSTATION	WORKSTATION.lksjkt.id	DHCP
ansible-srv	N/A	192.168.2.222/24