QUOTATION

LNL3D Solutions™

007-DRAFT

May 6, 2026

PREPARED FOR

Sofie

Cherry Quote

STATUS

Quoting

VALID UNTIL

Jun 5, 2026

RUSH

Standard

QUANTITY

1 pcs

JOB DETAILS

Material	PLA+
Total Print Time	132.00 h for 1 piece
Notes	19x19" cherry. Total height around 39"

PRICING SCHEDULE

QUANTITY	UNIT PRICE	TOTAL
1	$135.67	$135.67
50	$113.06	$5,653.11
100	$101.76	$10,175.59
500	$90.45	$45,224.84
1000	$79.14	$79,143.47
5000	$73.49	$367,451.85

MATERIAL OPTIONS AT QTY 1

MATERIAL	UNIT	TOTAL
PLA+	$148.01	$148.01
PETG	$173.60	$173.60
TPU	$208.42	$208.42
PETG-CF	$213.38	$213.38
ABS	$186.96	$186.96
ASA	$186.96	$186.96
LW PLA HT	$264.57	$264.57
LW PLA	$192.43	$192.43
PA12	$386.97	$386.97

QUOTED PRICE

$135.67 + tax

$135.67 / pc + tax

LNL3D Solutions™

Material Guide

Plain-language overview of available filament options — LNL3D

Not sure which material is right for your project? This guide explains the key differences and what each material is best suited for. Each material is rated 1–5 dots across six properties. We're happy to make a recommendation based on your specific needs — just ask!

PLA+

Great all-purpose everyday material

STRENGTH	●●●●○	HEAT RESIST.	●○○○○	FLEXIBILITY	●○○○○
OUTDOORS	●○○○○	STIFFNESS	●●●●●	SURFACE	●●●●○

BEST FOR

- Prototypes & display models
- Decorative parts & figurines
- Low-stress indoor brackets & clips

PETG

Tough, moisture-resistant all-rounder

STRENGTH	●●●●○	HEAT RESIST.	●●●○○	FLEXIBILITY	●●○○○
OUTDOORS	●●●○○	STIFFNESS	●●●○○	SURFACE	●●●○○

BEST FOR

- Functional enclosures & brackets
- Parts that need some flex without breaking
- Moisture-exposed indoor/outdoor parts

TPU

Flexible rubber-like filament

STRENGTH	●●○○○	HEAT RESIST.	●●○○○	FLEXIBILITY	●●●●●
OUTDOORS	●●●○○	STIFFNESS	●○○○○	SURFACE	●●○○○

BEST FOR

- Grips, handles & bumpers
- Phone cases & wearables
- Seals, gaskets & flexible connectors

PETG-CF

Carbon-reinforced — stiff & lightweight

STRENGTH	●●●●●	HEAT RESIST.	●●●○○	FLEXIBILITY	●○○○○
OUTDOORS	●●●○○	STIFFNESS	●●●●●	SURFACE	●●○○○

BEST FOR

- Structural frames & load-bearing brackets
- Drone, RC & robotics parts
- Lightweight parts that must stay rigid

ABS

Heat-resistant engineering plastic

STRENGTH	●●●●○	HEAT RESIST.	●●●●○	FLEXIBILITY	●●○○○
OUTDOORS	●●○○○	STIFFNESS	●●●●○	SURFACE	●●●●○

BEST FOR

- Electronics & appliance housings
- Automotive interior components
- Parts that will be sanded, drilled or painted

ASA

UV-stable for long-term outdoor use

STRENGTH	●●●●○	HEAT RESIST.	●●●●○	FLEXIBILITY	●●○○○
OUTDOORS	●●●●●	STIFFNESS	●●●●○	SURFACE	●●●○○

BEST FOR

- Garden fixtures & outdoor signage
- Automotive exterior trim
- Any part that lives in direct sunlight

LW PLA HT

Ultra-lightweight foam PLA, heat-tolerant

STRENGTH	●●○○○	HEAT RESIST.	●●●○○	FLEXIBILITY	●○○○○
OUTDOORS	●●○○○	STIFFNESS	●●○○○	SURFACE	●●○○○

BEST FOR

- RC aircraft & drone airframes
- Weight-critical parts up to ~90 °C
- Hobby models where every gram counts

LW PLA

Ultra-lightweight foam PLA

STRENGTH	●●○○○	HEAT RESIST.	●○○○○	FLEXIBILITY	●○○○○
OUTDOORS	●○○○○	STIFFNESS	●●○○○	SURFACE	●●○○○

BEST FOR

- RC planes & gliders
- Lightweight model airframes
- Display props & theatrical models

PA12

Premium nylon for demanding applications

STRENGTH	●●●●●	HEAT RESIST.	●●●●○	FLEXIBILITY	●●●○○
OUTDOORS	●●●○○	STIFFNESS	●●●○○	SURFACE	●●●○○

BEST FOR

- Industrial functional parts
- High-cycle mechanical components
- Chemical-resistant enclosures & fittings

Ratings are relative guides, not engineering specifications. Heat resistance is the approximate temperature at which the part may soften under load. All materials are FDM (fused deposition) 3D printed. Contact us with questions about material selection for your project.