



PREPARED FOR

Sofie
Cherry Quote

STATUS

Quoting

VALID UNTIL

Jun 6, 2026

RUSH

Standard

QUANTITY

1 pcs

JOB DETAILS

Material	PLA+
Total Print Time	132.00 h for 1 piece
Notes	19x19" cherry. Total height around 39"

PRICING SCHEDULE

QUANTITY	UNIT PRICE	TOTAL
1	\$135.67	\$135.67
50	\$113.06	\$5,653.11
100	\$101.76	\$10,175.59
500	\$90.45	\$45,224.84
1000	\$79.14	\$79,143.47
5000	\$73.49	\$367,451.85

MATERIAL OPTIONS AT QTY 1

MATERIAL	UNIT	TOTAL
PLA+	\$148.01	\$148.01
PETG	\$173.60	\$173.60
TPU	\$208.42	\$208.42
PETG-CF	\$213.38	\$213.38
ABS	\$186.96	\$186.96
ASA	\$186.96	\$186.96
LW PLA HT	\$264.57	\$264.57
LW PLA	\$192.43	\$192.43
PA12	\$386.97	\$386.97

QUOTED PRICE

\$135.67 + tax
\$135.67 / pc + tax



1

File Review
We sanity-check your STL/STEP for printability and contact you with any concerns.

2

Quote Confirmation
You approve material, finishing, and quantity. Deposit (if any) is collected.

3

Print Queue
Job is slotted into the production schedule. Rush orders skip the queue.

4

Post-Processing
Supports removed, surfaces sanded or smoothed, requested finishing applied.

5

QA & Ship
Each piece is inspected and packed. Tracking is sent on dispatch.

TYPICAL LEAD TIMES

QUANTITY	STANDARD	RUSH
1–10 pcs	3–5 days	1–2 days
11–50 pcs	1 week	3–4 days
51–500 pcs	2–3 weeks	1 week
500+ pcs	Custom	Custom

Standard turnaround starts when files are confirmed. Rush surcharge — see your quote's Rush field. Lead times exclude shipping transit.

Light sanding Knock down layer lines on visible faces. \$5.00 per part	Full smoothing Sand to satin finish, paint-ready surface. \$15.00 per part
Vapor smoothing Glossy chemical-smoothed finish (ABS / ASA only). \$25.00 per part	Primer + paint Single colour, automotive-grade enamel. \$30.00 per part
Threaded inserts Heat-set brass inserts (M3 / M4 / M5). \$2.00 per insert	Assembly Multi-part assembly with fasteners or adhesive. \$60.00 per hour
Color matching Custom-mixed paint to your sample / Pantone. \$40.00 flat fee	

Add finishing services to your quote — call or email us to confirm scope and pricing for your specific parts.

Not sure which material is right for your project? This guide explains the key differences and what each material is best suited for. Each material is rated 1–5 dots across six properties. We're happy to make a recommendation based on your specific needs — just ask!

PLA+

Great all-purpose everyday material

STRENGTH	●●●●●	HEAT RESIST.	●●●●●	FLEXIBILITY	●●●●●
OUTDOORS	●●●●●	STIFFNESS	●●●●●	SURFACE	●●●●●

BEST FOR

- Prototypes & display models
- Decorative parts & figurines
- Low-stress indoor brackets & clips

PETG

Tough, moisture-resistant all-rounder

STRENGTH	●●●●●	HEAT RESIST.	●●●●●	FLEXIBILITY	●●●●●
OUTDOORS	●●●●●	STIFFNESS	●●●●●	SURFACE	●●●●●

BEST FOR

- Functional enclosures & brackets
- Parts that need some flex without breaking
- Moisture-exposed indoor/outdoor parts

TPU

Flexible rubber-like filament

STRENGTH	●●●●●	HEAT RESIST.	●●●●●	FLEXIBILITY	●●●●●
OUTDOORS	●●●●●	STIFFNESS	●●●●●	SURFACE	●●●●●

BEST FOR

- Grips, handles & bumpers
- Phone cases & wearables
- Seals, gaskets & flexible connectors

PETG-CF

Carbon-reinforced — stiff & lightweight

STRENGTH	●●●●●	HEAT RESIST.	●●●●●	FLEXIBILITY	●●●●●
OUTDOORS	●●●●●	STIFFNESS	●●●●●	SURFACE	●●●●●

BEST FOR

- Structural frames & load-bearing brackets
- Drone, RC & robotics parts
- Lightweight parts that must stay rigid

ABS

Heat-resistant engineering plastic

STRENGTH	●●●●●	HEAT RESIST.	●●●●●	FLEXIBILITY	●●●●●
OUTDOORS	●●●●●	STIFFNESS	●●●●●	SURFACE	●●●●●

BEST FOR

- Electronics & appliance housings
- Automotive interior components
- Parts that will be sanded, drilled or painted

ASA

UV-stable for long-term outdoor use

STRENGTH	●●●●●	HEAT RESIST.	●●●●●	FLEXIBILITY	●●●●●
OUTDOORS	●●●●●	STIFFNESS	●●●●●	SURFACE	●●●●●

BEST FOR

- Garden fixtures & outdoor signage
- Automotive exterior trim
- Any part that lives in direct sunlight

LW PLA HT

Ultra-lightweight foam PLA, heat-tolerant

STRENGTH	●●●●●	HEAT RESIST.	●●●●●	FLEXIBILITY	●●●●●
OUTDOORS	●●●●●	STIFFNESS	●●●●●	SURFACE	●●●●●

BEST FOR

- RC aircraft & drone airframes
- Weight-critical parts up to ~90 °C
- Hobby models where every gram counts

LW PLA

Ultra-lightweight foam PLA

STRENGTH	●●●●●	HEAT RESIST.	●●●●●	FLEXIBILITY	●●●●●
OUTDOORS	●●●●●	STIFFNESS	●●●●●	SURFACE	●●●●●

BEST FOR

- RC planes & gliders
- Lightweight model airframes
- Display props & theatrical models

PA12

Premium nylon for demanding applications

STRENGTH	●●●●●	HEAT RESIST.	●●●●●	FLEXIBILITY	●●●●●
OUTDOORS	●●●●●	STIFFNESS	●●●●●	SURFACE	●●●●●

BEST FOR

- Industrial functional parts
- High-cycle mechanical components
- Chemical-resistant enclosures & fittings

Ratings are relative guides, not engineering specifications. Heat resistance is the approximate temperature at which the part may soften under load. All materials are FDM (fused deposition) 3D printed. Contact us with questions about material selection for your project.

Material properties are approximate and may vary by colour, print settings, and application.