

Endovascular Today - EUROPEAN Device Guide - Microcatheters

Company Name	Product Name	Type of Catheter Construction	Proximal Size (F)	Middle Size (F)	Distal Size (F)	Catheter Working Length (cm)	Catheter Endhole Diameter ID (inch)	Recommended Guidewire Size (inch)	Radiopaque Tip (Yes/No)	Hydrophilic Coating (Yes/No)
Acandis GmbH & Co. KG	NeuroSlider 17	Stainless steel braiding with inner PTFE liner	2.1	–	1.9	155	0.0165	0.014 (maximum)	Yes, two markers	Yes
Acandis GmbH & Co. KG	NeuroSlider 21	Stainless steel braiding with inner PTFE liner	2.5	–	2.4	155	0.021	0.018 (maximum)	Yes, two markers	Yes
Acandis GmbH & Co. KG	NeuroSlider 27	Stainless steel braiding with inner PTFE liner	3.6	–	3	155	0.027	0.021 (maximum)	Yes, one marker	Yes
Argon Medical Devices, Inc.	Drakon	Tungsten steel-braided shaft, PTFE inner lumen	2.9	–	2.4	105, 130, 150	0.022	0.018 (maximum)	Yes	Yes
Argon Medical Devices, Inc.	Drakon	Tungsten steel-braided shaft, PTFE inner lumen	2.9	–	2.7	105, 130, 150	0.025	0.021 (maximum)	Yes	Yes
Argon Medical Devices, Inc.	Drakon	Tungsten steel-braided shaft, PTFE inner lumen	3	–	2.8	105, 130, 150	0.027	0.021 (maximum)	Yes	Yes
Argon Medical Devices, Inc.	SeQure	Tungsten steel-braided shaft, PTFE inner lumen	3	–	2.8	105, 130, 150	0.027	0.021 (maximum)	Yes, two markerbands	Yes
Argon Medical Devices, Inc.	SeQure	Tungsten steel-braided shaft, PTFE inner lumen	2.9	–	2.4	105, 130, 150	0.022	0.018 (maximum)	Yes, two markerbands	Yes
Argon Medical Devices, Inc.	SeQure	Tungsten steel-braided shaft, PTFE inner lumen	2.9	–	2.7	105, 130, 150	0.025	0.021 (maximum)	Yes, two markerbands	Yes
Asahi Intecc Co Ltd.	Asahi Tellus	SUS braiding	2.8	–	1.9	105, 125, 150	0.019	0.016	Yes	Yes
Asahi Intecc Co Ltd.	Asahi Veloute	Braiding	2.8	–	1.7	105, 125, 150	0.017	0.016	Yes	Yes
Asahi Intecc Co Ltd.	Masters Parkway HF	Tungsten, PTFE	2.8	–	2.6	105, 125, 150	0.027	0.021	Yes	Yes
Asahi Intecc Co Ltd.	Masters Parkway Soft	Tungsten, PTFE	2.8	–	1.9	105, 125, 150	0.022	0.018 (maximum)	Yes	Yes
Boston Scientific Corporation	Direxion	Preshaped or shapeable steerable nitinol microcatheter	2.4	2.4	2.4	105, 130, 155	0.021	Up to 0.018	Yes (1 or 2 RO)	Yes
Boston Scientific Corporation	Direxion Hi-Flo	Preshaped or shapeable steerable nitinol microcatheter	2.8	2.8	2.8	105, 130, 155	0.027	Up to 0.021	Yes	Yes

Company Name	Product Name	Type of Catheter Construction	Proximal Size (F)	Middle Size (F)	Distal Size (F)	Catheter Working Length (cm)	Catheter Endhole Diameter ID (inch)	Recommended Guidewire Size (inch)	Radiopaque Tip (Yes/No)	Hydrophilic Coating (Yes/No)
Boston Scientific Corporation	Direxion Hi-Flo System	Preshaped or shapeable steerable nitinol preloaded microcatheter	2.8	2.8	2.8	105, 130, 155	0.027	Preloaded with Transend 18 or Fathom 16	Yes	Yes
Boston Scientific Corporation	Direxion System	Preshaped or shapeable steerable nitinol preloaded microcatheter	2.4	2.4	2.4	105, 130, 155	0.021	Preloaded with Transend 14 or Fathom 16	Yes (1 or 2 RO)	Yes
Boston Scientific Corporation	Renegade Hi-Flo Fathom Kit	Vortec plus braiding: fiber and platinum braid	3 (1 mm)	–	2.8 (0.93 mm)	105, 115, 135, 150	0.027 (0.69 mm)	Includes Fathom-16 guidewire	Yes	Yes
Boston Scientific Corporation	Renegade Hi-Flo Fathom Preloaded System	Vortec plus braiding: fiber and platinum braid	3 (1 mm)	–	2.8 (0.93 mm)	105, 115, 135, 150	0.027 (0.69 mm)	Includes preloaded Fathom-16 guidewire	Yes	Yes
Boston Scientific Corporation	Renegade Hi-Flo Microcatheter	Vortec plus braiding: fiber and platinum braid	3 (1 mm)	–	2.8 (0.93 mm)	105, 115, 135, 150	0.027 (0.69 mm)	0.018 (0.46 mm) (maximum)	Yes	Yes
Boston Scientific Corporation	Renegade Hi-Flo Transend Kit	Vortec plus braiding: fiber and platinum braid	3 (1 mm)	–	2.8 (0.93 mm)	105, 115, 135	0.027 (0.69 mm)	Includes Transend-18 guidewire	Yes	Yes
Boston Scientific Corporation	Renegade Microcatheter	Vortec fiber braiding	3 (1 mm)	–	2.5 (0.83 mm)	130, 150	0.021 (0.53 mm)	0.018 (0.46 mm) (maximum)	Yes	Yes
Boston Scientific Corporation	Renegade STC 18 Microcatheter	Vortec fiber and stainless steel braid	3 (1 mm)	–	2.4 (0.8 mm)	105, 130, 150	0.021 (0.53 mm)	0.018 (0.46 mm) (maximum)	Yes	Yes
Cerenovus	Prowler 10	Braid/coil design	2.3	–	1.7	150	0.015	0.012 (maximum)	Yes	Yes
Cerenovus	Prowler 14	Braid/coil design	2.8	–	1.9	150, 170	0.0165	0.014 (maximum)	Yes	Yes
Cerenovus	Prowler 27	Braid/coil design	3	–	2.6	150	0.027	0.018 (maximum)	Yes	Yes
Cerenovus	Prowler Plus	Braid/coil design	2.8	–	2.3	110, 135, 150	0.021	0.018 (maximum)	Yes	Yes
Cerenovus	Prowler Select LP-ES	Braid/coil design	2.8	–	1.9	150	0.0165	0.014 (maximum)	Yes	Yes
Cerenovus	Prowler Select Plus	Braid/coil design	2.3	–	2.3	150	0.021	0.018 (maximum)	Yes	Yes
Cerenovus	Rapidtransit Microcatheters	Braid/coil design	2.3	–	2.3	75, 155, 175 (proximal, middle, and distal lengths); 100, 135 (proximal lengths)	0.021	0.018 (maximum)	Yes	Yes

Company Name	Product Name	Type of Catheter Construction	Proximal Size (F)	Middle Size (F)	Distal Size (F)	Catheter Working Length (cm)	Catheter Endhole Diameter ID (inch)	Recommended Guidewire Size (inch)	Radiopaque Tip (Yes/No)	Hydrophilic Coating (Yes/No)
Cerenovus	Transit Microcatheters	Braid/coil design	2.8	–	2.5	135, 150	0.021	0.018 (maximum)	Yes	Yes
Cook Medical	Cantata 2.5	Braided stainless steel, PTFE, Pebax	2.5	2.5	2.5	110, 135, 150	0.021	0.018 (maximum)	Yes (1 or 2 RB)	Yes
Cook Medical	Cantata 2.8	Braided stainless steel, PTFE, Pebax	2.8	2.8	2.8	110, 135, 150	0.025	0.021 (maximum)	Yes (1 or 2 RB)	Yes
Cook Medical	Cantata 2.9	Braided stainless steel, PTFE, Pebax	2.9	2.9	2.9	110, 135, 150	0.027 (0.69 mm)	0.025 (maximum)	Yes	Yes
Medtronic	Apollo Detachable Tip Microcatheter	Distal nitinol braiding with detachable tip 1.5, 3, and 5 cm	2.7	–	1.5	165	0.010	0.010 (maximum)	Yes	Yes
Medtronic	Echelon-10	Four performance zones with smooth transitions and nitinol braiding with progressive PPI for optimal proximal pushability and support and enhanced torque response; tip configuration straight, 40°, and 90° bends	2.1	–	1.7	155	0.017	0.014 (maximum)	Yes	Yes
Medtronic	Echelon-14	Four performance zones with smooth transitions and nitinol braiding with progressive PPI for optimal proximal pushability and support and enhanced torque response; tip configuration straight, 40°, and 90° bends	2.4	–	1.9	155	0.017	0.014 (maximum)	Yes	Yes
Medtronic	Rebar-10	Stainless steel reinforced microcatheter	2.3	–	1.7	153	0.012	0.012 (maximum)	Yes	Yes
Medtronic	Rebar-14	Stainless steel reinforced microcatheter	2.4	–	1.9	153	0.014	0.014 (maximum)	Yes	Yes
Medtronic	Rebar-18	Stainless steel reinforced microcatheter	2.8	–	2.3	130, 153	0.018	0.018 (maximum)	Yes	Yes
Medtronic	Rebar-27	Stainless steel reinforced microcatheter	2.8	–	2.8	130, 145	0.027	0.027 (maximum)	Yes	Yes
Merit Medical Systems, Inc.	Maestro	Nylon ribbon braiding	2.8, 2.9	2.8, 2.9	2.1, 2.4, 2.8, 2.9	110, 130, 150	0.018, 0.020, 0.024, 0.027	0.016, 0.018, 0.021	Yes, one markerband	Yes
Merit Medical Systems, Inc.	Pursue Microcatheter	Metal braided	2.8, 2.9	2.8, 2.9	1.7, 2	110, 130, 150	0.016, 0.020	0.014, 0.018	Yes, one markerband	Yes
Merit Medical Systems, Inc.	SwiftNinja Steerable Microcatheter	Tungsten-braided shaft	2.9 (0.97 mm)	2.9 (0.97 mm)	2.4 (0.80 mm)	125	0.021	≤ 0.018	Yes, two markerbands	Yes

Company Name	Product Name	Type of Catheter Construction	Proximal Size (F)	Middle Size (F)	Distal Size (F)	Catheter Working Length (cm)	Catheter Endhole Diameter ID (inch)	Recommended Guidewire Size (inch)	Radiopaque Tip (Yes/No)	Hydrophilic Coating (Yes/No)
Penumbra, Inc. (Neuro)	PX Slim Delivery Microcatheter	Nitinol coil reinforced; eight extrusion zones	2.95	–	2.6	150	0.025	≤ 0.020	Yes, two markerbands	Yes
Penumbra, Inc. (Neuro)	Velocity Delivery Microcatheter	Nitinol coil reinforced; eight extrusion zones	2.95	–	2.6	160	0.025	≤ 0.020	Yes, one markerband	Yes
Penumbra, Inc. (Peripheral Vascular)	Lantern Delivery Microcatheter	Nitinol coil reinforced; eight extrusion zones; three tip shapes: straight, 45°, and 90°	2.95	–	2.6	115, 135, 150	0.025	≤ 0.023	Yes; two markerbands, radiopaque 3 cm	Yes
Reflow Medical, Inc	Spex35 Shapeable Support Microcatheter	Shapeable tip, braid reinforced	4.6	4.6	4.6	50, 90, 135, 150	0.038	0.035	Yes	Yes
Reflow Medical, Inc	SpexLP 14 Shapeable Support Microcatheter	Low profile, shapeable tip, braid reinforced	2.2	2.2	1.4	90, 135, 150	0.018	0.014	Yes	Yes
Reflow Medical, Inc	SpexLP 18 Shapeable Support Microcatheter	Low profile, shapeable tip, braid reinforced	2.5	2.5	1.6	90, 135, 150	0.021	0.018	Yes	Yes
Reflow Medical, Inc	SpexLP 35 Shapeable Support Microcatheter	Low profile, shapeable tip, braid reinforced	3.8	3.8	2.9	90, 135, 150	0.038	0.035	Yes	Yes
Reflow Medical, Inc	Wingman 14C CTO Crossing Catheter	Braided with extendable beveled tip	2.7	2.7	2.7	90, 135, 150	0.024	0.014	Yes	Yes
Reflow Medical, Inc	Wingman 35 CTO Crossing Catheter	Braided with extendable beveled tip	4.6	4.6	4.6	90, 135, 150	0.032	0.035	Yes	Yes
Reflow Medical, Inc	Wingman14 CTO Crossing Catheter	Braided with extendable beveled tip	2.7	2.7	2.7	65, 135, 150	0.022	0.014	Yes	No
Reflow Medical, Inc	Wingman18 CTO Crossing Catheter	Braided with extendable beveled tip	3.8	3.8	3.8	90, 135, 150	0.032	0.018	Yes	Yes
Stryker	Excelsior 1018	Braided, hydrophilic	2.6	–	2	150	0.019	0.016 (maximum)	Yes	Yes
Stryker	Excelsior SL-10	Braided, hydrophilic	2.4	–	1.7	150	0.0165	0.014 (maximum)	Yes	Yes
Stryker	Excelsior XT-17	Braided	2.4	–	1.7	150	0.017	0.014 (maximum)	Yes	Yes
Stryker	Excelsior XT-27	Braided, hydrophilic	2.9	–	2.7	135, 150	0.027	0.018 (maximum)	Yes	Yes
Stryker	Neuro Renegade Hi-Flo	Braided, hydrophilic	3	–	2.8	135, 150	0.027	0.018 (maximum)	Yes	Yes
Stryker	Renegade 18	Braided, hydrophilic	3	–	2.5	150	0.021	0.018 (maximum)	Yes	Yes
Stryker	Trevo Pro 14	Braided	2.4	–	2.0	157	0.017	0.014 (maximum)	Yes	Yes
Stryker	Trevo Pro 18	Braided	2.7	–	2.4	150	0.021	0.018 (maximum)	Yes	Yes
Stryker	Trevo Trak 21	Braided	2.7	–	2.4	162	0.021	0.018 (maximum)	Yes	Yes
Teleflex	SuperCross	Dual coil design; platinum/tungsten	3.2	–	2.4	130, 150	0.017	0.014	Yes, platinum/	Yes

Company Name	Product Name	Type of Catheter Construction	Proximal Size (F)	Middle Size (F)	Distal Size (F)	Catheter Working Length (cm)	Catheter Endhole Diameter ID (inch)	Recommended Guidewire Size (inch)	Radiopaque Tip (Yes/No)	Hydrophilic Coating (Yes/No)
	Microcatheter OTW - 0.014 Angled Tips: 45°, 90°, 120°, and 90° Extended Tip	coil tip							tungsten coil tip	
Teleflex	SuperCross Microcatheter OTW - 0.014 Straight and Flexible Tip	Braided	2.5	–	1.8	130, 150	0.017	0.014	Yes, single markerband	Yes
Teleflex	Turnpike Catheter	Hybrid multilayer: dual bidirectional coils with inner braid	2.9	2.6	1.6	135, 150	0.0165	0.014	Yes, tungsten-loaded tip	Yes
Teleflex	Turnpike Gold Catheter	Hybrid multilayer: dual bidirectional coils with inner braid and external nylon spiral coil	2.9	2.9	2.1	135	0.0165	0.014	Yes, gold-plated tip	Yes
Teleflex	Turnpike LP Catheter	Hybrid multilayer: dual bidirectional coils with inner braid	2.9	2.2	1.6	135, 150	0.0165	0.014	Yes, tungsten-loaded tip	Yes
Teleflex	Turnpike Spiral Catheter	Hybrid multilayer: dual bidirectional coils with inner braid and external nylon spiral coil	2.9	2.9	1.6	135, 150	0.0165	0.014	Yes, tungsten-loaded tip	Yes
Terumo Europe	Progreat	Hyperselective hydrophilic braided radiopaque microcatheters	2.4	2.7	2.8	110 (proximal), 130 (middle), 150 (distal)	0.022, 0.025, 0.027	< 0.021	3-cm gold marker	Yes
Terumo Neuro	Headway 17 Advanced	Tapered PTFE liner with coil reinforcement	2.4	–	1.7	150	0.017	0.017	Yes	Yes
Terumo Neuro	Headway 17 Advanced Soft	Tapered PTFE liner with coil reinforcement	2.4	–	1.7	150	0.017	0.017	Yes	Yes
Terumo Neuro	Headway 21	PTFE liner with coil reinforcement	2.5	–	2	150	0.021	0.021	Yes	Yes
Terumo Neuro	Headway 27	PTFE liner with coil reinforcement	3.1	–	2.6	150	0.027	0.027	Yes	Yes
Terumo Neuro	Headway Duo	Hybrid braid/coil design	2.1	–	1.6	156	0.0165	0.0165	Yes	Yes
Terumo Neuro	Headway Duo	Hybrid braid/coil design	2.1	–	1.6	167	0.0165	0.0165	Yes	Yes
Terumo Neuro	Wedge	Coil reinforcement and distal bulb	2.5	–	2	1.5 (distal length)	0.021	0.014	Yes	Yes
Tokai Medical Products, Inc	Carnelian 1.7	Tungsten-braided super-selective microcatheter; tip configuration, straight; 45° and W-angled	2.8	–	1.7	110, 135	0.017	0.016	Yes	Yes
Tokai Medical Products, Inc	Carnelian 1.8	Tungsten-braided super-selective microcatheter; tip configuration	2.7	–	1.8	110, 135, 150	0.017	0.016 (maximum)	Yes	Yes

Company Name	Product Name	Type of Catheter Construction	Proximal Size (F)	Middle Size (F)	Distal Size (F)	Catheter Working Length (cm)	Catheter Endhole Diameter ID (inch)	Recommended Guidewire Size (inch)	Radiopaque Tip (Yes/No)	Hydrophilic Coating (Yes/No)
		straight; 45° and cobra angled								
Tokai Medical Products, Inc	Carnelian 1.9	Tungsten-braided super-selective microcatheter; tip configuration, straight; 45° and W-angled	2.8	–	1.9	110, 135	0.019	0.018	Yes	Yes
Tokai Medical Products, Inc	Carnelian 2.2	Tungsten-braided selective microcatheter; tip configuration straight; 45° and cobra angled	2.9	–	2.2	70, 110, 130, 135, 150	0.021	0.018 (maximum)	Yes	Yes
Tokai Medical Products, Inc	Carnelian 2.7	Tungsten-braided high flow microcatheter; tip configuration straight	2.9	–	2.7	105, 125	0.027	0.025 (maximum)	Yes	Yes
Tokai Medical Products, Inc	Carnelian NT	Tungsten-braided super-selective microcatheter, specially for triaxial system	1.8, 1.9	–	1.6, 1.9	135, 155	0.015, 0.017	0.014	Yes	Yes
Tokai Medical Products, Inc	Carnelian SI - Straight Inner	Tungsten-braided super-selective microcatheter with straight inner; tip configuration straight; 45° and W angled	2.8	–	1.9	110, 135	0.021	0.018	Yes	Yes
TriSalus Life Sciences	Surefire Infusion System (SIS) 021	Braided stainless steel, PTFE, multiple polymers, microvalve tip	3.2	3.2	2.8	120, 150	0.021	0.018 (maximum)	Yes	Yes
TriSalus Life Sciences	Surefire Infusion System (SIS) 025	Braided stainless steel, PTFE, multiple polymers, microvalve tip	3.7	3.7	3.4	120, 150	0.025	0.018 (maximum)	Yes	Yes
Zylox-Tonbridge Medical Technology Co., Ltd.	Glycine 21	Reinforced with 304 stainless steel support coil; the inner lining is PTFE	2.7	-	2.4	110, 130, 153	0.021	0.018 (maximum)	Yes	Yes
Zylox-Tonbridge Medical Technology Co., Ltd.	Glycine 27	Reinforced with 304 stainless steel support coil; the inner lining is PTFE	2.8	-	2.8	110, 130, 145	0.027	0.021 (maximum)	Yes	Yes