

Endovascular Today - US Device Guide - Hydrophilic Guidewires						
Company Name	Product Name	Type	Diameter (inch)	Length (cm)	Tip Type	Comments
Abbott	Hi-Torque Command	Nitinol	0.014	190, 300	Shapeable tip	Designed for lower limb procedures, available in standard and extra support configurations
Abbott	Hi-Torque Command 18	Nitinol	0.018	190, 300	Shapeable tip	Designed for lower limb procedures; available as ST (short taper, 10 cm nitinol) and LT (long taper, 25 cm nitinol)
Abbott	HydroSteer	Nitinol	0.018	150, 180	Angled, straight	Hydrophilic coating
Abbott	HydroSteer	Nitinol	0.035, 0.038	150, 180, 260	Angled, straight, J-tip	Hydrophilic coating
Abbott	HydroSteer Guide Wire	Nitinol	0.035	150, 180, 260	Straight, angled	Nitinol core with polymer jacket
Abbott	Shepherd Peripheral Guidewires, 12 and 30 gram	Stainless steel, hydrophilic with spring coil tip	0.014, 0.018	300	Straight, shapeable	–
Abbott	Shepherd Peripheral Guidewires, 4 and 6 gram	Stainless steel, polymer jacket with hydrophilic coating	0.014, 0.018	300	Straight, shapeable	–
Asahi Intecc USA, Inc.	Asahi Chikai	Stainless steel with hydrophilic coating	0.014	200, 300	Straight	Designed as workhorse guidewire for neurointerventional procedures; Actone, dual-coil, provides exceptional torque response and durable tip-shape retention; designed with optimum balance between tip flexibility and microcatheter support
Asahi Intecc USA, Inc.	Asahi Chikai 10	Stainless steel with hydrophilic coating	0.010	200, 300	Straight	Designed as workhorse guidewire for neurointerventional procedures; Actone, dual-coil, provides exceptional torque response and durable tip-shape retention; designed with optimum balance between tip flexibility and microcatheter support
Asahi Intecc USA, Inc.	Asahi Chikai black	Stainless steel Actone structure	0.014	200	Round curve/90° angle	Neurointervention
Asahi Intecc USA, Inc.	Asahi Chikai black 18	Stainless steel Actone structure	0.016, 0.018 (reverse taper)	200	Round curve	Neurointervention
Asahi Intecc USA, Inc.	Asahi Chikai V	Stainless steel with hydrophilic coating	0.014	165	Straight	Designed for super selective embolization; Actone, dual-coil, provides exceptional torque response and durable tip-shape retention for distal branch and multiple vessel embolization
Asahi Intecc USA, Inc.	Asahi Gaia PV	Stainless steel with hydrophilic coating	0.018	200, 300	7.5-gf tip load, preshaped	A tapered guidewire with micro cone tip and ACT ONE technology for effective navigation, ease of advancement, and good penetration
Asahi Intecc USA, Inc.	Asahi Gladius 0.014	Stainless steel with polymer jacket and hydrophilic coating	0.014	200, 300	3-gf tip load, straight	A workhorse polymer-jacketed guidewire with ACT ONE technology for superior maneuverability and durability in a broad range of cases
Asahi Intecc	Asahi Gladius 0.018	Stainless steel with	0.018	200, 300	4-gf tip load, straight	A workhorse polymer-jacketed guidewire with ACT ONE technology

Company Name	Product Name	Type	Diameter (inch)	Length (cm)	Tip Type	Comments
USA, Inc.		hydrophilic coating				for superior maneuverability and durability in a broad range of cases
Asahi Intecc USA, Inc.	Asahi Gladius Mongo 18 PV ES	Stainless steel with a polymer jacket and hydrophilic coating	0.018	190, 300	3-gf tip load, straight, preshape	A workhorse polymer-jacketed guidewire with high steerability, good support, and the ability to form a narrow loop for crossing and treating stenosed lesions
Asahi Intecc USA, Inc.	Asahi Gladius Mongo ES	Stainless steel with polymer jacket and hydrophilic coating	0.014	190, 300	3-gf tip load, straight, preshape	A workhorse polymer-jacketed guidewire with high steerability, good support, and the ability to form a narrow loop for crossing and treating stenosed lesions
Asahi Intecc USA, Inc.	Asahi Halberd 0.014	Stainless steel with hydrophilic coating	0.014	200, 300	12-gf tip load, straight	A specialty guidewire with ACT ONE technology for superior directional control and effective lesion engagement
Asahi Intecc USA, Inc.	Asahi Halberd 0.018	Stainless steel with hydrophilic coating	0.018	200, 300	12-gf tip load, straight	A specialty guide wire with ACT ONE technology for superior directional control and effective lesion engagement
Asahi Intecc USA, Inc.	Asahi Meister 16	Stainless steel Actone structure	0.016	165, 180	45° angle/round curve/double angle	Interventional radiology procedure
Asahi Intecc USA, Inc.	Asahi Regalia XS 1.0	Stainless steel with a polymer jacket and hydrophilic coating	0.014	180, 300	1-gf tip load, straight	A soft polymer guidewire with flexible shaft for trackability in tight lesions and difficult anatomy
Asahi Intecc USA, Inc.	Astato 30	Stainless steel with hydrophilic coating	0.018	180, 300	30-gf tip load, straight	A specialty guidewire with tapered tip for crossing complex lesions with heavy calcification and/or tough fibrous tissue
Asahi Intecc USA, Inc.	Astato XS 20	Stainless steel with a tapered tip and hydrophilic coating	0.014	180, 300	20-gf tip load, straight	A specialty guidewire with tapered tip for crossing complex lesions with heavy calcification and/or tough fibrous tissue
Asahi Intecc USA, Inc.	Astato XS 40	Stainless steel with tapered tip and hydrophilic coating	0.014	200, 300	40-gf tip load, straight	A specialty guidewire with tapered tip and high tip load for crossing complex lesions with heavy calcification and/or tough fibrous tissue
Asahi Intecc USA, Inc.	CrossLead 0.035	Nitinol with a polymer jacket and hydrophilic coating	0.035	200, 300	Angled	A multipurpose nitinol guide wire with shapeable tip and narrow looping technology for sheath delivery, lesion crossing and device delivery in difficult anatomy and complex lesions
Asahi Intecc USA, Inc.	Treasure 12	Stainless steel with hydrophilic coating	0.018	180, 300	12-gf tip load, straight	A specialty guidewire for controlled drilling when targeting highly stenosed, calcified lesions
Asahi Intecc USA, Inc.	Treasure Floppy 0.018	Stainless steel with hydrophilic coating	0.018	190, 300	4-gf tip load, straight	Workhorse guidewire for nontotally occluded lesions
Balt	Hybrid Guidewire	Nitinol and stainless steel	0.012	310	Straight, shapeable	Designed for stable exchange
Balt	Hybrid Guidewire	Nitinol and stainless steel	0.008	220	Preshaped, double angle	Designed for durability and flexibility
Balt	Hybrid Guidewire	Nitinol and stainless steel	0.010	310	Straight, shapeable	Designed for stable exchange
Balt	Hybrid Guidewire	Nitinol and stainless steel	0.014	200	Straight, shapeable	Designed for durability and flexibility
Balt	Hybrid Guidewire	Nitinol and stainless steel	0.012	200	Straight, shapeable	Designed for durability and flexibility
Balt	Hybrid Guidewire	Nitinol and stainless steel	0.012	200	Preshaped, double angle	Designed for durability and flexibility
Balt	Hybrid Guidewire	Nitinol and stainless steel	0.007	220	Straight	Designed for durability and flexibility

Company Name	Product Name	Type	Diameter (inch)	Length (cm)	Tip Type	Comments
Balt	Hybrid Guidewire	Nitinol and Stainless Steel	0.007	220	Preshaped, double angle	Designed for durability and flexibility
Balt	Hybrid Guidewire	Nitinol and stainless steel	0.008	220	Straight, shapeable	Designed for durability and flexibility
BD Interventional	Porter	Stainless steel	0.014	195, 300	Straight, 3-, 6-, 9-, 12-gauge tip stiffness	Hydrophilic guidewire in various levels of tip stiffness, providing excellent trackability, steerability, visibility, and support for delivery of therapeutic devices
Boston Scientific Corporation	Enroute 0.014-inch Guidewire	Stainless steel with hydrophilic coating	0.014	95	Shapeable, 5-cm radiopaque tip	Designed for navigating tortuous short vessel segments with its unique combination of short length, short taper, and a shapeable tip; excellent torque control and device deliverability
Boston Scientific Corporation	Fathom-14 Guidewire	Hybrid stainless steel and nitinol	0.014	200, 300	10 cm with 2-cm shapeable or angled tip	Utilizes a unique slotted nitinol hypotube design to balance exceptional torquability with tip softness and proximal support
Boston Scientific Corporation	Fathom-16 Guidewire	Hybrid stainless steel and nitinol	0.016	140, 180, 200, 215	10, 20 cm with 2-cm shapeable or angled tip	Utilizes a unique slotted nitinol hypotube design to balance exceptional torquability with tip softness and proximal support
Boston Scientific Corporation	Transend-14 Steerable Guidewire	Hydrophilic coating with scitanium core	0.014	135, 165, 190	2-cm shapeable tip	Product features hydrophilic coating and good torque response
Boston Scientific Corporation	Transend-18 Steerable Guidewire	Hydrophilic coating with scitanium core	0.018	135, 165	2-cm shapeable tip	Product features hydrophilic coating and good torque response
Boston Scientific Corporation	V-14 ControlWire Guidewire	Scitanium stainless steel core, polymer sleeve	0.014	182, 300	Straight, angled (shapeable)	Distal radiopaque section (distal 2 cm); single-piece core with torque jacket for 1:1 torque control; shapeable tip intended to facilitate accurate placement; proximal PTFE jacket intended to provide firm support and low friction surface
Boston Scientific Corporation	V-18 ControlWire Steerable Guidewire	Scitanium stainless steel core, polymer sleeve	0.018	110, 150, 200, 300	Straight (shapeable)	Hydrophilic performance and torque control designed for distal, peripheral access and contralateral approaches; single-piece core with torque jacket for 1:1 torque control; robust shapeable 3-cm tip intended to facilitate accurate placement; proximal PTFE jacket intended to provide firm support and low friction surface
Boston Scientific Corporation	Victory Guidewire	Stainless steel core, polymer sleeve	0.014, 0.018	195, 300	Straight (shapeable)	12-g, 18-g, 25-g, and 30-g tip loads designed to cross highly resistant lesions; torque control designed for distal, peripheral access
Boston Scientific Corporation	Zipwire Hydrophilic Guidewire	Hydrophilic wire with nitinol core	0.018, 0.025, 0.035, 0.038	80, 150, 180, 260	Straight, angled, J-tip, long taper	Precise torque control, superior visibility, small vessel option (0.018 inch) diameter
Cerenovus	Agility 10 Steerable Guidewire	Stainless steel with hydrophilic coating	0.010	195	Shapeable tip	The soft tips enable easy shapeability and safe vessel access; available in standard and soft configurations
Cerenovus	Agility 14 Steerable Guidewire	Stainless steel with hydrophilic coating	0.014	205, 350	Shapeable tip	The soft tips enable easy shapeability and safe vessel access; available in standard and soft configurations
Cerenovus	Agility 16 Steerable Guidewire	Stainless steel with hydrophilic coating	0.016	175, 205	Shapeable tip	The soft tips enable easy shapeability and safe vessel access; available in standard and soft configurations
Cerenovus	Neuroscout 14 Steerable Guidewire	Stainless steel with hydrophilic coating	0.014	205, 300	Shapeable tip	Specifically designed for excellent tip shaping and shape retention

Company Name	Product Name	Type	Diameter (inch)	Length (cm)	Tip Type	Comments
Cook Medical	Roadrunner PC	Nitinol core with platinum coils, polyurethane jacket	0.035, 0.038	80, 145, 180, 260	Straight, angled	Available in either a standard or stiff shaft configuration and a standard or long-taper configuration
Cook Medical	Uniglide	Nitinol core, polyurethane jacket	0.018, 0.035	80, 150, 180, 260, 320	Straight, angled	Available in either a standard or stiff shaft configuration
Cordis	Aquatrack Hydrophilic Nitinol Guidewire	Nitinol	0.035	150, 180, 260	Straight, angled	–
Guerbet LLC	Axessio	Stainless steel with hydrophilic coating	0.018	180	Straight shapeable	PTFE and hydrophilic coating with platinum coil tip
Guerbet LLC	Axessio	Stainless steel with hydrophilic coating	0.014	180	Straight shapeable	PTFE and hydrophilic coating with platinum coil tip
Medcomp	Coated Mandrel Guidewires	Straight	0.010	60, 80	Platinum coil tip	Hydrophilic coating
Medtronic	Avigo .014” Hydrophilic Guidewire	Stainless steel	0.014	205	Shapeable tip	–
Medtronic	F14 and F18 Peripheral Guidewires	Stainless steel	0.014, 0.018	300, 400	Straight and shapeable tip	10 specialty and workhorse wires; multiple tip loads and a mix of polymer jackets or coils
Medtronic	Mirage .008” Hydrophilic Guidewire	Stainless steel	0.012 > 0.008	200	Shapeable tip	–
Medtronic	Silverspeed .010 Hydrophilic Guidewire	Stainless steel	0.010	200	Shapeable tip	–
Medtronic	Silverspeed .014 Hydrophilic Guidewire	Stainless steel	0.014	175, 200	Shapeable tip	–
Medtronic	X-Celerator Hydrophilic Exchange Guidewire	Stainless steel	0.010, 0.014	300, 350	Shapeable tip	–
Medtronic	X-Pedion .010 Hydrophilic Guidewires	Stainless steel	0.012 > 0.010	200	Shapeable tip	–
Medtronic	X-Pedion .014 Hydrophilic Guidewires	Stainless steel	0.014	200	Shapeable tip	–
Merit Medical Systems, Inc.	Splash Hydrophilic Coated Guide Wire	Nitinol fixed core	0.018, 0.025, 0.035, 0.038	80, 150, 180, 220, 260	Straight, angled, and straight long taper; tip flexibility 5 cm; available in standard and stiff configurations	Proprietary nitinol-core wire provides excellent 1:1 torque control; enhanced coating technology provides enduring lubricity for rapid vessel selection
Merit Medical Systems, Inc.	Tenor Steerable Micro Guide Wire	Stainless steel/platinum tip	0.014, 0.018	165	Straight and angled shapeable	Stainless steel core wire for pushability; hydrophilic-coated polyurethane section for excellent vascular tracking with a platinum tip for high visibility
Merit Medical Systems, Inc.	True Form Reshapable Guide Wire	Stainless steel	0.014	145, 165, 180	Straight, angled	Reshapable tip

Company Name	Product Name	Type	Diameter (inch)	Length (cm)	Tip Type	Comments
Mivi Neuroscience, Inc.	Mivi Vi-Radius 014	Stainless steel, hydrophilic coating	0.014	205	Radiopaque platinum tip	Platinum tip allows for customized shapeability and deflection through tortuous anatomy
Nipro	AquaLiner II Hydrophilic Super-Elastic Nitinol Guidewire	Nitinol	0.035, 0.038	150, 180, 260	Angled, straight	Engineered to provide optimal pushability, trackability, and kink resistance in challenging anatomy; offers lasting lubricity and tactile feel; our proprietary manufacturing process for the nitinol core results in a kink-resistant guidewire with torque performance that minimizes whip
Pediavascular	Spring Wire	Stainless steel	0.030	140	J curve, straight	2-cm floppy tip
Rapid Medical	Drivewire 24 Guidewire	Stainless steel with an inner nitinol braided flexible coil and hydrophilic coating on the distal segment of the wire	0.024	202	Steerable	Features a controllable distal end capable of on-demand shape modification, enabling precise navigation and enhanced support within the vasculature
Stryker	Synchro 10	Nitinol	0.010	200, 300	Shapeable	Microfabricated nitinol distal hypotube designed for efficient torque transfer
Stryker	Synchro 14 35-cm	Nitinol	0.014	200, 300	Shapeable	Microfabricated nitinol distal hypotube designed for efficient torque transfer with a 35-cm distal segment
Stryker	Synchro 14 45-cm	Nitinol	0.014	200, 300	Shapeable	Microfabricated nitinol distal hypotube designed for efficient torque transfer with a 45-cm distal segment
Stryker	Synchro Select Soft	Nitinol	0.014	215, 300	Shapeable, preshaped	Identical to Synchro Select Standard but with a softer tip and support profile
Stryker	Synchro Select Standard	Nitinol	0.014	215, 300	Shaped, preshaped	The trusted Synchro torque, reliability and stability with easier distal navigation and tip shape retention
Stryker	Synchro Select Support	Nitinol	0.014	215, 300	Shaped, preshaped	Identical to Synchro Select Standard with a more supportive profile
Stryker	Synchro2 Soft	Nitinol	0.014	200, 300	Shapeable, preshaped	Identical to Synchro2 Standard but with a softer tip and support profile
Stryker	Synchro2 Standard	Nitinol	0.014	200, 300	Shapeable, preshaped	Designed for torque control; intended for reliable stability and flexibility
Stryker	Synchro2 Support	Nitinol	0.014	215, 300	Shapeable, preshaped	Identical to Synchro2 Standard with a more supportive profile
Stryker	Transend .010	Stainless steel	0.010	205	Shapeable	0.010-inch guidewire identical to the Transend EX Standard; designed for pushability and flexibility
Stryker	Transend 14 EX	Stainless steel	0.014	182	Shapeable	Scitanium alloy core wire construction enhances torque transmission and distal support
Stryker	Transend 14 Floppy	Stainless steel	0.014	205	Shapeable	Identical to the Transend EX Standard but with a softer 3-cm platinum coil tip for improved tip-shape retention and enhanced

Company Name	Product Name	Type	Diameter (inch)	Length (cm)	Tip Type	Comments
						radiopacity
Stryker	Transend 14 Platinum	Stainless steel with platinum coil tip	0.014	205	Shapeable	Identical to the Transend EX Standard but designed for a more floppy distal segment
Stryker	Transend 14 Soft Tip	Stainless steel	0.014	205	Shapeable	Identical to the Transend EX Standard but engineered with a softer tip
Stryker	Transend 300 Extra Support	Stainless steel	0.014	300	Shapeable	300-cm exchange guidewire designed for proximal support with a soft platinum coil tip for superb radiopacity and atraumatic tip
Stryker	Transend 300 Floppy	Stainless steel	0.014	300	Shapeable	An exchange wire identical to the Transend 300 ES but with a floppier distal segment
Teleflex	PiggyBack Wire Converter	Polymer catheter wire converter	0.035 OD	145	Radiopaque marker embedded in distal tip	Wire converter with sliding lock securely fastens onto any standard 0.014-inch wire and converts it to a 0.035-inch wire platform
Terumo Interventional Systems	Glidewire Advantage Hydrophilic Coated Guidewire	Nitinol core	0.035	180, 260	Angled: 45°; tip flexibility: 5 cm	25-cm Glidewire hydrophilic distal portion for navigation; stiffer nitinol proximal portion to support device delivery with spiral PTFE coating
Terumo Interventional Systems	Glidewire Advantage Hydrophilic Coated Guidewire	Nitinol core	0.014, 0.018	180, 300	Angled: 45°; tip flexibility: 1 cm	25-cm Glidewire hydrophilic distal portion for navigation; stiffer nitinol proximal portion to support device delivery with spiral PTFE coating; 2-cm gold coil tip
Terumo Interventional Systems	Glidewire Advantage Track Peripheral Guidewire	Stainless steel proximal shaft; nitinol distal tip	0.014, 0.018	180, 300	Angled: 35°, flexibility: 1 cm	25-cm Glidewire hydrophilic distal portion for navigation; stiff stainless steel proximal portion to support device delivery with spiral PTFE coating; 2-cm gold coil tip
Terumo Interventional Systems	Glidewire Gold Hydrophilic Coated Guidewire	Nitinol	0.018	180, 300	45° angle, 70° angle; tip flexibility: 3 cm	Terumo Glide technology with 1-mm gold band at tip for enhanced radiopacity
Terumo Interventional Systems	Glidewire GT Hydrophilic Coated Guidewire	Nitinol	0.016, 0.018	180, 200	45° angle, 90° angle, 90°/60° double angle, straight (shapeable); tip flexibility: 25 cm	Terumo Glide technology hydrophilic coating with 2-cm gold coil at tip for enhanced radiopacity; flexible distal tip designed for superselectivity
Terumo Interventional Systems	Glidewire Hydrophilic Coated Guidewire	Nitinol	0.018, 0.025, 0.032, 0.035, 0.038	80, 120, 150, 180, 260, 350, 400, 450	Angled, straight, 3 mm J, 1.5 mm “Baby-J”, tip flexibility: 1, 3, 5, 8 cm	Terumo Glide technology hydrophilic coating with super elastic nitinol core and polyurethane jacket; standard or stiff shaft
Terumo Interventional Systems	R2P Glidewire Advantage Hydrophilic Coated Guidewire	Nitinol	0.035	350, 400, 450	Angle, 1.5-mm J	25-cm Glidewire hydrophilic distal portion for navigation; stiff stainless steel proximal portion to support device delivery with spiral PTFE coating
Terumo Interventional Systems	R2P Glidewire Advantage Hydrophilic Coated Guidewire	Stainless steel proximal shaft; nitinol distal tip	0.018	400, 450, 500	Angle	25-cm Glidewire hydrophilic distal portion for navigation; stiff stainless steel proximal portion to support device delivery with spiral PTFE coating; 2-cm gold coil tip
Terumo Interventional	Runthrough NS Extra Floppy	Stainless steel proximal shaft; nitinol distal tip	0.014	180 (can be extended),	Floppy	Hybrid wire that fuses nitinol and stainless steel for exceptional torque control and tip durability

Company Name	Product Name	Type	Diameter (inch)	Length (cm)	Tip Type	Comments
Systems				300		
Terumo Interventional Systems	Runthrough NS Hypercoat	Stainless steel proximal shaft; nitinol distal tip	0.014	180 (can be extended), 300	Straight (shapeable) nitinol	Enhanced hydrophilic guidewire for tortuous, distal, tight stenotic complex lesions
Terumo Interventional Systems	Runthrough NS Izanai	Stainless steel proximal shaft; nitinol distal tip	0.014	180 (can be extended), 300	Straight (shapeable) nitinol	Enhanced hydrophilic guidewire for complex, tortuous, distal, tight stenotic lesions
Terumo Neuro	Headliner Guidewire	Guidewire with Terumo Glide technology hydrophilic coating	0.012, 0.016	200	45°, 90° angle; 90°/150° double angle; 1.5-mm J-tip angle; tip flexibility: 20, 35 cm	Proprietary Glidewire technology with gold coil at tip for enhanced radiopacity; distal tip specifically engineered for delicate neuro procedures; floppy and standard tip taper available
Terumo Neuro	Traxcess 7 Mini	Hydrophilic guidewire	0.007	210	Soft	0.007-inch tip tapers to 0.014-inch guidewire body
Terumo Neuro	Traxcess Docking Wire	Docking wire	0.014	115	–	Compatible with Traxcess guidewire
Terumo Neuro	Traxcess Guidewire	Hybrid nitinol/stainless steel construction with hydrophilic coating	0.012; 0.014 (proximal)	200	Soft, atraumatic tip; shapeable 1.4-cm tip length; straight with 0.012-inch distal diameter to access small vessels	–
US Endovascular	Victoria	Super elastic nitinol	0.035	145, 180, 260	Straight/angled	Super elastic nitinol core/proprietary hydrophilic coating