

Endovascular Today - US Device Guide - Microcatheters

Company Name	Product Name	Type of Catheter Construction	Proximal Size (F)	Middle Size (F)	Distal Size (F)	Catheter Working Length (cm)	Catheter Endhole Diameter ID (inch)	Recommended Guidewire Size (inch)	Radiopaque Tip (Yes/No)	Hydrophilic Coating (Yes/No)
Abbott (manufactured by OrbusNeich)	Teleport Control Microcatheter	Stainless steel braid and coil with outer nylon Pebax jacket	2.7	–	2.1	135, 150	0.0157	0.014	Yes	Yes
Abbott (manufactured by OrbusNeich)	Teleport Microcatheter	Stainless steel braid and coil with outer nylon Pebax jacket	2.6	–	2	135, 150	0.0157	0.014	Yes	Yes
Acrostak	M-Cath	Stainless steel covered with blue Teflon (PTFE)	2.1	2.1	2.25	135	0.016	0.014	Yes	Yes
Argon Medical Devices, Inc.	Drakon	Tungsten steel-braided shaft, PTFE inner lumen	2.9	–	2.7	105, 130, 150	0.025	0.021 (maximum)	Yes	Yes
Argon Medical Devices, Inc.	Drakon	Tungsten steel-braided shaft, PTFE inner lumen	2.9	–	2.4	105, 130, 150	0.022	0.018 (maximum)	Yes	Yes
Argon Medical Devices, Inc.	Drakon	Tungsten steel-braided shaft, PTFE inner lumen	2.9	–	1.7	105, 130, 155	Tapered ID range: 0.022–0.017	0.014 (maximum)	Yes	Yes
Argon Medical Devices, Inc.	Drakon	Tungsten steel-braided shaft, PTFE inner lumen	2.9	–	1.9	105, 130, 155	Tapered ID range: 0.026-0.019	0.016 (maximum)	Yes	Yes
Argon Medical Devices, Inc.	Drakon	Tungsten steel-braided shaft, PTFE inner lumen	3	–	2.8	105, 130, 150	0.027	0.021 (maximum)	Yes	Yes
Argon Medical Devices, Inc.	Drakon	Tungsten steel-braided shaft, PTFE inner lumen	3	–	3	105, 130, 155	0.031	0.025 (maximum)	Yes	Yes
Argon Medical Devices, Inc.	SeQure	Tungsten steel-braided shaft, PTFE inner lumen	2.9	–	2.4	105, 130, 150	0.022	0.018 (maximum)	Yes, two markerbands	Yes
Argon Medical Devices, Inc.	SeQure	Tungsten steel-braided shaft, PTFE inner lumen	2.9	–	2.7	105, 130, 150	0.025	0.021 (maximum)	Yes, two markerbands	Yes
Argon Medical Devices, Inc.	SeQure	Tungsten steel-braided shaft, PTFE inner lumen	2.9	–	1.9	105, 130, 155	Tapered ID range: 0.026–0.019	0.016 (maximum)	Yes, two markerbands	Yes
Argon Medical Devices, Inc.	SeQure	Tungsten steel-braided shaft, PTFE inner lumen	2.9	–	1.7	105, 130, 155	Tapered ID range: 0.022–0.017	0.014 (maximum)	Yes, two markerbands	Yes
Argon Medical	SeQure	Tungsten steel-braided	3	–	3.0	105, 130, 155	0.031	0.025 (maximum)	Yes, two	Yes

Company Name	Product Name	Type of Catheter Construction	Proximal Size (F)	Middle Size (F)	Distal Size (F)	Catheter Working Length (cm)	Catheter Endhole Diameter ID (inch)	Recommended Guidewire Size (inch)	Radiopaque Tip (Yes/No)	Hydrophilic Coating (Yes/No)
Devices, Inc.		shaft, PTFE inner lumen							markerbands	
Argon Medical Devices, Inc.	SeQure	Tungsten steel-braided shaft, PTFE inner lumen	3	–	2.8	105, 130, 150	0.027	0.021 (maximum)	Yes, two markerbands	Yes
Argon Medical Devices, Inc.	SeQure XSB	Tungsten steel-braided shaft, PTFE inner lumen	2.9	–	2.7	130, 155	0.025	0.021 (maximum)	Yes, two markerbands	Yes
Asahi Intecc Co Ltd.	CrossWalk 0.014-inch	Braided shaft	2.7	2.7	1.6	90, 110, 135, 150, 170	0.015	0.014	Yes	Yes
Asahi Intecc Co Ltd.	CrossWalk 0.018-inch	Braided shaft	2.7	2.5	1.7	90, 110, 135, 150, 170	0.019	0.018	Yes	Yes
Asahi Intecc Co Ltd.	CrossWalk 0.035-inch	Braided shaft	4.2	4.2	3.2	90, 110, 135, 150, 170	0.037	0.035	Yes	Yes
Asahi Intecc USA, Inc.	Asahi Caravel	Stainless steel braided	2.6	1.9	1.4	135, 150	–	0.014	Yes, tungsten powder 5-mm tip	Yes
Asahi Intecc USA, Inc.	Asahi Corsair	Stainless steel braided	2.8	2.6	1.3	135, 150	0.015	0.014	Yes, tungsten powder 5-mm tip	Yes
Asahi Intecc USA, Inc.	Asahi Corsair Pro	Stainless steel braided	2.8	2.6	1.3	135, 150	0.015	0.014	Yes, tungsten powder 5-mm tip	Yes
Balt USA	Carrier LG	Consistent OD with tapered distal segment	5.2	5.2	2.4	152	0.021	0.018	Yes	Yes
Balt USA	Carrier MD	Consistent OD with tapered distal segment	4.7	4.7	2.4	152	0.021	0.018	Yes	Yes
Balt USA	Carrier SM	Consistent OD with tapered distal segment	4.5	4.5	2.4	152	0.021	0.018	Yes	Yes
Balt USA	Magic Flow Dependent Microcatheter	Extruded	2.7	2.4	1.2–1.8	155, 160, 165, 180	0.009–0.013	0.007–0.010	Yes	Yes
Baylis Medical Technologies	ProTrack Microcatheter	Coiled stainless steel, PTFE, Pebax	2.9	2.9	2.9	145	0.025	Up to 0.024	Yes	No
Baylis Medical Technologies	ProTrack Microcatheter	Coiled stainless steel, PTFE, Pebax	2.7	2.7	2.7	145	0.022	Up to 0.021	Yes	No
Boston Scientific Corporation	Direxion Fathom-16 System Preloaded Torqueable Microcatheter	Steerable laser-cut nitinol shaft	2.7	–	2.4	105, 130, 155	0.021	Includes preloaded Fathom-16 guidewire	Yes	Yes
Boston Scientific	Direxion Hi-Flo	Steerable laser-cut nitinol	3	–	2.8	105, 130, 155	0.027	Includes preloaded	Yes	Yes

Company Name	Product Name	Type of Catheter Construction	Proximal Size (F)	Middle Size (F)	Distal Size (F)	Catheter Working Length (cm)	Catheter Endhole Diameter ID (inch)	Recommended Guidewire Size (inch)	Radiopaque Tip (Yes/No)	Hydrophilic Coating (Yes/No)
Corporation	Fathom-16 System Preloaded Torqueable Microcatheter	shaft						Fathom-16 guidewire		
Boston Scientific Corporation	Direxion Hi-Flo Torqueable Microcatheter	Steerable laser-cut nitinol shaft	3	–	2.8	105, 130, 155	0.027	0.021 (maximum)	Yes	Yes
Boston Scientific Corporation	Direxion Hi-Flo Transend-18 System Preloaded Torqueable Microcatheter	Steerable laser-cut nitinol shaft	3	–	2.8	105, 130, 155	0.027	Includes preloaded Transend-18 guidewire	Yes	Yes
Boston Scientific Corporation	Direxion Torqueable Microcatheter	Steerable laser-cut nitinol shaft	2.7	–	2.4	105, 130, 155	0.021	0.018 (maximum)	Yes	Yes
Boston Scientific Corporation	Direxion Transend-14 System Preloaded Torqueable Microcatheter	Steerable laser-cut nitinol shaft	2.7	–	2.4	105, 130, 155	0.021	Includes preloaded Transend-14 guidewire	Yes	Yes
Boston Scientific Corporation	Renegade Hi-Flo Fathom Preloaded System	Vortec fiber and platinum braid	3	–	2.8	105, 115, 135, 150	0.027	Includes preloaded Fathom-16 guidewire	Yes	Yes
Boston Scientific Corporation	Renegade Hi-Flo Microcatheter	Vortec fiber and platinum braid	3	–	2.8	105, 115, 135, 150	0.027	0.018 (maximum)	Yes	Yes
Boston Scientific Corporation	Renegade Hi-Flo Transend Kit	Vortec fiber and platinum braid	3	–	2.8	105, 115, 135	0.027	Includes Transend-18 guidewire	Yes	Yes
Boston Scientific Corporation	Renegade Microcatheter	Vortec fiber braid	3	–	2.5	130, 150	0.021	0.018 (maximum)	Yes	Yes
Boston Scientific Corporation	Renegade STC 18 Microcatheter	Vortec fiber and stainless steel braid	3	–	2.4	105, 130, 150	0.021	0.018 (maximum)	Yes	Yes
Boston Scientific Corporation	TruSelect Microcatheter	Tungsten wire braided layer	2.8	–	2	105, 130, 155, 175	0.021	0.016 (maximum)	Yes	Yes
Cerenovus	Prowler 10	Braid/coil design	2.3	–	1.7	150	0.015	0.012 (maximum)	Yes	Yes
Cerenovus	Prowler 14	Braid/coil design	2.8	–	1.9	150, 170	0.0165	0.014 (maximum)	Yes	Yes
Cerenovus	Prowler 27	Braid/coil design	3	–	2.6	150	0.027	0.018 (maximum)	Yes	Yes
Cerenovus	Prowler Plus	Braid/coil design	2.8	–	2.3	110, 135, 150	0.021	0.018 (maximum)	Yes	Yes
Cerenovus	Prowler Select LP-ES	Braid/coil design	2.8	–	1.9	150	0.0165	0.014 (maximum)	Yes	Yes
Cerenovus	Prowler Select Plus	Braid/coil design	2.3	–	2.3	150	0.021	0.018 (maximum)	Yes	Yes

Company Name	Product Name	Type of Catheter Construction	Proximal Size (F)	Middle Size (F)	Distal Size (F)	Catheter Working Length (cm)	Catheter Endhole Diameter ID (inch)	Recommended Guidewire Size (inch)	Radiopaque Tip (Yes/No)	Hydrophilic Coating (Yes/No)
Cerenovus	Rapidtransit Microcatheters	Braid/coil design	2.3	–	2.3	75, 155, 175 (proximal, middle, and distal lengths); 100, 135 (proximal lengths)	0.021	0.018 (maximum)	Yes	Yes
Cerenovus	Transit Microcatheters	Braid/coil design	2.8	–	2.5	135, 150	0.021	0.018 (maximum)	Yes	Yes
Cook Medical	Cantata 2.5	Braided stainless steel, PTFE, Pebax	2.5	2.5	2.5	100, 110, 135, 150	0.021	0.018 (maximum)	Yes (one or two)	Yes
Cook Medical	Cantata 2.8	Braided stainless steel, PTFE, Pebax	2.8	2.8	2.8	100, 110, 135, 150	0.025	0.021 (maximum)	Yes (one or two)	Yes
Cook Medical	Cantata 2.9	Braided stainless steel, PTFE, Pebax	2.9	2.9	2.9	110, 135, 150	0.027	0.025 (maximum)	Yes	Yes
Embolx, Inc.	Sniper G3 Balloon Microcatheter	Steel braid coaxial, balloon maximum diameter 6 mm	2.9	2.9	2.2	110, 130, 150	0.020	0.016 (maximum)	Yes	Yes
Embolx, Inc.	Soldier High Flow Microcatheter	Steel braid coaxial	2.5	2.5	2.5	130, 155	0.027	0.018 (maximum)	Yes	Yes
Embolx, Inc.	Soldier High Flow Microcatheter	Steel braid coaxial	2	2	2	130, 155	0.022	0.018 (maximum)	Yes	Yes
Medtronic	Apollo Onyx Delivery Micro Catheter	–	2.7	–	1.5	165	0.013	0.010	Yes	Yes
Medtronic	Echelon 10 Micro Catheter	–	2.1	–	1.7	150	0.017	0.014	Yes	Yes
Medtronic	Echelon 14 Micro Catheter	–	2.4	–	1.9	150	0.017	0.014	Yes	Yes
Medtronic	Marathon Flow Directed Micro Catheter	–	2.7	–	1.5	165	0.013	0.010	Yes	Yes
Medtronic	Marksman Micro Catheter	–	3.2	–	2.8	105, 135, 150, 160	0.027	0.021	Yes	Yes
Medtronic	Orion Micro Catheter	–	2.4	–	2.6	150	0.021	0.018	Yes	Yes
Medtronic	Rebar 10 Reinforced Micro Catheter	–	2.3	–	1.7	153	0.015	0.012	Yes	Yes
Medtronic	Rebar 14 Reinforced Micro Catheter	–	2.4	–	1.9	153	0.017	0.014	Yes	Yes
Medtronic	Rebar 18 Reinforced	–	2.7	–	2.4	130, 153	0.021	0.018	Yes	Yes

Company Name	Product Name	Type of Catheter Construction	Proximal Size (F)	Middle Size (F)	Distal Size (F)	Catheter Working Length (cm)	Catheter Endhole Diameter ID (inch)	Recommended Guidewire Size (inch)	Radiopaque Tip (Yes/No)	Hydrophilic Coating (Yes/No)
	Micro Catheter									
Medtronic	Rebar 27 Reinforced Micro Catheter	–	2.8	–	2.8	130	0.027	0.021	Yes	Yes
Medtronic	UltraFlow HPC Micro Catheter	–	3	–	1.9	165	0.012	0.010	Yes	Yes
Merit Medical Systems, Inc.	Maestro	Nylon ribbon braiding	2.8, 2.9	2.8, 2.9	2.1, 2.4, 2.8, 2.9	110, 130, 150, 165	0.018, 0.020, 0.024, 0.027	0.016, 0.018, 0.021	Yes, one markerband	Yes
Merit Medical Systems, Inc.	Pursue	Metal braided	2.8, 2.9	2.8, 2.9	1.7, 2	110, 130, 150	0.018, 0.020	0.016, 0.018	Yes, one markerband	Yes
Merit Medical Systems, Inc.	SwiftNinja Steerable Microcatheter	Tungsten-braided shaft	2.6, 2.9	2.6, 2.9	2.4 (0.80 mm)	125, 150	0.021 (0.54 mm)	0.018	Yes, two markerbands	Yes
Penumbra, Inc. (Neuro)	PX Slim Microcatheter	Nitinol coil reinforced; eight extrusion zones; four tip shapes: straight, 45°, 90°, and 130°	2.95	–	2.6	150	0.025	0.014	Yes, two markerbands	Yes
Penumbra, Inc. (Neuro)	Velocity Delivery Microcatheter	Nitinol coil reinforced; eight extrusion zones	2.95	–	2.6	160	0.025	0.014	Yes, one markerband	Yes
Penumbra, Inc. (Peripheral Vascular)	Lantern Delivery Microcatheter	Nitinol coil reinforced; eight extrusion zones; three tip shapes: straight, 45°, and 90°	2.95	–	2.6	115, 135, 150	0.025	0.014/0.018	Yes, two markerbands, radiopaque 3 cm	Yes
Reflow Medical, Inc	coraCross Coronary Catheter	Polymer tip, stainless steel braid, integrated wire coating	3.2	3.2	2.2	135, 150	0.016	0.014	Yes	Yes
Reflow Medical, Inc	coraFlex Coronary Catheter	Polymer tip, stainless steel braid, integrated wire coating	2.2	2.2	1.4	135, 150	0.016	0.014	Yes	Yes
Reflow Medical, Inc	coraForce Coronary Catheter	Polymer tip, stainless steel braid, integrated wire coating	2.2	2.2	1.3	135, 150	0.016	0.014	Yes	Yes
Reflow Medical, Inc	Spex35 Shapeable Support Microcatheter	Shapeable tip, braid reinforced	4.6	4.6	4.6	50, 90, 135, 150	0.038	0.035	Yes	Yes
Reflow Medical,	SpexLP 14 Shapeable	Low profile, shapeable tip,	2.2	2.2	1.4	90, 135, 150	0.018	0.014	Yes	Yes

Company Name	Product Name	Type of Catheter Construction	Proximal Size (F)	Middle Size (F)	Distal Size (F)	Catheter Working Length (cm)	Catheter Endhole Diameter ID (inch)	Recommended Guidewire Size (inch)	Radiopaque Tip (Yes/No)	Hydrophilic Coating (Yes/No)
Inc	Support Microcatheter	braid reinforced								
Reflow Medical, Inc	SpexLP 18 Shapeable Support Microcatheter	Low profile, shapeable tip, braid reinforced	2.5	2.5	1.6	90, 135, 150	0.021	0.018	Yes	Yes
Reflow Medical, Inc	SpexLP 35 Shapeable Support Microcatheter	Low profile, shapeable tip, braid reinforced	3.8	3.8	2.9	90, 135, 150	0.038	0.035	Yes	Yes
Reflow Medical, Inc	Wingman 35 CTO Crossing Catheter	Braided with extendable beveled tip	4.6	4.6	4.6	65, 90, 135	0.038	0.050	Yes	Yes
Reflow Medical, Inc	Wingman14 CTO Crossing Catheter	Braided with extendable beveled tip	2.7	2.7	2.7	65, 135, 150	0.022	0.014	Yes	No
Reflow Medical, Inc	Wingman14C CTO Crossing Catheter	Braided with extendable beveled tip	2.7	2.7	2.7	90, 135, 150	0.024	0.014	Yes	Yes
Reflow Medical, Inc	Wingman18 CTO Crossing Catheter	Braided with extendable beveled tip	3.8	3.8	3.8	90, 135, 150	0.032	0.018	Yes	Yes
Spartan Micro, Inc.	Spartan MC 0165	–	2.4	–	1.8	158	0.017	0.014	Yes	Yes
Stryker	Excelsior 1018	Braided, hydrophilic	2.6	–	2	150	0.019	0.016 (maximum)	Yes	Yes
Stryker	Excelsior SL-10	Braided, hydrophilic	2.4	–	1.7	150	0.0165	0.014 (maximum)	Yes	Yes
Stryker	Excelsior XT-17	Braided, hydrophilic	2.4	–	1.7	150	0.017	0.014 (maximum)	Yes	Yes
Stryker	Excelsior XT-27	Braided, hydrophilic	2.9	–	2.7	135, 150	0.027	0.018 (maximum)	Yes	Yes
Stryker	Neuro Renegade Hi-Flo	Braided, hydrophilic	3	–	2.8	135, 150	0.027	0.018 (maximum)	Yes	Yes
Stryker	Renegade 18	Braided, hydrophilic	3	–	2.5	150	0.021	0.018 (maximum)	Yes	Yes
Stryker	Trevo Pro 14	Braided	2.4	–	2	157	0.017	0.014 (maximum)	Yes	Yes
Stryker	Trevo Pro 18	Braided	2.7	–	2.4	150	0.021	0.018 (maximum)	Yes	Yes
Stryker	Trevo Trak 21	Braided	2.7	–	2.4	162	0.021	0.018 (maximum)	Yes	Yes
Surmodics, Inc.	Sublime .014 Microcatheters	Dual stainless steel, locked-braid layers; PTFE-lined inner lumen, pristyne hydrophilic coating	2.4	–	2.2	65, 150, 200	0.015	0.014	Yes	Yes
Surmodics, Inc.	Sublime .018 Microcatheters	Dual stainless steel, locked-braid layers; PTFE-lined inner lumen, pristyne hydrophilic coating	2.6	–	2.6	65, 150, 200	0.019	0.018	Yes	Yes
Surmodics, Inc.	Sublime .035	Dual stainless steel, locked-	4	–	4	90, 135, 150, 200	0.036	0.035	Yes	Yes

Company Name	Product Name	Type of Catheter Construction	Proximal Size (F)	Middle Size (F)	Distal Size (F)	Catheter Working Length (cm)	Catheter Endhole Diameter ID (inch)	Recommended Guidewire Size (inch)	Radiopaque Tip (Yes/No)	Hydrophilic Coating (Yes/No)
	Microcatheters	braid layers; PTFE-lined inner lumen, pristyne hydrophilic coating								
Teleflex	SuperCross Microcatheter OTW - 0.014 Angled Tips - 45°, 90°, 120°, and 90° Extended Tip	Dual coil design, platinum/tungsten coil tip	3.2	–	2.4	130, 150	0.017	0.014	Yes, platinum/tungsten coil tip	Yes
Teleflex	SuperCross Microcatheter OTW - 0.014 Straight and Flexible Tip	Braided	2.5	–	1.8	130, 150	0.017	0.014	Yes, one markerband	Yes
Teleflex	Turnpike Catheter	Hybrid multilayer: dual bidirectional coils with inner braid	2.9	2.6	1.6	135, 150	0.0165	0.014	Yes, tungsten-loaded tip	Yes
Teleflex	Turnpike Gold Catheter	Hybrid multilayer: dual bidirectional coils with inner braid and external nylon spiral coil	2.9	2.9	2.1	135, 150	0.0165	0.014	Yes, gold-plated tip	Yes
Teleflex	Turnpike LP Catheter	Hybrid multilayer: dual bidirectional coils with inner braid	2.9	2.2	1.6	135, 150	0.0165	0.014	Yes, tungsten-loaded tip	Yes
Teleflex	Turnpike Spiral Catheter	Hybrid multilayer: dual bidirectional coils with inner braid and external nylon spiral coil	2.9	2.9	1.6	135, 150	0.0165	0.014	Yes, tungsten-loaded tip	Yes
Teleflex	Twin-Pass Dual Access Catheter	Dual-lumen catheter	3.4 X 2.7	–	2	135	0.017	0.014 (RX and OTW)	Yes, two markerbands	Yes
Teleflex	Twin-Pass Torque Dual Access Catheter	Dual-lumen catheter	3.5 X 3.5	–	2.1	135	0.017	0.014 (RX and OTW)	Yes, two markerbands	Yes
Terumo Interventional Systems	PG Pro Peripheral Microcatheter	Tungsten coil, PTFE inner layer	2.8	2.8	2.8	140, 165	0.027	< 0.021	Yes	Yes
Terumo Interventional Systems	Progreat Alpha Microcatheter	Tungsten coil, PTFE liner	2.7	–	2.0	110, 130, 150	0.019	Up to 0.016	Yes, platinum	Yes

Company Name	Product Name	Type of Catheter Construction	Proximal Size (F)	Middle Size (F)	Distal Size (F)	Catheter Working Length (cm)	Catheter Endhole Diameter ID (inch)	Recommended Guidewire Size (inch)	Radiopaque Tip (Yes/No)	Hydrophilic Coating (Yes/No)
Terumo Interventional Systems	Progreat Coaxial Microcatheter System	Tungsten coil, PTFE liner	2.9	–	2.7	110, 130	0.025	Includes an 0.021-inch Glidewire GT fixed to the hub of the Progreat	No	Yes
Terumo Interventional Systems	Progreat Coaxial Microcatheter System	Tungsten coil, PTFE liner	2.9	–	2.4	110, 130, 150	0.022	Includes an 0.018-inch Glidewire GT fixed to the hub of the Progreat	Yes, platinum	Yes
Terumo Interventional Systems	Progreat Coaxial Microcatheter System	Tungsten coil, PTFE liner	3	–	2.8	110, 130, 150	0.027	Includes an 0.021-inch Glidewire GT fixed to the hub of the Progreat	Yes, platinum	Yes
Terumo Interventional Systems	Progreat Lambda Microcatheter	Asymmetric, densely-pitched tungsten braid	2.8	–	1.9	165	0.019	0.016	Yes	Yes
Terumo Interventional Systems	Progreat Microcatheter	Tungsten coil, PTFE liner	2.9	–	2.7	110, 130	0.025	Up to 0.021	No	Yes
Terumo Interventional Systems	Progreat Microcatheter	Tungsten coil, PTFE liner	3	–	2.8	110, 130, 150	0.027	Up to 0.021	Yes, platinum	Yes
Terumo Interventional Systems	Progreat Microcatheter	Tungsten coil, PTFE liner	2.9	–	2.4	110, 130, 150	0.022	Up to 0.018	Yes, platinum	Yes
Terumo Neuro	Headway 17	Distal shaft provides support for coiling while the segmented design provides smooth trackability	2.4	–	1.7	150	0.017	0.014	Yes	Yes
Terumo Neuro	Headway 21	Coil reinforced catheter with multisegmented design	2.5	–	2	156	0.021	0.014	Yes	Yes
Terumo Neuro	Headway 27	Coil reinforced catheter with multisegmented design	3.1	–	2.6	156	0.027	0.014	Yes	Yes
Terumo Neuro	Headway DUO	Hybrid braid and coil design	2.1	–	1.3, 1.6	167, 156	0.013, 0.0165	–	Yes	Yes
Terumo Neuro	VIA	Designed for precise delivery, deployment, and	2.8, 3.2, 3.8	–	2.5, 3, 3.4	154, 154, 133	0.021, 0.027, 0.033	0.014	Yes	Yes

Company Name	Product Name	Type of Catheter Construction	Proximal Size (F)	Middle Size (F)	Distal Size (F)	Catheter Working Length (cm)	Catheter Endhole Diameter ID (inch)	Recommended Guidewire Size (inch)	Radiopaque Tip (Yes/No)	Hydrophilic Coating (Yes/No)
		retrieval of the WEB device								
Terumo Neuro	Wedge	Coil reinforcement and distal bulb	2.5	–	2	1.5 (distal length)	0.021	0.014	Yes	Yes
Transit Scientific	XO Cath 2.0F Microcatheter	Laser cut metal hypotube with hydrophilic coating and PTFE liner	2.6	–	2	90, 110, 130, 150, 175, 220	0.021	0.014, 0.018	Yes, 2 radiopaque markerbands	Yes
Transit Scientific	XO Cath 2.6F Microcatheter	Laser cut metal hypotube with hydrophilic coating and PTFE liner	2.8	–	2.6	90, 110, 130, 150, 175, 220	0.027	0.014, 0.018, 0.021	Yes, 2 radiopaque markerbands	Yes
Transit Scientific	XO Cross 14 Microcatheter	Metal exoskeleton with outer polymer layer	2	2	1.6	90, 135, 150, 175	0.018	0.014	Yes	No
Transit Scientific	XO Cross 14 Microcatheter With Hydrophilic Coating	Metal exoskeleton with outer polymer layer and hydrophilic coating	2	2	1.6	90, 135, 150, 175	0.018	0.014	Yes	Yes
Transit Scientific	XO Cross 18 Microcatheter	Metal exoskeleton with outer polymer layer	2.6	2.6	1.9	90, 135, 150	0.021	0.014, 0.018	Yes	No
Transit Scientific	XO Cross 18 Microcatheter With Hydrophilic Coating	Metal exoskeleton with outer polymer layer and hydrophilic coating	2.6	2.6	1.9	90, 135, 150	0.021	0.014, 0.018	Yes	Yes
Transit Scientific	XO Cross 35 Support Catheter	Metal exoskeleton with outer polymer layer	3.9	3.9	3.2	90, 135, 150, 175	0.038	0.014, 0.018, 0.035	Yes	No
Transit Scientific	XO Cross 35 Support Catheter With Hydrophilic Coating	Metal exoskeleton with outer polymer layer and hydrophilic coating	3.9	3.9	3.2	90, 135, 150, 175	0.038	0.014, 0.018, 0.035	Yes	Yes
TriSalus Life Sciences	Surefire Infusion System (SIS) 021	Braided stainless steel, PTFE, multiple polymers, microvalve tip	3.2	3.2	2.8	120, 150	0.021	0.018 (maximum)	Yes	Yes
TriSalus Life Sciences	Surefire Infusion System (SIS) 025	Braided stainless steel, PTFE, multiple polymers, microvalve tip	3.7	3.7	3.4	120, 150	0.025	0.018 (maximum)	Yes	Yes